



REMARKS:
 AAO CRITERION FOR ANNUAL AVERAGE FSP CONCENTRATION IS 50 µg/m³.

LEGEND:

- EXISTING REPRESENTATIVE ASR (FOR BOTH CONSTRUCTION AND OPERATIONAL PHASE ASSESSMENT)
- PLANNED REPRESENTATIVE ASR (FOR BOTH CONSTRUCTION AND OPERATIONAL PHASE ASSESSMENT)
- PLANNED REPRESENTATIVE ASR (FOR OPERATIONAL PHASE ASSESSMENT ONLY)
- (L,U) PATH Grid Cell (L,U)
- 500M ASSESSMENT AREA
- LTR/SMR R/W
- 500M ASSESSMENT AREA

This drawing has been prepared for the use of AECOM's client. It may not be used, modified, reproduced or relied upon by third parties, except as agreed by AECOM or as required by law. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that uses or relies on this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from the stated dimensions.

AECOM

Project
 DEVELOPMENT OF ANDERSON ROAD QUARRY SITE - INVESTIGATION, DESIGN AND CONSTRUCTION

CLIENT
 土木工程拓展署
 CEDD
 Civil Engineering and Development Department

CONSULTANT
 AECOM Asia Company Ltd.
 www.aecom.com

ISSUE/REVISION

NO.	DATE	DESCRIPTION	CHK.

STATUS

NO.	DATE	DESCRIPTION	CHK.

SCALE

A3 1 : 7000
KEY PLA

SHEET TITLE

CONTOURS OF CUMULATIVE ANNUAL AVERAGE RSP CONCENTRATION IN µg/m³ AT 1.5m ABOVE GROUND (LTR R/W) (UNMITIGATED)
SHEET NUMBER
 60328348/EIA_RIW/FIGURE 4.16

PROJECT NO. 60328348
CONTRACT NO. CE 10/2014 (CE)