

JOB NO.: TCS00491/09

DSD CONTRACT No.: DC/2009/08

CONSTRUCTION OF YUEN LONG SOUTH BRANCH SEWERS AND EXPANSION OF HA TSUEN SEWAGE PUMPING STATION

11TH ENVIRONMENTAL MONITORING & AUDIT MONTHLY REPORT – DECEMBER 2010

PREPARED FOR

CHINA STATE CONSTRUCTION ENGINEERING (HONG KONG) COMPANY LIMITED

Quality Index

Date	Reference No.	Prepared By	Certified By
29 June 2011	TCS00491/09/600/R0152v3	Dennis Ho (Environmental Consultant)	T.W. Tam (Environmental Team Leader)
		A	Time

Version	Date	Description
1	24 June 2011	Submission after reviewing against IEC's general comments
2	27 June 2011	Amended against IEC's comments on 27 June 2011
3	29 June 2011	Amended against IEC's comments on 29 June 2011

This report has been prepared by Action-United Environmental Services & Consulting with all reasonable skill, care and diligence within the terms of the Agreement with the client, incorporating our General Terms and Conditions of Business and taking account of the resources devoted to it by agreement with the client. We disclaim any responsibility to the client and others in respect of any matters outside the scope of the above. This report is confidential to the client and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies upon the report at their own risk.

安誠工程顧問有限公司

香港灣仔 皇后大道東183號 合和中心47樓

電話: (852) 2911 2233 傳真: (852) 2805 5028

Hyder Consulting Limited

Company Number 126012 47th Floor, Hopewell Centre 183 Queen's Road East Wan Chai, Hong Kong Tel: (852) 2911 2233

Fax: (852) 2805 5028 hyder.hk@hyderconsulting.com www.hyderconsulting.com

Our Ref: EB000586-F/E11-095594

Your Ref:



30 June 2011

By Post

Action-United Environmental Services & Consulting
Unit A, 20/F, Gold King Industrial Building,
35-41 Tai Lin Pai Road,

Kwai Chung, New Territories, Hong Kong.

For attention of: Mr. T. W. Tam

Dear Mr. Tam,

Contract No.: DC/2009/08

Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen Sewage

Pumping Station

Monthly EM&A Report for Designated Project, December 2010 – IEC Verification

With reference to ET's captioned report (ET's ref.: TCS00491/09/600/R0152v3 dated 29 June 2011) received on 29 June 2011, we have no comment and hereby verify the captioned report <u>excluding</u> the Landscape and Visual Impact section of the report.

We request the ET to submit the separate submission of Landscape and Visual Impact section of the report as soon as possible, for the completion of the captioned report.

Should there be any queries, please feel free to contact our William Law on 2911 2511.

Yours sincerely

F.C. TSANG

Independent Environmental Checker HYDER CONSULTING LIMITED

FCT/WL/my



Executive Summary

EXECUTIVE SUMMARY

- ES01. The China State Construction Engineering (Hong Kong) Limited (hereinafter "The Contractor") has been awarded by the Drainage Services Department (DSD) the Contract **DC/2009/08**Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen Sewage Pumping Station (the Project) in October 2009.
- ES01. For ease of reporting, it has been agreed among the Engineer's Representatives (ER, AECOM), Independent Environmental Checker (IEC, Hyder Consulting Limited), The Contractor (The China State Construction Engineering (Hong Kong) Limited), Environmental Team (Action-United Environmental Services and Consulting, ET) and Environmental Protection Department (EPD) that the EM&A report under the Project is split to the following two stand-alone parts:
 - Expansion of the existing Ha Tsuen Sewage Pumping Station (under Environmental Permit No.EP-327/2009/A)
 - Construction of a sewage pumping station near Shui Tsiu San Tsuen Road in Yuen Long South; and construction of about 9km of sewers and rising mains with diameter ranging from 200-1500mm in Yuen Long South and Ha Tsuen areas (without Environmental Permit).
- ES02. This is the 11th monthly EM&A Report *Expansion of Ha Tsuen Sewage Pumping Station* (hereinafter 'this Report') for designated works under Environmental Permit No.EP327/2009A (hereinafter 'the EP'), covering a period from 1 to 31 December 2010 (hereinafter 'the Reporting Period').

ENVIRONMENTAL MONITORING AND AUDIT ACTIVITIES

ES03. Environmental monitoring activities under the EM&A program in this reporting month are summarized in the following table.

Aspects	Environmental Monitoring Parameters / Inspection	Occasions
Aim Ovolity	1-hour Total Suspended Particulates (TSP)	42
Air Quality	24-hour Total Suspended Particulates (TSP)	12
Construction Noise	Leq (30min) Daytime	14
Water Quality	Total Suspended Solids	12
Inspection / Audit	ET Weekly Environmental Site Inspection	4

BREACH OF ACTION AND LIMIT (A/L) LEVELS

ES04. Breach of the air quality, construction noise and water quality in this reporting period is summarized in the following table.

Environmental	Monitoring	Action	Limit	Event & Action		
Aspects	Parameters Parameters	0		NOE Issued	Investigation	Corrective Actions
Air Quality	1-hour TSP	0	0	0		
All Quality	24-hour TSP	0	0	0		
Construction Noise	Leq (30min) Daytime	0	0	0		
	Dissolved Oxygen	0	0	0		
Water Quality	Turbidity	0	2	2	Not project related	
	Suspended Solids	0	1	1	Not project related	

Note: NOE – Notification of Exceedance

In this reporting period, no exceedance was recorded in air quality and noise quality. However, two Limit Level exceedances in Turbidity and one Limit Level exceedance in Suspended Solids were found in stream water quality monitoring. NOEs were issued to relevant parties upon confirmation of the results; The results was found that such exceedances were not project related.

R0152v3.doc



ENVIRONMENTAL COMPLAINT

ES05. No environmental complaint was recorded / received in this reporting month. The statistics of environmental complaint are summarized in the following table.

Donouting Dowled	Environmental Complaint Statistics			
Reporting Period	Frequency	Cumulative	Complaint Nature	
1–31 Dec 2010	0	0	NA	

NOTIFICATION OF SUMMONS AND SUCCESSFUL PROSECUTIONS

ES06. No environmental summons and successful prosecutions were recorded in this reporting month. The statistics of environmental complaint are summarized in the following tables.

Donauting David	Environmental Summons Statistics		
Reporting Period	Frequency	Cumulative	Complaint Nature
1–31 Dec 2010	0	0	NA

Donauting Davied	Environmental Prosecution Statistics		
Reporting Period	Frequency	Cumulative	Complaint Nature
1–31 Dec 2010	0	0	NA

REPORTING CHANGE

ES07. There are no reporting changes in this reporting month.

SITE INSPECTION BY EXTERNAL PARTIES

ES08. In this reporting period, no site inspection was carried by EPD or AFCD.

FUTURE KEY ISSUES

ES09. During dry season, special attention should be paid to the dust mitigation measures to avoid fugitive dust emissions from loose soil surface or haul road. Nevertheless, mitigation measures implemented for control the surface runoff including wheel wash facilities, covering of the loose soil surface or stockpile with tarpaulin sheet, etc., should be properly maintained to prevent any muddy or sandy runoff from the loose soil surface overflow on the site boundary; and also with construction noise and other environmental issues stipulated in the Environmental Monitoring and Audit Manual.

R0152v3.doc Executive Summary





TABLE OF CONTENTS

1	BACKGRO	DUCTION DUND TRUCTURE	1 1 1	
2	PROJECT ORGANIZATION AND CONSTRUCTION PROGRESS PROJECT ORGANIZATION AND MANAGEMENT STRUCTURE CONSTRUCTION PROGRESS SUMMARY OF ENVIRONMENTAL SUBMISSIONS		3 3 3 3	
3	SUMMARY OF IMPACT MONITORING REQUIREMENTS MONITORING PARAMETERS MONITORING LOCATIONS MONITORING FREQUENCY MONITORING METHODOLOGY AND EQUIPMENTS EQUIPMENT CALIBRATION METEOROLOGICAL INFORMATION DATA MANAGEMENT AND DATA QA/QC CONTROL DETERMINATION OF ACTION/LIMIT (A/L) LEVELS			
4			11 11 11 12 13	
5	WASTE MANAGEMENT RECORDS OF WASTE QUANTITIES		14 14	
6		SPECTIONS	15	
7	ENVIRONMENTAL COMPLAINTS AND NON-COMPLIANCE ENVIRONMENTAL COMPLAINT, SUMMONS AND PROSECUTION		16 16	
8	IMPLE	MENTATION STATUS OF MITIGATION MEASURES	17	
9	_	Γ FORCAST ES FOR THE COMING MONTH	22 22	
10	CONCLUSIONS AND RECOMMENTATIONS CONCLUSIONS RECOMMENDATIONS		23 23 23	
LIS	T OF TA	BLES		
Тав	LE 2-1	STATUS OF ENVIRONMENTAL LICENSES AND PERMITS		
	LE 3-1	SUMMARY OF MONITORING PARAMETERS		
	LE 3-2	AIR QUALITY MONITORING STATION		
	LE 3-3	CONSTRUCTION NOISE MONITORING STATION		
	LE 3-4	LOCAL STREAM WATER QUALITY MONITORING STATION		
	SLE 3-5 SLE 3-6	AIR QUALITY MONITORING EQUIPMENTS		
	LE 3-0 LE 3-7	NOISE MONITORING EQUIPMENTS WATER QUALITY MONITORING EQUIPMENTS		
	LE 3-7	ACTION AND LIMIT LEVELS FOR AIR QUALITY MONITORING		
	LE 3-8 LE 3-9	ACTION AND LIMIT LEVELS FOR CONSTRUCTION NOISE		
	LE 3-10	ACTION AND LIMIT LEVELS FOR A LOCAL STREAM WATER QUALITY M (R1B)	ONITORING	

DSD Contract No. DC/2009/08 - Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen Sewage Pumping Station Environmental Monitoring and Audit Monthly Report – December 2010





Table 4-1	SUMMARY OF 24-HOUR AND 1-HOUR TSP MONITORING RESULTS – AM1
TABLE 4-2	Summary of 24-hour and 1-hour TSP Monitoring Results – $AM2$
TABLE 4-3	SUMMARY OF CONSTRUCTION NOISE MONITORING RESULTS – NM1
TABLE 4-4	SUMMARY OF CONSTRUCTION NOISE MONITORING RESULTS – NM2
TABLE 4-5	SUMMARIES OF WATER QUALITY RESULTS – R1B
Table 5-1	SUMMARY OF QUANTITIES OF INERT C&D MATERIALS
TABLE 5-2	SUMMARY OF QUANTITIES OF C&D WASTES
Table 6-1	SITE OBSERVATIONS IN THE REPORTING MONTH
Table 7-1	STATISTICAL SUMMARY OF ENVIRONMENTAL COMPLAINTS
TABLE 7-2	STATISTICAL SUMMARY OF ENVIRONMENTAL SUMMONS
TABLE 7-3	STATISTICAL SUMMARY OF ENVIRONMENTAL PROSECUTION
TABLE 8-1	ENVIRONMENTAL MITIGATION MEASURES

LIST OF ANNEXES

APPENDIX A	SITE LAYOUT PLAN
APPENDIX B	ON-SITE ENVIRONMENTAL MANAGEMENT
APPENDIX C	MASTER CONSTRUCTION PROGRAM AND A THREE MONTHS ROLLING PROGRAM
APPENDIX D	MONITORING LOCATION OF EM&A PROGRAMME
APPENDIX E	CALIBRATION CERTIFICATES
APPENDIX F	METEOROLOGICAL INFORMATION
APPENDIX G	EVENT AND ACTION PLAN
APPENDIX H	MONITORING SCHEDULE IN REPORTING MONTH AND COMING MONTH
APPENDIX I	RESULTS DATA
APPENDIX J	GRAPHICAL PLOTS
APPENDIX K	MONTHLY SUMMARY WASTE FLOW TABLE
A PPENDIX I	INSPECTION CHECKLIST

R0152v3.doc Action-United Environmental Services and Consulting



1. INTRODUCTION

BACKGROUND

- 1.01 The China State Construction Engineering (Hong Kong) Limited (hereinafter "The Contractor") has been awarded by the Drainage Services Department (DSD) the Contract DC/2009/08 Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen Sewage Pumping Station (the Project) in October 2009.
- 1.02 The Project involves construction of about 9km of sewers and rising mains with diameter ranging from 200-1500mm in Yuen Long South and Ha Tsuen areas, a sewage pumping station near Shui Tsiu San Tsuen Road in Yuen Long South, expansion of existing Ha Tsuen Sewage Pumping Station. The site layout plan is shown in *Appendix A*.
- 1.03 The construction of expansion Ha Tsuen Sewage Pumping Station is under a statutory EIA (Register No. AEIAR-072/2003) study for "Upgrading and expansion of San Wai Sewage Treatment Works and expansion of Ha Tsuen Pumping Station" commissioned by the DSD. An Environmental Permit (No. EP-327/2009/A) for upgrading and expansion of Sewage Treatment Works at San Wai (excluded for the Project) and Ha Tsuen Sewage Pumping Station has been obtained by DSD in January 2009 for the relevant works.
- 1.04 According to the Section 25 of the Particular Specification (PS) and the Environmental Permit No. EP-327/2009/A, the scope of monitoring includes air quality, construction noise, water quality and environmental site audit. It should be undertaken in accordance with the Environmental Monitoring and Audit Manual as part of EIA report [AEIAR-072/2003] (hereafter "the EM&A Manual") by an independent Environmental Team (ET). Also, monitoring and audit works for landscaping and visual will be undertaken as part of the EM&A programme.
- 1.05 As the works of the Project has been commenced in different periods of time, the EM&A Report for the Project are split to two separate parts as follows:
 - (a) Expansion Ha Tsuen Sewage Pumping Station (under Environmental Permit No.EP-327/2009/A);
 - (b) Construction of sewers and rising mains with diameter ranging from 200-1500mm in Yuen Long South and Ha Tsuen areas and a sewage pumping station near Shui Tsiu San Tsuen Road in Yuen Long South (the works without Environmental Permit)
- 1.06 Action-United Environmental Services and Consulting (AUES) has been commissioned by the Contractor as the ET to implement the relevant EM&A program. As part of the project EM&A program, baseline monitoring was conducted between 22 December 2009 and 18 January 2010 to determine the ambient environmental conditions before the project commence any major construction works at Ha Tsuen Sewage Pumping Station and it had been verified by IEC and endorsed by EPD.
- 1.07 This is the 11th monthly EM&A Report Expansion of Ha Tsuen Sewage Pumping Station (hereinafter 'this Report') for designated works under Environmental Permit No.EP-327/2009 (hereinafter 'the EP'), covering a period from 1 to 31 December 2010 (hereinafter 'the Reporting Period').

REPORT STRUCTURE

1.08 The Monthly Environmental Monitoring and Audit (EM&A) Report is structured into the following sections:-


SECTION 1	INTRODUCTION
DECTION	INTRODUCTION

SECTION 2 PROJECT ORGANIZATION AND CONSTRUCTION PROGRESS

SECTION 3 SUMMARY OF IMPACT MONITORING REQUIREMENTS

SECTION 4 IMPACT MONITORING RESULTS

SECTION 5 WASTE MANAGEMENT





SECTION 6	SITE INSPECTIONS
SECTION 7	ENVIRONMENTAL COMPLAINTS AND NON-COMPLIANCE
SECTION 8	IMPLEMENTATION STATUES OF MITIGATION MEASURES
SECTION 9	IMPACT FORECAST
SECTION 10	CONCLUSIONS AND RECOMMENDATIONS



2. PROJECT ORGANIZATION AND CONSTRUCTION PROGRESS

PROJECT ORGANIZATION AND MANAGEMENT STRUCTURE

2.01 Organization structure and contact details of the Contractor and relevant parties with respect to the on-site environmental management are shown in *Appendix B*.

CONSTRUCTION PROGRESS

- 2.02 The tentative master construction programs and a three month rolling construction programme are enclosed in *Appendix C*. Also, the major construction activities undertaken in this reporting month are listed below:
 - Installation of temporary shoring system
 - Excavation

SUMMARY OF ENVIRONMENTAL SUBMISSIONS

2.03 Summary of the relevant permits, licences, and/or notifications on environmental protection for this Project in this reporting month is presented in *Table 2-1*.

Table 2-1 Status of Environmental Licenses and Permits

Item	Description	License/Permit Status
1	Environmental Permit (EP-329/2009/A)	Updated on 1 June 2010
	Chemical waste Producer Registration Registration No. 5213-511-C3570-01	Issued on 13 Nov 2009
3	Water Pollution Control Ordinance (Discharge License)	Issued on 12 Jan 2010 Expiry date: 31 Jan 2015
4	Billing Account for Disposal of Construction Waste (Account Number: 700947)	Issued on 7 October 2009

2.04 The baseline monitoring report - *Expansion of Ha Tsuen Sewage Pumping Station (Ref: TCS00491/09/600/R0023v6*) had been verified by IEC and endorsed by EPD.



3. SUMMARY OF IMPACT MONITORING REQUIREMENTS

3.01 The Environmental Monitoring and Audit requirements are set out in the EM&A Manual. Environmental issues such as air quality, construction noise and water quality were identified as the key issues during the construction phase of expansion of Ha Tsuen Pumping Station. Also, monitoring and audit works for landscaping and visual shall be undertaken as part of the EM&A programme.

MONITORING PARAMETERS

3.02 According to the *EM&A Manual*, the environmental aspect implemented by ET has to be included air quality, construction noise and water quality, also the landscape and visual impact to be monitored by a competent landscape architect. The monitoring parameters are summarized in *Table 3-1*.

Table 3-1 Summary of Monitoring Parameters

Environmental Aspect	Parameters		
Air Quality	• 1-hour Total Suspended Particulates (hereinafter '1-hr TSP'); and		
	• 24-hour Total Suspended Particulates (hereinafter '24-hr TSP').		
	• A-weighted equivalent continuous sound pressure level (30min) (hereinafter 'Leq(30min)' during the normal working hours; and		
Construction Noise	• A-weighted equivalent continuous sound pressure level (5min) (hereinafter 'Leq(5min)' for construction work during the restricted hours.		
Water Quality – Local	In Situ Measurement - Dissolved Oxygen (DO) and Turbidity		
Stream Course	Laboratory Analysis - Suspended Solids (SS)		
Water Quality –	In Situ Measurement - pH value		
Effluent Discharge	Laboratory Analysis - SS and Chemical oxygen demand (COD)		
Landscape and Visual	 Vegetation survey undertaken on an "area" basis to identify representative types and species composition; 		
Resources	Assessment of landscape character; and Tree survey report		
	• Tree survey report.		
	The inspection findings will be submitted separately.		

MONITORING LOCATIONS

Monitoring Location Stipulation in the EM&A Manual

3.03 According to *EM&A Manual Sections 2.2.1.18*, 3.4.1.1 & 4.4.1.4, and Figures 2.1, 2.2, 3.1, 3.2 and 4.2, there are four air and noise monitoring stations and one water quality monitoring station identified as sensitivity receivers during construction phase of the Project. For the four designated air and noise monitoring locations, two are located within the San Wai STW and other two are within the existing Ha Tsuen Pumping Station. Also, a local stream course of water quality monitoring station is identified in Tin Shui Wai Nullah. Besides, the area of landscape and visual monitoring is recommended for the entire selected route and within compounds in accordance with *the EM&A Manual Section 6.3.1.1*.

Air Quality

- 3.04 In order to identify and seek for the access for the air monitoring locations designated in the EM&A Manual, site inspection and the premises request about the monitoring locations have been carried out by the Contractor and ET. The designated monitoring location Yeung Chun Pui Care & Attention Home located at Sha Chau Lei Road has been identified, but the premise was granted by CEDD existing project CV/2008/03 for air quality monitoring. Also, the HVS installation at the other one designated air monitoring station Tin Shing Court, the premises is refused by the incorporated owners.
- 3.05 In this case, the alternative location Ho Tak Sum Primary School as one sensitive receiver

mentioned in the EIA Report (Register No. AEIAR-072/2003) is proposed to be the replacement to undertake air quality monitoring during the expansion works of Ha Tsuen Sewage Pumping Station in accordance with the EM&A Manual Clauses 2.2.1.20. Simultaneously, air monitoring at the designated location Yeung Chun Pui Care & Attention Home is proposed to be performed. The proposal and recommendation is agreed by IEC and as endorsed by EPD. The monitoring stations are detailed to list in *Table 3-2* and illustrated in *Appendix D*.

Table 3-2 Air Quality Monitoring Stations

Monitoring Location ID	Identified Address	Remarks	
AM1	Ho Tak Sum Primary School	Replace the Designated Monitoring Station Tin Shing Court	
AM2 Yeung Chun Pui Care & Attention Home		Designated in the EM&A Manual	

3.06 The graphic of air monitoring stations are illustrated in *Appendix D*.

Construction Noise

3.07 Similar to the air monitoring, the construction noise monitoring stations undertaken for EM&A programme is agreed by IEC and as endorsed by EPD. The detailed monitoring stations are listed in *Table 3-3* and shown in *Appendix D*.

Table 3-3 Construction Noise Monitoring Stations

Monitoring Location ID Identified Address		Remarks	
NM1	Ho Tak Sum Primary School	Replace the Designated Monitoring Station Tin Shing Court	
NM2	Yeung Chun Pui Care & Attention Home	e Designated in the EM&A Manual	

Water Quality

3.08 One designated location of a local stream course, Tin Shui Wai Nullah, is proposed to carry out water quality monitoring in accordance with the EM&A Manual. The designated sampling location R1 is located at the midpoint between two pedestrian flyovers athwart Tin Shui Wai Nullah, which are 320 meters apart, there is technical difficulty and safety is concerned. So, a new sampling point located at approximately 160m upstream of the R1 (hereinafter as R1b) was therefore proposed for the local stream impact monitoring. A proposal (submission ref.: TCS00491/09/300/L0080) has been verified by IEC and submitted to EPD with no further comments received.

3.09 The detailed monitoring station is listed in *Table 3-4* and show in *Appendix D*.

Table 3-4 Local Stream Water Quality Monitoring Station

Monitoring Location ID	Remarks
R1b	About 160 meters upstream from the designated location as stipulated in the EM&A Manual. Also, closer the existing Ha Tsuen Pumping Station

3.10 According to the EM&A Manual Section 4.3.1.5, the effluent water quality monitoring are proposed to be carried out at representative discharge point(s) where effluent from the construction sites is discharged into the local water course after being treated in a wastewater treatment system.

Landscape and Visual



3.11 The selected route and area, frequency and requirements of landscape & visual monitoring is proposed by a competent landscape architect.

MONITORING FREQUENCY

3.12 According to the *EM&A Manual* Sections 2.2.1.27, 3.6 and 4.4.1.8, impact monitoring is covered air quality, noise and water quality of local stream course.

Air Quality Monitoring

Parameters: 1-hour TSP and 24-hour TSP.

Frequency: Once every six days for 24-hour TSP and three times every six days for 1-hour

TSP

Duration: Throughout the construction period.

Noise Monitoring

Parameters: One set of Leq(30min) as 6 consecutive Leq(5min) between 0700-1900 hours

on normal weekdays.

Leq (5min), L10 and L90 during the construction undertaken during Restricted Hours (19:00 to 07:00 hours next of normal working day and full day of public

holiday and Sunday)

Frequency: Once every six days during 0700-1900 hours on normal weekdays. Restricted

Hour monitoring should depend on conditions stipulated in Construction Noise

Permit.

<u>Duration</u>: Throughout the construction period.

Water Quality Monitoring of Local Stream Course

<u>Parameters</u>: DO, Turbidity and SS.

<u>Frequency</u>: 3 days per week.

Depths: mid-depth

<u>Duration</u>: Throughout the construction period and the interval between 2 sets of

monitoring is not less than 36 hours

Water Quality Monitoring of Effluent Discharge

Parameters: pH, COD and SS.

<u>Frequency</u>: Depend on conditions stipulated in discharge license under **Section 20** of the

Water Pollution Control Ordinance.

<u>Duration</u>: Throughout the construction period

Landscape and Visual Monitoring

Parameters: Site inspection with broad scope of audit as listed in the EM&A Manuals

Frequency: Once every 2 weeks

<u>Duration</u>: Throughout the construction period

3.13 Post Project Monitoring will be performed at water quality monitoring local stream course. The requirements are same as baseline monitoring are presented below:

Parameters: DO, Turbidity and SS.

<u>Frequency</u>: 3 days per week.

<u>Depths</u>: mid-depth

<u>Duration</u>: 4 weeks and the interval between 2 sets of monitoring is not less than 36 hours

upon completion of the construction activities

MONITORING METHODOLOGY AND EQUIPMENT

Air Quality

3.14 The air quality monitoring equipment for 1-hour and 24-hour TSP are listed in *Table 3-5* and the specification of equipment was submitted before the EM&A programme commencement.



Table 3-5 Air Quality Monitoring Equipment

Equipment	Description	
1-hour TSP		
Portable dust meter	TSI DustTrak Model 8520 / Sibata LD-3 Laser Dust Meter	
24-hour TSP		
High Volume Air Sampler	Grasby Anderson GS 2310 HVS	
Calibration Kit	TISCH Model TE-5025A	

1-hour TSP

- 3.15 The 1-hour TSP monitor is conducted either with a TSI Dust Track Aerosol Monitor Model 8520 or a Sibata LD-3 Laser Dust Meter which is a portable, battery-operated laser photometer. The 1-hour TSP meter provides a real time 1-hour TSP measurement based on 90° light scattering. The 1-hour TSP monitor consists of the following:
 - (a.) A pump to draw sample aerosol through the optic chamber where TSP is measured;
 - (b.) A sheath air system isolates the aerosol in the chamber to keep the optics clean for maximum reliability; and
 - (c.) A built-in data logger compatible with Windows based program to facilitate data collection, analysis and reporting.
- 3.16 The 1-hour TSP meter is used within the valid period as follow manufacturer's Operation and Service Manual.

24-hour TSP

- 3.17 The equipment used for 24-hour TSP measurement is Thermo Andersen Model GS2310 TSP high volume air sampling system, which complied with EPA Code of Federal Regulation, Appendix B to Part 50. The High Volume Air Sampler (HVS) consists of the following:
 - (a.) An anodized aluminum shelter;
 - (b.) A 8"x10" stainless steel filter holder;
 - (c.) A blower motor assembly;
 - (d.) A continuous flow/pressure recorder;
 - (e.) A motor speed-voltage control/elapsed time indicator;
 - (f.) A 7-day mechanical timer; and
 - (g.) A power supply of 220V/50 Hz.
- 3.18 The HVS was operated and calibrated on a regular basis in accordance to the manufacturer's instruction using the NIST-certified standard calibrator (Tisch Calibration Kit Model TE-5025A). One point checking would be carried out in two-month interval while full point checking every six months.
- 3.19 24-hour TSP was collected by the ET on filters of HVS and quantified by a local HOKLAS accredited laboratory, ALS Technichem (HK) Pty Ltd (ALS), upon receipt of the samples. The ET kept all the sampled 24-hour TSP filters in normal air conditioned room conditions, i.e. 70% RH (Relative Humidity) and 25°C, for six months prior to disposal.

Noise

3.20 The equipment for noise monitoring is summarized in *Table 3-6* and the specification was submitted before the EM&A programme commencement.

Table 3-6 Noise Monitoring Equipment

Equipment	Description
Integrating Sound Level Meter	B&K Type 2238 or 2236



Equipment	Description
Calibrator	B&K Type 4231
Portable Wind Speed Indicator	Testo Anemometer

- 3.21 Sound level meters listed above comply with the International Electrotechnical Commission Publications 651: 1979 (Type 1) and 804: 1985 (Type 1) specifications, as recommended in Technical Memorandum (TM) issued under the Noise Control Ordinance (NCO).
- Noise measurements were taken in terms of the A-weighted equivalent sound pressure level (L_{eq}) measured in decibels (dB). Supplementary statistical results (L_{10} and L_{90}) were also obtained for reference.
- 3.23 During the construction noise monitoring, all noise measurements were performed with the meter set to FAST response and on the A-weighted equivalent continuous sound pressure level ($L_{\rm eq}$). $L_{\rm eq(30min)}$ in six consecutive $L_{\rm eq(5min)}$ measurements were used as the monitoring parameter for the time period between 0700-1900 hours on weekdays; and also $L_{\rm eq(15min)}$ in three consecutive $L_{\rm eq(5min)}$ measurements were used as monitoring parameter for other time periods (e.g. during restricted hours).
- 3.24 No noise extension cable was used to link the microphone with sound level meter for the measurement. The microphone was set about 1.2m height above ground and oriented such that it was pointed to the site with the microphone facing perpendicular to the line of sight. The windshield was fitted for all measurements. The monitoring locations AM1 and AM2 were normally set in a free field situation.
- 3.25 In prior of impact noise measurement, the accuracy of the sound level meter was checked using an acoustic calibrator generating a known sound pressure level at a known frequency. The checking was performed before and after the noise measurement. Also, the wind speed was checked with a portable wind speed meter. No fog and rain were encountered during the noise measurement, and the wind speed and gusts were also below 5m/s and 10m/s respectively

Water quality of Local Stream Course

3.26 The equipment for water monitoring is summarized in *Table 3-7* and the specifications were submitted before the EM&A programme commencement.

Table 3-7 Water Quality Monitoring Equipments

Equipment	Model / Description	
Water Sampler	Teflon bailer / bucket	
Thermometer & DO meter YSI 550A DO Meter		
Turbidimeter	Hach 2100p	
Sample Container	High density polythene bottles (provided by laboratory)	
Storage Container	'Willow' 33-litter plastic cool box	

3.27 Water quality monitoring was conducted at mid-depth of the water column.

Dissolved Oxygen (DO)

3.28 A portable YSI 550A DO Meter was used for in-situ DO measurement, which automates the measurements of temperature, dissolved oxygen and dissolved oxygen saturation simultaneously. The DO meter is capable of measuring DO in the range of 0 - 20 mg/L and 0 - 200 % saturation. Before each round of monitoring, the dissolved oxygen probe is calibrated by the wet bulb method with distilled water. Calibration of the equipment are performed by ALS on quarterly basis.

Turbidity

3.29 A portable Hach 2100p turbidity Meter was used for in-situ turbidity measurement. The turbidity meter is capable of measuring turbidity in the range of 0 – 1000 NTU. Calibration of the equipment is performed by ALS on quarterly basis.



Suspended Solids (SS)

3.30 SS will be determined by ALS upon receipt of the water samples using HOKLAS accredited analytical methods namely ALS Method EA-025.

Water Sampler

3.31 Water samples were collected by the ET using a plastic sampler, which has a volume of not less than 2 litres and can be sealed at both ends with cups to prevent metal contamination. The sampler was rinsed before collection with the sample to be taken. The water sample was collected at mid-depth level at the selected monitoring location for SS determination.

Sample Container

3.32 Water sample was contained in screw-cap PE (Poly-Ethylene) sampling bottle (1,000ml) to be provided by HOKLAS accredited laboratory ALS. Where appropriate, the sampling bottle was rinsed with the water to be contained in prior. Water sample was then transferred from the sampler to the sample bottles to 95% bottle capacity to allow possible volume expansion during delivery and storage.

Sample Storage

3.33 A 'Willow' 33-litter plastic cool box packed with ice was used to preserve the collected water samples prior to arrival at the laboratory. The water temperature of the cool box was maintained at a temperature as close to 4°C as possible without being frozen. Samples were delivered to laboratory within 24 hours and analyzed within 2 days of delivery or within the holding time as advised by the laboratory.

EQUIPMENT CALIBRATION

- 3.34 Calibration of the HVS was performed upon installation in accordance with the manufacturer's instruction using the NIST-certified standard calibrator (Tisch Calibration Kit Model TE-5025A). The calibration data are properly documented and the records are maintained by ET for future reference.
- 3.35 The 1-hour TSP meter was calibrated by the supplier prior to purchase. Zero response of the equipment was checked before and after each monitoring event. In-house calibration with the High Volume Sampler (HVS) in same condition was undertaken in yearly basis.
- 3.36 The sound level meter and calibrator are calibrated and certified by a laboratory accredited under HOKLAS or any other international accreditation scheme at yearly basis.
- 3.37 All updated calibration certificates of the monitoring equipment used for the impact monitoring program in this Reporting Month are attached in *Appendix E*.

METEOROLOGICAL INFORMATION

3.38 The meteorological information in this reporting month was downloaded from Lau Fau Shan Station of the Hong Kong Observatory (HKO) and presented in *Appendix F*.

DATA MANAGEMENT AND DATA QA/QC CONTROL

- 3.39 The impact monitoring data are handled by the ET's systematic data recording and management, which complies with in-house Quality Management System. Standard Field Data Sheets (FDS) are used in the impact monitoring program.
- 3.40 The monitoring data recorded in the equipment e.g. 1-hour TSP meters and noise meters are downloaded directly from the equipment at the end of each monitoring day. The downloaded monitoring data are input into a computerized database properly maintained by the ET. The laboratory results or water quality in-situ measurement records are input directly into the computerized database and QA/QC checked by personnel other than those who input the data.
- 3.41 For monitoring activities that require laboratory analysis, the local laboratory follows the QA/QC requirements as set out under the HOKLAS scheme for all laboratory testing.



DETERMINATION OF ACTION/LIMIT (A/L) LEVELS

3.42 According to the EM&A Manual, the air quality, construction noise and water quality criteria were set up, namely Action and Limit levels are listed in *Tables 3-8*, *3-9* and *3-10* as below:-

Table 3-8 Action and Limit Levels for Air Quality Monitoring

Monitoring	itoring Action Level (µg/m³)		Limit Level (μg /m³)	
Location	1-hour	24-hour	1-hour	24-hour
AM1	305	162	> 500	> 260
AM2	310	190	> 500	> 260

Table 3-9 Action and Limit Levels for Construction Noise

Monitoring	Action Level	Limit Level in dB(A)	
Location	0700-1900 hrs on normal weekdays		
NM1	When one or more documented complaints are	70 dB(A) of Leq(30min) during normal hours from 0700 to 1900 hours on normal weekdays, reduced to 65 dB(A) during school examination periods	
NM2	received	70 dB(A) of Leq(30min) during normal hours from 0700 to 1900 hours on normal weekdays	

Note: * Reduces to 65 dB(A) during the school examination periods.

Table 3-10 Action and Limit Levels for a Local Stream Water Quality Monitoring (R1b)

Parameter	Action Level	Limit Level
DO (mg/L)	4.6	4 mg/L or 40% saturation at 15°C
Turbidity (NTU)	15.6	16.2
SS (mg/L)	31.5	31.9

3.43 Should non-compliance of the environmental quality criteria occurs, remedial actions will be triggered according to the Event and Action Plan enclosed in *Appendix G*.



4. IMPACT MONITORING RESULTS

4.01 Further to the Contractor's instructions, the EM&A program commenced on 8 February 2010. The monitoring schedule was issued to relevant parties in prior impact monitoring. The monitoring activities undertaken in this reporting month is listed in *Appendix H*. The monitoring results are presented in the following sub-sections.

RESULTS OF AIR QUALITY MONITORING

4.02 In this reporting period, a total of 12 events of 24-hour TSP monitoring and 42 events of 1-hour TSP monitoring were undertaken and the results are summarized in *Tables 4-1 and 4-2*. The 24-hour TSP raw data sheets are shown in *Appendix I*. Also, the graphical plots for the 24-hour and 1-hour TSP monitoring result are shown in *Appendix J*.

Table 4-1 Summary of 24-hour and 1-hour TSP Monitoring Results – AM1

	24-hour		1-hour TSP (μg/m³)			
Date	TSP $(\mu g/m^3)$	Date	Start Time	1 st hour measured	2 nd hour measured	3 rd hour measured
6-Dec-10	98	1-Dec-10	9:03	84	71	86
11-Dec-10	147	7-Dec-10	13:31	87	101	94
17-Dec-10	64	13-Dec-10	9:04	82	96	87
23-Dec-10	84	18-Dec-10	13:12	86	77	80
28-Dec-10	76	24-Dec-10	13:06	69	76	75
30-Dec-10	83	28-Dec-10	9:09	69	66	73
		31-Dec-10	15:48	100	103	96
Average (Range)	92 (64 – 147)	Average 76 (Range) (62 – 93)				

Table 4-2 Summary of 24-hour and 1-hour TSP Monitoring Results – AM2

	24-hour	1-hour TSP (μg/m³)				
Date	TSP (μg/m³)	Date	Start Time	1 st hour measured	2 nd hour measured	3 rd hour measured
6-Dec-10	87	1-Dec-10	9:13	92	90	87
11-Dec-10	115	7-Dec-10	13:59	96	108	100
17-Dec-10	55	13-Dec-10	9:16	93	103	98
23-Dec-10	81	18-Dec-10	13:59	94	88	90
28-Dec-10	83	24-Dec-10	13:55	78	86	75
30-Dec-10	88	28-Dec-10	9:16	73	75	71
		31-Dec-10	15:31	111	124	129
Average	85	Avera	ge		93	
(Range)	(55 – 115)	(Rang	e)		(71 - 129)	

- 4.03 As shown in *Tables 4-1* and *4-2*, 1-hour and 24-hour TSP monitoring results fluctuated well below the Action Level in this Reporting Period.
- 4.04 The meteorological data during the impact monitoring days are summarized in *Appendix F*.

RESULTS OF CONSTRUCTION NOISE MONITORING

4.05 The noise monitoring results conducted at the designated locations are summarized in *Tables 4-3* and *4-4*. The sound level were set up in a free field situation and, therefore, a façade correction of +3 dB(A) was added according to acoustical principles and EPD guidelines.



Table 4-3 Summary of Construction Noise Monitoring Results – NM1

Date	Start Time	1 st Leq _{5min}	2 nd Leq _{5min}	$\begin{matrix} 3^{rd} \\ Leq_{5min} \end{matrix}$	4 th Leq _{5min}	5 th Leq _{5min}	6 th Leq _{5min}	Leq _{30min}	Corrected* Leq _{30min}
1-Dec-10	10:23	67.7	65.4	68.9	64.6	65.2	64.1	66.3	69.3
7-Dec-10	13:10	69.6	64.2	62.1	64.9	64.4	66.9	66.0	69.0
13-Dec-10	9:16	64.6	65.1	64.8	64.9	65.1	63.8	64.7	67.7
18-Dec-10	9:16	63.7	62.8	63.2	61.4	60.6	60.9	62.3	65.3
24-Dec-10	13:06	61.3	59.6	62.4	60.1	59.7	60.8	60.8	63.8
28-Dec-10	9:46	64.8	66.3	64.5	62.1	63.4	62.2	64.1	67.1
31-Dec-10	17:23	53.6	54.2	53.8	53.8	54.3	54.0	54.0	57.0
Limit L	evel				-			> 70	dB(A)

^(*) A façade correction of +3 dB(A) has been added according to acoustical principles and EPD guidelines.

Table 4-4 Summary of Construction Noise Monitoring Results – NM2

Date	Start Time	1 st Leq _{5min}	2 nd Leq _{5min}	3 rd Leq _{5min}	4 th Leq _{5min}	5 th Leq _{5min}	6 th Leq _{5min}	Leq _{30min}	Corrected* Leq _{30min}
1-Dec-10	11:07	67.2	62.7	62.3	63.7	62.9	63.6	64.1	67.1
7-Dec-10	13:51	64.0	64.7	65.1	65.4	64.4	61.3	64.3	67.3
13-Dec-10	9:50	64.8	66.0	62.5	63.9	63.8	62.8	64.1	67.1
18-Oct-10	9:59	63.6	64.3	61.7	63.6	62.4	64.6	63.5	66.5
24-Dec-10	13:52	64.2	63.4	62.6	62.7	62.3	61.9	62.9	65.9
28-Dec-10	10:31	66.4	64.8	62.9	62.3	64.8	66.1	64.8	67.8
31-Dec-10	16:43	66.4	65.7	66.2	63.4	65.3	64.2	65.3	68.3
Limit L	evel							> 70	dB(A)

^(*) A façade correction of +3 dB(A) has been added according to acoustical principles and EPD guidelines.

4.06 It was noted that no noise complaint (which is an Action Level exceedance) was received. In view of the results shown in *Tables 4-3* and *4-4*, No Action/Limit level exceedance was recorded during the reporting month. No corrective action was therefore required. The graphical plot is shown in *Appendix J*.

RESULTS OF WATER QUALITY MONITORING - LOCAL STREAM COURSE

- 4.07 In this Reporting Month, a total of 12 sampling days were performed for water quality monitoring at R1b of the local stream course, Tin Shui Wai Nullah. The monitoring results including in-situ measurements and laboratory testing results are provided in *Appendix I*. The graphical plots are shown in *Appendix J*.
- 4.08 Monitoring results of 3 key parameters: dissolved oxygen (DO), turbidity and suspended solids (SS) in this Reporting Month, are summarized in *Table 4-5*.

Table 4-5 Summaries of Water Quality Results – R1b

Sampling date	DO conc. (mg/L)	Turbidity (NTU)	SS (mg/L)
1-Dec-10	20.4	9.1	22.0
3-Dec-10	18.2	17.3	10.0
7-Dec-10	16.8	20.0	35.0
9-Dec-10	15.1	13.9	21.0
11-Dec-10	16.7	9.8	18.0
13-Dec-10	18.0	11.9	25.0
16-Dec-10	16.9	12.3	24.0
18-Dec-10	18.2	11.9	31.0
20-Dec-10	16.9	11.3	20.0
22-Dec-10	22.3	11.1	20.0
24-Dec-10	19.6	10.1	18.0
29-Dec-10	19.4	8.7	20.0
31-Dec-10	20.2	10.5	15.0



Remarks: Bold indicated Limit Level exceedance Bold and Italic indicated Action Level exceedance

- 4.09 In this Reporting Period, two Limit Level exceedances in Turbidity and one Limit Level exceedance in Suspended Solids were resulted from the samples collected at location R1b. NOEs were issued to relevant parties upon confirmation of the results; The results was found that such exceedances were not project related.
- 4.10 During the Reporting Period, field measurements showed that water temperature and pH value of the local stream are within 10.9° C to 24.9° C, and 8.3 to 9.9 respectively.

RESULTS OF LANDSCAPE AND VISUAL IMPACT

4.11 The landscape and visual impacts monitoring results and findings will be submitted separately as a stand-alone document.



5. WASTE MANAGEMENT

5.01 Waste management was carried out by an on-site Environmental Officer or an Environmental Supervisor from time to time.

RECORDS OF WASTE QUANTITIES

- 5.02 All types of waste arising from the construction work are classified into the following:
 - Construction & Demolition (C&D) Material;
 - Chemical Waste;
 - General Refuse; and
 - Excavated Soil.
- 5.03 The quantities of waste for disposal in this Reporting Period are summarized in *Tables 5-1* and 5-2 and the Monthly Summary Waste Flow Table is shown in *Appendix K*. Whenever possible, materials were reused on-site as far as practicable.

Table 5-1 Summary of Quantities of Inert C&D Materials

Type of Waste	Quantity	Disposal Location
C&D Materials (Inert) (m ³)	0	-
Reused in this Contract (Inert) (m ³)	0	-
Reused in other Projects (Inert) (m ³)	0	-
Disposal as Public Fill (Inert) (m ³)	2636	Tuen Mun Area 38

Table 5-2 Summary of Quantities of C&D Wastes

Type of Waste	Quantity	Disposal Location
Recycled Metal (kg)	0	-
Recycled Paper / Cardboard Packing (kg)	0	-
Recycled Plastic (kg)	0	-
Chemical Wastes (kg)	0	-
General Refuses (m ³)	3	NENT

- 5.04 There was no site effluent or surface runoff discharged in this monthly period.
- 5.05 To control over the site performance on waste management, the Contractor shall ensure that all solid and liquid waste management works are in full compliance with the relevant license/permit requirements, such as the effluent discharge licence and the chemical waste producer registration. The Contractor is also reminded to implement the recommended environmental mitigation measures according to the EM&A Manual based on actual site conditions.



6. SITE INSPECTIONS

- 6.01 According to the Environmental Monitoring and Audit Manual, the environmental site inspection should be formulated by ET Leader. Regular environmental site inspections had been carried out by ET joined with the Contractor and ER to confirm the environmental performance. During this Reporting Period, the joint site inspection was undertaken on 7, 14, 21 and 28 December 2010 to evaluate the site environmental performance. No non-compliance was noted.
- 6.02 Observations for the site inspections and monthly audit within this Reporting Period are summarized in *Table 6-1* and inspection checklist is attached in *Appendix L*.

Table 6-1 Site Observations in the Reporting Month

Date	Findings / Deficiencies	Follow-Up
7 December 2010	 Sedimentation tank at Shui Tsui San Tsuen Pumping Station was full of debit, the contractor was reminded to clean to maintain the tank efficiency. 	Rectified before the next inspection
	At Shui Tsiu San Tsuen Pumping Station, although drip trays for generator and oil drums are observed, the contractor was reminded to upgrade the mitigation measures to prevent oil spillage during fueling procedures.	Rectified before the next inspection
14 December 2010	 Sand and mud was observed at the site entrance, the contractor was reminded to clean to maintain the public area around the site area clean and tidy. 	Rectified before the next inspection
21 December 2010	It was reminded that the Contractor should provide proper impermeable cover to stockpile of materials.	Rectified before the next inspection
	Accumulation of stagnant water was observed on site. The Contractor was reminded to properly clear the water.	Rectified before the next inspection
	Waste plastic barriers were found onsite. The contractor was reminded to properly dispose the construction waste generated from the site.	Rectified before the next inspection
28 December 2010	Oil leakage from the air compressor was observed at Tai Shiu Ha works area, the contractor was requested to clean up immediately to prevent ant contamination.	Rectified before the 11 Jan 2011 inspection



7. ENVIRONMENTAL COMPLAINTS AND NON-COMPLIANCE

ENVIRONMENTAL COMPLAINT, SUMMONS AND PROSECUTION

7.01 No environmental complaint, summons and prosecution was received in this Reporting Period. The statistical summary table of environmental complaint is presented in *Tables 7-1*, 7-2 and 7-3.

Table 7-1 Statistical Summary of Environmental Complaints

Donauting Davied	Environmental Complaint Statistics					
Reporting Period	Frequency	Cumulative	Complaint Nature			
8 Feb – 31 Jul 2010	0	0	NA			
1 Jul – 30 Sep 2010	0	0	NA			
1 Oct – 30 Nov 2010	0	0	NA			
1 Dec - 31 Dec 2010	0	0	NA			

Table 7-2 Statistical Summary of Environmental Summons

D 4' D 1	Environmental Complaint Statistics					
Reporting Period	Frequency	Cumulative	Complaint Nature			
8 Feb – 31 Jul 2010	0	0	NA			
1 Jul – 30 Sep 2010	0	0	NA			
1 Oct – 30 Nov 2010	0	0	NA			
1 Dec - 31 Dec 2010	0	0	NA			

Table 7-3 Statistical Summary of Environmental Prosecution

Donauting David	Environmental Complaint Statistics				
Reporting Period	Frequency	Cumulative	Complaint Nature		
8 Feb – 31 Jul 2010	0	0	NA		
1 Jul – 30 Sep 2010	0	0	NA		
1 Oct – 30 Nov 2010	0	0	NA		
1 Dec - 31 Dec 2010	0	0	NA		



8. IMPLEMENTATION STATUS OF MITIGATION MEASURES

8.01 The environmental mitigation measures that recommended in the Environmental Monitoring and Audit Manual covered the issues of dust, noise and waste and they are summarized as following:

Dust Mitigation Measure

- (a) The contractor shall frequently clean and water the site to minimize fugitive dust emissions.
- (b) Effective water sprays shall be used during the delivery ad handling of aggregate, and other similar materials, when dust is likely to be created and to dampen all sited material during dry and windy weather.
- (c) Watering of exposed surfaces shall be exercised as often as possible depending on the circumstance.
- (d) Areas within the site where there is regular movement of vehicles must be regularly watered as often as necessary for effective suppression of dust or as often as directed by the Engineer.
- (e) Where dusty materials are being discharged to vehicle from a conveying system at a fixed transfer point, a three-sided roofed enclosure with a flexible curtain across the entry shall be provided. Exhausted fans shall be provided for this enclosure and vented to a suitable fabric filer system.
- (f) The Contractor shall restrict all motorized vehicles within the site, excluding those on public roads, to a maximum speed of 5km per hour and confine haulage and delivery vehicles to designated roadways inside the site.
- (g) Wheel washing facilities shall be installed and used by all vehicles leaving the site. No earth, mud, debris, dust and the like shall be deposited on public roads, water in wheel cleaning facility shall be changed at frequent intervals and sediments shall be removed regularly. The Contractor shall submit detailed proposals for the wheel cleaning facilities to the Engineer prior to construction of the facility. Such wheel washing facilities shall be usable prior to any earthworks excavating activity in the site.
- (h) Any material dropped in the roads will need to be cleaned up immediately to prevent dust nuisance.

Noise Mitigation Measure

- (a) During construction of the Project, temporary noise barriers should be used in order to reduce the noise impacts emanating from the construction sites on nearby Noise Sensitive Receivers (NSRs). The location of the temporary noise barriers should be along the site boundary of the expanded portion of Ha Tsuen Pumping Station.
- (b) Noisy equipment and activities should be sited by the Contractor as far from close-proximity sensitive receivers as practical. Prolonged operation of noisy equipment close to dwellings and schools should be avoided.
- (c) The Contractor should minimize construction noise exposure to the schools. Especially during examination periods, the Contractor should not carry out any construction activities. Activities shall be restricted to transit movements by construction vehicles during this period.
- (d) Noisy plant or processes should be replaced by quieter alternatives where possible. Silenced diesel and gasoline generators and power units, as well as silenced and super-silenced air compressors should be used.
- (e) Noisy activities should be scheduled to minimize exposure of nearby sensitive receivers to high levels of construction noise. For example, noisy activities can be scheduled for midday, or at times coinciding with periods of high background noise (such as during peak traffic hours).
- (f) Idle equipment should be turned off or throttled down. Noisy equipment should be properly maintained and used no more often than is necessary.
- (g) The power units of non-electric stationary plant and earth-moving plant should be quietened



- by vibration isolation and partial or full acoustic enclosures for individual noise-generating components.
- (h) Construction activities should be planned so that parallel operation of several sets of equipment close to a given receiver is avoided, thus reducing the cumulative impacts between operations. The numbers of operating items of powered mechanical equipment should be minimized.
- (i) Construction plant should be properly maintained (well-greased, damage and worn parts promptly replaced) and operated. Construction equipment often has silencing measures built in or added on, e.g. bulldozer silencers, compressor panels, and mufflers. Silencing measures should be properly maintained and utilized. Where possible, rubber or damping materials should be introduced between metal panels to avoid rattle and reverberation of noise.
- (j) Equipment known to emit sound strongly in one direction, should where possible, be oriented so that the noise is directed away from nearby NSRs.
- (k) Material stockpiles and other structures (such as site offices) should be effectively utilized, where practicable, to screen noise from on-site construction activities.
- (1) The Contractor should devise, arrange methods of working and carry out the works in such manner as to minimize noise impacts on the surrounding environment, and should provide experienced personnel with suitable training to ensure that these measures are implemented properly.

Water Quality Mitigation Measures

- (a) Exposed stockpiles should be covered with tarpaulin or impervious sheets before a rainstorm occurs;
- (b) The exposed soil surfaces should also be properly protected to minimise dust emission;
- (c) The stockpiles of materials should be placed in the locations away from the drainage channel so as to avoid releasing materials into the channel;
- (d) Wheel washing facilities should be provided at site exits to ensure that earth, mud and debris would not be carried out of the works areas by vehicles;
- (e) Provision of site drainage systems and treatment facilities would be required to minimize the water pollution;
- (f) A discharge licence needs to be applied from EPD for discharging effluent from the construction site;
- (g) The treated effluent quality is required to meet the requirements specified in the discharge licence;
- (h) Provision of chemical toilets is required to collect sewage from workforce. The chemical toilets should be cleaned on a regular basis;
- (i) Wastewater generated from kitchens should be discharged to public foul sewers or collected in a temporary storage tank if connection to public foul sewers is not feasible;
- (j) A licensed waste collector should be employed to clean the chemical toilets and temporary storage tank on a regular basis;
- (k) Illegal disposal of chemicals should be strictly prohibited;
- (l) Registration as a chemical waste producer is required if chemical wastes are generated and need to be disposed of. The Waste Disposal Ordinance (Cap 354) and its subsidiary regulations in particular the Waste Disposal (Chemical Waste) (General) Regulation should be observed and complied with for control of chemical wastes;
- (m) Disposal of chemical wastes should be carried out in compliance with the Waste Disposal Ordinance. The Code of Practice on the Packaging, Labelling and Storage of Chemical Wastes published under the Waste Disposal Ordinance should be used as a guideline for handing chemical wastes; and
- (n) The impact from accidental spillage of chemicals can be effectively controlled through good management practices.



Waste Mitigation Measures

- (a) Segregation and storage of different types of waste in different containers, skips or stockpiles to enhance reuse or recycling of materials and their proper disposal;
- (b) To encourage collection of aluminium cans by individual collectors, separate labelled bins should be provided to segregate this waste from other general refuse generated by the workforce;
- (c) Any unused chemicals or those with remaining functional capacity should be recycled;
- (d) Prior to disposal of C&D waste, it is recommended that wood, steel and other metals be separated for re-use and/or recycling and inert waste utilised as fill material to minimise the quantity of waste to be disposed of to landfill;
- (e) Proper storage and site practices to minimise the potential for damage or contamination of construction materials; and
- (f) Plan and stock construction materials carefully to minimise amount of waste generated and avoid unnecessary generation of waste.

Landscape and Visual Mitigation Measures

- (a) Prior to construction work the detailed tree survey should have been completed and, if appropriate, trees to be transplanted moved to their final positions.
- (b) The transplants and existing trees to be retained should be properly protected from damage by stout hoarding positioned as directed by a qualified Landscape Architect.
- (c) Hoarding will help screen the construction work from the view of passers by.
- (d) Typically a minimum of 4 months should be allowed prior to construction to prepare trees for transplanting.
- (e) During construction regular inspections of the retained and transplanted trees should be made to ensure the effectiveness of the hoarding.
- (f) Any topsoil excavated in the course of the works shall be stored and protected on site for reuse for restoration and screen planting works.



8.02 The Contractor had been implementing the required environmental mitigation measures according to the Environmental Monitoring and Audit Manual subject to the site condition. Environmental mitigation measures generally implemented by the Contractor in this Reporting Period are summarized in *Table 8-1*.

Table 8-1 Environmental Mitigation Measures

Issues	Environmental Mitigation Measures
Water	Wastewater were appropriately treated by treatment facilities;
Quality	• Drainage channels were provided to convey run-off into the treatment facilities;
	Drainage systems were regularly and adequately maintained.
	• De-silting facility was provided to treat the discharged water; also the treated
	water is reused for spraying the road surface;
	• Exposed stockpiles and exposed soil surfaces were covered with tarpaulin or
	impervious sheets to minimise dust emission;
	• The stockpiles of materials were placed in the locations away from the drainage channel so as to avoid releasing materials into the channel;
	 Wheel washing facilities should has been provided at site exits to ensure that
	earth, mud and debris would not be carried out of the works areas by vehicles;
	• Provision of site drainage systems and treatment facilities would be required to minimize the water pollution;
	• A discharge licence was applied from EPD for discharging effluent from the construction site;
	A licensed waste collector have been applied from EPD;
	• Illegal disposal of chemicals should be strictly prohibited; and
	Registration as a chemical waste producer have been applied from EPD
Air Quality	• Regular watering to reduce dust emissions from all exposed site surface, particularly during dry weather;
	• Frequent watering for particularly dusty construction areas and areas close to air sensitive receivers;
	• Cover all excavated or stockpile of dusty material by impervious sheeting or sprayed with water to maintain the entire surface wet;
	• Public roads around the site entrance/exit had been kept clean and free from dust;
	• Tarpaulin covering of any dusty materials on a vehicle leaving the site;
	• Water sprinkler system is provided at haul road to reduce dust emissions during
	the vehicles passing through the haul road'
	• The vehicle speed within the site is limited to 5km/hr;
	Wheel washing facilities have been provided at the site exit
Noise	• Good site practices to limit noise emissions at the sources;
	• Use of quite plant and working methods according to EP-329/2009;
	• Use of site hoarding with noise barriers to screen noise at ground level of NSRs;
	• Use of shrouds/temporary noise barriers to screen noise from relatively static
	PMEs according to EP-329/2009;
	• Use of temporary noise barrier with surface density 7kg/m² to be assumed that the noise reduction is 10 dB(A) for stable plants and 5dB(A) for movable plant
	in accordance with approved EIA Report Appendix 4A Table 4A3.2;
	• Idle equipment are turned off or throttled down;
	• No construction works shall be undertaken during school examination period in the Ha Tsuen Pumping Station according to EP-329/2009; and
	• Alternative use of plant items within one worksite, where practicable.



Issues	Environmental Mitigation Measures				
Waste and Chemical	• Excavated material should be reused on site as far as possible to minimize off-site disposal. Scrap metals or abandoned equipment should be recycled if				
Management					
	 Waste arising should be kept to a minimum and be handled, transported and disposed of in a suitable manner; 				
	 The Contractor should adopt a trip ticket system for the disposal of C&D materials to any designed public filling facility and/or landfill; and 				
	 Chemical waste shall be handled in accordance with the Code of Practice on the Packaging, Handling and Storage of Chemical Wastes. 				
	• Segregation and storage of different types of waste in different containers, skips or stockpiles to enhance reuse or recycling of materials and their proper disposal;				
	 To encourage collection of aluminium cans by individual collectors, separate labelled bins should be provided to segregate this waste from other general refuse generated by the workforce; 				
	 Any unused chemicals or those with remaining functional capacity should be recycled; 				
	 Prior to disposal of C&D waste, it is recommended that wood, steel and other metals be separated for re-use and/or recycling and inert waste utilised as fill material to minimise the quantity of waste to be disposed of to landfill; 				
	 Proper storage and site practices to minimise the potential for damage or contamination of construction materials; and 				
	 Plan and stock construction materials carefully to minimise amount of waste generated and avoid unnecessary generation of waste. 				
Landscape	The landscape and visual impacts monitoring results and findings will be submitted				
and Visual	in the stand-alone document.				
General	The site was generally kept tidy and clean.				



9. IMPACT FORCAST

KEY ISSUES FOR THE COMING MONTH

- 9.01 Key issues to be considered in the coming month include:
 - Implementation of dust suppression measures at all times;
 - Potential wastewater quality impact due to surface runoff;
 - Potential fugitive dust quality impact due from the dry/loose/exposure soil surface/dusty material;
 - Disposal of empty engine oil containers within site area;
 - Ensure dust suppression measures are implemented properly;
 - Sediment catch-pits and silt removal facilities should be regularly maintained;
 - Management of chemical wastes;
 - Discharge of site effluent to the nearby nullah or storm drainage, stockpiling or disposal of materials, and any dredging or construction area at this area are prohibited;
 - Follow-up of improvement on general waste management issues; and
 - Implementation of construction noise preventative control measures.



10. CONCLUSIONS AND RECOMMENTATIONS

CONCLUSIONS

- 10.01 This is the 11th monthly EM&A report, covering the construction period from 1 to 31 December 2010 (the Reporting Period).
- 10.02 No 1-hour TSP and 24-hour monitoring results that triggered the Action or Limit Level was recorded in this Reporting Period.
- 10.03 No noise complaint (which is an Action Level exceedance) was received and no construction noise measurement results that exceeded the Limit Level were recorded in this Reporting Period. No NOEs or the associated corrective actions were therefore issued.
- 10.04 In this Reporting Period, three Limit Level exceedances was recorded in the water quality monitoring. Investigation report was conducted and it was concluded that the exceedance was not related to the works under the Project.
- 10.05 No documented complaint, notification of summons or successful prosecution was received.
- 10.06 The ET had carried out a site inspection on **7**, **14**, **21**, **28 December 2010**. No non-compliance was observed during the inspections. In general, it was reminded that good housekeeping practice should be maintained; beside, the accumulation of stagnant water should be removed to or applied larvidical oil to prevent mosquitoes breeding during wet season. The environmental performance of the Project was therefore considered satisfactory.
- 10.07 The landscape and visual impacts monitoring results and findings will be submitted separately as a stand-alone document. The Contractor is reminded that the landscape and visual impacts site audit shall be carried out by a competent landscape architect, as a member of ET to implement the EM&A programme.


RECOMMENDATIONS

- 10.08 During dry season, special attention should be paid to the dust mitigation measures to avoid fugitive dust emissions from loose soil surface or haul road. Nevertheless, mitigation measures implemented for control the surface runoff including wheel wash facilities, covering of the loose soil surface or stockpile with tarpaulin sheet, etc., should be properly maintained to prevent any muddy or sandy runoff from the loose soil surface overflow on the site boundary; and also with construction noise and other environmental issues stipulated in the Environmental Monitoring and Audit Manual.
- 10.09 To control the site performance on waste management, the Contractor shall ensure that all solid and liquid waste management works are fully in compliance with the relevant license/permit requirements, such as the effluent discharge license and the chemical waste producer registration. The Contractor is also reminded to implement the recommended environmental mitigation measures according to the Environmental Monitoring and Audit Manual.



Appendix A

Site Layout Plan






Appendix B

On-site environmental management







Contact Details of Key Personnel

Organization	Project Role	Name of Key Staff	Tel No.	Fax No.
DSD	Employer	Mr. W. M. Lee		2827-8700
AECOM	Engineer's Representative	Mr. Alan Lee	9706 9568	2472 0132
Hyder	Independent Environmental Checker	Dr. F C Tsang	2911 2730	2805 5028
CSCE	Project Manager	Mr. Lu Xingmin	2472 0113	2472-0229
CSCE	Site Agent	Mr. Chan See Wai	2472 0113	2472-0229
CSCE	Site Engineer	Mr. Poon Kwong Keung	2472 0113	2472-0229
CSCE	Environmental Officer	Mr. Lee Tak Tai	2472 0113	2472-0229
CSCE	Safety Officer	Mr. Ng Ka Po	2472 0113	2472-0229
AUES	Environmental Team Leader	Mr. T. W. Tam	2959-6059	2959-6079
AUES	Environmental Consultant	Ms. Nicola Hon	2959-6059	2959-6079
AUES	Assistance Environmental Consultant	Mr. Ray Cheung	2959-6059	2959-6079
AUES	Team Supervisor	Mr. Ben Tam	2959-6059	2959-6079

Legend:

DSD (Employer) – Drainage Services Department

AECOM (Engineer) – AECOM

CSCE (Main Contractor) - China State Construction Engineering (Hong Kong) Ltd

Hyder (IEC) – Hyder Consulting Limited

AUES (ET) – Action-United Environmental Services & Consulting


R0152v3.doc Appendix




Appendix C

Master construction program

Contract No. DC/2009/08 Construction of Yuen Long South Branch Sewers and Expansion of HTS Pumping Station










Appendix D

Monitoring Location of EM&A Programme






DSD Contract No. DC/2009/08 – Construction of Yuen Long South Branch Sewers And Extension of Ha Tsuen Sewage Pumping Station

Proposed Water Quality Monitoring Location

AUES





Appendix

Appendix E

Calibration certificates



Equipment Calibration Certificates List

Items	Aspect	Description of Equipment	Date of Calibration	Date of Next Calibration
1		Thermo Andersen Model GS2310 TSP high volume air sampling system (AM1 - Yeung Chun Pui Care & Attention Home)	2 Dec 10	2 Feb 11
2		Thermo Andersen Model GS2310 TSP high volume air sampling system (AM2 - Ho Tak Sum Primary School)	2 Dec 10	2 Feb 11
3	Air	Calibration Kit TISCH Model TE-5025A –Orifcs ID 1612 and Rootsmeter S/N 9833620	2 Jun 10	2 Jun 11
4		TSI DustTrak Model 8520 (Serial Number 21060)	2 Dec 10	2 Dec 11
5		TSI DustTrak Model 8520 (Serial Number 23080)	2 Dec 10	2 Dec 11
6	Noise	Bruel & Kjaer 4231 Acoustical Calibrator (Serial Number 2326408)	26 Apr 10	26 Apr 11
7	Noise	Bruel & Kjaer 2238 Integrating Sound Level Meter (Serial Number 2285722)	26 Apr 10	26 Apr 11
8		YSI 550A (Serial No. 05F2063AZ)	19 Oct 10	19 Jan 11
9	Water	Extech pH Meter EC500 (Serial No. CE133298)	19 Oct 10	19 Jan 11
10		Turbidimeter HACH 2100p (Serial No. 950900008735)	19 Oct 10	19 Jan 11

Note: *Calibration certificates will only be provided when monitoring equipment is re-calibrated or new.

R0152v3.doc Appendix



Sun Creation Engineering Limited Calibration and Testing Laboratory

Certificate No.: C102287

Certificate of Calibration

This is to certify that the equipment

Description: Integrating Sound Level Meter (EQ009)

Manufacturer: Bruel & Kjaer

Model No.: 2238

Serial No.: 2285722

has been calibrated for the specific items and ranges. The results are shown in the Calibration Report No. C102287.

The equipment is supplied by

Co. Name: Action-United Environmental Services and Consulting

Address: Unit A, 20/F., Gold King Industrial Building, 35-41 Tai Lin Pai Road, Kwai Chung, N.T.

Date of Issue: 27 April 2010

Certified by:



Sun Creation Engineering Limited Calibration and Testing Laboratory

Report No.: C102287

Calibration Report

ITEM TESTED

DESCRIPTION

: Integrating Sound Level Meter (EQ009)

MANUFACTURER:

Bruel & Kjaer

MODEL NO.

2238

SERIAL NO.

: 2285722

TEST CONDITIONS

AMBIENT TEMPERATURE : $(23 \pm 2)^{\circ}$ C

RELATIVE HUMIDITY: $(55 \pm 20)\%$

LINE VOLTAGE

TEST SPECIFICATIONS

Calibration check

DATE OF TEST: 26 April 2010

JOB NO. : IC10-0951

TEST RESULTS

The results apply to the particular unit-under-test only.

All results are within manufacturer's specification.

The results are detailed in the subsequent page(s).

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory
- Rohde & Schwarz Laboratory, Germany
- Fluke Everett Service Center, USA
- Agilent Technologies, USA

Tested by:

Date: 27 April 2010



Sun Creation Engineering Limited Calibration and Testing Laboratory

Report No.: C102287

Calibration Report

- 1. The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 24 hours, and switched on to warm up for over 10 minutes before the commencement of the test.
- 2. Self-calibration using the B & K Acoustic Calibrator 4231, S/N: 2326408 was performed before the test.
- 3. The results presented are the mean of 3 measurements at each calibration point.
- 4. Test equipment:

Equipment ID

Description

Certificate No.

CL280 CL281 40 MHz Arbitrary Waveform Generator

C100067

Multifunction Acoustic Calibrator C101008

- 5. Test procedure: MA101N.
- 6. Results:
- 6.1 Sound Pressure Level

6.1.1 Reference Sound Pressure Level

	UUT	Setting		Applied Value		UUT	IEC 60651
Range	Parameter	Frequency	Time	Level	Freq.	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)	(kHz)	(dB)	(dB)
50 - 130	L_{AFP}	A	F	94.00	1	94.0	± 0.7

6.1.2 Linearity

	UU	T Setting		Applied	d Value	UUT
Range	Parameter	Frequency	Time	Level	Freq.	Reading
(dB)		Weighting	Weighting	(dB)	(kHz)	(dB)
50 - 130	L_{AFP}	A	F	94.00	1	94.0 (Ref.)
				104.00		104.0
				114.00		114.0

IEC 60651 Type 1 Spec. : \pm 0.4 dB per 10 dB step and \pm 0.7 dB for overall different.

6.2 Time Weighting

6.2.1 Continuous Signal

	UUT	Setting		Applied Value		UUT	IEC 60651
Range	Parameter	Frequency	quency Time		Freq.	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)	(kHz)	(dB)	(dB)
50 - 130	L_{AFP}	A F		94.00	1	94.0	Ref.
	L_{ASP}		S			94.0	± 0.1
	L_{AIP}		I			94.0	± 0.1



Sun Creation Engineering Limited Calibration and Testing Laboratory

Report No.: C102287

Calibration Report

6.2.2 Tone Burst Signal (2 kHz)

	one Dailet Orginal (D Itiliz)									
	UUT	Setting		Applied Value		UUT	IEC 60651			
Range	Parameter	Frequency Time		Level	Burst	Reading	Type 1 Spec.			
(dB)		Weighting	Weighting	(dB)	Duration	(dB)	(dB)			
30 - 110	L_{AFP}	A F		106.0	Continuous	106.0	Ref.			
	L_{AFMax}				200 ms	105.0	-1.0 ± 1.0			
	L_{ASP}		S		Continuous	106.0	Ref.			
	L_{ASMax}				500 ms	102.0	-4.1 ± 1.0			

6.3 Frequency Weighting

6.3.1 A-Weighting

A-weighting	<u> </u>						
	UUT	Setting		Appli	ed Value	UUT	IEC 60651
Range	Parameter	Frequency	Time	Level	Freq.	Reading	Type I Spec.
(dB)		Weighting	Weighting	(dB)	_	(dB)	(dB)
50 - 130	L_{AFP}	A	F	94.00	31.5 Hz	54.5	-39.4 ± 1.5
					63 Hz	67.7	-26.2 ± 1.5
					125 Hz	77.8	-16.1 ± 1.0
					250 Hz	85.3	-8.6 ± 1.0
					500 Hz	90.7	-3.2 ± 1.0
					1 kHz	94.0	Ref.
					2 kHz	95.2	$+1.2 \pm 1.0$
					4 kHz	95.0	$+1.0 \pm 1.0$
					8 kHz	92.8	-1.1 (+1.5 ; -3.0)
					12.5 kHz	89.7	-4.3 (+3.0 ; -6.0)

6.3.2 <u>C-Weighting</u>

	UUT	Setting		Applied Value		UUT	IEC 60651
Range	Parameter	Frequency	Time	Level	Freq.	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)		(dB)	(dB)
50 - 130	L_{CFP}	С	F	94.00	31.5 Hz	90.9	-3.0 ± 1.5
					63 Hz	93.2	-0.8 ± 1.5
					125 Hz	93.8	-0.2 ± 1.0
					250 Hz	94.0	0.0 ± 1.0
					500 Hz	94.0	0.0 ± 1.0
					1 kHz	94.0	Ref.
					2 kHz	93.8	-0.2 ± 1.0
					4 kHz	93.1	-0.8 ± 1.0
					8 kHz	90.9	-3.0 (+1.5; -3.0)
					12.5 kHz	87.8	-6.2 (+3.0 ; -6.0)



Sun Creation Engineering Limited Calibration and Testing Laboratory

Report No.: C102287

Calibration Report

6.4 Time Averaging

	UUT Setting				Applied Value					IEC 60804
Range (dB)	Mode	Frequency Weighting	Integrating Time	Frequency (kHz)	Burst Duration	Burst Duty	Burst Level	Equivalent Level	Reading (dB)	Type 1 Spec.
					(ms)	Factor	(dB)	(dB)		(dB)
30 - 110	L _{Aeq}	A	10 sec.	4	1	1/10	110.0	100	99.9	± 0.5
						1/10 ²		90	89.8	± 0.5
			60 sec.			1/10 ³		80	79.2	± 1.0
			5 min.			1/104		70	69.2	± 1.0

Remarks: - Mfr's Spec.: IEC 60651 Type 1 & IEC 60804 Type 1

- Uncertainties of Applied Value : 94 dB : 31.5 Hz - 125 Hz : \pm 0.40 dB

104 dB : 1 kHz : ± 0.10 dB (Ref. 94 dB) 114 dB : 1 kHz : ± 0.10 dB (Ref. 94 dB) Burst equivalent level : ± 0.2 dB (Ref. 110 dB

continuous sound level)

- The uncertainties are for a confidence probability of not less than 95 %.

Note

The values given in this Calibration Report only relate to the values measured at the time of the test and any uncertainties quoted will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the measurement. Sun Creation Engineering Limited shall not be liable for any loss or damage resulting from the use of the equipment.



Sun Creation Engineering Limited Calibration and Testing Laboratory

Certificate No.: C102285

Certificate of Calibration

This is to certify that the equipment

Description: Acoustical Calibrator (EQ081)

Manufacturer: Bruel & Kjaer

Model No.: 4231

Serial No.: 2326408

has been calibrated for the specific items and ranges. The results are shown in the Calibration Report No. C102285.

The equipment is supplied by

Co. Name: Action-United Environmental Services and Consulting

Address: Unit A, 20/F., Gold King Industrial Building, 35-41 Tai Lin Pai Road, Kwai Chung, N.T.

Date of Issue: 27 April 2010

Certified by:

The test equipment used for calibration are traceable to the National Standards as specified in this report. This report shall not be reproduced except in full and with prior written approval from this laboratory.

Tel: 2927 2606

Fax: 2744 8986

E-mail: callab@suncreation.com

Website: www.suncreation.com



Sun Creation Engineering Limited Calibration and Testing Laboratory

Report No.: C102285

Calibration Report

ITEM TESTED

DESCRIPTION : Acoustical Calibrator (EQ081)

MANUFACTURER:

Bruel & Kjaer

MODEL NO.

4231

SERIAL NO.

: 2326408

TEST CONDITIONS

AMBIENT TEMPERATURE : $(23 \pm 2)^{\circ}$ C

RELATIVE HUMIDITY: $(55 \pm 20)\%$

LINE VOLTAGE

TEST SPECIFICATIONS

Calibration check

DATE OF TEST: 26 April 2010

JOB NO. : IC10-0951

TEST RESULTS

The results apply to the particular unit-under-test only.

All results are within manufacturer's specification.

The results are detailed in the subsequent page(s).

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory
- Rohde & Schwarz Laboratory, Germany
- Fluke Precision Measurement Ltd., UK
- Fluke Everett Service Center, USA
- Agilent Technologies, USA

Tested by:

Date: 27 April 2010



Sun Creation Engineering Limited Calibration and Testing Laboratory

Report No.: C102285

Calibration Report

- 1. The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 24 hours before the commencement of the test.
- 2. The results presented are the mean of 3 measurements at each calibration point.
- 3. Test equipment:

Equipment ID TST150A CL130 CL281 <u>Description</u>
Measuring Amplifier
Universal Counter
Multifunction Acoustic Calibrator

Certificate No. C101008 C093122 DC090052

4. Test procedure: MA100N.

5. Results:

5.1 Sound Level Accuracy

UUT	Measured Value	Mfr's Spec.	Uncertainty of Measured Value
Nominal Value	(dB)	(dB)	(dB)
94 dB, 1 kHz	94.0	± 0.2	± 0.2
114 dB, 1 kHz	114.0		

5.2 Frequency Accuracy

UUT Nominal Value	Measured Value	Mfr's	Uncertainty of Measured Value
(kHz)	(kHz)	Spec.	(Hz)
1	1.000 0	1 kHz ± 0.1 %	± 0.1

Remark: - The uncertainties are for a confidence probability of not less than 95 %.

Note:

The values given in this Calibration Report only relate to the values measured at the time of the test and any uncertainties quoted will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the measurement. Sun Creation Engineering Limited shall not be liable for any loss or damage resulting from the use of the equipment.

TSP SAMPLER CALIBRATION CALCULATION SPREADSHEET

Location: Yeung Chun Pui Care & Attention Home

Location ID: AM1

Date of Calibration: 2-Dec-10

Next Calibration Date: 2-Feb-11

Technician: Mr. Ben Tam

CONDITIONS

Sea Level Pressure (hPa) 1014.5 Correct
Temperature (°C) 21.6

Corrected Pressure (mm Hg) 760.875 Temperature (K) 295

CALIBRATION ORIFICE

Make-> TISCH
Model-> 5025A
Calibration Date-> 2-Jun-10

Qstd Slope ->
Qstd Intercept ->
Expiry Date->

2.00279 -0.00494 2-Jun-11

CALIBRATION

ı	Plate	H20 (L)	H2O (R)	H20	Qstd	Ι	IC	LINEAR
ı	No.	(in)	(in)	(in)	(m3/min)	(chart)	corrected	REGRESSION
ı	18	4.5	4.5	9.0	1.510	53	53.64	Slope = 40.5478
ı	13	3.2	3.2	6.4	1.274	42	42.51	Intercept = -7.9708
ı	10	2.3	2.2	4.5	1.068	36	36.44	Corr. coeff. = 0.9977
ı	7	1.6	1.6	3.2	0.901	28	28.34	
ı	5	1.1	1.1	2.2	0.748	22	22.27	

Calculations:

Qstd = 1/m[Sqrt(H20(Pa/Pstd)(Tstd/Ta))-b]

IC = I[Sqrt(Pa/Pstd)(Tstd/Ta)]

Ostd = standard flow rate

IC = corrected chart respones

I = actual chart response

m = calibrator Qstd slope

b = calibrator Qstd intercept

Ta = actual temperature during calibration (deg K

Pstd = actual pressure during calibration (mm Hg

For subsequent calculation of sampler flow:

1/m((I)[Sqrt(298/Tav)(Pav/760)]-b)


m = sampler slope

b = sampler intercept

I = chart response

Tav = daily average temperature

Pav = daily average pressure



TSP SAMPLER CALIBRATION CALCULATION SPREADSHEET

Locatior Lions Clubs International Ho Tak Sum Primary School

Location ID: AM2

Date of Calibration: 2-Dec-10

Next Calibration Date: 2-Feb-11

Technician: Ben Tam

CONDITIONS

Sea Level Pressure (hPa) Temperature (°C) 1014.5 21.6

Corrected Pressure (mm Hg)
Temperature (K)

760.875 295

CALIBRATION ORIFICE

Make->	TISCH
Model->	5025A
Calibration Date->	2-Jun-10

Qstd Slope ->
Qstd Intercept ->
Expiry Date->

2.00279 -0.00494 2-Jun-11

CALIBRATION

Plate	H20 (L)	H2O (R)	H20	Qstd	I	IC	LINEAR
No.	(in)	(in)	(in)	(m3/min)	(chart)	corrected	REGRESSION
18	4.5	4.5	9	1.510	52	52.63	Slope = 41.9671
13	3.6	3.6	7.2	1.351	43	43.52	Intercept = -11.7885
10	2.6	2.6	5.2	1.148	36	36.44	Corr. coeff. = 0.9975
7	1.8	1.8	3.6	0.956	28	28.34	
5	1.2	1.2	2.4	0.781	21	21.25	

Calculations:

Qstd = 1/m[Sqrt(H20(Pa/Pstd)(Tstd/Ta))-b]

IC = I[Sqrt(Pa/Pstd)(Tstd/Ta)]

Qstd = standard flow rate

IC = corrected chart respones

I = actual chart response

m = calibrator Qstd slope

b = calibrator Qstd intercept

Ta = actual temperature during calibration (deg K

Pstd = actual pressure during calibration (mm Hg

For subsequent calculation of sampler flow:

1/m((I)[Sqrt(298/Tav)(Pav/760)]-b)


m = sampler slope

b = sampler intercept

I = chart response

Tay = daily average temperature

Pav = daily average pressure



AUES

Equipment Calibration Record

Equipment Calibrated:

Type: Dust Trak Model 8520

Manufacturer: TSI
Serial No. 21060
Equipment Ref: EQ021

Standard Equipment:

Standard Equipment: Higher Volume Sampler

Location & Location ID: Block A of Government Dockyard Offices

Equipment Ref: AM8
Last Calibration Date: 2-Nov-10

Equipment Calibration Results:


Calibration Date: 1-Dec-10

	Hour	Time	Temp °C	RH %	Dust Concentration in mg/m ³		
1	Tiour Time		Temp C	K11 /0	(Standard Equipment)	(Calibrated Equipment)	
	1	9:00 ~ 10:00	22.9	75	0.079	0.076	
	1	10:05 ~ 11:05	23.1	75	0.082	0.085	
	1	11:10 ~ 12:10	23.4	74	0.067	0.065	

Sensitivity Adjustment Zero Calibration (Before Calibration) 0 (mg/m³) Sensitivity Adjustment Zero Calibration (After Calibration) 0 (mg/m³)

Linear Regression of Y or X

Slope: 0.9975
Correlation Coefficient 0.9953
Validity of Calibration Record 1-Dec-11



Operator: Ray Cheung

Signature:

Date: 5/12/2010

QC Reviewer Ben Tam

Signature:

Date: 5/12/2010

AUES

Equipment Calibration Record

Equipment Calibrated:

Type: Dust Trak Model 8520

Manufacturer: TSI
Serial No. 23080
Equipment Ref: EQ063

Standard Equipment:

Standard Equipment: Higher Volume Sampler

Location & Location ID: Block A of Government Dockyard Offices

Equipment Ref: AM8
Last Calibration Date: 2-Nov-10

Equipment Calibration Results:


Calibration Date: 1-Dec-10

Hour	Time	Temp °C	RH %	Dust Concentration in mg/m ³		
Hour	ii Time Te		X11 /0	(Standard Equipment)	(Calibrated Equipment)	
1	9:00 ~ 10:00	22.9	75	0.079	0.079	
1	10:05 ~ 11:05	23.1	75	0.082	0.081	
1	11:10 ~ 12:10	23.4	74	0.067	0.065	

Sensitivity Adjustment Zero Calibration (Before Calibration) $0 \text{ (mg/m}^3)$ Sensitivity Adjustment Zero Calibration (After Calibration) $0 \text{ (mg/m}^3)$

Linear Regression of Y or X

Slope: 0.9899
Correlation Coefficient 0.9995
Validity of Calibration Record 1-Dec-11



Operator: Ray Cheung

Signature:

Date: 5/12/2010

QC Reviewer Ben Tam

Signature:

Date: 5/12/2010



TISCH ENVIROMENTAL, INC.
145 SOUTH MIAMI AVE.
VILLAGE OF CLEVES, OH 45002
513.467.9000
877.263.7610 TOLL FREE
513.467.9009 FAX
WWW.TISCH-ENV.COM

AIR POLLUTION MONITORING EQUIPMENT

ORIFICE TRANSFER STANDARD CERTIFICATION WORKSHEET TE-5025A

Date - Jun 02, 2010 Rootsmeter S/N 9833620 Ta (K) - 297 Operator Tisch Orifice I.D 1483 Pa (mm) - 746.76							
911	UME VOLUME CART STOP (3) (m3) NA	STOP VOLUME (m3) NA 1.00 NA 1.00 NA 1.00 NA 1.00 NA 1.00	DIFF TIME (min) 1.3990 0.9820 0.8770 0.8350 0.6910	METER DIFF Hg (mm) 3.2 6.4 7.9 8.8 12.8	ORFICE DIFF H2O (in.) 2.00 4.00 5.00 5.50 8.00		

DATA TABULATION

Vstd	(x axis) Qstd	(y axis)		Va	(x axis) Qa	(y axis)
0.9816 0.9775 0.9754 0.9742 0.9689	0.7017 0.9954 1.1122 1.1668 1.4023	1.4042 1.9858 2.2202 2.3286 2.8084		0.9957 0.9914 0.9893 0.9882 0.9828	0.7117 1.0096 1.1281 1.1835 1.4223	0.8919 1.2613 1.4102 1.4790 1.7837
Qstd slop intercept coefficie	t (b) = ent (r) =	2.00279 -0.00494 0.99994		Qa slope intercept coefficie	t (b) = ent (r) =	1.25411 -0.00314 0.99994
y axis =	SQRT [H2O (Pa/760)(298/	Га)]	y axis =	SQRT[H2O(7	ľa/Pa)]

CALCULATIONS

Vstd = Diff. Vol[(Pa-Diff. Hg)/760](298/Ta)
Qstd = Vstd/Time

Va = Diff Vol [(Pa-Diff Hg)/Pa] Qa = Va/Time


For subsequent flow rate calculations:

Qstd = $1/m\{[SQRT(H2O(Pa/760)(298/Ta))] - b\}$ Qa = $1/m\{[SQRT H2O(Ta/Pa)] - b\}$



TISCH ENVIROMENTAL, INC. 145 SOUTH MIAMI AVE. VILLAGE OF CLEVES, OH 45002 513.467.9000 877.263.7610 TOLL FREE 513.467.9009 FAX WWW.TISCH-ENV.COM

AIR POLLUTION MONITORING EQUIPMENT



* y-axis equations:

Qstd series:

$$\sqrt{\Delta \ H \ \left(\ \frac{P \ a}{P \ s \ t \ d} \right) \left(\ \frac{T \ s \ t \ d}{T \ a} \right)}$$

Qa series:

$$\sqrt{(\Delta H (Ta/Pa))}$$

#1483

CERTIFICATE OF ANALYSIS



Batch: HK1024697 Date of Issue: 22/10/2010

Client: ACTION UNITED ENVIRO SERVICES

Client Reference:

Calibration of Multimeter

Item: pH Meter Model No.: EXTECH EC500

ALS Lab ID: HK1024697-001 Equipment No.: --

Date of Calibration: 19 October, 2010 Serial No.: CE133298

Testing Results:

рН

Expected Reading	Recording Reading
4.00	3.92
7.00	7.00
10.0	9.92
Allowing Deviation	± 0.2 unit

Testing Method:

APHA (20th edition), 4500-H+B

Mr Chan Kwok Fai, Godfrey Laboratory Manager - Hong Kong

CERTIFICATE OF ANALYSIS



Batch: HK1024695 **Date of Issue:** 22/10/2010

Client: ACTION UNITED ENVIRO SERVICES

Client Reference:

Calibration of Multimeter

Item: Multimeter Model No.: YSI 550A

ALS Lab ID: HK1024695-001 Equipment No.: --

Date of Calibration: 19 October, 2010 Serial No.: 05F2063AZ

Testing Results:

DO

Expected Reading	Recording Reading
3.57 mg/L	3.52 mg/L
6.15 mg/L	6.14 mg/L
8.18 mg/L	8.15 mg/L
Allowing Deviation	± 0.2 mg/L

Testing Method:

APHA (20th edition), 4500-OC & G

Temperature

Expected Reading	Recording Reading
14.5 °C	14.9 °C
23.5 °C	23.6 °C
34.0 °C	33.9 °C
Allowing Deviation	±2.0°C

Testing Method:

In-House Method

Mr Chan Kwok Fai, Godfrey Laboratory Manager Hong Kong

ALS Technichem (HK) Pty Ltd

ALS Environmental

CERTIFICATE OF ANALYSIS



Batch:

HK1024699

Date of Issue: 22/10/2010

ACTION UNITED ENVIRO SERVICES

Client Reference:

Calibration of Multimeter

Item:

Turbidimeter

Date of Calibration:

ALS Lab ID: HK1024699-001 19 October, 2010

Model No.: HACH 2100P

Equipment No.: EQ091

Serial No.: 950900008735

Testing Results:

Turbidity

Expected Reading	Recording Reading
0.00 NTU	0.10 NTU
4.00 NTU	3.81 NTU
40.0 NTU	36.4 NTU
80.0 NTU	77.1 NTU
400 NTU	382 NTU
Allowing Deviation	± 10%

Testing Method:

APHA (19th edition), 2130B

Mr Chan Kwok Fal, Godfrey Laboratory Manager - Hong Kong

ALS Technichem (HK) Pty Ltd



Appendix F

Meteorological information



Meteorological Data Extracted from HKO during the Reporting Period

				Lau Fa	u Shan W	eather Stat	ion
Date		Weather	Total Rainfall (mm)	Mean Air Temperature (°C)	Wind Speed (km/h)	Mean Relative Humidity (%)	Wind Direction
1-Dec-10	Wed	Light to moderate northeasterly winds.	0	19.9	10.2	67.5	E/NE
2-Dec-10	Thu	Mainly fine apart from some haze.	0	20.7	8	74	E/SE
3-Dec-10	Fri	Fine and dry apart from some haze.	0	20.1	13.5	58.5	E/NE
4-Dec-10	Sat	Light winds	0	20.7	11.2	58.5	E
5-Dec-10	Sun	Hazy with sunny periods.	0	21.5	8.5	62.5	E/SE
6-Dec-10	Mon	Fresh northerly winds	0	23.1	12.8	65	N/NE
7-Dec-10	Tue	Fine and very dry.	0	17.8	28.5	49.5	NE
8-Dec-10	Wed	Moderate to fresh northerly winds	0	16.2	17	33.7	N
9-Dec-10	Thu	Mainly cloudy with mist.	0	17	10.7	28.2	E/SE
10-Dec-10	Fri	Moderate northeasterly winds	0	19.7	11.2	68.7	E/NE
11-Dec-10	Sat	There will be coastal fog.	0	19.9	10.6	70	Е
12-Dec-10	Sun	Light to moderate northeasterly winds	Trace	20.7	14.5	79.5	Е
13-Dec-10	Mon	Fresh easterly winds, strong over offshore waters.	Trace	22.5	8.2	83	E/NE
14-Dec-10	Tue	Cloudy with a few rain patches later.	Trace	21.7	9.1	79.7	E/NE
15-Dec-10	Wed	Cloudy with occasional rain.	12.9	14.8	18.5	86	Е
16-Dec-10	Thu	Moderate to fresh northerly winds.	5.3	7.8	38.5	74	N/NE
17-Dec-10	Fri	Fine and very dry.	0	8.3	14.7	47.2	N/NE
18-Dec-10	Sat	Light winds	0	12	11	57	E/SE
19-Dec-10	Sun	Fine and dry apart from some haze.	0	17.1	10.1	68.7	W/SW
20-Dec-10	Mon	Fine and dry but hazy.	0	20	9.7	73.5	W/SW
21-Dec-10	Tue	Fine but hazy. Light winds.	0	20.1	9.7	70.5	W/SW
22-Dec-10	Wed	Fine and dry.	0	18.9	12.7	62	E/NE
23-Dec-10	Thu	Mainly fine and dry apart from some haze.	0	17.1	9.5	62	E/SE
24-Dec-10	Fri	Mainly fine and dry.	0	19.4	12.1	67	Е
25-Dec-10	Sat	Holiday					
26-Dec-10	5-Dec-10 Sun Holiday						
27-Dec-10	27-Dec-10 Mon Holiday						
28-Dec-10	Tue	Light to moderate northeasterly winds.	0	13.7	10	62	SE
29-Dec-10	Wed	Fine and very dry.	0	15.5	10.8	66.5	E/SE
30-Dec-10	Thu	Moderate to fresh northerly winds	0	17.1	15.5	61	N/NE
31-Dec-10	Fri	Fine and very dry.	0	14.4	16.2	31	NE

Remark: The local wind speed was checked with a portable wind speed meter during the course of construction noise monitoring.

R0152v3.doc Appendix



Appendix G

Event and Action Plan

DSD Contract No. DC/2009/08 – Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen Sewage Pumping Station Event Action Plan – Air Quality



DYDNIO		ACT	ION	
EVENT	ET	IEC	ER	CONTRACTOR
Action Level being exceeded for one sample	 Identify source; Inform IEC and ER; Repeat measurement to confirm finding; Increase monitoring frequency to daily. 	Check monitoring data submitted by ET; Check Contractor's working method.	Notify Contractor.	Rectify any unacceptable practice; Amend working methods if appropriate.
Action Level being exceeded for two or more consecutive samples	 Identify source; Inform IEC and ER; Repeat measurements to confirm findings; Increase monitoring frequency to daily; Discuss with IEC and Contractor on remedial actions required; If exceedance continues, arrange meeting with IEC and ER; If exceedance stops, cease additional monitoring. 	 Check monitoring data submitted by ET; Check Contractor's working method; Discuss with ET and Contractor on possible remedial measures; Advise the ER on the effectiveness of the proposed remedial measures; Supervise implementation of remedial measures. 	 Confirm receipt of notification of failure in writing; Notify Contractor; Ensure remedial measures are properly implemented. 	 Submit proposals for remedial actions to IEC within 3 working days of notification; Implement the agreed proposals; Amend proposal if appropriate.
Limit Level being exceeded for one sample	 Identify source; Inform IEC, ER and EPD; Repeat measurement to confirm finding; Increase monitoring frequency to daily; Assess effectiveness of Contractor's remedial actions; Keep EPD and ER informed of the results. 	 Check monitoring data submitted by ET and Contractor's working method; Discuss with Contractor on the possible mitigation measures; Review the proposed mitigation measures submitted by Contractor and advise the ER accordingly. 	 Confirm receipt of notification of failure in writing; Notify Contractor; Check monitoring data and Contractor's working methods; Discuss with IEC and Contractor on potential remedial actions; Ensure remedial actions properly implemented. 	 Take immediate action to avoid further exceedance; Submit proposals for remedial actions to ER within 3 working days of notification; Implement the agreed proposals; Amend proposal if appropriate.
Limit Level being exceeded for two or more consecutive samples	 Identify source; Inform IEC, ER and EPD the causes & actions taken for the exceedances; Repeat measurement to confirm findings; Increase monitoring frequency to daily; Investigate the causes of exceedance; Arrange meeting with EPD and ER to discuss the remedial actions to be taken; Assess effectiveness of Contractor's remedial actions and keep EPD and ER informed of the results; If exceedance stops, cease additional monitoring. 	Check monitoring data submitted by ET and Contractor's working method; Discuss with Contractor on the possible mitigation measures; Review the proposed mitigation measures submitted by Contractor and advise the ER accordingly; Supervise the implementation of mitigation measures.	Confirm receipt of notification of failure in writing; Notify Contractor; Carry out analysis of Contractor's working procedures to determine possible mitigation to be implemented; Discuss with IEC and the Contractor on potential remedial actions; Review Contractor's remedial actions whenever necessary to assure their effectiveness; If exceedance continues, consider what portion of the work is responsible and instruct the Contractor to stop that portion of work until the exceedance is abated.	1. Take immediate action to avoid further exceedance; 2. Submit proposals for remedial actions to ER within 3 working days of notification; 3. Implement the agreed proposals; 4. Resubmit proposals if problem still not resolved; 5. Stop the relevant portion of works as determined by the ER until the exceedance is abated.



EVENT		ACT	TION		
EVENI	ET	IEC	ER	CONTRACTOR	
Action level	 Notify IEC and Contractor; Carry out investigation; Report the results of investigation to the IEC and Contractor; Discuss with the Contractor and formulate remedial measures; Increase monitoring frequency to check the effectiveness of mitigation measures. 	 Review the analyzed results submitted by the ET; Review the proposed remedial measures by the Contractor and advise the ER accordingly; Supervise the implementation of remedial measures. 	Ensure mitigation measures are properly implemented.	 Submit noise mitigation proposal to IEC; Implement noise mitigation proposals. 	
Limit level	 Notify IEC, ER, EPD & Contractor; Identify source; Repeat measurement to confirm findings; Increase monitoring frequency; Carry out analysis of Contractor's working procedures to determine possible mitigation to be implemented; Inform IEC, ER and EPD the causes and actions taken for the exceedances; Assess the effectiveness of Contractor's remedial actions and keep IEC, EPD and ER informed of the results; If exceedance stops, cease additional monitoring. 	Discuss amongst ER, ET, and Contractor on the potential remedial actions; Review Contractor's remedial actions whenever necessary to assure their effectiveness and advise the ER accordingly; Supervise the implementation of remedial measures.	Confirm receipt of notification in writing; Notify Contractor; Require Contractor to propose remedial measures for the analyzed noise problem; Ensure mitigation measures are properly implemented; If exceedances continue, consider what portion of the work is responsible and instruct the Contractor to stop that portion of work until the exceedance is abated.	Undertake immediate action to avoid further exceedance; Submit proposals for remedial actions to IEC within 3 working days of notification; Implement the agreed proposals; Resubmit proposals if problem still not under control; Stop the relevant portion of works as determined by ER, until the exceedance is abated.	

DSD Contract No. DC/2009/08 – Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen Sewage Pumping Station Event Action Plan – Water Quality (Local Stream)



Event		Ac	tion	
Event	ET Leader	IEC	ER	Contractor
Action Level being exceeded by one sampling day	Repeat in-situ measurement to confirm findings; Identify reasons for non-compliance and sources of impact; Inform IEC and Contractor; Check monitoring data, all plant, equipment and Contractor's working methods; Discuss mitigation measures with IEC and Contractor; Repeat measurement on next day of exceedance.	Discuss with ET and Contractor on the mitigation measures; Review proposals on mitigation measures submitted by Contractor and advise the ER accordingly; Assess the effectiveness of the implemented mitigation measures.	Discuss with IEC on the proposed mitigation measures; make agreement on the mitigation measures to be implemented; Assess the effectiveness of the implemented mitigation measures.	Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment; Consider changes of working methods; Discuss with ET and IEC and propose mitigation measures to IEC and ER; Implement the agreed mitigation measures.
Action Level being exceeded by more than two consecutive sampling days	Repeat in-situ measurement to confirm findings; Identify reasons for non-compliance and sources of impact; Inform IEC and Contractor; Check monitoring data, all plant, equipment and Contractor's working methods; Discuss mitigation measures with IEC and Contractor; Ensure mitigation measures are implemented; Prepare to increase the monitoring frequency to daily; Repeat measurement on next day of exceedance.	Discuss with ET and Contractor on the mitigation measures; Review proposals on mitigation measures submitted by Contractor and advise the ER accordingly; Assess the effectiveness of the implemented mitigation measures.	Discuss with IEC on the proposed mitigation measures; Make agreement on the mitigation measures to be implemented; Assess the effectiveness of the implemented mitigation measures.	Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment; Consider changes of working methods; Discuss with ET and IEC and propose mitigation measures to IEC and ER within 3 working days; Implement the agreed mitigation measures.
Limit Level being exceeded by one sampling day	Repeat in-situ measurement to confirm findings; Identify reasons for non-compliance and sources of impact; Inform IEC, Contractor and EPD; Check monitoring data, all plant, equipment and Contractor's working methods; Discuss mitigation measures with IEC, ER and Contractor; Ensure mitigation measures are implemented; Increase the monitoring frequency to daily until no exceedance of Limit Level.	Discuss with ET and Contractor on the mitigation measures; Review proposals on mitigation measures submitted by Contractor and advise the ER accordingly; Assess the effectiveness of the implemented mitigation measures.	Discuss with IEC, ET and Contractor on the proposed mitigation measures; Request Contractor to critically review the working methods; Make agreement on the mitigation measures to be implemented; Assess the effectiveness of the implemented mitigation measures.	Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment; Consider changes of working methods; Discuss with ET, IEC and ER and propose mitigation measures to IEC and ER within 3 working days; Implement the agreed mitigation measures.
Limit Level being exceeded by more than two consecutive sampling days	Repeat in-situ measurement to confirm findings; Identify reasons for non-compliance and sources of impact; Inform IEC, Contractor and EPD; Check monitoring data, all plant, equipment and Contractor's working methods; Discuss mitigation measures with IEC, ER and Contractor; Ensure mitigation measures are implemented; Increase the monitoring frequency to daily until no exceedance of Limit Level for two consecutive days.	Discuss with ET and Contractor on the mitigation measures; Review proposals on mitigation measures submitted by Contractor and advise the ER accordingly; Assess the effectiveness of the implemented mitigation measures.	Discuss with IEC, ET and Contractor on the proposed mitigation measures; Request Contractor to critically review the working methods; Make agreement on the mitigation measures to be implemented; Assess the effectiveness of the implemented mitigation measures; Consider and instruct, if necessary, the Contractor to slow down or to stop all or part of the marine work until no exceedance of Limit Level.	Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment; Consider changes of working methods; Discuss with ET, IEC and ER and propose mitigation measures to IEC and ER within 3 working days; Implement the agreed mitigation measures; As directed by the ER, to slow down or to stop all or part of the marine work or construction activities.



Appendix H

Monitoring Schedule in Reporting Month and Coming Month



Monitoring Schedule for Reporting Period

		Dust Mo	onitoring	NT 1 N# 1/	Water Onelity		
	Date	1-hour TSP	24-hour TSP	Noise Monitoring	Water Quality		
Wed	1-Dec-10						
Thu	2-Dec-10						
Fri	3-Dec-10						
Sat	4-Dec-10						
Sun	5-Dec-10						
Mon	6-Dec-10						
Tue	7-Dec-10						
Wed	8-Dec-10						
Thu	9-Dec-10						
Fri	10-Dec-10						
Sat	11-Dec-10						
Sun	12-Dec-10						
Mon	13-Dec-10						
Tue	14-Dec-10						
Wed	15-Dec-10						
Thu	16-Dec-10						
Fri	17-Dec-10						
Sat	18-Dec-10						
Sun	19-Dec-10						
Mon	20-Dec-10						
Tue	21-Dec-10						
Wed	22-Dec-10						
Thu	23-Dec-10						
Fri	24-Dec-10						
Sat	25-Dec-10						
Sun	26-Dec-10						
Mon	27-Dec-10						
Tue	28-Dec-10						
Wed	29-Dec-10						
Thu	30-Dec-10						
Fri	31-Dec-10						

Monitoring Day
Sunday or Public Holiday

R0152v3.doc Action-United Environmental Services and Consulting Appendix



Monitoring Schedule for Coming Month

Date		Dust Mo	onitoring	NT 1 N# 1/	W-4 O P4	
D	ate	1-hour TSP	24-hour TSP	Noise Monitoring	Water Quality	
Sat	1-Jan-11					
Sun	2-Jan-11					
Mon	3-Jan-11					
Tue	4-Jan-11					
Wed	5-Jan-11					
Thu	6-Jan-11					
Fri	7-Jan-11					
Sat	8-Jan-11					
Sun	9-Jan-11					
Mon	10-Jan-11					
Tue	11-Jan-11					
Wed	12-Jan-11					
Thu	13-Jan-11					
Fri	14-Jan-11					
Sat	15-Jan-11					
Sun	16-Jan-11					
Mon	17-Jan-11					
Tue	18-Jan-11					
Wed	19-Jan-11					
Thu	20-Jan-11					
Fri	21-Jan-11					
Sat	22-Jan-11					
Sun	23-Jan-11					
Mon	24-Jan-11					
Tue	25-Jan-11					
Wed	26-Jan-11					
Thu	27-Jan-11					
Fri	28-Jan-11					
Sat	29-Jan-11					
Sun	30-Jan-11					
Mon	31-Jan-11					

Monitoring Day
Sunday or Public Holiday

R0152v3.doc Action-United Environmental Services and Consulting Appendix



Appendix I

Results Data

DSD Contract No DC/2009/08 – Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen Sewage Pumping Station

Impact 24-Hour TSP Monitoring Results - AM1 (Lions Clubs International Ho Tak Sum Primary School)

										STANDAR	D	INITIAL	FINAL	WEIGHT	Dust
DATE	SAMPLE]	ELAPSED		MIN	MAX	AVG	AVG	AVG	FLOW	AIR	FILTER	FILTER	DUST	24-hr TSP
	NUMBER		TIME	-	CHART	CHART	CHART	TEMP	PRESS	RATE	VOLUME	WEIGHT	WEIGHT	COLLECTED	in air
		INITIAL	FINAL	(min)	READING	READING	READING	(oC)	(hPa)	(m3/min)	(std m3)	(g)	(g)	(g)	(ug/m^3)
6-Dec-10	22982	9005.01	9028.93	1435.20	35	36	35.5	23.5	1014.9	1.13	1621	2.8069	2.9666	0.1597	98
11-Dec-10	22984	9028.93	9053.49	1473.60	35	36	35.5	20.2	1012.3	1.13	1670	2.8087	3.0531	0.2444	147
17-Dec-10	23077	9053.49	9078.43	1496.40	36	37	36.5	10.4	1020.5	1.18	1760	2.8065	2.9192	0.1127	64
23-Dec-10	23025	9078.43	9103.12	1481.40	35	36	35.5	18.1	1015.6	1.14	1685	2.7973	2.9388	0.1415	84
28-Dec-10	23159	9103.12	9127.67	1473.00	37	38	37.5	15.4	1018.1	1.19	1755	2.7337	2.8656	0.1319	76
30-Dec-10	23096	9127.67	9153.63	1557.60	35	36	35.5	17.8	1018.1	1.14	1774	2.7685	2.9151	0.1466	83

Action Level: 162 Limit Level: 260

Impact 24-Hour TSP Monitoring Results - AM2 (Yeung Chun Pui Care & Attention Home)

										STANDAR	D	INITIAL	FINAL	WEIGHT	Dust
DATE	SAMPLE]	ELAPSED		MIN	MAX	AVG	AVG	AVG	FLOW	AIR	FILTER	FILTER	DUST	24-hr TSP
	NUMBER		TIME	-	CHART	CHART	CHART	TEMP	PRESS	RATE	VOLUME	WEIGHT	WEIGHT	COLLECTED	in air
		INITIAL	FINAL	(min)	READING	READING	READING	(oC)	(hPa)	(m3/min)	(std m3)	(g)	(ug/m ³)	(g)	(ug/m^3)
6-Dec-10	22983	10599.23	10623.75	1471.20	37	38	37.5	23.5	1014.9	1.12	1654	2.7993	2.9434	0.1441	87
11-Dec-10	22990	10623.75	10647.34	1415.40	37	38	37.5	20.2	1012.3	1.13	1597	2.7963	2.9789	0.1826	115
17-Dec-10	22991	10647.34	10670.87	1411.80	35	36	35.5	10.4	1020.5	1.10	1549	2.7985	2.8833	0.0848	55
23-Dec-10	23026	10670.87	10695.46	1475.40	37	38	37.5	18.1	1015.6	1.13	1672	2.7944	2.9286	0.1342	81
28-Dec-10	23155	10695.46	10719.13	1420.20	36	37	36.5	15.4	1018.1	1.11	1582	2.7315	2.8628	0.1313	83
30-Dec-10	23095	10719.13	10743.72	1475.40	36	37	36.5	17.8	1018.1	1.11	1638	2.7706	2.914	0.1434	88

Action Level: 190 Limit Level: 260

DSD Contract No DC/2009/08

Construction of Yuen Long South Branch Sewers and Extension of Ha Tsuen Sewage Pumping Station

	ACTION	LALIBALT			Summary	of Water C	Quality Mor	nitoring Re	esults - R1	b			1	
Date	ACTION	I/ LIMIT			DO (*	ma /I \	DOS	(0/)	Turbidi	ty (NITLI)		Н		SS
Location						ng/L)	DUS	(%)		ty (NTU)		in		
R1b					ACT LIM	4.6 4		1	ACT LIM	15.6 16.2	ACT LIM		ACT LIM	31.5 31.9
Date	3-D	ec-10												
Location	Time	Depth (m)	Temp	(oC)	DO (r	ng/L)	DOS	(%)	Turbidi	ty (NTU)	р	Н	,	SS
R1b	16:13	0.70	24.9	24.9	19.52	18.2	235.8	222.1	18.4	17.3	10	9.9	10	10.0
KIB	10.10	0.70	24.9	21.7	16.87	10.2	208.4	222.1	16.2	17.0	9.76	7.7	10	10.0
Date	7-D	ec-10												
Location	Time	Depth (m)	Temp	(oC)	DO (r	ng/L)	DOS	(%)	Turbidi	ty (NTU)	р	Н		SS
			22.9	` _	16.73		182.1		18.0		9.46		35	
R1b	16:55	0.70	23.1	23.0	16.79	16.8	179.7	180.9	21.9	20.0	9.38	9.4	35	35.0
1														
Date		ec-10	T	(-0)	DO ((0/)	T 1.41	L /BITLIN	_		1	00
Location	Time	Depth (m)		(00)		ng/L)	•	(%)		ty (NTU)		H		SS
R1b	11:03	0.70	19.4 18.6	19.0	15.43 14.78	15.1	164.3 177.8	171.1	13.0 14.8	13.9	9.58 8.62	9.1	21 21	21.0
			10.0		14.70		1//.0		14.0		0.02		21	1
Date	11-D	ec-10												
Location	Time	Depth (m)	Temp	(oC)	D0 (r	ng/L)	DOS	(%)	Turbidi	ty (NTU)	р	Н	,	SS
R1b	13:45	0.60	20.2	20.9	16.42	16.7	156.7	160.0	9.4	9.8	9.9	9.7	18	18.0
KID	13.43	0.00	21.6	20.7	17.07	10.7	163.2	100.0	10.1	7.0	9.53	7.7	18	10.0
Date	12-D	ec-10												
Location	Time	Depth (m)	Temp	(oC)	DO (r	ng/L)	DOS	(%)	Turbidi	ty (NTU)	р	Н		SS
			21.9		18.67		144.2		12.3	Ī	8.46		25	
R1b	16:30	0.70		22.1		18.0		148.0		11.9		8.8		25.0
			22.3		17.42	10.0	151.7	110.0	11.5	11.7	9.06	0.0	25	
	47.5	10	22.3		17.42	10.0	151.7	110.0	11.5	11.7	9.06	0.0	25	
Date		ec-10			•				•					
Date Location	16-D Time	Depth (m)	Тетр) (oC)	DO (r	ng/L)	DOS	(%)	Turbidi	ty (NTU)	р	H		ss
			Temp		•				•					
Location	Time	Depth (m)	Тетр) (oC)	DO (r	ng/L)	DOS 174.3	(%)	Turbidi 11.7	ty (NTU)	9.58	H	24	SS
Location	Time 13:08	Depth (m)	Temp) (oC)	DO (r	ng/L)	DOS 174.3	(%)	Turbidi 11.7	ty (NTU)	9.58	H	24	SS
R1b	Time 13:08	Depth (m) 0.70	Temp 10.4 11.3	10.9	DO (r 17.27 16.48	ng/L)	DOS 174.3 177.6	(%)	Turbidi 11.7 12.8	ty (NTU)	9.58 8.76	H	24 24	SS
R1b Date Location	13:08 18-D Time	0.70 ec-10 Depth (m)	Temp 10.4 11.3	10.9 10.9	DO (r 17.27 16.48 DO (r 18.96	mg/L) 16.9	DOS 174.3 177.6	(%) 176.0	Turbidi 11.7 12.8	ty (NTU) 12.3 ty (NTU)	9.58 8.76	H 9.2	24 24 24 31	\$\$\$ 24.0
R1b Date	13:08 18-D	0.70 ec-10	Temp 10.4 11.3	10.9	DO (r 17.27 16.48	ng/L) 16.9	DOS 174.3 177.6	(%) 176.0	Turbidi 11.7 12.8	ty (NTU) 12.3	9.58 8.76	H 9.2	24 24	SS 24.0
Date Location R1b R1b	13:08 18-D Time 16:43	Depth (m) 0.70 ec-10 Depth (m) 0.60	Temp 10.4 11.3 Temp 16.4	10.9 10.9	DO (r 17.27 16.48 DO (r 18.96	mg/L) 16.9	DOS 174.3 177.6 DOS 185.8	(%) 176.0	Turbidi 11.7 12.8 Turbidi 11.3	ty (NTU) 12.3 ty (NTU)	9.58 8.76 p	H 9.2	24 24 24 31	\$\$\$ 24.0
Location R1b Date Location R1b Date	13:08 18-D Time 16:43	Depth (m) 0.70 Dec-10 Depth (m) 0.60	Temp 10.4 11.3 Temp 16.4 17.3	10.9 10.9 0 (oC) 16.9	DO (r 17.27 16.48 DO (r 18.96 17.52	mg/L) 16.9 mg/L) 18.2	DOS 174.3 177.6 DOS 185.8 173.4	(%) 176.0 (%) 179.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4	ty (NTU) 12.3 ty (NTU) 11.9	P 9.58 8.76 P 7.68 8.93	H 9.2	24 24 24 31 31 31	\$\$\$ 24.0
Date Location R1b Date Location R1b Date Location	13:08 18-D Time 16:43 20-D Time	Depth (m) 0.70 ec-10 Depth (m) 0.60 ec-10 Depth (m)	Temp 10.4 11.3 Temp 16.4 17.3	10.9 10.9 16.9	DO (r 17.27 16.48 DO (r 18.96 17.52	mg/L) 16.9 mg/L) 18.2	DOS 174.3 177.6 DOS 185.8 173.4	(%) 176.0 (%) 179.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4	ty (NTU) 12.3 ty (NTU) 11.9	P 9.58 8.76 P 7.68 8.93	H 9.2	24 24 24 31 31 31	\$\$\$ 24.0
Date Location R1b Date Location R1b Date	13:08 18-D Time 16:43	Depth (m) 0.70 Dec-10 Depth (m) 0.60	Temp 10.4 11.3 Temp 16.4 17.3	10.9 10.9 0 (oC) 16.9	DO (r 17.27 16.48 DO (r 18.96 17.52	mg/L) 16.9 mg/L) 18.2	DOS 174.3 177.6 DOS 185.8 173.4	(%) 176.0 (%) 179.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi	ty (NTU) 12.3 ty (NTU) 11.9	P 9.58 8.76 P 7.68 8.93	H 9.2	24 24 24 31 31 31	SS 24.0 SS 31.0
Date Location R1b Date Location R1b Date Location R1b	13:08 18-D Time 16:43 20-D Time 11:09	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6	10.9 10.9 16.9	DO (r 17.27 16.48 DO (r 18.96 17.52	mg/L) 16.9 mg/L) 18.2	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7	(%) 176.0 (%) 179.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8	ty (NTU) 12.3 ty (NTU) 11.9	9.58 8.76 P 7.68 8.93	H 9.2	24 24 24 31 31 31 20	\$\$\$ 24.0
Date Location R1b Date Location R1b Date Location R1b Date Location R1b	13:08 18-D Time 16:43 20-D Time 11:09	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1	10.9 10.9 16.9 16.9	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39	mg/L) 16.9 mg/L) 18.2 mg/L) 16.9	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2	(%) 176.0 (%) 179.6 (%)	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7	ty (NTU) 12.3 ty (NTU) 11.9 ty (NTU) 11.3	P 9.58 8.76 P 7.68 8.93 P 9.56 8.94	H 9.2 H 9.3	24 24 24 31 31 31 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b Date Location R1b Date Location R1b	13:08 18-D Time 16:43 20-D Time 11:09	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1	10.9 10.9 16.9 16.9	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39	mg/L) 16.9 mg/L) 18.2	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2	(%) 176.0 (%) 179.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7	ty (NTU) 12.3 ty (NTU) 11.9	P 9.58 8.76 P 7.68 8.93 P 9.56 8.94	H 9.2	24 24 24 31 31 31 20 20	\$\$\$ 24.0
Date Location R1b Date Location R1b Date Location R1b Date Location R1b	13:08 18-D Time 16:43 20-D Time 11:09	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1	10.9 10.9 16.9 16.9	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39	mg/L) 16.9 mg/L) 18.2 mg/L) 16.9	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2	(%) 176.0 (%) 179.6 (%)	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7	ty (NTU) 12.3 ty (NTU) 11.9 ty (NTU) 11.3	P 9.58 8.76 P 7.68 8.93 P 9.56 8.94	H 9.2 H 9.3	24 24 24 31 31 31 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b Date Location R1b Date Location R1b Date Location	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70 Dec-10 Depth (m)	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1	10.9 10.9 16.9 16.9 19.9	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39	mg/L) 16.9 mg/L) 18.2 mg/L) 16.9	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3	(%) 176.0 (%) 179.6 (%) 193.0	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7	ty (NTU) - 12.3 ty (NTU) - 11.9 ty (NTU) - 11.3	P 9.58 8.76 P 7.68 8.93 P 9.56 8.94	H 9.2 H 8.3 H 9.3	24 24 24 31 31 31 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b Date Location R1b Date Location R1b Date Location	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time 15:26	Depth (m) 0.70 ec-10 Depth (m) 0.60 ec-10 Depth (m) 0.70 ec-10 Depth (m) 0.70	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1 23.3	10.9 10.9 16.9 16.9 19.9 2 (oC) 23.2	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39 DO (r 23.88 20.68	mg/L) 16.9 18.2 mg/L) 16.9 mg/L) 22.3	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3 207.8	(%) 176.0 (%) 179.6 (%) 193.0 (%) 222.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7 Turbidi 10.8 11.4	ty (NTU) 12.3 ty (NTU) 11.9 ty (NTU) 11.3 ty (NTU) 11.1	P 9.58 8.76 P 7.68 8.93 P 9.56 8.94	H 9.2 H 8.3 H 9.3	24 24 24 31 31 31 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b Date Location R1b Date Location R1b Date Location R1b	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time 15:26	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70 Dec-10 Depth (m) 0.70	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1 23.3	10.9 10.9 16.9 16.9 19.9 2 (oC) 23.2	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39 DO (r 23.88 20.68	mg/L) 16.9 mg/L) 18.2 mg/L) 16.9	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3 207.8	(%) 176.0 (%) 179.6 (%) 193.0	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7 Turbidi 10.8 11.4	ty (NTU) - 12.3 ty (NTU) - 11.9 ty (NTU) - 11.3	P 9.58 8.76 7.68 8.93 P 9.56 8.94 P 9.45 9.33	H 9.2 H 8.3 H 9.3	24 24 24 31 31 31 20 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time 15:26	Depth (m) 0.70 ec-10 Depth (m) 0.60 ec-10 Depth (m) 0.70 ec-10 Depth (m) 0.70	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1 23.3 Temp 22.5	10.9 10.9 16.9 16.9 19.9 2 (oC) 23.2	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39 DO (r 23.88 20.68	mg/L) 16.9 18.2 mg/L) 16.9 mg/L) 22.3	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3 207.8	(%) 176.0 (%) 179.6 (%) 193.0 (%) 222.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7 Turbidi 10.8 11.4 Turbidi 10.8	ty (NTU) 12.3 ty (NTU) 11.9 ty (NTU) 11.3 ty (NTU) 11.1	P 9.58 8.76 7.68 8.93 P 9.56 8.94 P 9.45 9.33	H 9.2 H 9.3 H 9.3	24 24 24 31 31 31 20 20 20	SS 24.0 SS 20.0 SS 20.0
Date Location R1b Date Location R1b Date Location R1b Date Location R1b Date Location	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time 15:26 24-D Time	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70 Dec-10 Depth (m) Depth (m)	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1 23.3	(oC) 10.9 16.9 16.9 19.9 2 (oC) 23.2	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39 DO (r 23.88 20.68	mg/L) 16.9 mg/L) 18.2 mg/L) 22.3	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3 207.8	(%) 176.0 (%) 179.6 (%) 193.0 (%) 222.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7 Turbidi 10.8 11.4	ty (NTU) 12.3 ty (NTU) 11.9 ty (NTU) 11.3	P 9.58 8.76 7.68 8.93 P 9.56 8.94 P 9.45 9.33	H 9.2 H 9.3 H 9.4	24 24 24 31 31 31 20 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time 15:26 24-D Time 14:08	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70 Dec-10 Depth (m) 0.70 Depth (m) 0.60	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1 23.3 Temp 22.5	(oC) 10.9 16.9 16.9 19.9 2 (oC) 23.2	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39 DO (r 23.88 20.68	mg/L) 16.9 mg/L) 18.2 mg/L) 22.3	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3 207.8	(%) 176.0 (%) 179.6 (%) 193.0 (%) 222.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7 Turbidi 10.8 11.4 Turbidi 10.8	ty (NTU) 12.3 ty (NTU) 11.9 ty (NTU) 11.3	P 9.58 8.76 7.68 8.93 P 9.56 8.94 P 9.45 9.33	H 9.2 H 9.3 H 9.4	24 24 24 31 31 31 20 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b Date Location R1b	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time 15:26 24-D Time 14:08	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70 Dec-10 Depth (m) 0.70 Dec-10 Depth (m) 0.60	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1 23.3 Temp 22.5 22.6	(oC) 10.9 16.9 16.9 16.9 23.2 22.6	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39 DO (r 23.88 20.68	mg/L) 16.9 mg/L) 18.2 mg/L) 22.3	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3 207.8 DOS 216.2 215.6	(%) - 176.0 - 179.6 - 179.6 - 193.0 - 222.6 - (%) - 215.9	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7 Turbidi 10.8 11.4 Turbidi 9.6	ty (NTU) 12.3 ty (NTU) 11.9 ty (NTU) 11.3	P 9.58 8.76 P 7.68 8.93 P 9.56 8.94 P 9.45 9.45 9.64 9.45	H 9.2 H 9.3 H 9.4	24 24 24 31 31 31 20 20 20 20	SS 24.0 SS 31.0 SS 20.0
Date Location R1b	Time 13:08 18-D Time 16:43 20-D Time 11:09 22-D Time 15:26 24-D Time 14:08	Depth (m) 0.70 Dec-10 Depth (m) 0.60 Dec-10 Depth (m) 0.70 Dec-10 Depth (m) 0.70 Depth (m) 0.60	Temp 10.4 11.3 Temp 16.4 17.3 Temp 19.6 20.1 Temp 23.1 23.3 Temp 22.5 22.6	(oC) 10.9 16.9 16.9 16.9 23.2 22.6	DO (r 17.27 16.48 DO (r 18.96 17.52 DO (r 16.42 17.39 DO (r 23.88 20.68	mg/L) 16.9 mg/L) 18.2 mg/L) 22.3 mg/L) 19.6	DOS 174.3 177.6 DOS 185.8 173.4 DOS 196.7 189.2 DOS 237.3 207.8 DOS 216.2 215.6	(%) 176.0 (%) 179.6 (%) 193.0 (%) 222.6	Turbidi 11.7 12.8 Turbidi 11.3 12.4 Turbidi 10.8 11.7 Turbidi 10.8 11.4 Turbidi 9.6	ty (NTU) - 12.3 ty (NTU) - 11.9 ty (NTU) - 11.3 ty (NTU) - 11.1	P 9.58 8.76 P 7.68 8.93 P 9.56 8.94 P 9.45 9.45 9.64 9.45	H 9.2 H 9.3 H 9.4 H 9.5	24 24 24 31 31 31 20 20 20 20	SS 24.0 SS 31.0 SS 20.0 SS 18.0

Date

Location

R1b

31-Dec-10

Depth (m)

0.70

Time

16:30

Temp (oC)

20.1

20.0

20.2

DO (mg/L)

20.2

21.61

18.7

DOS (%)

214.1

228.6 199.6 Turbidity (NTU)

10.5

10.2

10.8

SS

15.0

15

15

рН

9.2

9.05

9.26




Appendix J

Graphical plots




Air Quality – 24-Hr TSP




R0152v3.doc Appendix



Air Quality - 1 Hour TSP







R0152v3.doc Appendix



Construction Noise








R0152v3.doc Appendix



Water Quality – Local Stream Course (R1b)







Remarks: For better presenting the trend of the results, the monitoring data of 25 Nov 2010 (387mg/L) is not shown.



Appendix

Appendix K

Monthly Summary Waste Flow Table

Drainage Service Department Monthly Summary Waste Flow Table for Contract with Waste Management Plan under ETWB TCW No. 15/2003 Reporting Year: 2010

Contract No. _____DC/2009/08

(To be submitted to C&D MM Coordinator of Respective Division/Region via Engineer's Representative before 15th of the following month)

	Act	ual Quantities of Inc	ert C&D Materials	Generated / Import	ed (in '000 m ³)		Actual Quantities of Other C&D Materials / Wastes Generated							
Month	Total Quantities Generated	Broken Concrete (including rock for recycling into aggregates)	Reused in the Contract	Reused in Other Projects	Disposed as Public Fill	Imported C&D Material	Metal	Paper/ Cardboard Packaging	Plastic (bottles/containers, plastic sheets/ foams from package material)	Chemical Waste	Others (e.g. General Refuse etc.)			
	[a+b+c+d)	(a)	(b)	(c)	(d)		(in '000kg)	(in '000kg)	(in '000kg)	(in '000kg)	(in '000m³)			
January		0	0	0	0	0	0	0	0	0	0.011			
February	DAVEG.	0	0	0	0.036	0	0	0	0	0	0.003			
March	$\mathcal{A}_{i}(\mathcal{G}_{i})$	0	0	0	0.654	0	0	0	0	0	0.014			
April	, etle	0	0	0	0.579	0	0	0	0	0				
May	025	0	0	0	0.403	0	0	0	0	0.033	0.006 0			
June		0	0	0	0.711	0	0	0	0	0.055				
obstantings	7.38									DOMESTIC STREET	0.001			
July	1/621	0	0	0	0.649	0	0	0	0					
August	(6)	0	0	0	0.507	0	0	0	0	0	0.004			
September	$i_{\ell} \widetilde{\mathcal{L}}(t)$	0	0	0	0.640	0	0	0		0	0.003			
October	0.66	0	0	o l	1.086	0	0	 	0	0	0.099			
November	,Wx,	0	, 0	0	1.054	0		0	0	0	0.005			
December	Tight .	0	0	0	2.636		0.001	0.008	0.191	0	0.003			
era er lännik				Marchine March	2.030	0	0	0	0 .	0	0.003			



Appendix

Appendix L

Inspection Checklist



Proje	ct: DC/2009/08 Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen PS		spected b			K.P. Che	euna			
Inspe			C's repre		:	-	· y			
Date:	7 December 2010	ET's representative:				Ben Tam				
Time:	10:00		ontractor'	•	ntative:	T.T. Lee				
		С	hecklist N	0.		DC20090	08-071210			
PART		ntal Pe	_	N/A						
Weath			Rainy							
Humic										
Wind:			Calm							
PART	B: SITE AUDIT									
			Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks		
Section	on 1: Water Quality		_	_	_	_				
1.01	Is an effluent discharge license obtained for the Project?			\checkmark		Ш	Ш			
1.02	Is the effluent discharged in accordance with the discharge licence?			\checkmark						
1.03	Is the discharge of turbid water avoided?			\checkmark						
1.04	Are there proper desilting facilities in the drainage systems to reduce SS levels in effluent?					\checkmark		Photo 1		
1.05	Are there channels, sandbags or bunds to divert the surface ru to sedimentation tanks/desilting system prior discharge?	n-off		\checkmark						
1.06	Are there any temporary perimeter channels provided at site boundaries to intercept storm runoff from crossing the site?		\checkmark							
1.07	Is temporary drainage system (within site boundaries) and the nearby permanent drainage system (outside site boundaries) a well maintained?	re		\checkmark						
1.08	As excavation proceeds, are temporary access roads protected crushed stone or gravel?	by		\checkmark						
1.09	Are temporary exposed slopes properly covered?			\checkmark						
1.10	Are earthworks final surfaces well compacted or protected?			\checkmark						
1.11	Are manholes adequately covered or temporarily sealed?			\checkmark						
1.12	Are there any procedures and equipment for rainstorm protection	n?	\checkmark							
1.13	Are wheel washing facilities well maintained?			\checkmark						
1.14	Is overflow runoff from wheel washing facilities avoided?			\checkmark						
1.15	Are there chemical toilets provided on site?			\checkmark						
1.16	Are chemical toilets properly maintained?			\checkmark						
1.17	Are the vehicle and plant servicing areas paved and located wi roofed areas?	hin					$\overline{\checkmark}$			
1.18	Is the oil leakage from the on-site vehicles/plants or spillage duthe fuel refilling avoided?	ring		\checkmark						
1.19	Are there any measures to prevent oil leakage entering temporary/permanent drainage system?	the		\checkmark						
1.20	Are there any measures to collect spilt cement and concrete washings during concreting works?						$\overline{\checkmark}$			
1.21	Are there any oil interceptors/grease traps in the drainage system for vehicle and plant servicing areas, canteen kitchen, etc?	ems	\checkmark							
1.22	Are the oil interceptors/grease traps maintained properly?			\checkmark						



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
1.23	Is used bentonite recycled where appropriate?					\checkmark	
1.24	Is the sediment laden runoff from the unpaved surface to avoid discharge into the nearby aquatic environments, mash lands and moat ponds?		\checkmark				
Section	on 2: Air Quality						
2.01	Are there wheel washing facilities with high pressure jets provided at every vehicle exit point?					\checkmark	
2.02	Are vehicles washed to remove any dusty materials from their bodies and wheels before leaving construction sites?		\checkmark				
2.03	Are the excavated materials or exposure soil surface sprayed with water during handling?		\checkmark				
2.04	Are stockpiles of dusty materials sprayed with water, covered or placed in sheltered areas?		\checkmark				
2.05	Is the exposed earth properly treated within six months after the last construction activities?		\checkmark				
2.06	Are the access roads sprayed with water to maintain the entire road surface wet or paved and speed control (<15km/hr)?		\checkmark				
2.07	Is the surface where any drilling, cutting, polishing or breaking operation continuously sprayed with water?		\checkmark				
2.08	Is the load on vehicles covered entirely by clean impervious sheeting?		\checkmark				
2.09	Is the loading of materials to a level higher than the side and tail boards during transportation by vehicles avoided?		\checkmark				
2.10	Is the road leading to the construction site within 30m of the vehicle entrance kept clear of dusty materials?		\checkmark				
2.11	Is dark smoke emission from plant/equipment avoided?		\checkmark				
2.12	Are de-bagging, batching and mixing processes carried out in sheltered areas (3-sided roofed enclosure) during the use of bagged cement?		\checkmark				
2.13	Are site vehicles travelling within the speed limit (<15km/hour)?		\checkmark				
2.14	Are hoardings of not less than 2.4m high provided along the site boundary, which adjoins areas accessible to the public?		\checkmark				
2.15	Is open burning avoided?		\checkmark				
2.16	Are any materials dropped on the roads (Outside the site boundaries) had clean up immediately?		\checkmark				
Section	on 3: Noise						
3.01	Are noisy equipment and activities positioned as far as practicable from the sensitive receivers?		\checkmark				
3.02	Is silenced equipment adopted?		\checkmark				
3.03	Is idle equipment turned off or throttled down?		\checkmark				
3.04	Are all plant and equipment well maintained and in good condition?		\checkmark				
3.05	Are noise barriers or enclosures provided at areas where construction activities cause noise impact on sensitive receivers?		\checkmark				
3.06	Are hand held breakers fitted with valid noise emission labels during operation?	\checkmark					
3.07	Are air compressors fitted with valid noise emission labels during operation?		\checkmark				
3.08	Are flaps and panels of mechanical equipment closed during operation?		\checkmark				
3.09	Are Construction Noise Permit(s) applied for percussive piling works?					\checkmark	
3.10	Are Construction Noise Permit(s) applied for general construction works during restricted hours?					\checkmark	
3.11	Are valid Construction Noise Permit(s) posted at site entrances?		\checkmark				
Section	on 4: Waste/Chemical Management						
4.01	Are receptacles available for general refuse collection?		\checkmark				



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
4.02	Is general refuse sorting or recycling implemented?		\checkmark				
4.03	Is general refuse disposed of properly and regularly?		\checkmark				
4.04	Is the Contractor registered as a chemical waste producer?		\checkmark				
4.05	Are the chemical waste containers properly labelled?		\checkmark				
4.06	Are the chemical wastes stored in proper storage areas?		\checkmark				
4.07	Is the chemical waste storage area properly labelled?		\checkmark				
4.08	Is the chemical waste storage area used for storage of chemical waste only?		\checkmark				
4.09	Are incompatible chemical wastes stored in different areas?	\checkmark					
4.10	Are the chemical wastes disposed of by licensed collectors?	\checkmark					
4.11	Are trip tickets for chemical wastes disposal available for inspection?		\checkmark				
4.12	Are chemical/fuel storage areas bunded?		\checkmark				Photo 2
4.13	Are designated areas identified for storage and sorting of construction wastes?		\checkmark				
4.14	Are construction wastes sorted on site?		\checkmark				
4.15	Are construction wastes reused?		\checkmark				
4.16	Are construction wastes disposed of properly?		\checkmark				
4.17	Are site hoardings and signboards made of durable materials instead of timber?		\checkmark				
4.18	Is trip ticket system implemented for the disposal of construction wastes and records available for inspection?		\checkmark				
4.19	Are appropriate procedures followed if contaminated material exists?		\checkmark				
4.20	Is relevant license/ permit for disposal of construction waste or excavated materials available for inspection?		\checkmark				
Section	on 5: Landscape & Visual						
5.01	Are retained and transplanted trees in health condition?		\checkmark				
5.02	Are retained and transplanted trees properly protected?		\checkmark				
5.03	Are surgery works carried out for the damaged trees?	\checkmark					
5.04	Is damage to trees outside site boundary due to construction activities avoided?		\checkmark				
5.05	Is the night-time lighting controlled to minimize glare to sensitive receivers?		\checkmark				
Section	on 6: Others						
6.01	Are relevant Environmental Permits posted at all vehicle site entrances/exits?		\checkmark				



Remarks

Follow up of last Site Inspection:

- 1. Waste chemical container at Ha Tsuen PS was removed.
- 2. Cement bag near the site bound was removed.

Observations recorded in this Site Inspection: (7-12-2010)



Photo 1: Sedimentation tank at Shui Tsui San Tsuen PS was full of debit, the contractor was reminded to clean to maintain the tank efficiency.



Photo 2: At Shui Tsui San Tsuen PS, although drip trays for generator and oil drums are observed, the contractor was reminded to upgrade the mitigation measures to prevent oil spillage during fueling procedures.

RE's representative		IEC's representative		ET's representative	Contractor's representative	
()	()	(Ben Tam)	(



Projec	ct:		nspected b	у						
		Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen PS	RE's representative:			K.P. Che	eung			
Inspe	ction		IEC's representative:			-				
Date:		14 December 2010	ET's repres		Ben Tam					
Time:			Contractor'	•	ntative:	T.T. Lee				
DADT			Checklist N			DC20090	08-141210	<u>'</u>		
PART Weath		GENERAL INFORMATION Environmental F Sunny Fine Cloudy	Rainy	N/A						
	erature:	21.8 °C								
Humic	lity:	High Moderate V Low								
Wind:		Strong Breeze ✓ Light	Calm							
PART	B:	SITE AUDIT								
			Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks		
Section	on 1: W	ater Quality	_	_	_	_				
1.01		effluent discharge license obtained for the Project?		\checkmark						
1.02	Is the	effluent discharged in accordance with the discharge e?		\checkmark						
1.03	Is the	discharge of turbid water avoided?		\checkmark						
1.04	Are the	ere proper desilting facilities in the drainage systems to eS levels in effluent?		\checkmark						
1.05		ere channels, sandbags or bunds to divert the surface run-off imentation tanks/desilting system prior discharge?		\checkmark						
1.06	bound	ere any temporary perimeter channels provided at site aries to intercept storm runoff from crossing the site?	\checkmark							
1.07	nearby	porary drainage system (within site boundaries) and the permanent drainage system (outside site boundaries) are aintained?								
1.08		cavation proceeds, are temporary access roads protected by ed stone or gravel?		\checkmark						
1.09	Are ter	mporary exposed slopes properly covered?		\checkmark						
1.10	Are ea	arthworks final surfaces well compacted or protected?		\checkmark						
1.11	Are ma	anholes adequately covered or temporarily sealed?		\checkmark						
1.12	Are the	ere any procedures and equipment for rainstorm protection?	\checkmark							
1.13	Are wh	neel washing facilities well maintained?		\checkmark						
1.14	ls over	rflow runoff from wheel washing facilities avoided?		\checkmark						
1.15	Are the	ere chemical toilets provided on site?		\checkmark						
1.16	Are ch	emical toilets properly maintained?		\checkmark						
1.17		e vehicle and plant servicing areas paved and located within areas?					\checkmark			
1.18		oil leakage from the on-site vehicles/plants or spillage during el refilling avoided?		\checkmark						
1.19	tempo	nere any measures to prevent oil leakage entering the rary/permanent drainage system?		\checkmark						
1.20	washir	ere any measures to collect spilt cement and concrete ngs during concreting works?					\checkmark			
1.21		ere any oil interceptors/grease traps in the drainage systems nicle and plant servicing areas, canteen kitchen, etc?	\checkmark							
1.22	Are the	e oil interceptors/grease traps maintained properly?		\checkmark						



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
1.23	Is used bentonite recycled where appropriate?					\checkmark	
1.24	Is the sediment laden runoff from the unpaved surface to avoid discharge into the nearby aquatic environments, mash lands and moat ponds?		\checkmark				
Section	on 2: Air Quality						
2.01	Are there wheel washing facilities with high pressure jets provided at every vehicle exit point?					\checkmark	
2.02	Are vehicles washed to remove any dusty materials from their bodies and wheels before leaving construction sites?		\checkmark				
2.03	Are the excavated materials or exposure soil surface sprayed with water during handling?		\checkmark				
2.04	Are stockpiles of dusty materials sprayed with water, covered or placed in sheltered areas?		\checkmark				
2.05	Is the exposed earth properly treated within six months after the last construction activities?		\checkmark				
2.06	Are the access roads sprayed with water to maintain the entire road surface wet or paved and speed control (<15km/hr)?		\checkmark				
2.07	Is the surface where any drilling, cutting, polishing or breaking operation continuously sprayed with water?		\checkmark				
2.08	Is the load on vehicles covered entirely by clean impervious sheeting?		\checkmark				
2.09	Is the loading of materials to a level higher than the side and tail boards during transportation by vehicles avoided?		\checkmark				
2.10	Is the road leading to the construction site within 30m of the vehicle entrance kept clear of dusty materials?				\checkmark		Photo 1
2.11	Is dark smoke emission from plant/equipment avoided?		\checkmark				
2.12	Are de-bagging, batching and mixing processes carried out in sheltered areas (3-sided roofed enclosure) during the use of bagged cement?		\checkmark				
2.13	Are site vehicles travelling within the speed limit (<15km/hour)?		\checkmark				
2.14	Are hoardings of not less than 2.4m high provided along the site boundary, which adjoins areas accessible to the public?		\checkmark				
2.15	Is open burning avoided?		\checkmark				
2.16	Are any materials dropped on the roads (Outside the site boundaries) had clean up immediately?		\checkmark				
Section	on 3: Noise						
3.01	Are noisy equipment and activities positioned as far as practicable from the sensitive receivers?		\checkmark				
3.02	Is silenced equipment adopted?		\checkmark				
3.03	Is idle equipment turned off or throttled down?		\checkmark				
3.04	Are all plant and equipment well maintained and in good condition?		\checkmark				
3.05	Are noise barriers or enclosures provided at areas where construction activities cause noise impact on sensitive receivers?		\checkmark				
3.06	Are hand held breakers fitted with valid noise emission labels during operation?	\checkmark					
3.07	Are air compressors fitted with valid noise emission labels during operation?		\checkmark				
3.08	Are flaps and panels of mechanical equipment closed during operation?		\checkmark				
3.09	Are Construction Noise Permit(s) applied for percussive piling works?					\checkmark	
3.10	Are Construction Noise Permit(s) applied for general construction works during restricted hours?					\checkmark	
3.11	Are valid Construction Noise Permit(s) posted at site entrances?		\checkmark				
Section	on 4: Waste/Chemical Management						
4.01	Are receptacles available for general refuse collection?		\checkmark				



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
4.02	Is general refuse sorting or recycling implemented?		V				
4.03	Is general refuse disposed of properly and regularly?		\checkmark				
4.04	Is the Contractor registered as a chemical waste producer?		\checkmark				
4.05	Are the chemical waste containers properly labelled?		\checkmark				
4.06	Are the chemical wastes stored in proper storage areas?		\checkmark				
4.07	Is the chemical waste storage area properly labelled?		\checkmark				
4.08	Is the chemical waste storage area used for storage of chemical waste only?		\checkmark				
4.09	Are incompatible chemical wastes stored in different areas?	\checkmark					
4.10	Are the chemical wastes disposed of by licensed collectors?	\checkmark					
4.11	Are trip tickets for chemical wastes disposal available for inspection?		\checkmark				
4.12	Are chemical/fuel storage areas bunded?		\checkmark				Photo 2
4.13	Are designated areas identified for storage and sorting of construction wastes?		\checkmark				
4.14	Are construction wastes sorted on site?		\checkmark				
4.15	Are construction wastes reused?		\checkmark				
4.16	Are construction wastes disposed of properly?		\checkmark				
4.17	Are site hoardings and signboards made of durable materials instead of timber?		\checkmark				
4.18	Is trip ticket system implemented for the disposal of construction wastes and records available for inspection?		\checkmark				
4.19	Are appropriate procedures followed if contaminated material exists?		\checkmark				
4.20	Is relevant license/ permit for disposal of construction waste or excavated materials available for inspection?		\checkmark				
Section	on 5: Landscape & Visual						
5.01	Are retained and transplanted trees in health condition?		\checkmark				
5.02	Are retained and transplanted trees properly protected?		\checkmark				
5.03	Are surgery works carried out for the damaged trees?	\checkmark					
5.04	Is damage to trees outside site boundary due to construction activities avoided?		\checkmark				
5.05	Is the night-time lighting controlled to minimize glare to sensitive receivers?		\checkmark				
Section	on 6: Others						
6.01	Are relevant Environmental Permits posted at all vehicle site entrances/exits?		\checkmark				



Remarks

Follow up of last Site Inspection:

1. Debits inside the sedimentation tank observed at last inspection was cleared.

Observations recorded in this Site Inspection: (14-12-2010)



Photo 1: Sand and mud was observed at the site entrance, the contractor was reminded to clean to maintain the public area around the site area clean and tidy.



Photo 2: At Shui Tsui San Tsuen PS, although drip trays for generator and oil drums are observed, the contractor was reminded to upgrade the mitigation measures to prevent oil spillage during fueling procedures.

RE's representative	IEC's representative	ET's representative	Contractor's representative	
			representative	
		(Ben Tam)		



Proje	Construction of Yuen Long South E Sewers and Expansion of Ha Tsuen PS	Branch F	nspected b	entative:		Y K Ho				
Inspe Date:			EC's repres ET's repres			F. C. Tsa				
Time:			Contractor's representative:			T.T. Lee				
		(Checklist N	0.		DC200908-211210				
PART	A: GENERAL INFORMATION E	nvironmental P	ermit No.:	N/A						
Weath		Cloudy	Rainy							
	erature: 19.3 °C dity: High Moderate	Low								
Humic Wind:		Light	Calm							
PART	B: SITE AUDIT									
			Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks		
Section	on 1: Water Quality									
1.01	Is an effluent discharge license obtained for the Proje			$\overline{\mathbf{V}}$			<u></u> -			
1.02	Is the effluent discharged in accordance with the disc licence?	narge		\checkmark						
1.03	Is the discharge of turbid water avoided?			\checkmark						
1.04	Are there proper desilting facilities in the drainage system. reduce SS levels in effluent?	stems to		$\overline{\checkmark}$						
1.05	Are there channels, sandbags or bunds to divert the sto sedimentation tanks/desilting system prior discharge			\checkmark						
1.06	Are there any temporary perimeter channels provided boundaries to intercept storm runoff from crossing the	e site?	\checkmark							
1.07	Is temporary drainage system (within site boundaries nearby permanent drainage system (outside site boundaries) well maintained?			\checkmark						
1.08	As excavation proceeds, are temporary access roads crushed stone or gravel?	protected by		\checkmark						
1.09	Are temporary exposed slopes properly covered?					\checkmark		Photo 1		
1.10	Are earthworks final surfaces well compacted or prote	ected?		\checkmark						
1.11	Are manholes adequately covered or temporarily sea	led?		\checkmark						
1.12	Are there any procedures and equipment for rainstorn	m protection?	\checkmark							
1.13	Are wheel washing facilities well maintained?			\checkmark						
1.14	Is overflow runoff from wheel washing facilities avoided	ed?		\checkmark						
1.15	Are there chemical toilets provided on site?			\checkmark						
1.16	Are chemical toilets properly maintained?			\checkmark						
1.17	Are the vehicle and plant servicing areas paved and I roofed areas?	ocated within					$\overline{\checkmark}$			
1.18	Is the oil leakage from the on-site vehicles/plants or s the fuel refilling avoided?	pillage during		\checkmark						
1.19	Are there any measures to prevent oil leakage temporary/permanent drainage system?	entering the		\checkmark						
1.20	Are there any measures to collect spilt cement and cowashings during concreting works?						$\overline{\checkmark}$			
1.21	Are there any oil interceptors/grease traps in the drain for vehicle and plant servicing areas, canteen kitchen		\checkmark							
1.22	Are the oil interceptors/grease traps maintained proper	erly?		\checkmark						



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
1.23	Is used bentonite recycled where appropriate?					\checkmark	
1.24	Is the sediment laden runoff from the unpaved surface to avoid discharge into the nearby aquatic environments, mash lands and moat ponds?		\checkmark				
Section	on 2: Air Quality						
2.01	Are there wheel washing facilities with high pressure jets provided at every vehicle exit point?					\checkmark	
2.02	Are vehicles washed to remove any dusty materials from their bodies and wheels before leaving construction sites?		\checkmark				
2.03	Are the excavated materials or exposure soil surface sprayed with water during handling?		\checkmark				
2.04	Are stockpiles of dusty materials sprayed with water, covered or placed in sheltered areas?		\checkmark				
2.05	Is the exposed earth properly treated within six months after the last construction activities?		\checkmark				
2.06	Are the access roads sprayed with water to maintain the entire road surface wet or paved and speed control (<15km/hr)?		\checkmark				
2.07	Is the surface where any drilling, cutting, polishing or breaking operation continuously sprayed with water?		\checkmark				
2.08	Is the load on vehicles covered entirely by clean impervious sheeting?		\checkmark				
2.09	Is the loading of materials to a level higher than the side and tail boards during transportation by vehicles avoided?		\checkmark				
2.10	Is the road leading to the construction site within 30m of the vehicle entrance kept clear of dusty materials?		\checkmark				
2.11	Is dark smoke emission from plant/equipment avoided?		\checkmark				
2.12	Are de-bagging, batching and mixing processes carried out in sheltered areas (3-sided roofed enclosure) during the use of bagged cement?		\checkmark				
2.13	Are site vehicles travelling within the speed limit (<15km/hour)?		\checkmark				
2.14	Are hoardings of not less than 2.4m high provided along the site boundary, which adjoins areas accessible to the public?		\checkmark				
2.15	Is open burning avoided?		\checkmark				
2.16	Are any materials dropped on the roads (Outside the site boundaries) had clean up immediately?		\checkmark				
Section	on 3: Noise						
3.01	Are noisy equipment and activities positioned as far as practicable from the sensitive receivers?		\checkmark				
3.02	Is silenced equipment adopted?		\checkmark				
3.03	Is idle equipment turned off or throttled down?		\checkmark				
3.04	Are all plant and equipment well maintained and in good condition?		\checkmark				
3.05	Are noise barriers or enclosures provided at areas where construction activities cause noise impact on sensitive receivers?		\checkmark				
3.06	Are hand held breakers fitted with valid noise emission labels during operation?	\checkmark					
3.07	Are air compressors fitted with valid noise emission labels during operation?		\checkmark				
3.08	Are flaps and panels of mechanical equipment closed during operation?		\checkmark				
3.09	Are Construction Noise Permit(s) applied for percussive piling works?					\checkmark	
3.10	Are Construction Noise Permit(s) applied for general construction works during restricted hours?					\checkmark	
3.11	Are valid Construction Noise Permit(s) posted at site entrances?		\checkmark				
Section	on 4: Waste/Chemical Management						
4.01	Are receptacles available for general refuse collection?		\checkmark				



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
4.02	Is general refuse sorting or recycling implemented?		V				
4.03	Is general refuse disposed of properly and regularly?		\checkmark				
4.04	Is the Contractor registered as a chemical waste producer?		\checkmark				
4.05	Are the chemical waste containers properly labelled?		\checkmark				
4.06	Are the chemical wastes stored in proper storage areas?		\checkmark				
4.07	Is the chemical waste storage area properly labelled?		\checkmark				
4.08	Is the chemical waste storage area used for storage of chemical waste only?		\checkmark				
4.09	Are incompatible chemical wastes stored in different areas?	\checkmark					
4.10	Are the chemical wastes disposed of by licensed collectors?	\checkmark					
4.11	Are trip tickets for chemical wastes disposal available for inspection?		\checkmark				
4.12	Are chemical/fuel storage areas bunded?		\checkmark				
4.13	Are designated areas identified for storage and sorting of construction wastes?		\checkmark				
4.14	Are construction wastes sorted on site?		\checkmark				
4.15	Are construction wastes reused?		\checkmark				
4.16	Are construction wastes disposed of properly?				\checkmark		Photo 3
4.17	Are site hoardings and signboards made of durable materials instead of timber?		\checkmark				
4.18	Is trip ticket system implemented for the disposal of construction wastes and records available for inspection?		\checkmark				
4.19	Are appropriate procedures followed if contaminated material exists?		\checkmark				
4.20	Is relevant license/ permit for disposal of construction waste or excavated materials available for inspection?		\checkmark				
Section	n 5: Landscape & Visual						
5.01	Are retained and transplanted trees in health condition?		\checkmark				
5.02	Are retained and transplanted trees properly protected?		\checkmark				
5.03	Are surgery works carried out for the damaged trees?	\checkmark					
5.04	Is damage to trees outside site boundary due to construction activities avoided?		\checkmark				
5.05	Is the night-time lighting controlled to minimize glare to sensitive receivers?		\checkmark				
Section	on 6: Others						
6.01	Are relevant Environmental Permits posted at all vehicle site entrances/exits?		\checkmark				

Remarks

Follow up of last Site Inspection:

Debris found near site boundary was cleared

Observations recorded in this Site Inspection: (21-12-2010)



Photo 1: It was reminded that the Contractor should provide proper impermeable cover to stockpile of materials.



Photo 2: Accumulation of stagnant water was observed on site. The Contractor was reminded to properly clear the water.



Photo 3: Waste plastic barriers were found onsite. The contractor was reminded to properly dispose the construction waste generated from the site.



Projec	Construction of Yuen Long South Branch Sewers and Expansion of Ha Tsuen PS	Inspected by RE's representative:		K.P. Cheung						
Inspectors Date:		IEC's representative:		:	- Don Tom					
Time:			ET's representative: Contractor's representative:			Ben Tam Mandy Lam				
			Checklist No.				DC200908-281210			
PART A: GENERAL INFORMATION Environmental Permit No.: N/A										
Weath		F	Rainy							
Temperature: 15.4 °C										
Humid Wind:			Calm							
PART	B: SITE AUDIT									
			lot bs.	Yes	No	Follow up	N/A	Photo/ Remarks		
Section	on 1: Water Quality	_								
1.01	Is an effluent discharge license obtained for the Project?			\checkmark						
1.02	Is the effluent discharged in accordance with the discharge licence?			\checkmark						
1.03	Is the discharge of turbid water avoided?			\checkmark						
1.04	Are there proper desilting facilities in the drainage systems to reduce SS levels in effluent?			\checkmark						
1.05	Are there channels, sandbags or bunds to divert the surface run to sedimentation tanks/desilting system prior discharge?	-off [\checkmark						
1.06	Are there any temporary perimeter channels provided at site boundaries to intercept storm runoff from crossing the site?	[
1.07	Is temporary drainage system (within site boundaries) and the nearby permanent drainage system (outside site boundaries) are well maintained?			\checkmark						
1.08	As excavation proceeds, are temporary access roads protected by crushed stone or gravel?			\checkmark						
1.09	9 Are temporary exposed slopes properly covered?			\checkmark						
1.10	Are earthworks final surfaces well compacted or protected?			\checkmark						
1.11	Are manholes adequately covered or temporarily sealed?			\checkmark						
1.12	Are there any procedures and equipment for rainstorm protection	n? [
1.13	Are wheel washing facilities well maintained?			\checkmark						
1.14	Is overflow runoff from wheel washing facilities avoided?			\checkmark						
1.15	Are there chemical toilets provided on site?			\checkmark						
1.16	Are chemical toilets properly maintained?			\checkmark						
1.17	Are the vehicle and plant servicing areas paved and located with roofed areas?	nin [$\overline{\checkmark}$			
1.18	Is the oil leakage from the on-site vehicles/plants or spillage duri the fuel refilling avoided?	ng [\checkmark		Photo 1		
1.19	Are there any measures to prevent oil leakage entering temporary/permanent drainage system?	the [\checkmark						
1.20	Are there any measures to collect spilt cement and concrete washings during concreting works?						$\overline{\checkmark}$			
1.21	Are there any oil interceptors/grease traps in the drainage system for vehicle and plant servicing areas, canteen kitchen, etc?	ms [
1.22	Are the oil interceptors/grease traps maintained properly?			\checkmark						



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
1.23	Is used bentonite recycled where appropriate?					\checkmark	
1.24	Is the sediment laden runoff from the unpaved surface to avoid discharge into the nearby aquatic environments, mash lands and moat ponds?		\checkmark				
Section	on 2: Air Quality						
2.01	Are there wheel washing facilities with high pressure jets provided at every vehicle exit point?					\checkmark	
2.02	Are vehicles washed to remove any dusty materials from their bodies and wheels before leaving construction sites?		\checkmark				
2.03	Are the excavated materials or exposure soil surface sprayed with water during handling?		\checkmark				
2.04	Are stockpiles of dusty materials sprayed with water, covered or placed in sheltered areas?		\checkmark				
2.05	Is the exposed earth properly treated within six months after the last construction activities?		\checkmark				
2.06	Are the access roads sprayed with water to maintain the entire road surface wet or paved and speed control (<15km/hr)?		\checkmark				
2.07	Is the surface where any drilling, cutting, polishing or breaking operation continuously sprayed with water?		\checkmark				
2.08	Is the load on vehicles covered entirely by clean impervious sheeting?		\checkmark				
2.09	Is the loading of materials to a level higher than the side and tail boards during transportation by vehicles avoided?		\checkmark				
2.10	Is the road leading to the construction site within 30m of the vehicle entrance kept clear of dusty materials?		\checkmark				
2.11	Is dark smoke emission from plant/equipment avoided?		\checkmark				
2.12	Are de-bagging, batching and mixing processes carried out in sheltered areas (3-sided roofed enclosure) during the use of bagged cement?		\checkmark				
2.13	Are site vehicles travelling within the speed limit (<15km/hour)?		\checkmark				
2.14	Are hoardings of not less than 2.4m high provided along the site boundary, which adjoins areas accessible to the public?		\checkmark				
2.15	Is open burning avoided?		\checkmark				
2.16	Are any materials dropped on the roads (Outside the site boundaries) had clean up immediately?		\checkmark				
Section	Section 3: Noise						
3.01	Are noisy equipment and activities positioned as far as practicable from the sensitive receivers?		\checkmark				
3.02	Is silenced equipment adopted?		\checkmark				
3.03	Is idle equipment turned off or throttled down?		\checkmark				
3.04	Are all plant and equipment well maintained and in good condition?		\checkmark				
3.05	Are noise barriers or enclosures provided at areas where construction activities cause noise impact on sensitive receivers?		\checkmark				
3.06	Are hand held breakers fitted with valid noise emission labels during operation?	\checkmark					
3.07	Are air compressors fitted with valid noise emission labels during operation?		\checkmark				
3.08	Are flaps and panels of mechanical equipment closed during operation?		\checkmark				
3.09	Are Construction Noise Permit(s) applied for percussive piling works?					\checkmark	
3.10	Are Construction Noise Permit(s) applied for general construction works during restricted hours?					\checkmark	
3.11	Are valid Construction Noise Permit(s) posted at site entrances?		\checkmark				
Section 4: Waste/Chemical Management							
4.01	Are receptacles available for general refuse collection?		\checkmark				



		Not Obs.	Yes	No	Follow up	N/A	Photo/ Remarks
4.02	Is general refuse sorting or recycling implemented?		V				
4.03	Is general refuse disposed of properly and regularly?		\checkmark				
4.04	Is the Contractor registered as a chemical waste producer?		\checkmark				
4.05	Are the chemical waste containers properly labelled?		\checkmark				
4.06	Are the chemical wastes stored in proper storage areas?		\checkmark				
4.07	Is the chemical waste storage area properly labelled?		\checkmark				
4.08	Is the chemical waste storage area used for storage of chemical waste only?		\checkmark				
4.09	Are incompatible chemical wastes stored in different areas?	\checkmark					
4.10	Are the chemical wastes disposed of by licensed collectors?	\checkmark					
4.11	Are trip tickets for chemical wastes disposal available for inspection?		\checkmark				
4.12	Are chemical/fuel storage areas bunded?		\checkmark				
4.13	Are designated areas identified for storage and sorting of construction wastes?		\checkmark				
4.14	Are construction wastes sorted on site?		\checkmark				
4.15	Are construction wastes reused?		\checkmark				
4.16	Are construction wastes disposed of properly?		\checkmark				
4.17	Are site hoardings and signboards made of durable materials instead of timber?		\checkmark				
4.18	Is trip ticket system implemented for the disposal of construction wastes and records available for inspection?		\checkmark				
4.19	Are appropriate procedures followed if contaminated material exists?		\checkmark				
4.20	Is relevant license/ permit for disposal of construction waste or excavated materials available for inspection?		\checkmark				
Section 5: Landscape & Visual							
5.01	Are retained and transplanted trees in health condition?		\checkmark				
5.02	Are retained and transplanted trees properly protected?		\checkmark				
5.03	Are surgery works carried out for the damaged trees?	\checkmark					
5.04	Is damage to trees outside site boundary due to construction activities avoided?		\checkmark				
5.05	Is the night-time lighting controlled to minimize glare to sensitive receivers?		\checkmark				
Section 6: Others							
6.01	Are relevant Environmental Permits posted at all vehicle site entrances/exits?		\checkmark				



Remarks

Follow up of last Site Inspection:

- 1. Stockpile covered with tarpaulin sheets was observed.
- 2. Stagnant water observed at last inspection was removed.
- 3. Waste plastic barriers observed at last inspection was removed.

Observations recorded in this Site Inspection: (28-12-2010)



Photo 1: Oil leakage from the air compressor was observed at Tai Shiu Ha works area, the contractor was request to clean up immediately to prevent ant contamination.

RE's representative	IEC's representative	ET's representative	Contractor's representative
() ()	(Ben Tam)	()