

**GOVERNMENT OF THE HONG KONG SPECIAL ADMINISTRATION REGION  
TERRITORY DEVELOPMENT DEPARTMENT**

**KAI TAK AIRPORT NORTH APRON  
DECOMMISSIONING**

**Decontamination Pilot Test - Final Report**

**Volume 1**

**March 1999**

**MAUNSELL CONSULTANTS ASIA LTD**

**in association with**

**Maunsell Environmental Management Consultants Ltd**

**MAUNSELL ENVIRONMENTAL  
MANAGEMENT CONSULTANTS LTD**


**POLICY STATEMENT ON  
QUALITY ASSURANCE**

MEMCL undertakes environmental consultancy works in Hong Kong and overseas for Government Departments, authorities and commercial companies. This activity, carried out in every case in accordance with the contractual and general requirements of the individual Client, relies on the experience, expertise, reliability and quality of the work of MEMCL.

MEMCL is committed to providing our clients with the most responsive and professional environmental consulting services in Asia.

In pursuit of these objectives, the Directors have implemented Quality Systems which have achieved Third Party Certification to BS EN ISO 9001:1994. All employees of the Company have a responsibility for quality and are expected to exercise reasonable skill and care in providing a quality service to Clients. Every employee has access to the Quality Manual and its contents are explained to all individuals. Quality Plans produced for projects define the responsibilities and duties of the principal staff.

The quality procedures are under continual review by Senior Management to ensure that the changing needs of the Company's Clients are met.

<b>REPORT NO.</b>	1565 (Volume 1)
<b>STATUS</b>	Final
<b>DATE OF ISSUE</b>	1 March 1999
<b>APPROVED BY</b>	 (Director)

**REMARKS:**

The information supplied and contained within this report is, to the best of our knowledge, correct at the time of printing. Where information has been supplied by third parties, such information is reproduced here in good faith and MEMCL accepts no responsibility for the accuracy of the supplied information.

MEMCL accepts no responsibility for changes made to this report by third parties.

# TABLE OF CONTENTS

	Page
1 INTRODUCTION	1
1.1 Background to Pilot Test	1
1.2 Review of Previous Findings	3
1.2.1 Contamination Hot Spots	3
1.2.2 Laboratory Test of Hydraulic Conductivity of Soil Samples Collected in Hot Spot B	3
1.2.3 Field-Based Permeability Test Outside of Hot Spot B	4
1.3 Design of Pilot Test	4
2 OBJECTIVES AND SCOPE OF PILOT TEST	5
3 METHODOLOGY	6
3.1 Setting Out and Utility Survey	6
3.2 Boring Log and Soil Particle Size Analyses	6
3.3 Installation of Testing Wells and Monitoring Wells	6
3.3.1 Soil Vapour Extraction Wells	6
3.3.2 Soil Vapour Monitoring Wells	6
3.3.3 Air Sparging Wells	7
3.3.4 Groundwater Monitoring Wells	7
3.3.5 Comparison to Actual Design Well Layout	8
3.4 Assembly of SVE and AS System	8
3.4.1 Soil Vapour Extraction System	8
3.4.2 Air Sparging System	8
3.5 Pilot Testing	9
3.5.1 Short-term Soil Vapour Extraction Tests	9
3.5.2 Long-term Soil Vapour Extraction Tests	9
3.5.3 Short-term Air Sparging Tests	9
3.5.4 Tracer (Helium) Tests	10
3.5.5 Long-term Combined Soil Vapour Extraction/ Air Sparging Tests	10
3.5.6 Equipment Employed	15
3.6 Computer Modelling for Soil Permeability	15
4 RESULTS	16
4.1 Setting Out and Utility Survey	16
4.2 Boring Log and Soil Particle Size Analyses	16
4.3 Short-term Soil Vapour Extraction Tests	16
4.4 Long-term Soil Vapour Extraction Tests	16
4.5 Short-term Air Sparging Tests	18
4.6 Tracer (Helium) Tests	19
4.7 Long-term Combined Soil Vapour Extraction/ Air Sparging Tests	20
4.8 Cross-checking of VOC Measurements	22
4.9 Computer Modelling on Permeability of Soil	23

5	DATA INTERPRETATION	24
5.1	General Description of Site Geology	24
5.2	Short-term Soil Vapour Extraction Tests	24
5.3	Long-term Soil Vapour Extraction Test	25
5.4	Short-term Air Sparging Tests	26
5.5	Tracer (Helium) Tests	28
5.6	Long-term Combined Soil Vapour Extraction/ Air Sparging Tests	29
5.7	Computer Modelling on Permeability of Soil	30
6	EVALUATION OF RESULTS AGAINST CRITERIA IN EIA REPORT	31
6.1	Radius of Influence (ROI)	31
6.1.1	ROI for SVE	31
6.1.2	ROI for AS	32
6.2	Clean Up Time Based on Volatilisation	33
6.2.1	Clean Up Time Based on Site Data	33
6.2.2	Clean Up Time Based on Typical Literature Values	35
6.3	Clean Up Time Based on Biodegradation	36
6.3.1	Clean Up Time Based on Site Data	36
6.3.2	Clean Up Time Based on Typical Literature Values	37
6.4	Groundwater Extraction by SVE	38
6.5	Implication on VOC Emission Treatment	38
6.6	Lateral Migration of Free Product	38
6.7	Preferential Pathways	39
7	CONCLUSIONS AND RECOMMENDATIONS	40

### List of Tables

Table 3.1	Measuring Parameters, Locations and Frequency for Pilot Tests	12
Table 4.1	Baseline Conditions of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> for Long-term SVE Test Conducted at VT1	17
Table 4.2	Baseline Conditions of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> for Long-term SVE Test Conducted at VT2	17
Table 4.3	Baseline Conditions of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> for Long-term SVE Test Conducted at VT3	17
Table 4.4	Baseline Conditions of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> for Long-term SVE Test Conducted at VT4	18
Table 4.5	Baseline Conditions of DO for Short-term AS Tests Conducted at VT3 and VT4	19
Table 4.6	Baseline Conditions of Helium for Tracer (Helium) Tests Conducted at VT3 and VT4	20
Table 4.7	Baseline Conditions of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> for Long-term Combined SVE/AS Test Conducted at VT3	21
Table 4.8	Baseline Conditions of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> for Long-term Combined SVE/AS Test Conducted at VT4	21
Table 4.9	Baseline Conditions of DO for Long-term Combined SVE/AS Tests Conducted at VT3 T3 and VT4	22
Table 4.10	Summary of Results of Computer Modelling on Permeability of Soil	23

Table 6.1	Summary of ROIs for SVE	32
Table 6.2	Summary of ROIs for AS	33
Table 6.3	Calculation Table for Contaminant Removal by SVE/AS at VT4	34
Table 6.4	Vertical Distribution of TPH at Six Most Contaminated Locations Within Hot Spot B	35
Table 6.5	Quantification of Proportion of C6-C11 Fraction	35
Table 6.6	Clean Up Time for Volatile Fraction at VT1 to VT4	36
Table 6.7	Calculation Table for Contaminant Removal by Biodegradation at VT4	37
Table 6.8	Clean Up Time Based on Biodegradation Within Hot Spot B	38

## List of Figures

Figure 1.1	Programme of Pilot Test
Figure 1.2	Three Hot Spots of TPH Contamination
Figure 1.3	TPH Level for Soil at 1m above Groundwater Level
Figure 1.4	TPH Level for Soil at 1m below Groundwater Level
Figure 1.5	Applicability of SVE Treatment
Figure 1.6	Range of Values of Hydraulic Conductivity and Permeability for Geological Materials
Figure 1.7	Hydraulic Conductivity of Soil Samples Taken at Hot Spot B
Figure 1.8	Contours of Hydraulic Conductivity of Soil Across Hot Spot B
Figure 1.9	Testing Locations of the Previous Further Site Investigation
Figure 2.1	Four Testing Locations of Pilot Test
Figure 3.1	Layout of SVE Wells and Monitoring Points at VT1 and VT2
Figure 3.2	Layout of SVE Wells, AS Wells and Monitoring Points at VT3
Figure 3.3	Layout of SVE Wells, AS Wells and Monitoring Points at VT4
Figure 3.4	Detailed Arrangement of SVE Wells, AS Wells and Monitoring Points at VT3 and VT4
Figure 3.5	Schematic Diagram of Soil Vapour Extraction Well
Figure 3.6	Schematic Diagram of Soil Vapour Monitoring Well
Figure 3.7	Schematic Diagram of Air Sparging Well
Figure 3.8	Schematic Diagram Groundwater Monitoring Well
Figure 3.9	Schematic Configuration of Soil Vapour Extraction System
Figure 3.10	Schematic Configuration of Air Sparging System
Figure 4.1	Particle Size Distribution of Soil Taken at VT1-1m and VT1-2m
Figure 4.2	Particle Size Distribution of Soil Taken at VT1C-1m and VT1C-2m
Figure 4.3	Particle Size Distribution of Soil Taken at VT2-1m and VT2-2m
Figure 4.4	Particle Size Distribution of Soil Taken at VT2C-1m and VT2C-2m
Figure 4.5	Particle Size Distribution of Soil Taken at VT3-1m and VT3-2m
Figure 4.6	Particle Size Distribution of Soil Taken at VT3D-1m and VT3D-2m
Figure 4.7	Particle Size Distribution of Soil Taken at VT3E-2m and VT3E-3m
Figure 4.8	Particle Size Distribution of Soil Taken at VT3F-2m and VT3F-3m
Figure 4.9	Particle Size Distribution of Soil Taken at VT3AS-4m and VT3AS-5m
Figure 4.10	Particle Size Distribution of Soil Taken at VT3AS-6m
Figure 4.11	Particle Size Distribution of Soil Taken at VT3W3-2m and VT3W3-3m

- Figure 4.12 Particle Size Distribution of Soil Taken at VT4-1m and VT4-2m
- Figure 4.13 Particle Size Distribution of Soil Taken at VT4C-1m and VT4C-2m
- Figure 4.14 Particle Size Ranges According to Several Soil Classification Systems
- Figure 4.15 Applied Vacuum vs. Extracted Air Flow Rate (Short-term SVE Tests at VT1 and VT2)
- Figure 4.16 Applied Vacuum vs. Extracted Air Flow Rate (Short-term SVE Tests at VT3 and VT4)
- Figure 4.17 Steady State Vacuum at Vapour Probes vs. Distance from SVE Well (Short-term SVE Tests at VT1)
- Figure 4.18 Steady State Vacuum at Vapour Probes vs. Distance from SVE Well (Short-term SVE Tests at VT2)
- Figure 4.19 Steady State Vacuum at Vapour Probes vs. Distance from SVE Well (Short-term SVE Tests at VT3)
- Figure 4.20 Steady State Vacuum at Vapour Probes vs. Distance from SVE Well (Short-term SVE Tests at VT4)
- Figure 4.21 Steady State Vacuum at Radial Vapour Probes vs. Direction from SVE Well (Short-term SVE Tests at VT3)
- Figure 4.22 Concentration of VOC, CO<sub>2</sub>, O<sub>2</sub> and CH<sub>4</sub> at Blower Outlet vs. Time (Long-term SVE Test at VT1)
- Figure 4.23 Concentration of VOC, CO<sub>2</sub>, O<sub>2</sub> and CH<sub>4</sub> at Blower Outlet vs. Time (Long-term SVE Test at VT2)
- Figure 4.24 Concentration of VOC, CO<sub>2</sub>, O<sub>2</sub> and CH<sub>4</sub> at Blower Outlet vs. Time (Long-term SVE Test at VT3)
- Figure 4.25 Concentration of VOC, CO<sub>2</sub>, O<sub>2</sub> and CH<sub>4</sub> at Blower Outlet vs. Time (Long-term SVE Test at VT4)
- Figure 4.26 Steady State Pressure at Vapour Probes vs. Distance from AS Well (Short-term AS Tests at VT3)
- Figure 4.27 Steady State Pressure at Vapour Probes vs. Distance from AS Well (Short-term AS Tests at VT4)
- Figure 4.28 Steady State Pressure at Radial Vapour Probes vs. Direction from AS Well (Short-term AS Tests at VT3)
- Figure 4.29 Steady State Pressure at Radial Vapour Probes vs. Direction from AS Well (Short-term AS Tests at VT4)
- Figure 4.30 Depth to Water Table at Groundwater Monitoring Wells vs. Time (Short-term AS Tests at VT3)
- Figure 4.31 Depth to Water Table at Groundwater Monitoring Wells vs. Time (Short-term AS Tests at VT4)
- Figure 4.32 D.O. Concentration at Shallow Groundwater Monitoring Wells vs. Time (Short-term AS Tests at VT3)
- Figure 4.33 D.O. Concentration at Deep Groundwater Monitoring Wells vs. Time (Short-term AS Tests at VT3)
- Figure 4.34 D.O. Concentration at Shallow Groundwater Monitoring Wells vs. Time (Short-term AS Tests at VT4)
- Figure 4.35 D.O. Concentration at Deep Groundwater Monitoring Wells vs. Time (Short-term AS Tests at VT4)
- Figure 4.36 Helium Concentration at Shallow Vapour Probes vs. Time (Helium Test at VT3, Helium concentration = 25%)

Figure 4.37	Helium Concentration at Deep Vapour Probes vs. Time (Helium Test at VT3, Helium concentration = 25%)
Figure 4.38	Helium Concentration at Shallow Vapour Probes vs. Time (Helium Test at VT3 Helium concentration = 16.5%)
Figure 4.39	Helium Concentration at Deep Vapour Probes vs. Time (Helium Test at VT3, Helium concentration = 16.5%)
Figure 4.40	Helium Concentration at Shallow Vapour Probes vs. Time (Helium Test at VT4, Helium concentration = 9%)
Figure 4.41	Helium Concentration at Deep Vapour Probes vs. Time (Helium Test at VT4, Helium concentration = 9%)
Figure 4.42	Helium Concentration at Shallow Vapour Probes vs. Time (Helium Test at VT4 Helium concentration = 8.33%)
Figure 4.43	Helium Concentration at Deep Vapour Probes vs. Time (Helium Test at VT4, Helium concentration = 8.33%)
Figure 4.44	Depth to Water Table at Groundwater Monitoring Wells vs. Time (Long-term Combined SVE/AS Test at VT3)
Figure 4.45	Depth to Water Table at SVE Well and Groundwater Monitoring Wells vs. Time (Long-term Combined SVE/AS Test at VT4)
Figure 4.46	D.O. Concentration at Shallow and Deep Groundwater Monitoring Wells vs. Time (Long-term Combined SVE/AS Test at VT3)
Figure 4.47	D.O. Concentration at Shallow and Deep Groundwater Monitoring Wells vs. Time (Long-term Combined SVE/AS Test at VT4)
Figure 4.48	Concentration of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> at Blower Outlet vs. Time (Long-term Combined SVE/AS Test at VT3)
Figure 4.49	Concentration of VOC, CO <sub>2</sub> , O <sub>2</sub> and CH <sub>4</sub> at Blower Outlet vs. Time (Long-term Combined SVE/AS Test at VT4)
Figure 5.1	Typical CO <sub>2</sub> and O <sub>2</sub> Concentration in Soil Gas during Bioventing

## Appendices

Appendix A	Table of Conversion Factors for Units of Relevant Physical Quantities
Appendix B	General Scope of Pilot Test
Appendix C	Responses and Comments from EPD and OCTF Regarding Pilot Test
Appendix D	Health, Safety and Environmental Plan
Appendix E	Lists of Equipment and Specification of Measuring Equipment
Appendix F	Calibration Records of Measuring Equipment
Appendix G	Recommendation for HyperVentilate
Appendix H	Report of Utility Survey
Appendix I	Boring Log and Well Installation Log
Appendix J	Report of Particle Size Analyses of Soil
Appendix K	Records of Cross-checking of VOC Measurements
Appendix L	Printouts of Results of Computer Modelling on Permeability Test Using HyperVentilate
Appendix M	Example of Air Sparging and Soil Vapour Extraction Treatment for Contaminated Site
Appendix N	Calculation of SVE ROI Using Pore Volume Exchange and Pore Gas Velocity

Appendix O	Calculation of SVE ROI Based on Oxygen Utilisation
Appendix P	Calculation of Clean Up Time Based on Volatilisation for Hot Spot B
Appendix Q	Calculation of Clean Up Time Based on Biodegradation for Hot Spot B
Appendix R	Calculation of Benzene Emission