

MTR Corporation Limited

Tsim Sha Tsui Station Northern Subway

Final Environmental Monitoring and Audit Report

March 2017

Verified By:



Sam Tsoi

Independent Environmental Checker

Date:

5 May 2017

MTR Corporation Limited

Tsim Sha Tsui Station Northern Subway

Final Environmental Monitoring and Audit Report

March 2017

Verified By:



Felice Wong

Environmental Team Leader

Date:

- 5 MAY 2017

EXECUTIVE SUMMARY

The Tsim Sha Tsui Northern Subway Project (TNS) was awarded to the respective contractor in late Dec 2012. The EM&A programme for (TNS) Project commenced on 8 Feb 2013, the commencement date of construction of the Project, and the EM&A programme was completed on 22 Mar 2017. This is the Final Environmental Monitoring and Audit (EM&A) Report for TNS Project. The Report presents the summary of EM&A works throughout the project period.

The impact monitoring for air quality and noise were conducted for the TNS Project in accordance to the EM&A Manual requirement throughout the project period. Both dust and noise monitoring results were below action limits. It can be concluded that the EIA predictions for TNS Project was valid.

No environmental notification of summon and prosecution was received throughout the project period. Only 1 recorded complaint was referred from government hotline in October 2014 regarding wastewater, investigation has been carried out in accordance with the EM&A requirement, and the founding was reported in the October 2014 Monthly EM&A Report.

Regular joint site inspections, led by the ER with the presence with representatives from the Contractor and Environmental Team, were conducted on weekly basis to monitor Contractors' performance on environmental management and implementation of environmental pollution control and mitigation measures for the Project.

The Environmental Permit (EP-317/2009/A), which is a variation to the original permit and issued on 27 January 2014, is being used for the TNS Project.

Throughout the project period, no non-conformance was identified and no reporting change of circumstances which may affect the compliance with the recommendations of the EIA Report.

It is concluded that the environmental monitoring and audit works for the TNS Project has been performing in an acceptable standard complying with the requirements of the EM&A manual and the construction works of TNS were undertaken in an appropriately environmentally sensitive manner. The environmental protection and pollution control measures provided by the Contractor were found to be effective and efficient.

EXECUTIVE SUMMARY

- 1 Introduction And Project Information***
 - 1.1 Project Background***
 - 1.2 Project Programme***
 - 1.3 Project Management Organization and Contact Details***
 - 1.4 Project Works Sites and Areas and Environmental Monitoring Locations***
 - 1.5 Status of Statutory Submissions***
- 2 Summary of EM&A Requirements***
 - 2.1 Air Quality Monitoring Requirement***
 - 2.2 Noise Monitoring Requirement***
 - 2.3 Requirement for Landscape and Visual***
 - 2.4 Requirement for Water Quality***
 - 2.5 Requirement for Built Heritage***
 - 2.6 Requirement for Waste Management***
- 3 Summary of Impact Monitoring And Site Audit Results***
 - 3.1 Air Quality***
 - 3.2 Noise***
 - 3.3 Landscape and Visual***
 - 3.4 Water Quality***
 - 3.5 Built Heritage***
 - 3.6 Waste Management***
 - 3.7 Site Inspections***
- 4 Summary of Exceedance, Non-Compliance and Complaint***
 - 4.1 Exceedance***
 - 4.2 Non-Compliance, Notification of Summon and Prosecution***
 - 4.3 Record of Environmental Complaints***
- 5 Review of the TNS EM&A***
 - 5.1 Review of the Monitoring Methodology***
 - 5.2 Effectiveness and Efficiency of Mitigation Measures***
- 6 Conclusions***

List of Appendices

Appendix A Figures

Appendix B Implementation Schedule

Appendix C Calibration Details

Appendix D Event Action Plans

Appendix E Air Quality Monitoring

Appendix F Noise Monitoring

Appendix G Photographic Records

1 INTRODUCTION AND PROJECT INFORMATION

1.1 Project Background

MTR Corporation Limited (MTRCL) proposes to construct Tsim Sha Tsui Station Northern Subway, otherwise referred 'TNS'. This EM&A report is for the phase 1 of the TNS, which is the modification of existing Tsim Sha Tsui Station Entrance A1. The scope of this phase 1 work is to upgrade the Entrance A1 to replace the existing concrete structure with a new transparent box reconstructed on the same site with improved access to the station with new disable lift serving Tsim Sha Tsui concourse level, street and Kowloon Park; and escalators serving street and the existing Entrance A1 Adit. The remaining subway running from the north end of Tsim Sha Tsui Station to the new satellite concourse at The One shopping (previous Tung Ying Building) and then to Miramar Shopping Centre will be grouped at the phase 2 of the TNS project. The phase 2 is still under planning stage.

1.2 Project Programme

The TNS Project Phase 1 contract with contract number C6564-11C was awarded to the Goldfield N&W Construction Company Limited (GNW) in late Dec 2012. The commencement of construction was on 8 Feb 2013. The Entrance A1 was been opened and operating since May 2016, and the remaining reinstatement and landscaping works were completed in Feb 2017.

From early to mid 2013 the main construction activities were the ground works (breaking, excavation and installation of sheet piles) to enable construction of a temporary entrance. The construction of the temporary entrance commenced in late 2013.

The demolition of the existing Entrance A1 and the excavation for the new Entrance A1 commenced in 2014, subsequently in 2015 construction of the structure for the new Entrance A1 and lift started and completed in 2016. The new entrance was opened in May 2016.

The demolition of the temporary entrance commenced in 2016 and completed in August 2016, and reinstatement works for the Kowloon Park entrance followed. The bulk of the reinstatement and landscaping works were completed in Feb 2017 with a few minor defect fixing carried out in Mar 2017.

1.3 Project Management Organization and Contact Details

The TNS Project organization chart is presented in **Chart 1**. Contacts of key environmental personnel of the Project are shown in **Tables 1a** and **1b** respectively.




Chart 1 Project Organization

Table 1a Contact List of Key Personnel for Project Management

Organization	Name	Telephone
Engineer's Representative		
Construction Manager	Kevin Man	3547 0001
Senior Construction Engineer	Jack Chan	3547 0086
Construction Engineer	Andy Chan	3547 0087
Independent Environmental Checker		
Arup	Sam Tsoi	2268 3097
Environmental Team		
Environmental Team Leader	Felice Wong	2688 1760

Table 1b Contact List of Environmental Authority

Organization	Name	Telephone
Environmental Protection Department		
Environmental Protection Officer (Regional East) 61	Arthur Lee	2150 8021

1.4 Project Works Sites and Areas and Environmental Monitoring Locations

- The TNS Project works sites and areas are summarized in **Table 2** below and shown in **Appendix A** Figure 1.
- The locations of environmental monitoring locations are indicated in **Appendix A** Figure 2.

- **Table 3** shows the details of the active monitoring stations as reported in Sections 2.1 and 2.2.

Table 2 Summary of TNS Project Works Sites and Areas

Contact C6564-11C Works Sites and Areas	
Works Sites	Tsim Sha Tsui Entrance A

Table 3 Summary of impact air quality and noise monitoring stations

ID	Monitoring Station
Air	
D1	Hai Phong Road
Noise	
M1	Hai Phong Mansion
M2	Comfort Building
M3	Burlington Arcade

1.5 Status of Statutory Submissions

A summary of the status of the clauses required under the TNS Environmental Permit as of March 2017 is shown in **Table 4** below:

Table 4 Summary of EP Submissions

EP-317/2009 Clause No.	Description		Status
1.11	1	Notification of commencement of construction	Construction commenced on 8 Feb 2013
2.1	2	Establishment of ET with ET Leader	ET set up since Oct 2012
2.2	4	Employment of IEC	IEC set up since Oct 2012
2.3	5	Notification of the management organization of main construction companies and/or any form of JV	Set up in Dec 2012
2.4	6	Submission of Waste Management Plan	Comments received and RTC is being prepared. The WMP has been revised accordingly
5.4	7	Submission of Baseline Monitoring Report	Submitted
5.7	8	Notification of setting up A community liaison procedure and channel	Established since Jan 2013
6.2	9	Notification of Internet address to place EM&A data	Established on 7 March 2013
5.5	10	Monitoring Report for Feb 2017	Submitted

A summary of the status of all relevant environmental permits and licenses as of March 2017 is shown in **Table 5** below:

Table 5 Summary of Permits and Licenses

Descriptions	License / Permit Reference	Issue Date	Expired Date
Environmental Permit for Tsim Sha Tsui Station Northern Subway Project	EP-317/2009/A	27 January 2014	NA
Wastewater Discharge License	WT00017459-2013	1 November 2013	30 Jun 2018
Registration as a Chemical Waste Producer	Waste Producer Number: 5213-214-G2417-05	12 March 2013	NA
Disposal of Construction Waste	Billing Account no. 7016610 activated	27 Dec 2012	NA

A variation to the Environmental Permit has been granted by EPD on 27 January 2014. The variation concerns works near OVT 73 and demolition existing exit.

2 SUMMARY OF EM&A REQUIREMENTS

The EM&A programme mainly requires environmental monitoring for air quality, noise, landscape & visual, water quality, built heritage and waste management as specified in the EM&A Manual.

A summary of impact EM&A requirements as applicable to this EM&A Report is presented in **Table 6** below.

Table 6 Summary of Impact EM&A Requirements

Parameters	Descriptions	Locations	Monitoring Frequencies	Duration
Air Quality	24hr- TSP	Shown in Table 3	Once a week	Construction Stage
Noise	$L_{eq(30min)}$	Shown in Table 3	Once a week	Construction Stage
Landscape and Visual	On-Site Audit	Active Works Sites	Bi-weekly	Construction Stage
Water Quality	On-Site Audit	Active Works Sites	Weekly	Construction Stage
Built Heritage	On-Site Audit	Active Works Sites	Bi-weekly	Construction Stage
Waste	On-Site Audit	Active Works Sites	Weekly	Construction Stage
General Site Conditions	Environmental Site Inspection	Active Works Sites	Weekly	Construction Stage

The TNS Civil Works Contractors are required to implement the mitigation measures as specified in the EP, EIA Report and EM&A Manual. During the regular environmental site inspections, the Contractors' implementation of mitigation measures were inspected and reviewed. A schedule of the implementation of mitigation measures identified in the TNS EM&A Manual is given in **Appendix B**.

2.1 Air Quality Monitoring Requirement

24 Hour TSP Level Monitoring and Calibration Requirements

The TSP was measured by Andersen High Volume Sampler, model G25A. The sampling procedure follows that described in the App. B of Pt 50 in 40CFR Ch.1 (U.S. Environmental Protection Agency). TSP is sampled by drawing air through a conditioned, pre-weighed filter paper inside the high volume sampler at a controlled rate. After 24-hour sampling the filter paper with retained particles is collected and returned to the laboratory for drying in a desiccator followed by weighing. TSP levels are calculated from the ratio of the mass of particulate retained on the filter paper to the total volume of air sampled.

The samplers should be properly maintained. Prior to dust monitoring commencing, appropriate checks should be made to ensure that all equipment and necessary power supply are in good working condition.

The flow rate of the high volume sampler with mass flow controller will be calibrated using an orifice calibrator. Initial calibration (five points) will be conducted upon installation and prior to commissioning. Calibration will be carried out every six months. The latest Calibration certificates are attached in **Appendix C**.

Monitoring Location and Performance Limits

To examine the construction dust levels, 24-hour TSP monitoring was undertaken according to the EM&A Manual. The dust monitoring location is shown in the Section 1.4 above and **Appendix A** Figure 2. The monitoring location is subjected to construction dust impact from Works Site, is available to check the environmental performance of the work site and assess the effectiveness of the mitigation measures.

The Action and Limit Levels for the 24-hour TSP monitoring is as follow:

Monitoring Station	Action Level ($\mu\text{g}/\text{m}^3$)	Limit Level ($\mu\text{g}/\text{m}^3$)
D1	226	260

The Action and Limit Levels for the 1-hour TSP monitoring is as follow:

Monitoring Station	Action Level ($\mu\text{g}/\text{m}^3$)	Limit Level ($\mu\text{g}/\text{m}^3$)
D1	310	500

Event and Action Plan for air quality is shown in **Appendix D**.

2.2 Noise Monitoring Requirement

Noise Monitoring and Calibration Requirements

B&K 2250 sound level meters which complied with the International Electrotechnical Commission Publication 651:1979 (Type 1) and 804:1985 (Type 1), specification as referred to in the Technical Memoranda to the NCO were used for the construction noise impact monitoring. The B&K sound level meters and B&K 4231 calibrator are verified by the certified laboratory or manufacturer once every two years to ensure they perform to the same level of accuracy as stated in the manufacturer’s specifications. The latest calibration certificates are attached in **Appendix C**.

Immediately prior to and following each set of measurements at any NSR, the accuracy of the sound level meter was checked using an acoustic calibrator generating a known sound pressure level at a known frequency. If the calibration levels before and after the measurement differs by more than 1.0dB the

measurement shall be repeated to obtain a reliable result. Periods of prolonged or repeated overloading of the sound level meter detector were avoided by setting the meter with adequate headroom prior to commencing measurements. Measurements were recorded to the nearest whole dB, with values of 0.5 or more being rounded up.

Monitoring Location and Performance Limits

Impact noise monitoring of $L_{Aeq(30min)}$ was undertaken to measure construction noise levels in accordance with the EM&A Manual. The noise monitoring locations are shown in Section 1.4 above and **Appendix A** Figure 2.

The Action and Limit Levels for all noise monitoring points are as follow:

Time Period	Action Level	Limit Level (dB(A)), $L_{eq(30min)}$
0700-1900 hr on normal weekdays	When one documented complaint is received	75

Event and Action Plan for noise level is shown in **Appendix D**.

2.3 Requirement for Landscape and Visual

Monitoring of the implementation of the landscape and visual mitigation measures during construction phase was conducted in accordance with the requirements as stipulated in the EM&A Manual.

The landscape and visual monitoring and audit was conducted once every two weeks throughout the construction stage.

2.4 Requirement for Water Quality

Site audit of the implementation of the water quality mitigation measures during construction phase was conducted in accordance with the requirements as stipulated in the EM&A Manual.

Weekly site inspection was conducted to ensure the recommended mitigation measures are properly implemented and license conditions are observed.

2.5 Requirement for Built Heritage

Site audit of the implementation of the built heritage mitigation measures during construction phase was conducted in accordance with the requirements as stipulated in the EM&A Manual.

Bi-weekly site inspection was conducted to ensure the recommended mitigation measures are properly implemented.

2.6 Requirement for Waste Management

Site audit of the implementation of the waste management mitigation measures during construction phase was conducted in accordance with the requirements as stipulated in the EM&A Manual.

Weekly site inspection was conducted to ensure the recommended mitigation measures are properly implemented.

3 SUMMARY OF IMPACT MONITORING AND SITE AUDIT RESULTS

3.1 Air Quality

To examine the construction dust levels, 24-hour TSP monitoring was undertaken according to the EM&A Manual. The dust monitoring location is shown in the Section 1.4 above and **Appendix A**. The monitoring location is subjected to construction dust impact from Works Site, is available to check the environmental performance of the work site and assess the effectiveness of the mitigation measures.

Monitoring results and the graphical plot of the trends are presented in **Appendix E**. The 24-hour TSP monitoring results throughout the project is in the range from 36.6 to 218.0 $\mu\text{g}/\text{m}^3$, it shows that the dust levels generated by the construction activities were within the Action Level, and that the mitigation measures implemented were effective.

Based on the monitoring results and regular site audit, it can be concluded that for air quality impact, the mitigation measures were effective and the environmental performance of the Project was acceptable.

3.2 Noise

Impact noise monitoring of $L_{Aeq(30min)}$ was undertaken to measure construction noise levels in accordance with the EM&A Manual. The noise monitoring locations are shown in Section 1.4 above and **Appendix A**.

The monitoring results and the graphical plot of the trends are presented in **Appendix F**. The noise monitoring results throughout the project is in the range from 61 to 72 dB(A), and it shows that the noise levels generated by the construction activities were within the Limit Level, and that the mitigation measures implemented were effective.

Based on the monitoring results and regular site audit, it can be concluded that for noise impact, the mitigation measures were effective and the environmental performance of the Project was acceptable.

3.3 Landscape and Visual

Monitoring and audit was undertaken in accordance with the EM&A Manual. The Registered Landscape Architect of Environmental Team or his representatives conducted inspections and audits and the tree protection works were implemented by the respective contractor. No non-conformance was identified throughout the project period.

OVT T30 and T31 had fallen due to non-project related causes since the EIA Report, other OVTs were in good health.

The transplantation of the two *Elaeocarpus balansae* in front of Entrance A1 was carried out in May 2013, to sites within Kowloon Park as pre-agreed with LCSD. Both trees have been handed over to LCSD already.

T69, T70 and T71 (all *Delonix Regia*) at Hai Phong Road were removed on 14 September 2013 as approved under the Tree Removal Applications. The planting of 4 no. of *Tabebuia chryantha* as approved under the TRA along Haiphong Road had been completed as shown in the photo record of **Appendix G**.

3.4 Water Quality

Monitoring and audit was undertaken in accordance with the EM&A Manual. No non-conformance with regards to water quality was identified throughout the project period.

An effluent discharge license was granted in November 2013. Wastewater was generated in earlier construction activities, such during site formation, excavation and breaking activities. No construction activity would generate major wastewater discharge during subsequent reinstatement works after opening of the new entrance. Throughout the project period, recommended mitigation measures were properly implemented and license conditions are observed where applicable. The environmental performance of the project was generally acceptable.

A complaint was referred from government hotline in Oct 2014, details of the complaint and investigation is presented in section 4.3 below.

3.5 Built Heritage

Monitoring and audit was undertaken in accordance with the EM&A Manual. No non-conformance with regards to built heritage was identified throughout the project period.

There are two built heritage resources have been identified in the close proximity to the work site. The two built heritage resources, the retaining wall and the Block S4 of former Whitfield Barracks were inspected visually. They were well kept and no observable impact due to the project was identified. The two granite columns previously relocated to Kowloon Park during the construction phase was in good condition and was relocated to the park entrance as shown in the photo record in **Appendix G**.

3.6 Waste Management

Monitoring and audit was undertaken in accordance with the EM&A Manual. No non-conformance with regards to waste management was identified throughout the project period.

The quantities disposed in the reporting period are summarized in **Table 7**:

Table 7 Amount of Construction Waste Disposed

Reporting Period	Inert C&D Materials to Public Fill (m³)	Inert C&D Materials Reused (m³)	Non-Inert Waste to Landfill (m³)	Chemical Waste to Designated Treatment Facility (trips)
Year 2013	715	0	92	0
Year 2014	796	0	8	0
Year 2015	4,809	0	6	0
Year 2016	111	0	0	0
Jan 2017	0	0	0	0
Feb 2017	0	0	0	0
Mar 2017	0	0	0	0
Total	6,431	0	106	0

3.7 Site Inspections

Regular site inspections led by the Engineer's Representative and anticipated by ET and respective Contractors and IEC audits were undertaken in accordance with the EM&A Manual throughout the project period. The contractors' performance on environmental matters were assessed and found in an acceptable manner. The inspection findings and the associated recommendations on improvement to the environmental protection and pollution control works were raised to the contractors for reference and/ or action and have been recorded in the monthly EM&A Reports.

The most recent EPD inspection was conducted on 10th March 2017, and no major observation/comment was received.

4 SUMMARY OF EXCEEDANCE, NON-COMPLIANCE AND COMPLAINT

4.1 Exceedance

Throughout the project period, no exceedance of Action Level and Limit Level was recorded for both 24-hr TSP monitoring and noise monitoring. Details can be referred to Section 3.1, 3.2 and **Appendix E** and **Appendix F**.

4.2 Non-Compliance, Notification of Summon and Prosecution

Throughout the project period, no non-compliance, notification of summon and prosecution related to environmental issue was recorded. A summary of environmental prosecution of the recent month and since commencement of construction is shown in **Table 8** below:

Table 8 Summary of Prosecution

Reporting Period	Frequency	Cumulative	Nature	Status
March 2017	0	0	N/A	N/A
Cumulative	0	0	N/A	N/A

4.3 Record of Environmental Complaints

Throughout the project period, there was one recorded complaint. The complaint was referred from government hotline in early October 2014 regarding wastewater discharge. Investigation has been carried out in accordance to the EM&A requirements. Discharge records and test report results were reviewed and were within the licence limit. No further adverse observation during subsequent site inspections. Nonetheless, contractor was reminded to keep close monitoring to ensure the performance of the wastewater treatment system is in compliance with the license requirements. The complaint and the investigation were reported in the October 2014 Monthly EM&A Report.

5 REVIEW OF THE TNS EM&A

5.1 Review of the Monitoring Methodology

The monitoring methodology and the EM&A programme have been reviewed. Based on day-to-day experience of the TNS project and the monitoring results, it is found that the monitoring methodology and the EM&A programme is effective.

5.2 Effectiveness and Efficiency of Mitigation Measures

Based on the environmental monitoring results of throughout the project period, the effectiveness and efficiency of the mitigation measures implemented were found to be satisfactory.

6 CONCLUSIONS

The Report presents the results of EM&A works and the impact monitoring throughout the project period from Feb 2013 to March 2017. Construction and EM&A programme has been completed.

Throughout the project period, no record of exceedance for noise and dust action level and limit level.

No notification of summon and prosecution were received throughout the project period. Only 1 recorded complaint was referred from government hotline in October 2014 regarding wastewater, investigation has been carried out in accordance to the EM&A requirement.

Regular site inspections led by the Engineer's Representative and participated by the representatives from ET and the respective Contractors' Team were conducted on a weekly basis to monitor the implementation of environmental pollution control and mitigation measures for the Project. No non-conformance to the environmental requirements was identified by the Environmental Team in the project period. The performances of the respective contractors on site environmental management were found in a responsible manner in this reporting period.

It is concluded from the environmental monitoring and audit works for the Tsim Sha Tsui Northern Subway Project were undertaken in a responsible manner. The environmental protection and pollution control measures provided by the contractor were generally acceptable.

Appendix A
Figures

Figure 1. TNS Project Works Area





Figure 2. TNS Project Dust and Noise Monitoring Location Plan



Appendix B
Implementation Schedule

APPENDIX B IMPLEMENTATION SCHEDULE OF THE PROPOSED MITIGATION MEASURES

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
3.10.1	2.9.2	<p>Construction Air Quality Impact</p> <ul style="list-style-type: none"> watering of active construction works area twice a day skip hoist for material transport shall be totally enclosed by impervious sheeting every vehicle shall be washed to remove any dusty materials from its body and wheels before leaving a construction site the area where vehicle washing takes place and the section of the road between the washing facilities and the exit point shall be paved with concrete, bituminous materials or hardcores where a site boundary adjoins a road, streets or other accessible to the public, hoarding of not less than 2.4m high from ground level shall be provided along the entire length except for a site entrance or exit every stack of more than 20 bags of cement shall be covered entirely by impervious sheeting places in an area sheltered on the top and the 3 sides all dusty materials shall be sprayed with water prior to any loading, unloading or transfer operation so as to maintain the dusty materials wet the height from which excavated materials are dropped shall be controlled to a minimum practical height to limit fugitive dust generation from unloading stockpile of excavated or dusty materials shall be covered entirely by clean impervious sheeting the load of dusty materials carried by vehicle leaving a construction site shall be covered entirely by clean impervious sheeting to ensure dust materials do not leak from the vehicle instigation of an environmental monitoring and auditing 	Contractor	Works Area	Construction Phase	EIAO-TM Air Pollution Control (Construction Dust) Regulation

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
4.9.2-4.9.3		program to monitor the construction process in order to enforce controls and modify method of work if dusty conditions arise				
4.9.4	3.8.1	<p>Construction Noise Impact</p> <ul style="list-style-type: none"> Adoption of Quieter PME 	Contractor	Works Area	Construction Phase	EIAO-TM Noise Control Ordinance
4.9.5	3.8.1	<ul style="list-style-type: none"> Use of Movable Noise Barrier 5 dB(A) reduction for movable PME and 10 dB(A) for stationary PME can be achieved depending on the actual design of movable noise barrier Barrier material of surface mass in excess of 7 kg/m² is recommended to achieve the predicted screening effect Use of Noise Enclosure/Acoustic Shed Noise Enclosure or Acoustic Shed is to cover stationary PME such as air compressor and concrete pump. With the adoption of the noise enclosure, the PME could be completely screened, and noise reduction of 15 dB(A) can be achieved according to the GW-TM 	Contractor	Works Area	Construction Phase	EIAO-TM Noise Control Ordinance
4.9.6	3.8.1	<ul style="list-style-type: none"> Use of Silencer Silencers are recommended to be used in fan ventilation system to attenuate noise generated during fan operation to achieve a noise reduction of 15dB(A). The Contractor shall be responsible for selection of appropriate silencers for the ventilation fans. 	Contractor	Works Area	Construction Phase	EIAO-TM Noise Control Ordinance
4.9.7	3.8.1	<ul style="list-style-type: none"> Use of Noise Insulating Fabric Noise insulating fabric (the Fabric) can be adopted for certain PME (e.g. drill rig, piling auger etc) The Fabric should be lapped such that no opening or gaps on the joints. Technical data from manufacturer states that by using the Fabric, a noise reduction of over 10 dB(A) can be achieved on noise level (Reference was 	Contractor	Works Area	Construction Phase	EIAO-TM Noise Control Ordinance

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to Implement	Relevant Legislation and Guidelines
4.6.6	3.8.1	<p>made from Modifications to MTRC Tsim Sha Tsui Station Variation of Environmental Permit EP-113/2001/C). As an conservative approach, a noise reduction of 10 dB(A) for the PME lapped with the Fabric was assumed.</p> <ul style="list-style-type: none"> Decking over the excavation areas at the Entrance A1 and satellite concourse 	Contractor	Works Area	Construction Phase	EIAO-TM Noise Control Ordinance
4.10.8	3.8.1	<p><u>Good Site Practices</u></p> <ul style="list-style-type: none"> Only well-maintained plant shall be operated on-site and plant shall be serviced regularly during the construction program. Silencers or mufflers on construction equipment shall be utilised and shall be properly maintained during the construction program. Mobile plant, if any, shall be sited as far away from NSRs as possible. Machines and plant (such as trucks) that may be in intermittent use shall be shut down between works periods or shall be throttled down to a minimum. Plant known to emit noise strongly in one direction shall, wherever possible, be orientated so that the noise is directed away from the nearby NSRs. Material stockpiles and other structures shall be effectively utilised, wherever practicable, in screening noise from on-site construction activities. 	Contractor	Works Area	Construction Phase	EIAO-TM Noise Control Ordinance
Operation Noise Impact Table 4.8	Table 3.4	<ul style="list-style-type: none"> The maximum Sound Power Levels (SWLs) for the ventilation shaft openings shall be complied with during the selection of ventilation fans and mitigation measures. 	Designer	Station, ventilation shafts and E&M plant items	Design Phase	EIAO-TM

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
4.9.10	3.9.2	<ul style="list-style-type: none"> Choose quieter plant such as those which have been effectively silenced. Include noise levels specification when ordering new plant (including chiller and E/M equipment). Locate fixed plant/louvers away from any NSRs as far as practicable. Locate fixed plant in walled plant rooms or in specially designed enclosures. Locate noisy machines in a basement or a completely separate building. Install direct noise mitigation measures including silencers, acoustic louvers and acoustic enclosure where necessary. Develop and implement a regularly scheduled plant maintenance programme so that equipment is properly operated and serviced in order to maintain controlled level of noise. The programme should be implemented by properly trained personnel. 	Designer / Contractor	Station, ventilation shafts and E&M plant items	Design / Operational Phase	EIAO-TM Noise Control Ordinance
Construction Water Quality Impact						
5.13.2	4.3.2	<p>Construction runoff and site drainage should be prevented or minimized in accordance with the guidelines stipulated in ProPECC PN 1/94 "Construction Site Drainage". The specified mitigation measures and practices include the following:</p> <ul style="list-style-type: none"> Provision of perimeter drains to intercept off-site water around the site with internal drainage works and erosion and sedimentation control facilities implemented. These shall be constructed in advance of site formation works and earthworks. Earth bunds or sand bag barriers shall be provided on-site to direct storm water to silt removal facilities. The design of the temporary on-site drainage system will be undertaken by the Contractor prior to the commencement of construction. All drainage facilities and erosion and sediment control 	Contractor	Works Area	Construction Phase	ProPECC PN 1/94 Construction Site Drainage EIAO-TM Water Pollution Control Ordinance Waste Disposal Ordinance

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
		<p>structures shall be regularly inspected and maintained to ensure proper and efficient operation at all times and particularly during rainstorms. Deposited silt and grit shall be regularly removed, at the onset of and after each rainstorm to ensure that these facilities are functioning properly at all times.</p> <ul style="list-style-type: none"> • Exposed slope/soil surface shall be covered by tarpaulin as soon as possible to reduce the potential of soil erosion. Arrangements should always be in place to ensure that adequate surface protection measures can be safely carried out well before the arrival of a rainstorm. Other measures that need to be implemented before, during and after rainstorms are summarized in ProPECC PN 1/94. • Open stockpiles of construction materials (e.g. aggregates, sand and fill material) or construction wastes on-site shall be covered with tarpaulin or similar fabric during rainstorms. • Construction works shall be programmed to minimise surface excavation works during the rainy seasons (April to September). All exposed earth areas shall be completed and vegetated as soon as possible after earthworks have been completed, or alternatively, within 14 days of the cessation of earthworks where practicable. If excavation of soil cannot be avoided during the rainy season, or at any time of year when rainstorms are likely, exposed surfaces shall be covered by tarpaulin or other means. • Manholes shall always be adequately covered and temporarily sealed so as to prevent silt, construction materials or debris being washed into the drainage system and storm runoff being directed into foul sewers. • Precautions be taken at any time of year when rainstorms are likely, actions to be taken when a 				

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
		<p>rainstorm is imminent or forecasted, and actions to be taken during or after rainstorms are summarised in Appendix A2 of ProPECC PN 1/94.</p> <ul style="list-style-type: none"> • All vehicles and plant should be cleaned before leaving a construction site to ensure no earth, mud, debris and the like is deposited by them on roads. An adequate designed and sited wheel washing facilities shall be provided at every construction site exit, where practicable. Wash-water shall have sand and silt settled out and removed at least on a weekly basis to ensure the continued efficiency of the process. The section of access road leading to, and exiting from, the wheel-wash bay to the public road shall be paved with sufficient backfall toward the wheel-wash bay to prevent vehicle tracking of soil and silty water to public roads and drains. • Oil interceptors shall be provided in the drainage system downstream of any oil/fuel pollution sources. The oil interceptors shall be emptied and cleaned regularly to prevent the release of oil and grease into the storm water drainage system after accidental spillage. A bypass shall be provided for the oil interceptors to prevent flushing during heaving rain. • Construction solid waste, debris and rubbish on site shall be collected, handled and disposed of properly to avoid water quality impacts. 	Contractor	Works Area	Construction Phase	ProPECC PN 1/94 Construction Site Drainage EIAO-TM Water Pollution Control Ordinance
5.13.4-5.13.6	4.3.3 – 4.3.5	<p><u>Underground Work</u></p> <ul style="list-style-type: none"> • Underground works shall be conducted sequentially to limit the amount of construction runoff generated from exposed areas during the wet season (April to September). • Uncontaminated discharge shall pass through settlement tanks prior to off-site discharge. • The wastewater including surface runoff and ingressive 	Contractor	Works Area	Construction Phase	ProPECC PN 1/94 Construction Site Drainage EIAO-TM Water Pollution Control Ordinance

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
5.13.7	4.3.6	<p>water in underground area with a high concentration of SS shall be treated (e.g. by settlement in tanks with sufficient retention time) before discharge. Oil interceptors would also be installed to remove the oil, lubricants and grease from the wastewater.</p> <p><u>Sewage Effluent</u></p> <ul style="list-style-type: none"> Temporary sanitary facilities, such as portable chemical toilets, shall be employed on-site where necessary to handle sewage from the workforce. A licensed contractor would be responsible for appropriate disposal of waste matter and maintenance of these facilities. 	Contractor	Works Area	Construction Phase	ProPECC PN 1/94 Construction Site Drainage EIAO-TM Water Pollution Control Ordinance
5.14.1 – 5.14.2	4.3.7 – 4.3.8	<p><u>General Construction Site Activities</u></p> <ul style="list-style-type: none"> Debris and rubbish generated on-site shall be collected, handled and disposed of properly to avoid being flushed or blown by wind into the drainage culvert. Stockpiles of cement and other construction materials should be kept covered when not being used. Oils and fuels shall only be used and stored in designated areas which have pollution prevention facilities. To prevent spillage of fuels and solvents, all fuel tanks and storage areas shall be provided with locks and be sited on sealed areas, within bunds of a capacity equal to 110% of the storage capacity of the largest tank. The bund shall be drained of rainwater after a rain event. 				
Waste Management						
6.7.1	5.2.3	<p><u>Good Site Practices</u></p> <ul style="list-style-type: none"> Nomination of an approved person, such as a site manager, to be responsible for good site practices, arrangements for collection and effective disposal to an appropriate facility, of all wastes generated at the site. 	Contractor	Works Area	Construction Phase	EIAO-TM Waste Disposal Ordinance ETWB TCW No. 19/2005

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
6.7.2	5.2.4	<ul style="list-style-type: none"> • Training of site personnel in proper waste management and chemical waste handling procedures. • Provision of sufficient waste disposal points and regular collection for disposal. • Appropriate measures to minimise windblown litter and dust during transportation of waste by either covering trucks or by transporting wastes in enclosed containers. • Regular cleaning and maintenance programme for drainage systems, sumps and oil interceptors. • A Waste Management Plan should be prepared and submitted to the Engineer for approval. One may make reference to ETWB TCW No. 19/2005 for details. • A recording system for the amount of wastes generated, recycled and disposed (including the disposal sites) should be proposed. 				
6.7.3	5.2.5	<p><u>Waste Reduction Measures</u></p> <ul style="list-style-type: none"> • Segregation and storage of different types of waste in different containers, skips or stockpiles to enhance reuse or recycling of materials and their proper disposal. • Encourage collection of aluminium cans, PET bottles and paper by providing separate labelled bins to enable these wastes to be segregated from other general refuse generated by the work force. • Any unused chemicals or those with remaining functional capacity shall be recycled. • Proper storage and site practices to minimise the potential for damage or contamination of construction materials. 	Contractor	Works Area	Construction Phase	EIAO-TM

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to Implement	Relevant Legislation and Guidelines
6.7.6 & 6.7.7	5.2.7 – 5.2.8	<ul style="list-style-type: none"> Plan and stock construction materials carefully to minimise amount of waste generated and avoid unnecessary generation of waste. <p><u>Construction and Demolition Material</u></p> <p>Within stockpile areas, the following measures shall be taken to control potential environmental impacts or nuisance:</p> <ul style="list-style-type: none"> covering stockpile of C&D material entirely by clean impervious sheet to reduce potential dust impact. locating stockpiles to minimise potential visual impacts. minimizing land intake of stockpile areas as far as possible. When disposing C&D material at a public fill reception facility, the material shall only consist of soil, rock, concrete, brick, cement plaster/mortar, inert building debris, aggregates and asphalt. The material shall be free from marine mud, household refuse, plastic, metals, industrial and chemical waste, animal and vegetable matter, and other material considered to be unsuitable by the Filling Supervisor. 	Contractor	Works Area	Construction Phase	ETWB TCW No. 33/2002 ETWB TCW No. 19/2005
6.7.8	5.2.9	<p><u>Chemical Wastes</u></p> <ul style="list-style-type: none"> After use, chemical wastes (for example, cleaning fluids, solvents, lubrication oil and fuel) should be handled according to the <i>Code of Practice on the Packaging, Labelling and Storage of Chemical Wastes</i>. Spent chemicals should be collected by a licensed collector for disposal at the CWTC or other licensed facility. 	Contractor	Works Area	Construction Phase	EIAO-TM Waste Disposal (Chemical Waste) (General) Regulation
6.7.9	5.2.10	<p><u>General Refuse</u></p> <ul style="list-style-type: none"> General refuse shall be stored in enclosed bins or compaction units separate from C&D material. A licensed waste collector shall be employed by the 	Contractor	Works Area	Construction Phase	Public Health and Municipal Services Ordinance

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to Implement	Relevant Legislation and Guidelines
		<p>contractor to remove general refuse from the site, separately from C&D material.</p> <ul style="list-style-type: none"> Preferably an enclosed and covered area shall be provided to reduce the occurrence of 'wind blown' light material. 				
Landscape and Visual Impact						
Table 7.5	6.3.1	<ul style="list-style-type: none"> CM1: Existing trees including OVTs to be retained and maintained on site should be carefully protected during construction. Encroachment of any works close to the drip line of OVTs should be avoided. CM2: Trees of high amenity and survival rate after transplanting which unavoidably affected by the works should be transplanted where practical. CM3: Control of night – time lighting. CM4: Erection of decorative screen hoarding compatible with surrounding setting. 	Contractor	Works Area	Construction Phase	EIAO-TM
Table 7.6	6.3.1	<ul style="list-style-type: none"> OM1: Aesthetic design of Entrance A1 (Minimisation of building bulk and adoption of transparent material) and Emergency Exit OM2: Reinstatement of Entrance to Kowloon Park OM3: Planting of 4 nos. of <i>Delonix regia</i> or species as agreed with LCSD along Haiphong Road 	Contractor	Works Area	Operation Phase	EIAO-TM
Built Heritage Impact						
8.7.4	7.1.1	<ul style="list-style-type: none"> Temporary removal of the two granite columns (east of brick wall of modern extension of Block S4) and will be stored securely during construction period, and reinstated back to its original location after completion of works. 	Contractor	Works Area	Construction Phase	EIAO-TM
8.8.1 – 8.8.2	7.2.1 – 7.2.4	<ul style="list-style-type: none"> Precautions shall be taken throughout the construction stage to prevent any damage to the historical building. Structural monitoring system, including preconstruction survey shall be designed and implemented by a Registered Structural Engineer to ensure compliance with the Building Ordinance. Consult AMO on any other mitigation measures that 	Contractor	Works Area	Construction Phase	EIAO-TM; Building Ordinance

EIA Ref.	EM&A Ref.	Recommended Mitigation Measures	Implementation Agent	Location of the Measure	When to implement	Relevant Legislation and Guidelines
		<p>would be required administratively or under Antiquities and Monuments Ordinance. Implement these requirements from AMO during the construction period.</p> <ul style="list-style-type: none"> • use of sensibly designed hoardings to minimize the temporary visual impact during construction phase 				

Appendix C
Calibration Details

ANDERSEN INSTRUMENTS INC.

GS2310 Series Sampler Calibration

(Dickson Recorder)

Customer -> MTRC	SITE	Certificate -> 20161101
Location -> TNS		Date -> 12-Nov-16
Sampler -> 1294-1096		Tech -> Chan Kin Fung

CONDITIONS

Sea Level Pressure (hpa)	1017.9	Sampler Elevation (feet)	50
Sea Level Pressure (in Hg)	30.06	Corrected Pressure (mm Hg)	763.49
Temperature (deg C)	23.3	Temperature (deg K)	296.30
Seasonal SL Pressure (in Hg)	30.06	Corrected Seasonal (mm Hg)	763.49
Seasonal Temperature (deg C)	23.30	Seasonal Temperature(deg K)	296.30

CALIBRATION ORIFICE

Make -> TISCH	Qstd Slope ->	2.06617
Model -> TE-5025A	Qstd Intercept ->	-0.2528
Serial# -> 2821	Date Certified ->	13-May-16

CALIBRATION

	Plate or	H ₂ O	Qstd	I	IC	LINEAR
	Test #	(in)	(M ³ /min)	(chart)	(corrected)	REGRESSION
1	18	12.6	1.766	58	59.938	Slope = 29.6947
2	13	10.3	1.598	53	52.943	Intercept = 5.6016
3	10	8.1	1.418	48	47.949	Corr. Coeff. = 0.9996
4	7	5	1.117	39	38.958	
5	5	3.2	0.895	32	31.966	

Calculations

$$Qstd = 1/m [\text{Sqrt} (H_2O (Pa/Pstd) (Tstd/Ta)) - b]$$

$$IC = I [\text{Sqrt} (Pa/Pstd) (Tstd/Ta)]$$

Qstd = standard flow rate

IC = corrected chart response

I = actual chart response

m = calibrator Qstd slope

b = calibrator Qstd intercept

Ta = actual temperature during calibration (deg K)

Pa = actual pressure during calibration (mm Hg)

Tstd = 298 deg K

Pstd = 760 mm Hg

For subsequent calculation of sampler flow:

$$1/m ((I) [\text{Sqrt} (298/Tav) (Pav/760)] - b)$$

m = sampler slope

b = sampler intercept

I = chart response

Tav = daily average temperature

Pav = daily average pressure

This is to certify that the above equipment has been calibrated in accordance with manufacturer's procedure.





綜合試驗有限公司

SOILS & MATERIALS ENGINEERING CO., LTD.

香港黃竹坑道37號利達中心12樓
12/F., Leader Centre, 37 Wong Chuk Hang Road, Aberdeen, Hong Kong.
E-mail: smec@sigismec.com Website: www.sigismec.com

Tel: (852) 2873 6860
Fax: (852) 2555 7533



CERTIFICATE OF CALIBRATION

Certificate No.: 16CA1025 02-03 Page 1 of 2

Item tested

Description:	Sound Level Meter (Type 1)	Microphone	Preamp
Manufacturer:	B & K	B & K	B & K
Type/Model No.:	2250	4189	ZC0032
Serial/Equipment No.:	2551244	2550229	5051
Adaptors used:	-	-	-

Item submitted by

Customer Name: MTR Corporation
Address of Customer: 8/F, Fo Tan Railway House, Fo Tan, N.T. Hong Kong
Request No.: -
Date of receipt: 25-Oct-2016

Date of test: 26-Oct-2016

Reference equipment used in the calibration

Description:	Model:	Serial No.	Expiry Date:	Traceable to:
Multi function sound calibrator	B&K 4226	2288444	18-Jun-2017	CIGISMEC
Signal generator	DS 360	33873	18-Apr-2017	CEPREI
Signal generator	DS 360	61227	18-Apr-2017	CEPREI

Ambient conditions

Temperature: 22 ± 1 °C
Relative humidity: 55 ± 10 %
Air pressure: 1005 ± 5 hPa

Test specifications

- The Sound Level Meter has been calibrated in accordance with the requirements as specified in BS 7580: Part 1: 1997 and the lab calibration procedure SMTP004-CA-152.
- The electrical tests were performed using an electrical signal substituted for the microphone which was removed and replaced by an equivalent capacitance within a tolerance of ±20%.
- The acoustic calibration was performed using an B&K 4226 sound calibrator and corrections was applied for the difference between the free-field and pressure responses of the Sound Level Meter.

Test results

This is to certify that the Sound Level Meter conforms to BS 7580: Part 1: 1997 for the conditions under which the test was performed.

Details of the performed measurements are presented on page 2 of this certificate.

Actual Measurement data are documented on worksheets.

Approved Signatory:  Date: 27-Oct-2016 Company Chop:

Huang Jun Qi/Feng Jun Qi



Comments: The results reported in this certificate refer to the condition of the instrument on the date of calibration and carry no implication regarding the long-term stability of the instrument.



CERTIFICATE OF CALIBRATION

(Continuation Page)

Certificate No.: 16CA1025 02-03 Page 2 of 2

1. Electrical Tests

The electrical tests were performed using an equivalent capacitance substituted for the microphone. The results are given in below with test status and the estimated uncertainties. The "Pass" means the result of the test is inside the tolerances stated in the test specifications. The "-" means the result of test is outside these tolerances.

Test:	Subtest:	Status:	Expanded Uncertainty (dB)	Coverage Factor
Self-generated noise	A	Pass	0.3	
	C	Pass	0.8	
	Lin	Pass	1.6	
Linearity range for Leq	At reference range, Step 5 dB at 4 kHz	Pass	0.3	
	Reference SPL on all other ranges	Pass	0.3	
	2 dB below upper limit of each range	Pass	0.3	
	2 dB above lower limit of each range	Pass	0.3	
Linearity range for SPL	At reference range, Step 5 dB at 4 kHz	Pass	0.3	
	Frequency weightings			
	A	Pass	0.3	
	C	Pass	0.3	
	Lin	Pass	0.3	
Time weightings	Single Burst Fast	Pass	0.3	
	Single Burst Slow	Pass	0.3	
Peak response	Single 100µs rectangular pulse	Pass	0.3	
R.M.S. accuracy	Crest factor of 3	Pass	0.3	
Time weighting 1	Single burst 5 ms at 2000 Hz	Pass	0.3	
	Repeated at frequency of 100 Hz	Pass	0.3	
Time averaging	1 ms burst duty factor 1/10 ³ at 4kHz	Pass	0.3	
	1 ms burst duty factor 1/10 ⁴ at 4kHz	Pass	0.3	
Pulse range	Single burst 10 ms at 4 kHz	Pass	0.4	
Sound exposure level	Single burst 10 ms at 4 kHz	Pass	0.4	
Overload indication	SPL	Pass	0.3	
	Leq	Pass	0.4	

2. Acoustic tests

The complete sound level meter was calibrated on the reference range using a B&K 4226 acoustic calibrator with 1000Hz and SPL 94 dB. The sensitivity of the sound level meter was adjusted. The test result at 125 Hz and 8000 Hz are given in below with test status and the estimated uncertainties.

Test:	Subtest	Status	Expanded Uncertainty (dB)	Coverage Factor
Acoustic response	Weighting A at 125 Hz	Pass	0.3	
	Weighting A at 8000 Hz	Pass	0.5	

3. Response to associated sound calibrator

N/A

The expanded uncertainties have been calculated in accordance with the ISO Publication "Guide to the expression of uncertainty in measurement", and gives an interval estimated to have a level of confidence of 95%. A coverage factor of 2 is assumed unless explicitly stated.

- End -

Calibrated by:		Checked by:	
Date:	26-Oct-2016	Date:	27-Oct-2016

The standard(s) and equipment used in the calibration are traceable to national or international recognised standards and are calibrated on a schedule to maintain the required accuracy level.



Sound level meter type:	2250	Serial No.	2551244	Date	26-Oct-2016
Microphone type:	4189	Serial No.	2550229	Report:	16CA1025 02-03
Preamp type:	ZC0032	Serial No.	5051		

SELF GENERATED NOISE TEST

The noise test is performed in the most sensitive range of the SLM with the microphone replaced by an equivalent impedance.

Noise level in A weighting	12.5	dB
Noise level in C weighting	13.8	dB
Noise level in Lin	20.1	dB

LINEARITY TEST

The linearity is tested relative to the reference sound pressure level using a continuous sinusoidal signal of frequency 4 kHz. The measurement is made on the reference range for indications at 5 dB intervals starting from the 94 dB reference sound pressure level. And until within 5 dB of the upper and lower limits of the reference range, the measurements shall be made at 1 dB intervals. (SLM set to LEQ/SPL)

Reference/Expected level	Actual level		Tolerance	Deviation	
	non-integrated	integrated		non-integrated	integrated
dB	dB	dB	+/- dB	dB	dB
94.0	94.0	94.0	0.7	0.0	0.0
99.0	99.0	99.0	0.7	0.0	0.0
104.0	104.0	104.0	0.7	0.0	0.0
109.0	109.0	109.0	0.7	0.0	0.0
114.0	114.0	114.0	0.7	0.0	0.0
119.0	119.0	119.0	0.7	0.0	0.0
124.0	124.0	124.0	0.7	0.0	0.0
129.0	129.0	129.0	0.7	0.0	0.0
134.0	134.0	134.0	0.7	0.0	0.0
135.0	135.0	135.0	0.7	0.0	0.0
136.0	136.0	136.0	0.7	0.0	0.0
137.0	137.0	137.0	0.7	0.0	0.0
138.0	138.0	138.0	0.7	0.0	0.0
139.0	139.0	139.0	0.7	0.0	0.0
140.0	140.0	140.0	0.7	0.0	0.0
89.0	89.0	89.0	0.7	0.0	0.0
84.0	84.0	84.0	0.7	0.0	0.0
79.0	79.0	79.0	0.7	0.0	0.0
74.0	74.0	74.0	0.7	0.0	0.0
69.0	69.0	69.0	0.7	0.0	0.0
64.0	64.0	64.0	0.7	0.0	0.0
59.0	59.0	59.0	0.7	0.0	0.0
54.0	53.9	53.9	0.7	-0.1	-0.1
49.0	49.0	49.0	0.7	0.0	0.0
44.0	44.0	43.9	0.7	0.0	-0.1
39.0	38.9	38.9	0.7	-0.1	-0.1



Test Data for Sound Level Meter

Page 2 of 5

Sound level meter type: 2250 Serial No. 2551244 Date 26-Oct-2016
 Microphone type: 4189 Serial No. 2550229
 Preamp type: ZC0032 Serial No. 5051 Report: 16CA1025 02-03

34.0	34.0	33.9	0.7	0.0	-0.1
33.0	33.0	33.0	0.7	0.0	0.0
32.0	32.0	32.0	0.7	0.0	0.0
31.0	31.0	31.0	0.7	0.0	0.0
30.0	30.0	30.0	0.7	0.0	0.0

Measurements for an indication of the reference SPL on all other ranges which include it

Other ranges	Expected level	Actual level	Tolerance	Deviation
dB	dB	dB	+/- dB	dB
20-140	94.0	94.0	0.7	0.0

Measurements on all level ranges for indications 2 dB below the upper limit and 2 dB above the lower limit

Ranges	Reference/Expected level	Actual level	Tolerance		Deviation
			+/- dB	dB	
20-140	30.0	30.0	0.7	0.0	
	138.0	138.0	0.7	0.0	

FREQUENCY WEIGHTING TEST

The frequency response of the weighting networks are tested at octave intervals over the frequency ranges 31.5 Hz to 12500 Hz. The signal level at 1000 Hz is set to give an indication of the reference SPL.

Frequency weighting A:

Frequency	Ref. level	Expected level	Correction of electrical response	Actual level	Tolerance(dB)		Deviation *
					+	-	
Hz	dB	dB	dB	dB			dB
1000.0	94.0	94.0	0.0	94.0	0.0	0.0	0.0
31.6	94.0	54.6	N/A	54.6	1.5	1.5	0.0
63.1	94.0	67.8	0.0	67.8	1.5	1.5	0.0
125.9	94.0	77.9	0.0	77.9	1.0	1.0	0.0
251.2	94.0	85.4	0.0	85.4	1.0	1.0	0.0
501.2	94.0	90.8	0.0	90.8	1.0	1.0	0.0
1995.0	94.0	95.2	0.0	95.2	1.0	1.0	0.0
3981.0	94.0	95.0	0.0	95.0	1.0	1.0	0.0
7943.0	94.0	92.9	0.0	92.9	1.5	3.0	0.0
12590.0	94.0	89.7	-0.5	89.2	3.0	6.0	0.0

Frequency weighting C:

Frequency	Ref. level	Expected level	Correction of electrical response	Actual level	Tolerance(dB)		Deviation *
					+	-	
Hz	dB	dB	dB	dB			dB
1000.0	94.0	94.0	0.0	94.0	0.0	0.0	0.0
31.6	94.0	91.0	N/A	91.0	1.5	1.5	0.0
63.1	94.0	93.2	0.0	93.2	1.5	1.5	0.0
125.9	94.0	93.8	0.0	93.8	1.0	1.0	0.0
251.2	94.0	94.0	0.0	94.0	1.0	1.0	0.0



Test Data for Sound Level Meter

Page 3 of 5

Sound level meter type: 2250 Serial No. 2551244 Date 26-Oct-2016
Microphone type: 4189 Serial No. 2550229
Preamp type: ZC0032 Serial No. 5051 Report: 16CA1025 02-03

501.2	94.0	94.0	0.0	94.0	1.0	1.0	0.0
1995.0	94.0	93.8	0.0	93.8	1.0	1.0	0.0
3981.0	94.0	93.2	0.0	93.2	1.0	1.0	0.0
7943.0	94.0	91.0	0.0	91.0	1.5	3.0	0.0
12590.0	94.0	87.8	-0.5	87.3	3.0	6.0	0.0

Frequency weighting Lin:

Frequency	Ref. level	Expected level	Correction of electrical response	Actual level	Tolerance(dB)		Deviation *
					+	-	
Hz	dB	dB	dB	dB			dB
1000.0	94.0	94.0	0.0	94.0	0.0	0.0	0.0
31.6	94.0	94.0	N/A	94.0	1.5	1.5	0.0
63.1	94.0	94.0	0.0	94.0	1.5	1.5	0.0
125.9	94.0	94.0	0.0	94.0	1.0	1.0	0.0
251.2	94.0	94.0	0.0	94.0	1.0	1.0	0.0
501.2	94.0	94.0	0.0	94.0	1.0	1.0	0.0
1995.0	94.0	94.0	0.0	94.0	1.0	1.0	0.0
3981.0	94.0	94.0	0.0	94.0	1.0	1.0	0.0
7943.0	94.0	94.0	0.0	94.0	1.5	3.0	0.0
12590.0	94.0	94.0	-0.5	93.5	3.0	6.0	0.0

*Deviation = Actual level - (Expected level + Correction of electrical response)

The correction of electrical response is specified in the Table A.2 of technical documentation of BE 1712-21. The maximum expanded uncertainty of correction of electrical response is 0.29 dB.

TIME WEIGHTING FAST TEST

Time weighting F is tested on the reference range with a single sinusoidal burst of duration 200 ms at a frequency 2000 Hz and an amplitude which produces an indication 4 dB below the upper limit of the primary indicator range when the signal is continuous. (Weight A, Maximum hold)

Ref. level	Expected level	Actual level	Tolerance(dB)		Deviation
			+	-	
dB	dB	dB			dB
116.0	115.0	115.0	1.0	1.0	0.0

TIME WEIGHTING SLOW TEST

Time weighting S is tested on the reference range with a single sinusoidal burst of duration 500 ms at a frequency 2000 Hz and an amplitude which produces an indication 4 dB below the upper limit of the primary indicator range when the signal is continuous. (Weight A, Maximum hold)

Ref. level	Expected level	Actual level	Tolerance(dB)		Deviation
			+	-	
dB	dB	dB			dB
116.0	111.9	111.9	1.0	1.0	0.0

PEAK RESPONSE TEST

The onset time of the peak detector is tested on the reference range by comparing the response to a 100 us rectangular test pulse with the response to a 10 ms reference pulse of the same amplitude. The amplitude of the 10 ms reference pulse is such as to produce an indication 1 dB below the upper limit of the primary indicator range.



Test Data for Sound Level Meter

Page 4 of 5

Sound level meter type: 2250 Serial No. 2551244 Date 26-Oct-2016
Microphone type: 4189 Serial No. 2550229
Preamp type: ZC0032 Serial No. 5051 Report: 16CA1025 02-03

Positive polarities: (Weighting Z, set the generator signal to single, LZPeak)

Ref. level	Response to 10 ms	Response to 100 us	Tolerance	Deviation
dB	dB	dB	+/- dB	dB
119.0	119.0	118.7	2.0	-0.3

Negative polarities:

Ref. level	Response to 10 ms	Response to 100 us	Tolerance	Deviation
dB	dB	dB	+/- dB	dB
119.0	119.0	119.2	2.0	0.2

RMS ACCURACY TEST

The RMS detector accuracy is tested on the reference range for a crest factor of 3.

Test frequency: 2000 Hz
Amplitude: 2 dB below the upper limit of the primary indicator range.
Burst repetition frequency: 40 Hz
Tone burst signal: 11 cycles of a sine wave of frequency 2000 Hz. (Set to INT)

Time weighting	Ref. Level	Expected level	Tone burst signal indication(dB)	Tolerance	Deviation
	dB	dB		+/- dB	dB
Slow	118.0+6.6	118.0	118.0	0.5	0.0

TIME WEIGHTING IMPULSE TEST

Time weighting I is tested on the reference range (Set the SLM to LAImax)

Test frequency: 2000 Hz
Amplitude: The upper limit of the primary indicator range.

Single sinusoidal burst of duration 5 ms:

Ref. Level	Single burst indication		Tolerance	Deviation
	Expected (dB)	Actual (dB)		
120.0	111.2	111.1	2.0	-0.1

Repeated at 100 Hz

Ref. Level	Repeated burst indication		Tolerance	Deviation
	Expected (dB)	Actual (dB)		
120.0	117.3	117.2	1.0	-0.1

TIME AVERAGING TEST

This test compares the SLM reading for continuous sine signals with readings obtained from a sine tone burst sequence having the same RMS level. The test level is 30 dB below the upper limit of the linearity range and repeated for Type 1 SLM with 40 dB below the upper limit of the linearity.

Frequency of tone burst: 4000 Hz

Duration of tone burst: 1 ms

Repetition Time	Level of tone burst	Expected Leq	Actual Leq	Tolerance	Deviation	Remarks
msec	dB	dB	dB	+/- dB	dB	
1000	110.0	110.0	109.9	1.0	-0.1	60s integ.
10000	100.0	100.0	99.9	1.0	-0.1	6min. integ.

PULSE RANGE AND SOUND EXPOSURE LEVEL TEST



Test Data for Sound Level Meter

Page 5 of 5

Sound level meter type: 2250 Serial No. 2551244 Date 26-Oct-2016
Microphone type: 4189 Serial No. 2550229
Preamp type: ZC0032 Serial No. 5051 Report: 16CA1025 02-03

The test tone burst signal is superimposed on a baseline signal corresponding to the lower limit of reference range

Test frequency: 4000 Hz
Integration time: 10 sec

The integrating sound level meter set to Leq:

Duration msec	Rms level of tone burst (dB)	Expected dB	Actual dB	Tolerance +/- dB	Deviation dB
10	120.0	90.0	89.8	1.7	-0.2

The integrating sound level meter set to SEL:

Duration msec	Rms level of tone burst (dB)	Expected dB	Actual dB	Tolerance +/- dB	Deviation dB
10.0	120.0	100.0	100.0	1.7	0.0

OVERLOAD INDICATION TEST

For SLM capable of operating in a non-integrating mode.

Test frequency: 2000 Hz
Amplitude: 2 dB below the upper limit of the primary indicator range.
Burst repetition frequency: 40 Hz
Tone burst signal: 11 cycles of a sine wave of frequency 2000 Hz.

Level at overload (dB)	Level reduced by 1 dB	Further reduced 3 dB	Difference dB	Tolerance dB	Deviation dB
134.3	133.4	130.5	2.9	1.0	-0.1

For integrating SLM, with the instrument indicating Leq.

For integrating SLM, with the instrument indicating Leq and set to the reference range. The test signal as follow
The test tone burst signal is superimposed on a baseline signal corresponding to the lower limit of reference range
Test frequency: 4000 Hz
Integration time: 10 sec
Single burst duration: 1 msec

Rms level at overload (dB)	Level reduced by 1 dB	Expected level dB	Actual level dB	Tolerance dB	Deviation dB
141.8	140.8	100.8	100.7	2.2	-0.1

ACOUSTIC TEST

The acoustic test of the complete SLM is tested at the frequency 125 Hz and 8000 Hz using a B&K type 4226 Multifunction Acoustic Calibrator. The test is performed in A weighting.

Frequency Hz	Expected level dB	Actual level Measured (dB)		Tolerance (dB)		Deviation dB
				+	-	
1000	94.0	94.0		0.0	0.0	0.0
125	77.9	77.8		1.0	1.0	-0.1
8000	92.9	93.4		1.5	3.0	0.5

-----END-----



綜合試驗有限公司
SOILS & MATERIALS ENGINEERING CO., LTD.

香港黃竹坑道37號利達中心12樓
12/F, Leader Centre, 37 Wong Chuk Hang Road, Aberdeen, Hong Kong.
E-mail: smec@sigismec.com Website: www.sigismec.com

Tel: (852) 2873 6860
Fax: (852) 2555 7533



CERTIFICATE OF CALIBRATION

Certificate No.: 16CA1025 02-04 Page: 1 of 2

Item tested

Description: Acoustical Calibrator (Class 1)
Manufacturer: B & K
Type/Model No.: 4231
Serial/Equipment No.: 2725557
Adaptors used: -

Item submitted by

Customer: MTR Corporation
Address of Customer: 8/F, Fo Tan Railway House, Fo Tan, N.T. Hong Kong
Request No.: -
Date of receipt: 25-Oct-2016

Date of test: 27-Oct-2016

Reference equipment used in the calibration

Description:	Model:	Serial No.	Expiry Date:	Traceable to:
Lab standard microphone	B&K 4180	2412857	14-Apr-2017	SCL
Preamplifier	B&K 2673	2743150	28-Apr-2017	CEPREI
Measuring amplifier	B&K 2610	2346941	28-Apr-2017	CEPREI
Signal generator	DS 360	61227	18-Apr-2017	CEPREI
Digital multi-meter	34401A	US36087050	18-Apr-2017	CEPREI
Audio analyzer	8903B	GB41300350	19-Apr-2017	CEPREI
Universal counter	53132A	MY40003662	19-Apr-2017	CEPREI

Ambient conditions

Temperature: 22 ± 1 °C
Relative humidity: 55 ± 10 %
Air pressure: 1005 ± 5 hPa

Test specifications

- The Sound Calibrator has been calibrated in accordance with the requirements as specified in IEC 60942 1997 Annex B and the lab calibration procedure SMTP004-CA-156.
- The calibrator was tested with its axis vertical facing downwards at the specific frequency using insert voltage technique.
- The results are rounded to the nearest 0.01 dB and 0.1 Hz and have not been corrected for variations from a reference pressure of 1013.25 hectoPascals as the maker's information indicates that the instrument is insensitive to pressure changes.

Test results

This is to certify that the sound calibrator conforms to the requirements of annex B of IEC 60942: 1997 for the conditions under which the test was performed. This does not imply that the sound calibrator meets IEC 60942 under any other conditions.

Details of the performed measurements are presented on page 2 of this certificate.

Approved Signatory:

Huang Jie Min/Feng Jun Qi

Date: 27-Oct-2016

Company Chop:



Comments: The results reported in this certificate refer to the condition of the instrument on the date of calibration and carry no implication regarding the long-term stability of the instrument.



CERTIFICATE OF CALIBRATION
(Continuation Page)

Certificate No.: 16CA1025 02-04 Page: 2 of 2

1, Measured Sound Pressure Level

The output Sound Pressure Level in the calibrator head was measured at the setting and frequency shown using a calibrated laboratory standard microphone and insert voltage technique. The results are given in below with the estimated uncertainties.

Frequency Shown Hz	Output Sound Pressure Level Setting dB	Measured Output Sound Pressure Level dB	(Output level in dB re 20 μ Pa) Estimated Expanded Uncertainty dB
1000	94.00	94.11	0.10

2, Sound Pressure Level Stability - Short Term Fluctuations

The Short Term Fluctuations was determined by measuring the maximum and minimum of the fast weighted DC output of the B&K 2610 measuring amplifier over a 20 second time interval as required in the standard. The Short Term Fluctuation was found to be:

At 1000 Hz **STF = 0.002 dB**
Estimated expanded uncertainty 0.005 dB

3, Actual Output Frequency

The determination of actual output frequency was made using a B&K 4180 microphone together with a B&K 2673 preamplifier connected to a B&K 2610 measuring amplifier. The AC output of the B&K 2610 was taken to an universal counter which was used to determine the frequency averaged over 20 second of operation as required by the standard. The actual output frequency at 1 KHz was:


At 1000 Hz **Actual Frequency = 1000.0 Hz**
Estimated expanded uncertainty 0.1 Hz Coverage factor k = 2.2

4, Total Noise and Distortion


For the Total Noise and Distortion measurement, the unfiltered AC output of the B&K 2610 measuring amplifier was connected to an Agilent Type 8903 B distortion analyser. The TND result at 1 KHz was:

At 1000 Hz **TND = 0.5 %**
Estimated expanded uncertainty 0.7 %

The expanded uncertainties have been calculated in accordance with the ISO Publication "Guide to the expression of uncertainty in measurement", and gives an interval estimated to have a level of confidence of 95%. A coverage factor of 2 is assumed unless explicitly stated.

Calibrated by: 
Date: 27-Oct-2016

- End -

Checked by: 
Date: 27-Oct-2016

The standard(s) and equipment used in the calibration are traceable to national or international recognised standards and are calibrated on a schedule to maintain the required accuracy level.

Appendix D
Event Action Plans

Table 2.3 Event / Action Plan for Air Quality (Dust)

Event	Action			
	ET	Contractor	ER	
<p>Action Level being exceeded</p>	<ol style="list-style-type: none"> 1. Conduct additional measurement to confirm finding. 2. Identify source and investigate the causes of exceedance, if caused by MTRCL's work. 3. Inform IEC, ER and Contractor. 4. Discuss with IEC, ER and Contractor on remedial actions required. 5. If necessary, conduct additional monitoring to assess the effectiveness of Contractor's remedial actions. 6. If exceedance continues, arrange meeting with IEC and ER to review implementation and identify further appropriate mitigation measures. 7. If exceedance stops, cease additional monitoring. 	<ol style="list-style-type: none"> 1. Discuss with ET on proper remedial actions. 2. Submit proposals for remedial actions to ER within 3 working days of notification. 3. Amend proposal if appropriate. 4. Implement the agreed proposals. 5. Liaise with ER to optimize the effectiveness of the agreed mitigation. 	<ol style="list-style-type: none"> 1. Confirm receipt of notification of exceedance. 2. Notify Contractor. 3. Check Contractor's working methods. 4. Agree with the Contractor on the remedial measures to be implemented. 5. Ensure proper implementation of remedial measures. 6. Assess the efficiency of remedial actions and keep the Contractor informed. 	<ol style="list-style-type: none"> 1. Check Contractor's working method. 2. Advise ET on the effectiveness of the proposed remedial measures.

Event	Action		
	ET	Contractor	ER
Limit level being exceeded	<ol style="list-style-type: none"> 1. Conduct additional measurement to confirm findings. 2. Identify source and investigate the causes of exceedance; 3. Notify EPD, IEC, ER and Contractor. 4. Check Contractor's working procedures. 5. Discuss with IEC, ER and Contractor on remedial actions required. 6. If necessary, conduct additional monitoring to assess effectiveness of Contractor's remedial actions. 7. Keep EPD, IEC and ER informed of the monitoring results. 8. If exceedance continues, arrange meeting with IEC and ER to review implementation and identify further appropriate mitigation measures. 9. If exceedance stops, cease additional monitoring. 	<ol style="list-style-type: none"> 1. Take immediate action to avoid further exceedance. 2. Discuss with ET and ER on proper remedial actions. 3. Submit proposals for remedial actions to ER within 3 working days of notification. 4. Implement the agreed proposals. 5. Liaise with ER to optimize the effectiveness of the agreed mitigation. 	<ol style="list-style-type: none"> 1. Confirm receipt of notification of exceedance. 2. Notify Contractor. 3. Check Contractor's working methods. 4. Agree with the Contractor on the remedial measures to be implemented. 5. Ensure proper implementation of remedial measures. 6. Assess the efficiency of remedial actions and keep the Contractor informed.
			IEC

Table 3.3 Event and Action Plan for Construction Noise

Event	Action		
	ET	Contractor	ER
<p>Action Level being exceeded</p>	<ol style="list-style-type: none"> 1. Undertake measurement to establish validity of complaint. 2. Identify source(s) of complaint. 3. Notify IEC, ER and Contractor. 4. Discuss with the IEC, ER and Contractor on remedial measures required. 5. Increase monitoring frequency to check mitigation effectiveness. 6. If exceedance continues, arrange meeting with IEC and ER to review implementation and identify further appropriate mitigation measures. 7. If exceedance stops, cease additional monitoring. 	<ol style="list-style-type: none"> 1. Submit noise mitigation proposals to ER within three working days of notification. 2. Amend proposal if appropriate. 3. Implement noise mitigation proposals. 4. Liaise with ER to optimize the effectiveness of the agreed mitigation. 	<ol style="list-style-type: none"> 1. Confirm receipt of notification of complaint. 2. Notify Contractor. 3. Check Contractor's working methods. 4. Agree with the Contractor on the remedial measures to be implemented. 5. Ensure proper implementation of remedial measures. 6. Assess the efficiency of remedial actions and keep the Contractor informed. 7. Inform complainant of actions taken.
			<ol style="list-style-type: none"> 1. Check Contractor's working methods. 2. Review the proposed remedial measures by the Contractor and advise the ET accordingly.

Event	Action			IEC
	ET	Contractor	ER	
<p>Limit Level being exceeded</p> <ol style="list-style-type: none"> 1. Repeat measurement to confirm findings. 2. Identify source and investigate the cause of exceedance. 3. Inform EPD, IEC, ER and Contractor. 4. Check Contractor's working procedures. 5. Discuss with the IEC, Contractor and ER on remedial measures required. 6. Increase monitoring frequency to assess effectiveness of Contractor's mitigation actions and keep EPD, IEC and ER informed the results. 7. If exceedance continues, arrange meeting with IEC and ER to review implementation and identify further appropriate mitigation measures. 8. If exceedance stops, cease additional monitoring. 	<ol style="list-style-type: none"> 1. Take immediate action to avoid further exceedance. 2. Submit proposals for remedial actions to ER within 3 working days of notification. 3. Implement the agreed proposals. 4. Liaise with ER to optimize the effectiveness of the agreed mitigation. 	<ol style="list-style-type: none"> 1. Confirm receipt of notification of exceedance. 2. Notify Contractor. 3. Check Contractor's working methods. 4. Agree with the Contractor on the remedial measures to be implemented. 5. Ensure proper implementation of remedial measures. 6. Assess the efficiency of remedial actions and keep the Contractor informed. 	<ol style="list-style-type: none"> 1. Check Contractor's working methods. 2. Review Contractor's remedial actions whenever necessary to assure their effectiveness and advise the ET accordingly. 	

Appendix E
Air Quality Monitoring

D1 Site Boundary				
Date	24hr TSP (ug/m3)	Action Level (ug/m3)	Limit Level (ug/m3)	Weather Condition
14-02-13	108.0	226	260	Cloudy
20-02-13	112.0	226	260	Sunny
27-02-13	127.0	226	260	Cloudy
06-03-13	150.0	226	260	Cloudy
13-03-13	176.0	226	260	Cloudy
20-03-13	135.0	226	260	Cloudy
27-03-13	140.0	226	260	Occasional Rain
02-04-13	135.0	226	260	Occasional Rain
09-04-13	97.0	226	260	Occasional Rain
16-04-13	112.0	226	260	Occasional Rain
23-04-13	69.0	226	260	Occasional Rain
30-04-13	85.0	226	260	Occasional Rain
07-05-13	96.0	226	260	Occasional Rain
14-05-13	102.0	226	260	Occasional Rain
21-05-13	82.0	226	260	Occasional Rain
28-05-13	110.0	226	260	Occasional Rain
04-06-13	112.0	226	260	Occasional Rain
11-06-13	65.0	226	260	Occasional Rain
18-06-13	94.0	226	260	Overcast
25-06-13	108.0	226	260	Occasional Rain
02-07-13	100.2	226	260	Overcast
09-07-13	102.6	226	260	Overcast
16-07-13	79.1	226	260	Occasional Rain
23-07-13	116.8	226	260	Occasional Rain
30-07-13	98.5	226	260	Overcast
06-08-13	132.0	226	260	Sunny
15-08-13	85.0	226	260	Occasional Rain
21-08-13	88.0	226	260	Occasional Rain
27-08-13	119.0	226	260	Sunny
03-09-13	107.7	226	260	Occasional Rain
10-09-13	156.0	226	260	Sunny
17-09-13	110.8	226	260	Sunny
24-09-13	72.0	226	260	Occasional Rain
02-10-13	182.7	226	260	Sunny
08-10-13	155.5	226	260	Overcast
15-10-13	148.5	226	260	Sunny
22-10-13	184.7	226	260	Sunny
29-10-13	173.2	226	260	Sunny
05-11-13	162.2	226	260	Occasional Rain
12-11-13	117.7	226	260	Occasional Rain
19-11-13	129.9	226	260	Overcast
26-11-13	198.3	226	260	Sunny
03-12-13	154.1	226	260	Sunny
10-12-13	169.3	226	260	Overcast
19-12-13	187.5	226	260	Sunny
23-12-13	210.1	226	260	Sunny
31-12-13	187.5	226	260	Sunny



D1 Site Boundary				
Date	24hr TSP (ug/m3)	Action Level (ug/m3)	Limit Level (ug/m3)	Weather Condition
07-01-14	210.0	226	260	Overcast
14-01-14	210.0	226	260	Sunny
21-01-14	218.0	226	260	Sunny
28-01-14	193.7	226	260	Sunny
05-02-14	134.2	226	260	Overcast
11-02-14	111.6	226	260	Overcast
19-02-14	176.0	226	260	Overcast
25-02-14	125.2	226	260	Sunny
07-03-14	88.0	226	260	Overcast
11-03-14	210.3	226	260	Overcast
18-03-14	170.8	226	260	Overcast
25-03-14	198.0	226	260	Sunny
01-04-14	61.7	226	260	Occasional Rain
09-04-14	67.7	226	260	Overcast
16-04-14	118.7	226	260	Overcast
22-04-14	162.2	226	260	Overcast
29-04-14	142.3	226	260	Overcast
08-05-14	77.0	226	260	Occasional Rain
13-05-14	71.0	226	260	Occasional Rain
20-05-14	102.0	226	260	Occasional Rain
27-05-14	162.0	226	260	Sunny
03-06-14	84.0	226	260	Sunny
10-06-14	149.0	226	260	Sunny
17-06-14	131.0	226	260	Sunny
24-06-14	85.0	226	260	Overcast
02-07-14	103.0	226	260	Sunny
08-07-14	178.0	226	260	Sunny
14-07-14	95.0	226	260	Occasional Rain
22-07-14	100.0	226	260	Occasional Rain
29-07-14	74.0	226	260	Sunny
05-08-14	71.0	226	260	Occasional Rain
12-08-14	84.0	226	260	Occasional Rain
19-08-14	78.0	226	260	Occasional Rain
26-08-14	99.3	226	260	Sunny
02-09-14	76.7	226	260	Sunny
08-09-14	121.2	226	260	Occasional Rain
17-09-14	111.7	226	260	Occasional Rain
23-09-14	155.9	226	260	Sunny
29-09-14	169.3	226	260	Sunny
07-10-14	202.4	226	260	Overcast
14-10-14	142.8	226	260	Overcast
21-10-14	69.8	226	260	Overcast
28-10-14	199.9	226	260	Overcast
04-11-14	138.2	226	260	Overcast
11-11-14	140.7	226	260	Sunny
18-11-14	208.1	226	260	Overcast
25-11-14	148.9	226	260	Sunny

D1 Site Boundary				
Date	24hr TSP (ug/m3)	Action Level (ug/m3)	Limit Level (ug/m3)	Weather Condition
02-12-14	89.6	226	260	Occasional Rain
08-12-14	133.0	226	260	Overcast
16-12-14	147.7	226	260	Sunny
23-12-14	150.8	226	260	Overcast
30-12-14	185.7	226	260	Sunny
06-01-15	133.7	226	260	Sunny
13-01-15	81.6	226	260	Occasional Rain
20-01-15	171.0	226	260	Sunny
27-01-15	191.6	226	260	Sunny
03-02-15	201.0	226	260	Sunny
10-02-15	140.6	226	260	Sunny
16-02-15	199.8	226	260	Overcast
24-02-15	189.0	226	260	Overcast
03-03-15	168.5	226	260	Overcast
10-03-15	204.3	226	260	Overcast
17-03-15	145.4	226	260	Sunny
24-03-15	148.7	226	260	Sunny
01-04-15	79.2	226	260	Sunny
09-04-15	112.2	226	260	Occasional Rain
14-04-15	146.4	226	260	Sunny
21-04-15	144.4	226	260	Overcast
28-04-15	151.1	226	260	Sunny
06-05-15	132.6	226	260	Overcast
12-05-15	169.7	226	260	Sunny
18-05-15	105.1	226	260	Overcast
27-05-15	101.0	226	260	Overcast
02-06-15	120.0	226	260	Occasional Rain
09-06-15	110.2	226	260	Overcast
17-06-15	77.1	226	260	Sunny
23-06-15	87.6	226	260	Occasional Rain
29-06-15	137.6	226	260	Overcast
07-07-15	108.9	226	260	Sunny
14-07-15	99.9	226	260	Sunny
21-07-15	81.0	226	260	Occasional Rain
28-07-15	182.6	226	260	Overcast
04-08-15	186.0	226	260	Sunny
11-08-15	52.4	226	260	Occasional Rain
18-08-15	57.3	226	260	Overcast
25-08-15	90.7	226	260	Sunny
04-09-15	80.5	226	260	Sunny
08-09-15	136.6	226	260	Sunny
15-09-15	149.8	226	260	Sunny
22-09-15	90.5	226	260	Occasional Rain
02-10-15	90.3	226	260	Occasional Rain
06-10-15	57.0	226	260	Occasional Rain
13-10-15	115.2	226	260	Overcast
19-10-15	94.4	226	260	Sunny

D1 Site Boundary				
Date	24hr TSP (ug/m3)	Action Level (ug/m3)	Limit Level (ug/m3)	Weather Condition
27-10-15	79.0	226	260	Sunny
03-11-15	102.2	226	260	Overcast
10-11-15	84.0	226	260	Overcast
17-11-15	104.5	226	260	Sunny
24-11-15	103.1	226	260	Overcast
01-12-15	70.2	226	260	Sunny
08-12-15	76.5	226	260	Overcast
14-12-15	74.7	226	260	Overcast
22-12-15	118.9	226	260	Overcast
30-12-15	116.6	226	260	Overcast
05-01-16	53.8	226	260	Occasional Rain
12-01-16	59.3	226	260	Sunny
19-01-16	177.4	226	260	Sunny
26-01-16	100.1	226	260	Overcast
02-02-16	58.7	226	260	Overcast
11-02-16	123.0	226	260	Overcast
16-02-16	116.1	226	260	Sunny
23-02-16	81.7	226	260	Overcast
01-03-16	196.1	226	260	Sunny
09-03-16	72.9	226	260	Occasional Rain
15-03-16	106.2	226	260	Overcast
22-03-16	65.1	226	260	Occasional Rain
29-03-16	89.0	226	260	Overcast
05-04-16	65.2	226	260	Overcast
12-04-16	59.1	226	260	Occasional Rain
19-04-16	65.9	226	260	Overcast
26-04-16	59.5	226	260	Overcast
03-05-16	62.3	226	260	Occasional Rain
10-05-16	45.6	226	260	Occasional Rain
17-05-16	83.4	226	260	Occasional Rain
24-05-16	72.3	226	260	Overcast
30-05-16	76.4	226	260	Overcast
07-06-16	44.5	226	260	Occasional Rain
14-06-16	57.3	226	260	Overcast
21-06-16	36.6	226	260	Sunny
28-06-16	41.4	226	260	Occasional Rain
05-07-16	46.2	226	260	Occasional Rain
12-07-16	41.7	226	260	Overcast
19-07-16	70.0	226	260	Occasional Rain
30-07-16	69.0	226	260	Overcast
05-08-16	53.4	226	260	Overcast
09-08-16	45.8	226	260	Occasional Rain
19-08-16	47.2	226	260	Occasional Rain
23-08-16	62.8	226	260	Sunny
30-08-16	67.5	226	260	Sunny
06-09-16	74.7	226	260	Occasional Rain
13-09-16	64.8	226	260	Occasional Rain

D1 Site Boundary				
Date	24hr TSP (ug/m3)	Action Level (ug/m3)	Limit Level (ug/m3)	Weather Condition
20-09-16	55.5	226	260	Occasional Rain
29-09-16	41.4	226	260	Overcast
04-10-16	71.3	226	260	Sunny
11-10-16	67.4	226	260	Overcast
18-10-16	60.2	226	260	Occasional Rain
25-10-16	64.3	226	260	Overcast
02-11-16	72.5	226	260	Sunny
08-11-16	61.3	226	260	Occasional Rain
15-11-16	64.2	226	260	Overcast
22-11-16	62.2	226	260	Occasional Rain
29-11-16	67.8	226	260	Sunny
06-12-16	69.4	226	260	Overcast
13-12-16	71.3	226	260	Overcast
20-12-16	66.5	226	260	Sunny
29-12-16	68.4	226	260	Sunny
03-01-17	68.2	226	260	Sunny
10-01-17	67.3	226	260	Sunny
20-01-17	56.9	226	260	Overcast
26-01-17	61.3	226	260	Sunny
03-02-17	69.7	226	260	Sunny
07-02-17	70.2	226	260	Sunny
14-02-17	67.5	226	260	Sunny
21-02-17	62.4	226	260	Occasional Rain
27-02-17	68.9	226	260	Sunny
07-03-17	64.0	226	260	Overcast
14-03-17	61.1	226	260	Occasional Rain
21-03-17	65.7	226	260	Occasional Rain

TNS 24 Hrs TSP Level at D1 Site Boundary



Appendix F
Noise Monitoring

M1 Hai Phong Mansion			
Date	Measured Leq (dBA)	Limit Level (dBA)	Weather Condition
14/02/13	65	75	Cloudy
20/02/13	68	75	Sunny
27/02/13	71	75	Cloudy
06/03/13	72	75	Cloudy
13/03/13	72	75	Cloudy
20/03/13	71	75	Cloudy
27/03/13	72	75	Occasional Rain
02/04/13	71	75	Occasional Rain
09/04/13	69	75	Occasional Rain
16/04/13	65	75	Occasional Rain
23/04/13	65	75	Occasional Rain
30/04/13	66	75	Occasional Rain
07/05/13	65	75	Occasional Rain
14/05/13	65	75	Occasional Rain
21/05/13	64	75	Occasional Rain
28/05/13	65	75	Occasional Rain
04/06/13	65	75	Occasional Rain
11/06/13	65	75	Occasional Rain
18/06/13	64	75	Overcast
25/06/13	66	75	Occasional Rain
02/07/13	63	75	Overcast
09/07/13	65	75	Overcast
16/07/13	63	75	Occasional Rain
23/07/13	66	75	Occasional Rain
30/07/13	63	75	Overcast
06/08/13	63	75	Sunny
15/08/13	64	75	Occasional Rain
21/08/13	64	75	Occasional Rain
27/08/13	63	75	Sunny
03/09/13	63	75	Occasional Rain
10/09/13	63	75	Sunny
17/09/13	64	75	Sunny
24/09/13	63	75	Occasional Rain
02/10/13	63	75	Sunny
08/10/13	63	75	Overcast
15/10/13	63	75	Sunny
22/10/13	66	75	Sunny
29/10/13	63	75	Sunny
06/11/13	64	75	Overcast
12/11/13	63	75	Occasional Rain
19/11/13	63	75	Overcast

M2 Comfort Building			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
14/02/13	63	75	Cloudy
20/02/13	65	75	Sunny
27/02/13	68	75	Cloudy
06/03/13	68	75	Cloudy
13/03/13	68	75	Cloudy
20/03/13	68	75	Cloudy
27/03/13	69	75	Occasional Rain
02/04/13	68	75	Occasional Rain
09/04/13	69	75	Occasional Rain
16/04/13	68	75	Occasional Rain
23/04/13	68	75	Occasional Rain
30/04/13	68	75	Occasional Rain
07/05/13	68	75	Occasional Rain
14/05/13	68	75	Occasional Rain
21/05/13	68	75	Occasional Rain
28/05/13	68	75	Occasional Rain
04/06/13	70	75	Occasional Rain
11/06/13	67	75	Occasional Rain
18/06/13	68	75	Overcast
25/06/13	68	75	Occasional Rain
02/07/13	66	75	Overcast
09/07/13	68	75	Overcast
16/07/13	67	75	Occasional Rain
23/07/13	68	75	Occasional Rain
30/07/13	67	75	Overcast
06/08/13	66	75	Sunny
15/08/13	66	75	Occasional Rain
21/08/13	68	75	Occasional Rain
27/08/13	67	75	Sunny
03/09/13	66	75	Occasional Rain
10/09/13	67	75	Sunny
17/09/13	67	75	Sunny
24/09/13	66	75	Occasional Rain
02/10/13	66	75	Sunny
08/10/13	66	75	Overcast
15/10/13	65	75	Sunny
22/10/13	67	75	Sunny
29/10/13	67	75	Sunny
06/11/13	67	75	Overcast
12/11/13	67	75	Occasional Rain
19/11/13	66	75	Overcast

M3 Burlington Arcade			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
14/02/13	63	75	Cloudy
20/02/13	64	75	Sunny
27/02/13	67	75	Cloudy
06/03/13	67	75	Cloudy
13/03/13	67	75	Cloudy
20/03/13	68	75	Cloudy
27/03/13	68	75	Occasional Rain
02/04/13	68	75	Occasional Rain
09/04/13	67	75	Occasional Rain
16/04/13	65	75	Occasional Rain
23/04/13	64	75	Occasional Rain
30/04/13	67	75	Occasional Rain
07/05/13	67	75	Occasional Rain
14/05/13	66	75	Occasional Rain
21/05/13	65	75	Occasional Rain
28/05/13	68	75	Occasional Rain
04/06/13	64	75	Occasional Rain
11/06/13	64	75	Occasional Rain
18/06/13	67	75	Overcast
25/06/13	65	75	Occasional Rain
02/07/13	62	75	Overcast
09/07/13	68	75	Overcast
16/07/13	64	75	Occasional Rain
23/07/13	64	75	Occasional Rain
30/07/13	64	75	Overcast
06/08/13	63	75	Sunny
15/08/13	63	75	Occasional Rain
21/08/13	64	75	Occasional Rain
27/08/13	64	75	Sunny
03/09/13	63	75	Occasional Rain
10/09/13	63	75	Sunny
17/09/13	64	75	Sunny
24/09/13	64	75	Occasional Rain
02/10/13	64	75	Sunny
08/10/13	64	75	Overcast
15/10/13	63	75	Sunny
22/10/13	64	75	Sunny
29/10/13	64	75	Sunny
06/11/13	64	75	Overcast
12/11/13	64	75	Occasional Rain
19/11/13	64	75	Overcast

M1 Hai Phong Mansion			
Date	Measured Leq (dBA)	Limit Level (dBA)	Weather Condition
26/11/13	65	75	Sunny
02/12/13	64	75	Sunny
10/12/13	63	75	Overcast
18/12/13	64	75	Sunny
24/12/13	63	75	Sunny
31/12/13	63	75	Sunny
07/01/14	64	75	Overcast
14/01/14	64	75	Sunny
21/01/14	63	75	Sunny
27/01/14	64	75	Sunny
04/02/14	64	75	Overcast
11/02/14	65	75	Sunny
19/02/14	64	75	Sunny
26/02/14	64	75	Sunny
05/03/14	64	75	Overcast
12/03/14	65	75	Overcast
18/03/14	69	75	Overcast
25/03/14	65	75	Sunny
02/04/14	65	75	Occasional Rain
09/04/14	65	75	Overcast
16/04/14	71	75	Overcast
22/04/14	65	75	Overcast
30/04/14	71	75	Overcast
08/05/14	67	75	Occasional Rain
14/05/14	66	75	Overcast
23/05/14	65	75	Occasional Rain
27/05/14	66	75	Sunny
04/06/14	67	75	Sunny
11/06/14	68	75	Sunny
18/06/14	67	75	Occasional Rain
25/06/14	67	75	Occasional Rain
03/07/14	67	75	Sunny
09/07/14	65	75	Sunny
16/07/14	66	75	Sunny
22/07/14	67	75	Occasional Rain
30/07/14	67	75	Sunny
06/08/14	66	75	Occasional Rain
12/08/14	65	75	Occasional Rain
19/08/14	65	75	Occasional Rain
26/08/14	71	75	Sunny
03/09/14	71	75	Sunny

M2 Comfort Building			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
26/11/13	67	75	Sunny
02/12/13	65	75	Sunny
10/12/13	66	75	Overcast
18/12/13	66	75	Sunny
24/12/13	68	75	Sunny
31/12/13	67	75	Sunny
07/01/14	67	75	Overcast
14/01/14	66	75	Sunny
21/01/14	66	75	Sunny
27/01/14	67	75	Sunny
04/02/14	67	75	Overcast
11/02/14	66	75	Sunny
19/02/14	67	75	Sunny
26/02/14	67	75	Sunny
05/03/14	67	75	Overcast
12/03/14	69	75	Overcast
18/03/14	68	75	Overcast
25/03/14	69	75	Sunny
02/04/14	67	75	Occasional Rain
09/04/14	69	75	Overcast
16/04/14	68	75	Overcast
22/04/14	69	75	Overcast
30/04/14	69	75	Overcast
08/05/14	68	75	Occasional Rain
14/05/14	68	75	Overcast
23/05/14	68	75	Occasional Rain
27/05/14	68	75	Sunny
04/06/14	68	75	Sunny
11/06/14	68	75	Sunny
18/06/14	68	75	Occasional Rain
25/06/14	70	75	Occasional Rain
03/07/14	69	75	Sunny
09/07/14	68	75	Sunny
16/07/14	69	75	Sunny
22/07/14	69	75	Occasional Rain
30/07/14	69	75	Sunny
06/08/14	68	75	Occasional Rain
12/08/14	68	75	Occasional Rain
19/08/14	70	75	Occasional Rain
26/08/14	68	75	Sunny
03/09/14	69	75	Sunny

M3 Burlington Arcade			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
26/11/13	66	75	Sunny
02/12/13	65	75	Sunny
10/12/13	64	75	Overcast
18/12/13	64	75	Sunny
24/12/13	64	75	Sunny
31/12/13	64	75	Sunny
07/01/14	64	75	Overcast
14/01/14	64	75	Sunny
21/01/14	62	75	Sunny
27/01/14	64	75	Sunny
04/02/14	64	75	Overcast
11/02/14	63	75	Sunny
19/02/14	64	75	Sunny
26/02/14	65	75	Sunny
05/03/14	66	75	Overcast
12/03/14	65	75	Overcast
18/03/14	67	75	Overcast
25/03/14	65	75	Sunny
02/04/14	65	75	Occasional Rain
09/04/14	65	75	Overcast
16/04/14	66	75	Overcast
22/04/14	67	75	Overcast
30/04/14	66	75	Overcast
08/05/14	64	75	Occasional Rain
14/05/14	64	75	Overcast
23/05/14	66	75	Occasional Rain
27/05/14	66	75	Sunny
04/06/14	67	75	Sunny
11/06/14	66	75	Sunny
18/06/14	66	75	Occasional Rain
25/06/14	68	75	Occasional Rain
03/07/14	66	75	Sunny
09/07/14	66	75	Sunny
16/07/14	66	75	Sunny
22/07/14	66	75	Occasional Rain
30/07/14	66	75	Sunny
06/08/14	65	75	Occasional Rain
12/08/14	65	75	Occasional Rain
19/08/14	66	75	Occasional Rain
26/08/14	66	75	Sunny
03/09/14	66	75	Sunny

M1 Hai Phong Mansion			
Date	Measured Leq (dBA)	Limit Level (dBA)	Weather Condition
10/09/14	66	75	Overcast
18/09/14	72	75	Overcast
23/09/14	66	75	Sunny
30/09/14	68	75	Occasional Rain
08/10/14	68	75	Sunny
14/10/14	72	75	Overcast
21/10/14	65	75	Overcast
29/10/14	66	75	Overcast
05/11/14	66	75	Sunny
10/11/14	63	75	Overcast
19/11/14	62	75	Overcast
25/11/14	63	75	Sunny
02/12/14	67	75	Occasional Rain
10/12/14	70	75	Occasional Rain
17/12/14	65	75	Sunny
23/12/14	66	75	Overcast
30/12/14	66	75	Sunny
07/01/15	65	75	Overcast
14/01/15	65	75	Sunny
21/01/15	66	75	Overcast
27/01/15	66	75	Sunny
04/02/15	65	75	Overcast
11/02/15	67	75	Sunny
16/02/15	66	75	Overcast
25/02/15	66	75	Overcast
04/03/15	68	75	Overcast
11/03/15	65	75	Overcast
18/03/15	70	75	Sunny
25/03/15	66	75	Occasional Rain
01/04/15	66	75	Sunny
09/04/15	66	75	Overcast
15/04/15	69	75	Sunny
21/04/15	69	75	Overcast
29/04/15	69	75	Sunny
06/05/15	70	75	Overcast
12/05/15	68	75	Sunny
20/05/15	66	75	Occasional Rain
27/05/15	70	75	Overcast
03/06/15	70	75	Overcast
11/06/15	67	75	Overcast
17/06/15	69	75	Sunny

M2 Comfort Building			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
10/09/14	69	75	Overcast
18/09/14	67	75	Overcast
24/09/14	68	75	Overcast
30/09/14	68	75	Occasional Rain
08/10/14	68	75	Sunny
14/10/14	71	75	Overcast
21/10/14	69	75	Overcast
29/10/14	68	75	Overcast
05/11/14	67	75	Sunny
10/11/14	67	75	Overcast
19/11/14	69	75	Overcast
25/11/14	68	75	Sunny
02/12/14	69	75	Occasional Rain
10/12/14	69	75	Occasional Rain
17/12/14	68	75	Sunny
23/12/14	67	75	Overcast
30/12/14	68	75	Sunny
06/01/15	68	75	Sunny
14/01/15	67	75	Sunny
21/01/15	67	75	Overcast
28/01/15	68	75	Overcast
04/02/15	68	75	Overcast
11/02/15	69	75	Sunny
16/02/15	68	75	Overcast
25/02/15	69	75	Overcast
04/03/15	68	75	Overcast
11/03/15	69	75	Overcast
18/03/15	70	75	Sunny
25/03/15	68	75	Occasional Rain
01/04/15	67	75	Sunny
09/04/15	68	75	Overcast
15/04/15	68	75	Sunny
21/04/15	68	75	Overcast
29/04/15	68	75	Sunny
06/05/15	68	75	Overcast
12/05/15	67	75	Sunny
20/05/15	67	75	Occasional Rain
28/05/15	69	75	Overcast
03/06/15	68	75	Overcast
11/06/15	66	75	Overcast
17/06/15	69	75	Sunny

M3 Burlington Arcade			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
10/09/14	65	75	Overcast
18/09/14	66	75	Overcast
24/09/14	66	75	Overcast
30/09/14	65	75	Occasional Rain
08/10/14	66	75	Sunny
14/10/14	68	75	Overcast
21/10/14	68	75	Overcast
29/10/14	65	75	Overcast
05/11/14	65	75	Sunny
10/11/14	66	75	Overcast
19/11/14	65	75	Overcast
25/11/14	61	75	Sunny
02/12/14	66	75	Occasional Rain
10/12/14	65	75	Occasional Rain
17/12/14	64	75	Sunny
23/12/14	65	75	Overcast
30/12/14	65	75	Sunny
06/01/15	66	75	Sunny
14/01/15	64	75	Sunny
21/01/15	65	75	Overcast
28/01/15	65	75	Overcast
04/02/15	65	75	Overcast
11/02/15	65	75	Sunny
16/02/15	65	75	Overcast
25/02/15	65	75	Overcast
04/03/15	65	75	Overcast
11/03/15	65	75	Overcast
18/03/15	66	75	Sunny
25/03/15	66	75	Occasional Rain
01/04/15	65	75	Sunny
09/04/15	66	75	Overcast
15/04/15	66	75	Sunny
21/04/15	66	75	Overcast
29/04/15	66	75	Sunny
06/05/15	66	75	Overcast
12/05/15	65	75	Sunny
20/05/15	64	75	Occasional Rain
28/05/15	66	75	Overcast
03/06/15	66	75	Overcast
11/06/15	64	75	Overcast
17/06/15	68	75	Sunny

M1 Hai Phong Mansion			
Date	Measured Leq (dBA)	Limit Level (dBA)	Weather Condition
25/06/15	67	75	Occasional Rain
30/06/15	69	75	Overcast
07/07/15	69	75	Sunny
15/07/15	68	75	Overcast
23/07/15	66	75	Occasional Rain
29/07/15	69	75	Occasional Rain
05/08/15	70	75	Sunny
12/08/15	67	75	Overcast
18/08/15	69	75	Overcast
26/08/15	67	75	Overcast
01/09/15	67	75	Occasional Rain
09/09/15	67	75	Overcast
16/09/15	65	75	Occasional Rain
23/09/15	66	75	Overcast
30/09/15	66	75	Overcast
07/10/15	66	75	Occasional Rain
14/10/15	66	75	Sunny
22/10/15	66	75	Sunny
28/10/15	66	75	Overcast
05/11/15	67	75	Overcast
11/11/15	66	75	Overcast
18/11/15	66	75	Sunny
25/11/15	66	75	Sunny
02/12/15	67	75	Overcast
08/12/15	67	75	Overcast
16/12/15	66	75	Sunny
23/12/15	66	75	Overcast
30/12/15	67	75	Overcast
06/01/16	68	75	Overcast
13/01/16	66	75	Sunny
20/01/16	67	75	Overcast
27/01/16	66	75	Overcast
03/02/16	66	75	Overcast
12/02/16	65	75	Overcast
17/02/16	66	75	Overcast
23/02/16	65	75	Overcast
02/03/16	66	75	Sunny
10/03/16	66	75	Occasional Rain
17/03/16	66	75	Occasional Rain
22/03/16	65	75	Occasional Rain
30/03/16	65	75	Overcast

M2 Comfort Building			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
25/06/15	67	75	Occasional Rain
30/06/15	70	75	Overcast
07/07/15	68	75	Sunny
15/07/15	68	75	Overcast
23/07/15	67	75	Occasional Rain
29/07/15	67	75	Occasional Rain
05/08/15	68	75	Sunny
11/08/15	66	75	Occasional Rain
18/08/15	69	75	Overcast
26/08/15	67	75	Overcast
01/09/15	69	75	Occasional Rain
09/09/15	68	75	Overcast
16/09/15	68	75	Occasional Rain
23/09/15	68	75	Overcast
30/09/15	69	75	Overcast
07/10/15	67	75	Occasional Rain
14/10/15	67	75	Sunny
22/10/15	68	75	Sunny
28/10/15	68	75	Overcast
05/11/15	68	75	Overcast
11/11/15	68	75	Overcast
18/11/15	68	75	Sunny
25/11/15	67	75	Sunny
02/12/15	68	75	Overcast
08/12/15	68	75	Overcast
16/12/15	67	75	Sunny
23/12/15	67	75	Overcast
30/12/15	67	75	Overcast
06/01/16	68	75	Overcast
13/01/16	67	75	Sunny
20/01/16	68	75	Overcast
27/01/16	67	75	Overcast
03/02/16	67	75	Overcast
12/02/16	67	75	Overcast
17/02/16	67	75	Overcast
23/02/16	67	75	Overcast
02/03/16	67	75	Sunny
10/03/16	68	75	Occasional Rain
17/03/16	66	75	Occasional Rain
22/03/16	67	75	Occasional Rain
30/03/16	67	75	Overcast

M3 Burlington Arcade			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
25/06/15	65	75	Occasional Rain
30/06/15	67	75	Overcast
07/07/15	66	75	Sunny
15/07/15	65	75	Overcast
23/07/15	65	75	Occasional Rain
29/07/15	66	75	Occasional Rain
05/08/15	66	75	Sunny
11/08/15	64	75	Occasional Rain
18/08/15	68	75	Overcast
26/08/15	65	75	Overcast
01/09/15	65	75	Occasional Rain
09/09/15	66	75	Overcast
16/09/15	64	75	Occasional Rain
23/09/15	66	75	Overcast
30/09/15	65	75	Overcast
07/10/15	67	75	Occasional Rain
14/10/15	65	75	Sunny
22/10/15	65	75	Sunny
28/10/15	66	75	Overcast
05/11/15	65	75	Overcast
11/11/15	65	75	Overcast
18/11/15	66	75	Sunny
25/11/15	65	75	Sunny
02/12/15	66	75	Overcast
08/12/15	65	75	Overcast
16/12/15	65	75	Sunny
23/12/15	66	75	Overcast
30/12/15	67	75	Overcast
06/01/16	66	75	Overcast
13/01/16	65	75	Sunny
20/01/16	66	75	Overcast
27/01/16	66	75	Overcast
03/02/16	66	75	Overcast
12/02/16	65	75	Overcast
17/02/16	64	75	Overcast
23/02/16	65	75	Overcast
02/03/16	65	75	Sunny
10/03/16	66	75	Occasional Rain
17/03/16	65	75	Occasional Rain
22/03/16	65	75	Occasional Rain
30/03/16	65	75	Overcast

M1 Hai Phong Mansion			
Date	Measured Leq (dBA)	Limit Level (dBA)	Weather Condition
07/04/16	67	75	Sunny
13/04/16	66	75	Occasional Rain
20/04/16	65	75	Overcast
27/04/16	65	75	Occasional Rain
04/05/16	65	75	Overcast
13/05/16	66	75	Overcast
18/05/16	67	75	Sunny
24/05/16	68	75	Overcast
02/06/16	66	75	Sunny
10/06/16	67	75	Occasional Rain
15/06/16	67	75	Occasional Rain
22/06/16	67	75	Sunny
28/06/16	66	75	Occasional Rain
08/07/16	67	75	Sunny
13/07/16	68	75	Occasional Rain
20/07/16	68	75	Occasional Rain
27/07/16	67	75	Overcast
03/08/16	67	75	Occasional Rain
12/08/16	66	75	Overcast
17/08/16	66	75	Occasional Rain
24/08/16	66	75	Sunny
30/08/16	66	75	Sunny
08/09/16	66	75	Occasional Rain
14/09/16	65	75	Occasional Rain
21/09/16	65	75	Occasional Rain
27/09/16	69	75	Sunny
05/10/16	65	75	Overcast
12/10/16	65	75	Overcast
20/10/16	66	75	Sunny
26/10/16	66	75	Sunny
02/11/16	66	75	Sunny
08/11/16	66	75	Occasional Rain
15/11/16	66	75	Overcast
24/11/16	66	75	Overcast
29/11/16	66	75	Sunny
06/12/16	67	75	Overcast
13/12/16	66	75	Overcast
20/12/16	66	75	Sunny
29/12/16	66	75	Sunny
04/01/17	66	75	Sunny
11/01/17	67	75	Sunny

M2 Comfort Building			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
07/04/16	67	75	Sunny
13/04/16	67	75	Occasional Rain
20/04/16	67	75	Overcast
27/04/16	67	75	Occasional Rain
04/05/16	68	75	Overcast
13/05/16	68	75	Overcast
18/05/16	68	75	Sunny
24/05/16	69	75	Overcast
02/06/16	71	75	Sunny
10/06/16	69	75	Occasional Rain
15/06/16	68	75	Occasional Rain
22/06/16	69	75	Sunny
28/06/16	68	75	Occasional Rain
08/07/16	68	75	Sunny
13/07/16	70	75	Occasional Rain
20/07/16	69	75	Occasional Rain
27/07/16	69	75	Overcast
03/08/16	68	75	Occasional Rain
12/08/16	69	75	Overcast
17/08/16	69	75	Occasional Rain
24/08/16	68	75	Sunny
30/08/16	68	75	Sunny
08/09/16	68	75	Occasional Rain
14/09/16	68	75	Occasional Rain
21/09/16	68	75	Occasional Rain
27/09/16	70	75	Sunny
05/10/16	70	75	Overcast
12/10/16	69	75	Overcast
20/10/16	68	75	Sunny
26/10/16	69	75	Sunny
02/11/16	69	75	Sunny
08/11/16	68	75	Occasional Rain
15/11/16	69	75	Overcast
24/11/16	69	75	Overcast
29/11/16	67	75	Sunny
06/12/16	68	75	Overcast
13/12/16	68	75	Overcast
20/12/16	69	75	Sunny
29/12/16	68	75	Sunny
04/01/17	69	75	Sunny
11/01/17	68	75	Sunny


M3 Burlington Arcade			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
07/04/16	66	75	Sunny
13/04/16	65	75	Occasional Rain
20/04/16	65	75	Overcast
27/04/16	65	75	Occasional Rain
04/05/16	65	75	Overcast
13/05/16	65	75	Overcast
18/05/16	65	75	Sunny
24/05/16	66	75	Overcast
02/06/16	67	75	Sunny
10/06/16	65	75	Occasional Rain
15/06/16	66	75	Occasional Rain
22/06/16	65	75	Sunny
28/06/16	65	75	Occasional Rain
08/07/16	66	75	Sunny
13/07/16	66	75	Occasional Rain
20/07/16	65	75	Occasional Rain
27/07/16	66	75	Overcast
03/08/16	65	75	Occasional Rain
12/08/16	65	75	Overcast
17/08/16	66	75	Occasional Rain
24/08/16	65	75	Sunny
30/08/16	66	75	Sunny
08/09/16	66	75	Occasional Rain
14/09/16	66	75	Occasional Rain
21/09/16	65	75	Occasional Rain
27/09/16	67	75	Sunny
05/10/16	66	75	Overcast
12/10/16	65	75	Overcast
20/10/16	67	75	Sunny
26/10/16	66	75	Sunny
02/11/16	65	75	Sunny
08/11/16	66	75	Occasional Rain
15/11/16	66	75	Overcast
24/11/16	65	75	Overcast
29/11/16	65	75	Sunny
06/12/16	66	75	Overcast
13/12/16	65	75	Overcast
20/12/16	66	75	Sunny
29/12/16	66	75	Sunny
04/01/17	65	75	Sunny
11/01/17	65	75	Sunny

M1 Hai Phong Mansion			
Date	Measured Leq (dBA)	Limit Level (dBA)	Weather Condition
20/01/17	67	75	Overcast
26/01/17	66	75	Sunny
03/02/17	67	75	Sunny
07/02/17	67	75	Sunny
14/02/17	66	75	Sunny
21/02/17	67	75	Occasional Rain
27/02/17	66	75	Sunny
07/03/17	66	75	Overcast
14/03/17	67	75	Occasional Rain
21/03/17	66	75	Occasional Rain


M2 Comfort Building			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
20/01/17	68	75	Overcast
26/01/17	67	75	Sunny
03/02/17	68	75	Sunny
07/02/17	67	75	Sunny
14/02/17	68	75	Sunny
21/02/17	69	75	Occasional Rain
27/02/17	67	75	Sunny
07/03/17	67	75	Overcast
14/03/17	67	75	Occasional Rain
21/03/17	68	75	Occasional Rain

M3 Burlington Arcade			
Date	Leq (dBA)	Limit Level (75 dBA)	Weather Condition
20/01/17	65	75	Overcast
26/01/17	65	75	Sunny
03/02/17	66	75	Sunny
07/02/17	65	75	Sunny
14/02/17	65	75	Sunny
21/02/17	65	75	Occasional Rain
27/02/17	65	75	Sunny
07/03/17	66	75	Overcast
14/03/17	66	75	Occasional Rain
21/03/17	65	75	Occasional Rain


Noise Level at M1 Hai Phong Mansion



Noise Level at M2 Comfort Building



Noise Level at M3 Burlington Arcade



Appendix G
Photographic Records



Photo record of the 4 replanted trees on Hai Phong Road



Photo record of the granite columns reinstated at Kowloon Park entrance