Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong,

Hong Kong.

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



# ENVIRONMENTAL MONITORING & AUDIT MONTHLY REPORT

### March 2017

Client : SANG HING – KULY JOINT VENTURE

Contract Name: Castle Peak Road Trunk Sewer and Tuen Mun

Village Sewerage (Sewage Pumping Station at

Lok Chui Street near Castle Peak Villas)

**Contract No.** : DC/2014/01

**EP No.** : EP-068/2000/A

Title of Project: Sewage Pumping Stations at Tai Lam Chung Tsuen

Luen On San Tsuen, Tai Lam Valley and Lok Chui Street near Castle Peak Villas under the scope of "Tuen Mun Sewerage –

Eastern Coastal Sewerage Extension"

**Report No.** : 0367/15/ED/0759A

Prepared by: Wingo H. W. So

Reviewed by : Cyrus C. Y. Lai

Certified by :

Colin K. L. Yung

Environmental Team Leader MateriaLab Consultants Limited

13 April 2017



Drainage Services Department 42/F., Revenue Tower 5 Gloucester Road

Wan Chai Hong Kong

Attention: Ms Winnie Ng

Your reference:

Our reference:

HKDSD202/50/104248

Date:

20 April 2017

BY EMAIL & POST

(email: wyng03@dsd.gov.hk)

Dear Sirs

Agreement No.: PM 08/2014

Services for Independent Environmental Checker for Construction of Lok Chui Street Sewage Pumping Station Verification of Monthly EM&A Report (March 2017)

We refer to emails of 13, 18 and 19 April 2017 attaching a monthly EM&A Report (March 2017) for the captioned project prepared by the ET.

We have no further comment and hereby verify the monthly EM&A Report in accordance with Clause 3.5 of the Environmental Permit no. EP-068/2000/A.

Please do not hesitate to contact the undersigned or our Mr Nic Lam at 2618 2836 should you have any queries.

Yours faithfully
ANEWR CONSULTING LIMITED

Independent Environmental Checker

LYMA/LHHN/LPYL/csym

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



## **TABLE OF CONTENTS**

<b>EXE</b>	CUTIVE SUMMARY	1
1.	INTRODUCTION	2
2.	AIR QUALITY	5
3.	NOISE	7
4.	LANDSCAPE AND VISUAL	10
5.	ENVIRONMENTAL SITE INSPECTION AND AUDIT	11
6.	ADVICE ON THE SOLID AND LIQUID WASTE MANAGEMENT STATUS	12
7.	ENVIRONMENTAL COMPLAINT AND NON-COMPLIANCE	13
8.	IMPLEMENTATION STATUS OF ENVIRONMENTAL MITIGATION MEASURES	14
9.	FUTURE KEY ISSUES	15
10.	CONCLUSIONS	16

## **FIGURES**

Figure 1	Site Layout Plan

Figure 2 Air Quality and Noise Monitoring Stations

## **LIST OF APPENDICES**

Appendix A	Construction Programme
Appendix B	Project Organization Chart
Appendix C	Action and Limit Levels for Air Quality and Noise
Appendix D	Calibration Certificates of Monitoring Equipment
Appendix E	Environmental Monitoring and Data Recovery Schedules
Appendix F	Air Quality Monitoring Data and Graphical Presentations
Appendix G	Noise Monitoring Data and Graphical Presentations
Appendix H	Cumulative Statistics on Exceedances, Complaints, Notifications of Summons and
	Successful Prosecutions
Appendix I	Site Audit Summary
Appendix J	Event and Action Plans
Appendix K	Implementation Status of Environmental Mitigation Measures
Appendix L	Weather and Meteorological Conditions during Monitoring Period
Appendix M	Monthly Summary of Waste Flow Table
Appendix N	Proactive Environmental Protection Proforma

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Fax Email: mcl@fugro.com Hong Kong.



### **EXECUTIVE SUMMARY**

i. This is the 13<sup>th</sup> monthly EM&A Report which summaries the impact monitoring results and audit findings for the Project within the period from 1 March to 31 March 2017.

## **Construction Activities for the Reporting Period**

- ii. During this reporting period, the principal work activities within the site included:
  - Welding of capping plate
  - Construction of Wet Well Chamber

## **Breaches of Action and Limit Levels for Air Quality**

iii. No Action or Limit Level Exceedance of 1-hr TSP monitoring was recorded in the reporting period.

### **Breaches of Action and Limit Levels for Noise**

iv. No exceedance was recorded at all monitoring stations in the reporting period.

### **Complaint, Notifications of Summons and Successful Prosecutions**

v. No Action or Limit Level Exceedance of noise monitoring was recorded in the reporting period.

### Reporting Change

vi. There was no reporting change required in the reporting period.

## **Future Key Issues**

## **Construction Activities for the Coming Reporting Period**

- vii. During the coming reporting period, the principal work activities within the site included:
  - Construction of Wet Well Chamber
- viii. Potential environmental impacts due to the construction activities, including air quality, noise, water quality, waste, landscape and visual, will be monitored or reviewed. The ET will continue to implement the environmental monitoring & audit programme in accordance with the EM&A Manual and Environmental Permit requirements. The recommended environmental mitigation measures shall be implemented on site and regular inspections as required will be carried out to ensure that the environmental conditions are acceptable.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Fax : mcl@fugro.com Hong Kong Email



#### 1. INTRODUCTION

#### 1.1 **Background**

- Contract No. DC/2014/01 - Castle Peak Road Trunk Sewer and Tuen Mun Village Sewerage ("the Project") includes the construction of a sewage pumping station at Lok Chui Street near Castle Peak Villas as shown in Figure 1.
- The environmental impact assessment (EIA) report (Tuen Mun Sewerage Eastern Coastal Sewerage Extension) - EIA Report (Register No. AEIAR-034/2000) for the Project was approved by Environmental Protection Department (EPD) dated 7 June 2000. The EIA Report involves the construction of four sewage pumping stations at Tai Lam Chung Tsuen, Luen On San Tsuen, Tai Lam Valley and Lok Chui Street near Castle Peak Villas. The scope of this EM&A Manual focuses on the Sewage Pumping Station at Lok Chui Street near Castle Peak Villas in the EIA Report. The Project is designated under Schedule 2, section F3(b) and Q1 of the Environmental Impact Assessment Ordinance (EIAO). EPD subsequently issued the Environmental Permit (EP) EP- 068/2000 on 25 July 2000.
- 1.1.3 A Register of Change to Environmental Permit was submitted to EPD to register any change to the conditions in the EP for adoption of the latest design of the Pumping Station at Lok Chui Street and justify that the latest changes would not violate the conditions as stated in the approved EIA Report and EP based on the latest engineering design information. A Variation of Environmental Permit (VEP) EP-068/2000/A was issued on 10 April 2015 and it is the current permit for the Project.
- 1.1.4 The amended EP (EP-068/2000/A) is the current permit for the Project.
- In accordance to EP-068/2000/A Condition 2.3 and 2.4, an updated EM&A Manual was duly certified by ETL and verified by IEC and submitted to EPD for approval on 18 January 2016.
- The construction phase and EM&A programme of the Project commenced on 29 February 2016.
- This is the 13th monthly EM&A Report which summaries the impact monitoring results and audit findings for the Project within the period from 1 March to 31 March 2017.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email: mcl@fugro.com



#### 1.2 **Project Organization**

1.2.1 The Project Organization structure is shown in **Appendix B**. The key personnel contact names and numbers are summarized in Table 1.1.

Contact Information of Key Personnel Table 1.1

Party	Position	Name	Telephone	Fax
Drainage Services Department, HKSAR (DSD)	Project Management	Ms. Winnie Ng	2594 7265	2827 8526
Engineer/Engineer's Representative	Resident Engineer	Ms. Jacqueline Chan	3127 5103	2441 1755
(AECOM)	Senior Inspector of Works	Mr. Raymond Au	3127 5160	2441 1755
Independent Environmental Checker (ANEWR)	Independent Environmental Checker	Mr. Adi Lee	2618 2836	3007 8648
Contractor	Site Agent	Mr. Alan Lo		
Contractor (SKLV)	Environmental Officer	Mr. Calvin Lam	2674 3888	2674 6688
Environmental Team (MCL)	Environmental Team Leader	Mr. Colin Yung	3565 4114	3565 4160

#### 1.3 **Construction Programme and Activities**

- 1.3.1 The construction phase of the Project under the EP commenced on 29 February 2016.
- The construction programme of the Project is shown in **Appendix A**. 1.3.2

#### 1.4 Works undertaken during the month

- 1.4.1 During this reporting period, the principal work activities within the site included:
  - Welding of capping plate
  - Construction of Wet Well Chamber
- 1.4.2 Illustrations of works undertaken during the reporting period are shown in **Table 1.2**:

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



Table 1.2 Works undertaken Illustrations





Welding of capping plate

Construction of Wet Well Chamber

#### 1.5 Status of Environmental Licences, Notification and Permits

1.5.1 A summary of the relevant permits, licences and/or notifications on environmental protection for this Contract is presented in Table 1.3.

Table 1.3 Status of Environmental Licences, Notification and Permits

Permit / Direction / License	Ref No	Valid From	Valid Till
Environmental Permit	EP-068/2000/A	10/04/2015	N/A
Notification of Works Under APCO	391923	06/08/2015	N/A
Wastewater Discharge Licence	WT00022654-2015	23/10/2015	31/10/2020
Registration as a Chemical Waste Producer	5111-421-S3879-01	02/09/2015	N/A
Billing Account for Disposal of Construction Waste	7022922	06/08/2015	N/A

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

Profit Industrial Building, Tel : (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



### 2. AIR QUALITY

## 2.1 Monitoring Requirement

2.1.1 In accordance with the updated EM&A Manual, for regular impact monitoring, the sampling frequency of at least once per week shall be strictly observed at designated monitoring stations for 1-hr TSP monitoring using the direct reading method.

## 2.2 Monitoring Equipment and Detection Limits

- 2.2.1 The impact air quality (1-hr TSP) monitoring was performed using the portable TSP Monitors (Sibata Model LD-3B).
- 2.2.2 **Table 2.1** summarizes the detail of monitoring equipment and detection limits:

Table 2.1 Air Quality Monitoring Equipment

Item	Equipment	Model Number	Serial Number	Measuring accuracy	Measuring range
1	Portable TSP	Sibata Model	2Z6243	±10% of calibrated	0.001 –
2	Monitor	LD-3B	2Z6244	particles	10.00mg/m <sup>3</sup>

## 2.3 Monitoring Parameters, Frequency and Duration

2.3.1 **Table 2.2** summarizes the monitoring parameters, monitoring duration and frequencies of air quality monitoring.

Table 2.2 Monitoring Parameters, Frequency and Duration of Air Quality Monitoring

Parameter	Duration	Frequency
1-hr TSP	1 hour	At least 3 times in every 6 days

## 2.4 Monitoring Locations

2.4.1 In accordance with the updated EM&A Manual, two designated air quality monitoring stations, LC6a and LC9 are selected for the Project Area of constructing a sewage pumping station at Lok Chui Street near Castle Peak Villas as they are the representative air sensitive receivers located near to the Project site. All designated air quality monitoring stations listed in the updated EM&A Manual and the air quality monitoring stations are shown in Table 2.3 and the monitoring locations are shown in Figure 2.

Table 2.3 Air Quality Monitoring Locations

Monitoring Station	Location
LC6a	The Castle Bay
LC9	Castle Peak Villas Block C

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Fax Email: mcl@fugro.com Hong Kong.



#### 2.5 Monitoring Methodology and QA/QC Procedures

- 2.5.1 The measuring procedures of the 1-hr dust meter are in accordance with the Manufacturer's instruction Manual as follows:
  - Pull up the air sampling inlet cover
  - Change the Mode 0 to BG with once
  - Push Start/Stop switch once
  - Turn the knob to SENSI.ADJ and press it
  - Push Start/Stop switch once
  - Return the knob to the position MEASURE slowly
  - Push the timer set switch to set measuring time
  - Remove the cap and make a measurement

## Maintenance / Calibration

2.5.2 The portable TSP Monitors should be calibrated at 1 year intervals, Current calibration certificates are given in Appendix D.

#### 2.6 **Results and Observations**

- 2.6.1 The schedule of air quality monitoring and data recovery schedule in reporting period is provided in Appendix E.
- 2.6.2 The weather conditions during the monitoring are provided in **Appendix L**.
- The monitoring data of 1-hr TSP are summarized in **Table 2.4**. Detailed monitoring data are presented in Appendix F.

Table2.4 Summary of 1-hr TSP Monitoring Results

Monitoring Station	Average (µg/m³)	Range (µg/ m³)	Action Level (µg/ m³)	Limit Level (µg/ m³)
LC6a	67	39-101	344	500
LC9	62	45-85	335	500

- 2.6.4 The adopted Action and Limit Levels for air quality impact monitoring are presented in Appendix C.
- 2.6.5 The Event and Action Plan for air quality is given in **Appendix J**.
- No Action or Limit Level Exceedance of 1-hr TSP monitoring was recorded in the 2.6.6 reporting period.

## Other factor influencing the monitoring results

There were no other noticeable external factors generally affecting the monitoring results in this reporting period.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Fax

: (852)-24508238 : (852)-24508032 : mcl@fugro.com Hong Kong Email



#### 3. NOISE

#### 3.1 **Monitoring Requirement**

In accordance with the updated EM&A Manual, Leg (30min) monitoring is conducted for at least once a week during the construction phase between 0700 and 1900 on normal weekdays at the designated monitoring locations.

#### 3.2 **Monitoring Equipment and Detection Limits**

- The sound level meter used in noise monitoring will comply with the International 3.2.1 Electrotechnical Commission Publication (IEC) 651:1979 (Type 1) and 804:1985 (Type 1) specifications as referred to in the Technical Memorandum issued under the Noise Control Ordinance (NCO).
- Sound level calibrator will be used for the on-site calibration of the meter. This calibrator complies with the IEC Publication 942 (1988) Class 1 and ANSI S1.40 - 1984. Noise measurements were only accepted to be valid if the calibration levels from before and after the measurement agree to within 1.0dB.
- 3.2.3 Measurements shall be recorded to the nearest 1dB(A). This noise monitors are programmed to measure A-weighted equivalent continuous sound pressure level at 30minute intervals between 0700 and 1900 during the daytime. The noise measurement shall be carried out at each of the designated monitoring stations closest to the areas of active construction works once every week.
  - **Table 3.1** summarizes the detail of monitoring equipment and detection limits:

Table 3.1 Noise Monitoring Equipment

Item	Equipment	Model Number	Serial Number	Measuring accuracy	Measuring range
1	Integrating Sound Level Meter	Casella CEL- 63X Series	2451083	N.A	20-140 dB
2	Calibrator	Casella CEL- 120/1	3321858	±0.1dB	94/114 dB
3	Wind Speed Anemometer	Smart Sensor AR816+	N.A	±5%	0-30m/s

#### 3.3 **Monitoring Parameters and Frequency**

3.3.1 **Table 3.2** presents the noise monitoring parameters and frequencies.

Table3.2 Monitoring Parameters and Frequencies of Noise Monitoring

Monitoring Stations	Parameter	Frequency and Period
LC6a & LC9	LAeq (30min)  L10 and L90 will be recorded for reference	At each station at 0700-1900 hours on normal weekdays at a frequency of once a week

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Fax : mcl@fugro.com Hong Kong. Email



#### 3.4 **Monitoring Locations**

3.4.1 Noise monitoring were conducted at two designated monitoring stations as described in **Table 3.3** and the monitoring locations are shown in **Figure 2**.

Table 3.3 Location of noise monitoring station

Monitoring Station	Location
LC6a <sup>1</sup>	The Castle Bay
LC9	Castle Peak Villas Block C

### Note:

The measurement of sound level is carried out at the fence wall outside the building of the sensitive receiver, a correction should be made to the measured level during impact monitoring in order to represent the actual sound level at the sensitive receiver building façade (Block E6, The Castle Bay).

#### 3.5 Monitoring Methodology and QA/QC Procedures

- 3.5.1 The monitoring procedures are as follows:
  - Monitoring Stations:
    - LC6a: The monitoring station was set at a point 1m from the exterior of the sensitive receiver fence wall and set at a position 1.2m above the ground. Façade measurement is carried out for noise monitoring.
    - LC9: The monitoring station was set at the top of parapet wall of sensitive receivers building and the noise monitoring station is set at a point 1m from the exterior of the sensitive receivers building facade and set at a position 5m above
  - The battery condition was checked to ensure good functioning of the meter.
  - Parameters such as frequency weighting, the time weighting and the measurement time was set as follows:
    - frequency weighting : A
    - time weighting : Fast
    - measurement time: Leq (30min) was used as the monitoring parameter for the time period between 0700 - 1900 hours on normal weekdays. For all other time periods, Leq (5min) was recorded.
  - Prior to and after noise measurement, the meter was calibrated using the calibrator for 94.0 dB at 1000 Hz. If the difference in the calibration level before and after measurement is more than 1.0 dB, the measurement will be considered invalid and repeat of noise measurement is required after re-calibration or repair of the equipment.
  - The wind speed at the monitoring station was checked with the portable wind meter. Noise monitoring should be cancelled in the presence of fog, rain, and wind with a steady speed exceeding 5 m/s, or wind with gusts exceeding 10 m/s.

### Maintenance / Calibration

- 3.5.2 Maintenance and Calibration procedures are as follows:
  - The microphone head of the sound level meter and calibrator should be cleaned with a soft cloth at quarterly intervals.
  - The sound level meter and calibrator should be calibrated annually by a HOKLAS laboratory.
  - Relevant calibration certificates are provided in **Appendix D**.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



#### 3.6 **Results and Observations**

- 3.6.1 The schedule of noise monitoring and data recovery schedule in reporting period is provided in Appendix E.
- 3.6.2 The weather conditions during the monitoring period are provided in **Appendix L**.
- The noise monitoring data are summarized in Table 3.4. Detailed monitoring data are 3.6.3 presented in Appendix G.

Table 3.4 Summary of Noise Impact Monitoring Results

Monitoring	Leq <sub>(30min)</sub> Range, dB(A)		Leq (30min)	
Station	Measured	Corrected	Limit Level, dB(A)	
LC6a <sup>1</sup>	63-73	58-68	75	
LC9	62-70	N.A	75	

## Note:

- Leq (30min) was measured at day-time (0700-1900) on normal weekdays.
- 1) A distance correction of -5dB(A) has been applied in monitoring data of LC6a according to baseline monitoring report (Appendix G).
- 3.6.4 The adopted Action and Limit Levels for noise impact monitoring are presented in Appendix C.
- 3.6.5 The Event and Action Plan for noise is given in **Appendix J**.
- 3.6.6 No Action or Limit Level Exceedance of noise monitoring was recorded in the reporting period.

## Other factor influencing the monitoring results

3.6.7 There were no other noticeable external factors generally affecting the monitoring results in this reporting period.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Fax Hong Kong. Email: mcl@fugro.com



#### 4. LANDSCAPE AND VISUAL

#### 4.1 **Audit Requirements**

4.1.1 In accordance with the updated EM&A Manual, the landscape and visual mitigation measures during the construction phase are audited by a Landscape Architect, as a member of the ET, on a regular basis to ensure compliance with the intended aims of the measures. Site inspections are undertaken at least once every two weeks throughout the construction period and once every two months during the operational phase to ensure compliance with the intended aims of the measures.

#### 4.2 **Results and Observations**

- 4.2.1 Site audits were carried out to monitor and audit the implementation of landscape and visual mitigation measures. The summary of the site audits are given in Appendix I.
- 4.2.2 Should non-compliance of the landscape and visual impact occur, action in accordance to the event action plan presented in **Appendix J** shall be carried out.
- 4.2.3 No non-compliance of the landscape and visual impact was recorded in the reporting month.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



#### 5. **ENVIRONMENTAL SITE INSPECTION AND AUDIT**

#### 5.1 **Site Inspection**

- 5.1.1 Weekly site inspections and bi-weekly landscape and visual impact inspections were carried out to monitor the implementation of proper environmental pollution control and mitigation measures for the Project.
- In the reporting period, site inspections were carried out on 2, 10, 16, 23 and 30 March 2017 and the landscape and visual impact inspections were carried out on 9 and 24 March 2017.
- 5.1.3 The summary of the site audits are given in **Appendix I**.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



#### 6. Advice on the Solid and Liquid Waste Management status

- The Contractor has been registered as a chemical waste producer for the Project. Construction and demolition (C&D) material sorting was carried out on site. Receptacles were available for general refuse collection.
- As advised by the Contractor, 910m<sup>3</sup> of C&D waste was generated and 0m<sup>3</sup> general refuse were generated in the reporting period. Monthly summary of waste flow table is detailed in Appendix M.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email: mcl@fugro.com



#### 7. **ENVIRONMENTAL COMPLAINT AND NON-COMPLIANCE**

#### 7.1 **Environmental Exceedance**

- 7.1.1 No Action or Limit Level Exceedance of 1-hr TSP monitoring was recorded in the reporting period.
- 7.1.2 No Action or Limit Level Exceedance of noise monitoring was recorded in the reporting period.

#### 7.2 Complaints, Notification of Summons and Successful Prosecution

- 7.2.1 No complaints, notification of summons or successful prosecutions were received in the reporting period.
- 7.2.2 Cumulative complaint log, summaries of complaints, notification of summons and successful prosecutions are presented in Appendix H.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



#### 8. IMPLEMENTATION STATUS OF ENVIRONMENTAL MITIGATION MEASURES

#### 8.1 **Implementation Status**

The Contractor has implemented environmental mitigation measures and requirements as 8.1.1 stated in the EIA Reports, the EP and the EM&A Manuals. The implementation status of the mitigation measures during the reporting period is summarized in **Appendix K**.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Fax Hong Kong. Email: mcl@fugro.com



#### 9. **FUTURE KEY ISSUES**

#### 9.1 **Construction Works for the Coming Month**

- 9.1.1 During the coming reporting period, the principal work activities within the site included:
  - Construction of Wet Well Chamber

#### 9.2 **Key Issues for the Coming Month**

- 9.2.1 Potential environmental impacts due to the construction activities, including air quality, noise, water quality, waste, landscape and visual, will be monitored or reviewed. The ET will continue to implement the environmental monitoring & audit programme in accordance with the EM&A Manual and Environmental Permit requirement. The recommended environmental mitigation measures shall be implemented on site and regular inspections as required will be carried out to ensure that the environmental conditions are acceptable.
- The anticipated impact of principal work activities within the site and the recommended 9.2.2 mitigation measures are shown in **Appendix N**.

#### 9.3 **Monitoring Schedules for the Coming Months**

9.3.1 The tentative schedules for environmental monitoring in the coming months are provided in Appendix E.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



#### 10. **CONCLUSIONS**

- 10.1.1 The construction phase and EM&A programme of the Project commenced on 29 February 2016.
- 10.1.2 No Action or Limit Level Exceedance of 1-hr TSP monitoring was recorded in the reporting period.
- 10.1.3 No Action or Limit Level Exceedance of noise monitoring was recorded in the reporting period.
- 10.1.4 In the reporting period, site inspections were carried out on 2, 10, 16, 23 and 30 March 2017 and the landscape and visual impact inspections were carried out on 9 and 24 March
- 10.1.5 No complaints, notification of summons or successful prosecutions were received in the reporting period.


Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



Figure 1

**Project General Layout** 



Location of the Proposed Sewage Pumping Station at Lok Chui Street near Castle Peak Villas 位於樂翠街近青山別墅的擬建污水泵水站

Figure 1


Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Figure 2

**Air and Noise Monitoring Locations** 



Room 723 & 725, 7/F, Block B, Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong,

Hong Kong.

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com **MateriaLab** 

## LC6a: The Castle Bay



## LC9: Castle Peak Villas Block C



#### Note:

- 1) LC6a: The air and noise monitoring station is set at a point 1m from the exterior of the sensitive receiver fence wall, and set at a position 1.2m above ground. Façade measurement will be carried out for noise monitoring.
- 2) LC9: The air monitoring station is set at the top of parapet wall of sensitive receivers building and the noise monitoring station is set at a point 1m from the exterior of the sensitive receivers building façade and set at a position 5m above the ground.

Legend: Prop

Proposed Air Monitoring Location

Proposed Noise Monitoring Location

1m from the exterior building façade


Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Appendix A

**Construction Programme** 



Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com




## Appendix B

**Project Organization Chart** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com





### Remark:

# The Landscape Architect with a minimum of 1-2 years on site experience as a member of the ET to monitor and audit the landscaping installation works and landscape protection measures.

Legend:			
	Line of Reporting		
	Line of Communication		

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Appendix C

Action and Limit Levels for Air Quality and Noise

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



**Action and Limit Levels for Air Quality** 

Parameter	Monitoring Station	Action Level (µg/m³)	Limit Level (µg/ m³)
1-hr TSP	LC6a	344	500
(µg/m³)	LC9	335	500

## **Action and Limit Levels for Construction Noise**

Time Period	Location	Action	Limit
0700-1900 hrs on normal weekdays	LC6a LC9	When one documented complaint is received	75* dB(A)

<sup>\*</sup> reduce to 70 dB(A) for schools and 65 dB(A) during school examination periods.

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Appendix D

**Calibration Certificates of Monitoring Equipment** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

: (852)-24508238 : (852)-24508032 Fax Email : mcl@fugro.com



### FUGRO TECHNICAL SERVICES LIMITED

Fugro Development Centre. 5 Lok Yi Street, Tai Lam, Tuen Mun, N.T., Hong Kong.

: +852 2450 8233 Tel +852 2450 6138 : matlab@fugro.com E-mail Website: www.materialab.com



Report no.: 940891CA161364(2) Page 1 of 1

## CALIBRATION CERTIFICATE OF DUST METER

Client : Fugro Technical Services Limited

Project : Calibration Services

### **Client Supplied Information**

Details of Unit Under Test, UUT

Description : Laser Dust Monitor

: SIBATA

Manufacturer Model No.

: LD-3B

Serial No.

: 2Z6243

Specification Limit

: NA

Next Calibration Date : 23-May-2017

## **Laboratory Information**

Description

: Reference balance

Equipment ID.

: R-039-10

Date of Calibration : 24-May-2016

Ambient Temperature : 28 °C

Calibration Location : Calibration Lab. of MateriaLab

Method Used

: By direct comparison the weight of dust particle trapped in a filter paper using high volume sampler (TSP method) for a certain period, with the reading of the UUT. They should be placed at the same location and powered on and off at the same time.

Reference concentration (mg/m³)	Total count for 1 hour	CPM (Count per minute)
0.0778	3541	59.02
0.0683	2785	46.42
0.0661	2717	45.28

### Remarks:

1. The equipment being used in this calibration is traceable to recognized National Standards.

2. The interpolation equation : Concentration  $(mg/m^3) = K \times UUT$  reading (CPM) where K = 0.001408

3. Correlation coefficient (r):

0.9943

Date: TV 6 2016 Certified by:

28 JUN 2016

Kwok Chi Wa (Assistant Manager) CA-R-297 (22/07/2009)

\*\* End of Report \*\*

The copyright of this document is owned by Fugro Technical Services Limited. It may not be reproduced except with prior written approval from the Company

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

: (852)-24508238 : (852)-24508032 Fax Email : mcl@fugro.com



### FUGRO TECHNICAL SERVICES LIMITED

Fugro Development Centre, 5 Lok Yî Street, Tai Lam, Tuen Mun, N.T., Hong Kong.

: +852 2450 8233 Tel +852 2450 6138 E-mail : matlab@fugro.com Website: www.materialab.com



Report no.: 940891CA161364(4)

Page 1 of 1

### **CALIBRATION CERTIFICATE OF DUST METER**

Client : Fugro Technical Services Limited

Project : Calibration Services

### **Client Supplied Information**

Details of Unit Under Test, UUT

Description

: Laser Dust Monitor

Manufacturer

: SIBATA

Model No.

: LD-3B

Serial No.

: 2Z6244

Specification Limit

: NA

Next Calibration Date : 23-May-2017

### **Laboratory Information**

Description

: Reference balance

Equipment ID.

: R-039-10

Date of Calibration : 24-May-2016

Ambient Temperature : 28 °C

Calibration Location : Calibration Lab. of MateriaLab

Method Used

: By direct comparison the weight of dust particle trapped in a filter paper using high volume sampler (TSP method) for a certain period, with the reading of the UUT. They

should be placed at the same location and powered on and off at the same time.

### Calibration Results

Reference concentration (mg/m³)	Total count for 1 hour	CPM (Count per minute)
0.0778	3423	57.05
0.0683	2864	47.73
0.0661	2820	47.00

### Remarks:

1. The equipment being used in this calibration is traceable to recognized National Standards.

2. The interpolation equation : Concentration  $(mg/m^3) = K \times UUT$  reading (CPM) where K = 0.001398

3. Correlation coefficient (r):

0.9933

CA-R-297 (22/07/2009)

Date : 6 6 2016 Certified by :

\*\* End of Report \*\*

The copyright of this document is owned by Fugro Technical Services Limited. It may not be reproduced except with prior written approval from the Company

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong,

Hong Kong.

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



### FUGRO TECHNICAL SERVICES LIMITED

Fugro Development Centre, 5 Lok Yi Street, Tai Lam, Tuen Mun, N.T., Hong Kong. Tel :+852 2450 8233
Fax :+852 2450 6138
E-mail : matlab@fugro.com
Website : www.materialab.com,hk



Report no.: 161966CA161737

Page 1 of 1

### CALIBRATION CERTIFICATE OF SOUND LEVEL METER

Client: Materialab Consultants Ltd.

Project : Calibration Services Client Supplied Information Details of Unit Under Test, UUT

Description

: Sound Level Meter

Manufacturer

: Casella (Model no. CEL-63X(meter), CEL-251(microphone), CEL-495(Preamplifier))

Serial No.

: 2451083 (meter), 01361(microphone), 002845 (Preamplifier))

Next Calibration Date : 23-Aug-2017

Specification Limit :

: EN 61672: 2003 Type 1

### Laboratory Information

Description

: B & K Acoustic Multifunction Calibrator 4226 (Traditional free field setting)

Equipment ID. : R-108-1

Date of Calibration :

24-Aug-2016

Ambient Temperature: 21 °C

Calibration Location: Calibration Laboratory of MateriaLab

Method Used : By direct comparison

## Calibration Results :

Parameters		Mean Value (dB)	Specification Limit(dB)		
	4000Hz	0.6	2.6	to	-0.6
	2000Hz	0.5	2.8	to	-0.4
	1000Hz	0.0	1.1	to	-1.1
A-weighing frequency response	500Hz	-3.0	-1.8	to	-4.6
	250Hz	-8.3	-7.2	to	-10.0
	125Hz	-15.7	-14.6	to	-17.6
	63Hz	-25.7	-24.7	to	-27.7
	31.5Hz	-37.4	-37.4	to	-41.4
Differential level linearity	94dB-104dB	0.0		± 0.€	3
	104dB-114dB	0.0		± 0.6	3

### Remarks:

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. For calibration: Reference SPL are 94, 104 & 114dB, range setting is 20-140dB & time weighing is fast
- 4. The equipment does compty with EN 61672: 2003 Type 1 sound level meter for the above measurement.

Date: A & 2016 Certified by

by: \_\_\_\_\_ Date : Chan Chun Wai (Manager) /

1. 1. L. Dil

Kwok Chi Wa (Assistant Manager)

\*\* End of Report \*\*

The copyright of this document is owned by Fugro Technical Services Limited. It may not be reproduced except with prior written approval from the Company.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong,

Hong Kong.

: (852)-24508238 : (852)-24508032 Fax Email : mcl@fugro.com



### **FUGRO TECHNICAL SERVICES LIMITED**

Fugro Development Centre, 5 Lok Yi Street, Tai Lam, Tuen Mun, N.T., Hong Kong.

Tel : +852 2450 8233 Fax : +852 2450 6138 E-mail: matlab@fugro.com Website: www.materialab.com.hk



Report no.: 161966CA162202(1)

Page 1 of 1

## CALIBRATION CERTIFICATE OF SOUND CALIBRATOR

### Client Supplied Information

Client: Materialab Consultants Ltd.

Address: Room 723 & 725, 7/F., Block B Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Chung, N.T.

Project : Calibration Services

Details of Unit Under Test, UUT

Description

: Sound Calibrator

Manufacturer

: Casella (Model no. CEL-120/1)

Serial No.

: 3321858

Next Calibration Date : 31-Oct-2017

Specification Limit

: ±0.5dB

### Laboratory Information

Description

Reference Sound level meter

Equipment ID. : Date of Calibration:

R-119-1

Ambient Temperature: 22 °C

Calibration Location: Calibration Laboratory of MateriaLab

Method Used

By direct comparison

01-Nov-2016

### Calibration Results:

Parameters (Setting of UUT)	Mean Value (error of measurement)	Specification Limit(dB)
94dB	-0.3 dB	10.54D
114dB	-0.2 dB	±0.5dB

### Remarks:

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. The equipment does comply with the specification limit.

Checked by:

Date: 3-11-2000 Certified by:

CA-R-297 (22/07/2009)

\*\* End of Report \*\*

The copyright of this document is owned by Fugro Technical Services Limited. It may not be reproduced except with prior written approval from the Company

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Appendix E

**Environmental Monitoring and Data Recovery Schedule** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



# Project: Sewage Pumping Stations at Tai Lam Chung Tsuen Luen On San Tsuen, Tai Lam Valley and Lok Chui Street near Castle Peak Villas under the scope of "Tuen Mun Sewerage – Eastern Coastal Sewerage Extension" – DC/2014/01

Impact Monitoring Schedule (March 2017)

Sun	Mon	Tue	Wed	Thur	Fri	Sat
			1	2	3 A & N Impact Monitoring	4
5	6	7	8	9 A & N Impact Monitoring	10	11
12	13	14	15 A & N Impact Monitoring	16	17	18
19	20	21 A & N Impact Monitoring	22	23	24	25
26	27 A & N Impact Monitoring	28	29	30	31	

#### Remarks

- 1. A: 1-hr TSP monitoring at LC6a and LC9.
- 2. N: Noise monitoring at LC6a and LC9.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

Profit Industrial Building, Tel 1-15 Kwai Fung Crescent, Kwai Fong, Fa: Hong Kong. Em

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



## **DATA RECOVERY SCHEDULE**

	Air Quality Monitoring Noise Monitoring					
Date	Monitorin	g Station*	Monitoring Station*			
Date	1-hr		LAeq	(30min)		
	LC6a	LC9	LC6a	LC9		
1						
2	,			,		
3	$\sqrt{}$	√	√	$\sqrt{}$		
4						
5						
6						
7						
8						
9	$\sqrt{}$	V	$\sqrt{}$	V		
10						
11						
12						
13						
14						
15	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$		
16						
17						
18						
19						
20						
21	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$		
22						
23						
24						
25						
26						
27	$\sqrt{}$	V	$\sqrt{}$	V		
28						
29						
30						
31						
% of R	100	100	100	100		

<sup>\*</sup> Remark type of parameters

 $\% \ of \ R \quad The \ percentage \ of \ Data \ Recovery \ is \ the \ actual \ monitoring \ over \ the \ scheduled \ monitoring$ 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508032 Hong Kong.

Email : mcl@fugro.com



## **Project:** Sewage Pumping Stations at Tai Lam Chung Tsuen Luen On San Tsuen, Tai Lam Valley and Lok Chui Street near Castle Peak Villas under the scope of "Tuen Mun Sewerage - Eastern Coastal Sewerage Extension" - DC/2014/01

Tentative Impact Monitoring Schedule (April 2017)

Sun	Mon	Tue	Wed	Thur	Fri	Sat
						1 A & N Impact Monitoring
2	3	4	5	6	7 A & N Impact Monitoring	8
9	10	11	12	13 A & N Impact Monitoring	14	15
16	17	18	19 A & N Impact Monitoring	20	21	22
23	24	25 A & N Impact Monitoring	26	27	28	29 A & N Impact Monitoring
30						

#### Remarks

- 1. A: 1-hr TSP monitoring at LC6a and LC9.
- N: Noise monitoring at LC6a and LC9.
- 3. Actual monitoring schedule may be subjected to change due to any safety concern or adverse weather condition.

The copyright of this document is owned by MateriaLab Consultants Ltd. It may not be reproduced except with prior written approval from the Company.

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Appendix F

**Air Quality Monitoring Data and Graphical Presentations** 

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



LC6a The Castle Bay

	1-hour TSP (μg/m³)							
Date	Start Time	1st hr	2nd hr	3rd hr	Weather			
03-Mar-17	13:50	48	55	57	Fine			
09-Mar-17	14:12	51	54	51	Cloudy			
15-Mar-17	13:00	60	39	48	Cloudy			
21-Mar-17	13:35	85	78	83	Fine			
27-Mar-17	08:35	97	101	94	Fine			
	Average		67					
	Max		101					
	Min		39					


## LC9 Castle Peak Villas Block C


LUS Castie	LC9 Castle Feak Villas Block C							
	1-hour TSP (μg/m³)							
Date	Start Time	1st hr	2nd hr	3rd hr	Weather			
03-Mar-17	14:00	52	48	53	Fine			
09-Mar-17	14:19	56	59	48	Cloudy			
15-Mar-17	13:10	50	49	45	Cloudy			
21-Mar-17	13:48	76	80	73	Fine			
27-Mar-17	08:46	78	85	80	Fine			
	Average		62					
	Max		85					
	Min		45					

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com







#### Note:

- The QA/QC procedures and detection Limits refer to section 2.2 and 2.5.
- The other factors influencing the monitoring results refer to section 2.7.

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



# Appendix G

**Noise Monitoring Data and Graphical Presentations** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



**LC6a The Castle Bay** 

Date	Start Time	L <sub>eq</sub> 30min dB(A)	Corrected L <sub>eq</sub> 30min dB(A) <sup>1</sup>	L <sub>90</sub> dB(A)	L <sub>10</sub> dB(A)	Weather
03-Mar-17	15:00	71	66	67	72	Fine
09-Mar-17	15:00	73	68	64	74	Cloudy
15-Mar-17	13:30	65	60	57	66	Cloudy
21-Mar-17	14:33	63	58	52	66	Fine
27-Mar-17	09:36	64	59	57	63	Fine

#### Note:

# LC9 Castle Peak Villas Block C


Date	Start Time	L <sub>eq</sub> 30min dB(A)	Corrected L <sub>eq</sub> 30min dB(A)	L <sub>90</sub> dB(A)	L <sub>10</sub> dB(A)	Weather
03-Mar-17	14:15	67	N.A	64	70	Cloudy
09-Mar-17	14:21	70	N.A	65	72	Cloudy
15-Mar-17	14:17	64	N.A	58	66	Cloudy
21-Mar-17	13:50	62	N.A	57	65	Fine
27-Mar-17	08:48	65	N.A	60	68	Fine


<sup>1)</sup> A distance correction of -5dB(A) has been applied in monitoring data of LC6a according to baseline monitoring report (Appendix G).

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com







#### Note:

- The QA/QC procedures and detection Limits refer to section 3.2 and 3.5.
- The other factors influencing the monitoring results refer to section 3.7.

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



## Appendix H

**Cumulative Statistics on Exceedances, Complaints, Notifications of Summons and Successful Prosecutions** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



**Environmental Complaints Log** 

Complaint Log No.	Date of Receipt	Received From and Received By	Nature of Complaint	Date Investigated	Outcome	Date of Reply
Nil	-	-	-	-	-	-

**Cumulative Statistics on Complaints** 

Environmental Parameters	Cumulative No. Brought Forward	No. of Complaints This Month	Cumulative Project-to-Date	
Air	0	0	0	
Noise	0	0	0	
Water	0	0	0	
Waste	0	0	0	
Total	0	0	0	

## **Cumulative Statistics on Notifications of Summons and Successful Prosecutions**

Environmental Parameters	Cumulative No. Brought Forward	No. of Prosecutions This Month	Cumulative Project-to-Date
Air	0	0	0
Noise	0	0	0
Water	0	0	0
Waste	0	0	0
Total	0	0	0

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Appendix I

**Site Audit Summary** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong,

: (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



# **Summary of Site Audit**

Inspection Date	Observation/ Comment	Follow Up Action	Completion Date
16/03/2017	Stockpile was observed without covering.	The Contractor should spray with water regularly during the construction work or cover the stockpile with tarpaulin sheet to prevent dust nuisance to the surrounding.	23 Mar 2017
	Generator was not provided with drip tray.	The Contractor should provide drip tray with the generator to prevent chemical leakage and cause land contamination.	23 Mar 2017
23/03/2017	No drip trays provided beneath the diesel drums on site.	The Contractor should place these drums onto drip trays.	30 Mar 2017
Landscape and	Visual Impact Inspection		
09/03/2017	Tree inspection report and Form 2 of the dead trees, LC-TC03 (R), LC-TC04 (R) and LC-TC06, have been prepared by tree specialist and have noticed AECOM and ET.	Tree specialist/ Site safety staff should continue to monitor the risk of falling before tree felling is completed. Trunks should be stabilized with external support.	ASAP
	Broken twigs, 30% dieback and yellow leaves were found on LC-TC07	Tree health and soil condition should be assessed by tree specialist with follow up treatment.	ASAP
	Trunks of the dead trees LC-TC03 (R), LC-TC04 (R) and LC-TC06 should be stabilized with external support before tree felling is completed.	Tree specialist/ Site safety staff should continue to monitor the risk of falling.	ASAP
24/03/2017	Broken twigs, 30% dieback and yellow leaves were found on LC-TC07. It was infected by Icerya aegyptiaca (介殼蟲)	Tree health and soil condition should be assessed by tree specialist with follow up treatment	ASAP
	5% yellow leaves were found on T0489(R), T0490(R). They were infected by Icerya aegyptiaca (介殼蟲)	Tree health and soil condition should be assessed by tree specialist with follow up treatment	ASAP

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



## Appendix J

**Events and Action Plans** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 : (852)-24508032 Tel 1-15 Kwai Fung Crescent, Kwai Fong, Fax Hong Kong. Email : mcl@fugro.com



**Event / Action Plan for Air Quality** 

Event / Action Plan for Air Quality  ACTION						
EVENT	ET	IEC	ER Contractor			
Action Level Exceedance for one sample.	Identify the source. Inform the IEC and the ER. Repeat measurement to confirm finding. Increase monitoring frequency to daily.	Check monitoring data submitted by the ET.     Check Contractor's working method.	Notify Contractor.	Rectify any unacceptable practice.     Amend working methods if appropriate.		
Exceedance for two or more consecutive samples.	Identify the source. Inform the IEC and the ER. Repeat measurements to confirm findings. Increase monitoring frequency to daily. Discuss with the IEC and the Contractor on remedial actions required. If exceedance continues, arrange meeting with the IEC and the ER. If exceedance stops, cease additional monitoring.	Check monitoring data submitted by the ET. Check the Contractor's working method. Discuss with the ET and the Contractor on possible remedial measures. Advise the ER on the effectiveness of the proposed remedial measures. Supervisor implementation of remedial measures.	Confirm receipt of notification of failure in writing.     Notify the Contractor.     Ensure remedial measures properly implemented.	Submit proposals for remedial actions to IEC within 3 working days of notification.     Implement the agreed proposals.     Amend proposal if appropriate.		
Limit Level	· ·	<u> </u>	<u>.                                    </u>	<u> </u>		
Exceedance for one sample.	Identify the source. Inform the ER and the DEP. Repeat measurement to confirm finding. Increase monitoring frequency to daily. Assess effectiveness of Contractor's remedial actions and keep the IEC, the DEP and the ER informed of the results.	Check monitoring data submitted by the ET. Check Contractor's working method. Discuss with the ET and the Contractor on possible remedial measures. Advise the ER on the effectiveness of the proposed remedial measures. Supervisor implementation of remedial measures.	Confirm receipt of notification of failure in writing.     Notify the Contractor.     Ensure remedial measures are properly implemented.	Take immediate action to avoid further exceedance. Submit proposals for remedial actions to IEC within 3 working days of notification. Implement the agreed proposals. Amend proposal if appropriate.		
Exceedance for two or more consecutive samples	Notify the IEC, the ER, the DEP and the Contractor. Identify the source. Repeat measurements to confirm findings. Increase monitoring frequency to daily. Carry out analysis of the Contractor's working procedures to determine possible mitigation to be implemented. Arrange meeting with the IEC and the ER to discuss the remedial actions to be taken. Assess effectiveness of the Contractor's remedial actions and keep the IEC, the DEP and the ER informed of the results. If exceedance stops, cease additional monitoring.	Discuss amongst the ER, ET and the Contractor on the potential remedial actions.     Review the Contractor's remedial actions whenever necessary to assure their effectiveness and advise the ER accordingly.     Supervise the implementation of remedial measures.	Confirm receipt of notification of failure in writing.     Notify the Contractor.     In consultation with the IEC, agree with the Contractor on the remedial measures to be implemented.     Ensure remedial measures are properly implemented.     If exceedance continues, consider what activity of the work is responsible and instruct the Contractor to stop that activity of work until the exceedance is abated.	Take immediate action to avoid further exceedance. Submit proposals for remedial actions to IEC within 3 working days of notification. Implement the agreed proposals. Resubmit proposals if problem still not under control. Stop the relevant activity of works as determined by the ER until the exceedance is abated.		

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Fax Hong Kong.

: (852)-24508238 : (852)-24508032 Email : mcl@fugro.com



## **Event / Action Plan for Construction Noise**

EV/ENT	Tan for Constructi			
EVENT	ET	IEC	ER	Contractor
Action Level	Notify the IEC and the Contractor. Carry out investigation. Report the results of investigation to the IEC and the Contractor. Discuss with the Contractor and formulate remedial measures. Increase monitoring frequency to check mitigation effectiveness.	Review the analysed results submitted by the ET.     Review the proposed remedial measures by the Contractor and advise the ER accordingly.     Supervise the implementation of remedial measures.	Confirm receipt of notification of failure in writing.     Notify the Contractor.     Require the Contractor to propose remedial measures for the analysed noise problem.     Ensure remedial measures are properly implemented.	Submit noise mitigation proposals to IEC     Implement noise mitigation proposals
Limit Level	Notify the IEC, the ER, the DEP and the Contractor. Identify the source. Repeat measurement to confirm findings. Increase monitoring frequency. Carry out analysis of Contractor's working procedures to determine possible mitigation to be implemented. Inform the IEC, the ER and the DEP the causes & actions taken for the exceedances. Assess effectiveness of the Contractor's remedial actions and keep the IEC, the DEP and the ER informed of the results. If exceedance stops, cease additional monitoring.	Discuss amongst the ER, the ET and the Contractor on the potential remedial actions.     Review the Contractor's remedial actions whenever necessary to assure their effectiveness and advise the ER accordingly.     Supervise the implementation of remedial measures.	Confirm receipt of notification of failure in writing. Notify the Contractor. Require the Contractor to propose remedial measures for the analysed noise problem. Ensure remedial measures are properly implemented. If exceedance continues, consider what activity of the work is responsible and instruct the Contractor to stop that activity of work until the exceedance is abated.	Take immediate action to avoid further exceedance. Submit proposals for remedial actions to IEC within 3 working days of notification. Implement the agreed proposals. Resubmit proposals if problem still not under control. Stop the relevant activity of works as determined by the ER until the exceedance is abated.

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 : (852)-24508032 Tel 1-15 Kwai Fung Crescent, Kwai Fong, Fax Hong Kong. Email : mcl@fugro.com



Event / Action Plan for Landscape and Visual Impact

EVENT	Plan for Landscape and Visual Impact ACTION					
ACTION LEVEL	ET	IEC	ER	Contractor		
Design Check	Check final design conforms to the requirements of EP and prepare report.	Check report.     Recommend remedial design if necessary	Undertake remedial design if necessary			
Nonconformity on one occasion	Identify Source Inform IEC and ER Discuss remedial actions with IEC, ER and Contractor Monitor remedial actions until rectification has been completed	Check report Check Contractor's working method Discuss with ET and Contractor on possible remedial measures Advise ER on effectiveness of proposed remedial measures. Check implementation of remedial measures	Notify Contractor     Ensure remedial measures are properly implemented	Amend working methods     Rectify damage and undertake any necessary replacement		
Repeated Nonconformity	Identify Source Inform IEC and ER Increase monitoring frequency Discuss remedial actions with IEC, ER and Contractor Monitor remedial actions until rectification has been completed If nonconformity stops, cease additional monitoring	Check monitoring report Check Contractor's working method Discuss with ET and Contractor on possible remedial measures Advise ER on effectiveness of proposed remedial measures Supervise implementation of remedial measures	Notify Contractor     Ensure remedial measures are properly implemented	Amend working methods     Rectify damage and undertake any necessary replacement		

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



# Appendix K

Implementation Status of **Environmental Mitigation Measures** 

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

**MateriaLab** 

**Air Quality** 

EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
4.5	Undertake all air pollution measures to prevent dust nuisance as a result of and during construction activities.	All unpaved haul roads, bulldozed material, exposed site areas / Throughout construction period	Contractor	TMEIA	*
4.5	No debris or other materials shall be burnt on the works areas.	All areas / Throughout construction period	Contractor	TMEIA. Avoid smoke impacts and disturbance	۸
4.5	Dust suppression measures shall be provided and to be submitted to and approved by the Engineer.	All areas / Throughout construction period	Contractor	TMEIA	۸
4.5	Stockpiles of imported material kept on site shall be contained within hoardings, dampened and/or covered during dry and windy weather.	All areas / Throughout construction period	Contractor	TMEIA Avoid dust generation	۸
4.5	Material stockpiled along side trenches should be covered with tarpaulins whenever works are within village boundaries.	All areas / Throughout construction period	Contractor	TMEIA Avoid dust generation / visual impacts	*
4.5	Water sprays shall be used during the delivery and handling of cement, sands aggregates and the like.	All areas / Throughout construction period	Contractor	TMEIA Avoid dust generation	۸
4.5	No batching of concrete should be carried out on site. Concrete should be used in ready mixed form and off loaded adjacent to designated works areas.	All areas / Throughout construction period	Contractor	TMEIA	٨

Room 723 & 725, 7/F, Block B, Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
4.5	Any vehicle used for moving cement, sands, aggregates and construction waste and the like shall have properly fitting side and tail boards. Materials shall not be loaded to a level higher than the side and tail boards, and shall be covered by a clean tarpaulin. The tarpaulin shall be properly secured and shall extend at least 300mm over the edges of the side and tail boards.	All areas / Throughout construction period	Contractor	TMEIA Avoid dust and spillage of material	^
4.5	No earth, mud, debris, dust and the like shall be deposited on public roads. Details of proposals for the wheel cleaning facilities shall be agreed with the Engineer. Such wheel washing facility shall be usable prior to any earthworks excavation activity on the Site.	All areas, particularly pumping station sites / Contractor Throughout construction period		TMEIA Avoid spread/ deposition of mud	^
4.6.9	Pumping station vent shafts should be located away from sensitive receivers.	All pumping stations	DSD	TMEIA Avoid odour impacts	N/A
4.6.18	Use a covered container to store and transport the screenings from the pump house.	All pumping stations /operational phase	DSD	TMEIA Avoid odour impacts	N/A
4.6.18	Undertake the collection of the screenings and transfer to the covered container within the confines of the pump house.	All pumping stations / operational phase	DSD	TMEIA Avoid odour impacts	N/A
11.2.8	EM&A in the form of 1 hour total suspended particulates monitoring once per week	All sensitive representative receivers / Throughout construction period	Contractor	EM&A Manual	۸

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



## **Noise**

EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
5.7.1 & 5.8.1	Ensure silencers are installed on the exhaust pipes of the trucks, excavators, compactors, concrete lorry mixer, and cranes for all activities.	All areas / Throughout construction period	Contractor	TMEIA	^
5.7.1 & 5.8.1	Use of mufflers on the breakers for all activities.	All areas / Throughout construction period Contractor		TMEIA	۸
5.7.1 & 5.8.1	Use of temporary noise barriers for all activities at the pumping station sites and during main sewer construction. During main sewer construction, barriers should be used to screen the activities of mobile equipment including the crane and excavator.	All pumping stations and main sewer construction locations / Throughout construction period	Contractor	TMEIA	٨
5.5.10	Use of temporary noise barriers for all activities in the villages, where there is at least a 5m clearance	Village sewer alignment / Throughout Contractor construction period		TMEIA	۸
5.8.6 & 5.9.6	Manual breaking of concrete, where the concrete is less than 50mm thick.	Sewer alignment construction / concrete breaking activities		TMEIA	N/A
5.8.6 & 5.9.6	Use of alternative pavement removal methods/equipment (kick ripper), where the concrete is less than 100mm thick	Sewer alignment construction / concrete breaking activities	Contractor	TMEIA	N/A

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

Tel : (852)-24508238 ng, Fax : (852)-24508032 Email : mcl@fugro.com



EIA Reference	Environmental Protection Measures	Location/ Timing	Location/ Timing Implementation Agent		Implementation Status in Construction Phase
5.8.6 & 5.9.6	Use of acoustic enclosure in place of a barrier where there is a 6m clearance.	Sewer alignment construction / Throughout construction period		TMEIA	^
5.8.6 & 5.9.6	Scheduling the numbers and operating times of equipment, when noise levels cannot be reduced to within the standards by other means	Sewer alignment construction / Throughout construction period		TMEIA	^
5.8.11	The construction activities should be carried out in the daytime period (08.00- 18.00) only and shall exclude Sundays and public holidays.	All areas	Contractor	TMEIA	^
5.8.11	Powered mechanical equipment shall not be used within 5m of an NSR without the permission of the Engineer	All areas / Throughout construction period	Contractor	TMEIA	۸
5.8.11	Carry out good site practice to limit noise emission at source.	All areas / Throughout construction period	Contractor	TMEIA	^
5.8.11	Avoid simultaneous noisy activities.	All areas / Throughout construction period	Contractor	TMEIA	۸
11.2.8	EM&A in the form of noise monitoring.	All representative receivers / Throughout construction period	Contractor	EM&A Manual	^

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



**Water Quality** 

EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
6.4.3	Stockpiles of excavated material should be kept to a minimum and covered during times of heavy rainfall.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	^
6.4.10	Pass any trench dewatering through a portable sand/silt removal traps prior to discharge.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	^
6.5.2	When works are carried out during the rainy season exposed slopes, stockpiles should be covered with tarpaulin and temporary access roads protected with a layer of gravel or crushed stone.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
りりと	Surface run off should be discharged to storm drains via sand/silt removal traps.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	^
6.5.2	Channels, bunds or sand bags should be used to direct any storm water to the traps and perimeter channels should be constructed before the main works begin to prevent external run off from crossing the site.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	^
6.5.2	Silt removal structures, channels and manholes should be maintained to remove accumulated material, specifically at the onset and end of rainy periods.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	^

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
6.5.2	Trenches for the sewer main should be dug and backfilled in short sections to minimise the quantities of rain water which will need to be pumped from them and upslope bunding provided to prevent surface water from flowing into the trenches.		Contractor	WPCO, TMEIA & ProPECC PN 1/94	٨
6.5.2	Rainwater pumped from the trenches should be discharged to storm drains via sand/silt removal traps.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
<b>にんり</b>	Discharges to natural water courses should only take place when the effluent can be shown to comply with the relevant specified standards.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94 & Technical Memorandum on Standards for Effluent Discharged in Drainage and Sewerage Systems, Inland and Coastal Waters	٨
6.5.3	All plant should be in proper working order and maintained such that there is no leakage of fuel or oil. Any waste oils should be collected in designated tanks prior to disposal off site.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	٨

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
6.5.3	All mechanical plant maintenance and refuelling areas shall be sited on paved areas. All storm water run-off from these areas should be discharged via oil separators/petrol separators and sand/silt removal traps.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
	Groundwater pumped out of excavations for the construction of pump sumps should only be discharged following removal of silt by sand/silt removal traps.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
16 5 5	Water from drilling of rock should be discharged following removal of silt by sand/silt removal traps.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
6.5.6	The wheels of all vehicles leaving the construction site should be washed before leaving the site to minimise the carry over of mud onto public roads. Wheel wash water should be recycled and only discharged following removal of silt by sand/silt removal traps.	All areas particularly pumping station sites / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
	Run off from the roofs of site buildings should be conveyed in closed drains to the nearest surface water course to prevent the generation of excessive quantities of surface water run off carrying suspended solids.	Site Office areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
6.5.7	All spillages should be cleaned up immediately to prevent their downward migration into the groundwater.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸

The copyright of this document is owned by MateriaLab Consultants Ltd. It may not be reproduced except with prior written approval from the Company.

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
6.5.7	Sewage from toilets and any kitchens in the site facilities should be treated via a septic tank system or if this is not practicable chemical toilets should be provided and the waste from these together with 'grey water' removed from the site on a daily basis for disposal at an appropriate receiving point.	All areas / throughout construction period	Contractor	WPCO, TMEIA & ProPECC PN 1/94	۸
6.6.2	Overflow bypasses to be used in emergency situations only and no effluent should be discharged during regular maintenance.	All pumping stations / Operation	DSD	WPCO, TMEIA	N/A
6.6.3 & 6.6.4	Supply pumping stations with stand-by pumps, emergency power supplies and telemetry system.	All Pumping Stations	DSD	WPCO, TMEIA & ProPECC PN 1/94	N/A
11.2.8	EM&A in the form of site supervision to ensure water quality protection measures are implemented.	All areas/ Throughout construction period	Contractor	EM&A	^

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



**Waste Management** 

EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
7.12.1	The Contractor shall identify a coordinator for the management of waste. The coordinator shall prepare a Waste Management Plan which specifies procedures such as a ticketing system, to facilitate tracking of loads and to ensure that illegal disposal of wastes does not occur, and protocols for the maintenance of records of the quantities of wastes generated, recycled and disposed. The Waste Management Plan shall be prepared with reference to Works Branch Technical Circular (WBTC) No. 5/99 for the Trip-ticket System for Disposal of Construction and Demolition Material and issued to the DEP and CED to confirm the availability for C&D and public fill waste.	Plan to be prepared prior to the start of construction, Implementation throughout construction period / All areas	Contractor	TMEIA.Works Branch Technical Circular (WBTC) No. 5/99 for the Trip-ticket System for Disposal of Construction and Demolition Material	۸
7.12.1	Stockpiled material should avoid vegetated areas where possible and covered by tarpaulins. Storage of material on site should be kept to a minimum.	All areas/ Throughout construction period	Contractor	TMEIA. Prevent windblown dust and/or surface run-off / avoid nuisance to local residents	*
7.12.1	Surplus material should be sorted on site into C&D waste and that suitable for public fill	All areas /throughout construction period	Contractor	TMEIA. Maximise reusable material	۸
7.12.1	The contractor should provide a temporary storage area for general refuse during the construction phase which should be enclosed to avoid refuse being windblown and affected by rain. General refuse should be stored on site for a minimum period and disposed of at a licenced facility.	All areas / throughout construction period	Contractor	TMEIA	۸

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Relevant Standard or Requirement	Implementation Status in Construction Phase
7.12.1	Excavated material in trucks shall be covered by tarpaulins to reduce the potential for spillage.	All areas / throughout construction period	Contractor	TMEIA	۸
7.12.1	Suitable chemical waste storage areas shall be formed on the site for temporary storage pending collection. All chemical wastes shall be handled, stored, transported and disposed of in accordance with the relevant practices.	All areas / throughout construction period	Contractor	TMEIA/ Code of Practice on the Package, Labelling and Storage of Chemical Wastes and A Guide to the Chemical Waste Control Scheme	^
7.12.1	Nightsoil arising from chemical toilets and on site chemical treatment facilities shall be transported by a licensed contractor to government Sewage Treatment Works for disposal.	All areas / throughout construction period	Contractor	TMEIA/ Sanitation and Conservancy (Regional Council) By-laws	^
7.12.1	Any screenings and grit that are removed during maintenance shall be disposed of at a landfill site. The material shall be suitably contained and covered.	All areas / operational phase	DSD	TMEIA	N/A
11.2.8	EM&A in the form of supervision of waste management practices	All areas / throughout construction period	Contractor	EM&A	^

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



Landscape and Visual

EIA Reference	Environmental Protection Measures	Location/ Timing	Implementation Agent	Standard or	Implementation Status in Construction Phase
10.8.5, 10.9.15, 10.10.6, 10.10.11, 10.10.20, 10.11.6	Use of a suitable colour scheme to the pump station building to match the design of the adjacent properties.	All pumping stations	DSD & Contractor	Reduce visual intrusion of pumping stations	N/A
10.8.5, 10.9.15, 10.10.11, 10.10.20, 10.11.6	Construction of boundary wall similar to the adjacent housing instead of standard chain link and barbed wire fence.	All pumping stations except Tai Lam Correctional Institution	DSD & Contractor	Screen pumping stations	N/A
10.8.5, 10.9.15, 10.10.11, 10.10.20, 10.11.6	Planting of trees and shrubs to the boundary of the pumping station compound.	All pumping stations except Tai Lam Correctional Institution	DSD & Contractor	Screen pumping stations	N/A
10.8.6	Minimise damage to the rootball of the tree east of the pumping station site.	East of Castle Peak Villas pumping station/ During excavation	DSD and Contractor		۸
11.2.8	EM&A in the form of site supervision of protection measures for trees and landscaping and compensatory planting establishment during the construction and operational phases respectively	All areas	Contractor	EM&A	۸

Remarks: ^ Compliance of mitigation measure

\* Recommendation was made during site audit but improved/ rectified by the Contractor

N/A Not Applicable at this stage as no such site activities were conducted in the reporting month

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 : (852)-24508032 1-15 Kwai Fung Crescent, Kwai Fong, Fax Hong Kong. Email : mcl@fugro.com



## Appendix L

Weather and Meteorological Conditions during Monitoring Period

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Email : mcl@fugro.com

Hong Kong.



	Mean	Ai	r Temperatu	Mean Relative	Total	
Date	Pressure (hPa)	Maximum (deg. C)	Mean (deg. C)	Minimum (deg. C)	Humidity (%)	Rainfall (mm)
			March 2017			
1	1019.5	22.9	18.8	15.9	67	0
2	1019.2	23.9	19.4	17.2	45	0
3	1017.0	20.1	17.4	15.7	67	0
4	1014.1	21.8	18.7	16.8	73	0
5	1012.4	24.0	20.7	18.7	83	0
6	1013.7	23.5	20.3	17.9	80	Trace
7	1016.5	20.7	18.0	17.1	75	Trace
8	1017.5	17.3	16.3	15.0	86	2.8
9	1015.7	19.6	17.0	16.0	74	Trace
10	1012.5	19.2	17.8	16.4	90	Trace
11	1015.1	18.4	17.5	16.7	88	Trace
12	1014.3	19.5	18.4	17.0	90	1
13	1011.8	24.4	21.7	19.4	92	0
14	1015.8	22.0	19.1	16.8	94	8.5
15	1018.2	17.9	16.8	16.2	75	Trace
16	1016.4	19.0	17.8	16.8	78	Trace
17	1017.2	20.4	18.1	17.0	86	Trace
18	1017.8	20.1	18.9	17.4	90	0.3
19	1017.3	20.6	19.8	18.9	94	10.7
20	1015.1	27.1	21.9	18.6	86	Trace
21	1015.0	27.6	22.9	19.1	85	0.6
22	1014.1	19.7	18.8	17.6	88	0.9
23	1015.0	24.6	21.2	19.0	84	0
24	1016.3	22.4	20.8	18.9	83	Trace
25	1017.2	23.4	20.2	16.5	84	Trace
26	1022.0	16.9	15.8	13.8	76	1
27	1022.7	21.5	18.9	16.3	55	0
28	1019.2	24.9	20.6	18.1	70	0
29	1018.3	23.7	21.7	20.4	84	0.3
30	1017.3	23.1	21.9	21.0	89	Trace
31	1015.3	23.7	20.1	15.5	92	21.9

Source: Hong Kong Observatory – Hong Kong Observatory

Room 723 & 725, 7/F, Block B, Profit Industrial Building,

: (852)-24508238 1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032 Hong Kong. Email : mcl@fugro.com



# Weather Conditions during noise monitoring

## **LC6a The Castle Bay**

Date	Start Time	Weather	Wind Speed m/s	Wind Direction
03-Mar-17	15:00	Fine	2.1	NE
09-Mar-17	15:00	Cloudy	0.4	NE
15-Mar-17	13:30	Cloudy	0.3	Е
21-Mar-17	14:33	Fine	1.3	Е
27-Mar-17	09:36	Fine	1.2	Е

#### LC9 Castle Peak Villas Block C

Date	Start Time	Weather	Wind Speed m/s	Wind Direction
03-Mar-17	14:15	Cloudy	2.4	NE
09-Mar-17	14:21	Cloudy	0.9	SE
15-Mar-17	14:17	Cloudy	0.1	E
21-Mar-17	13:50	Fine	1.1	Е
27-Mar-17	08:48	Fine	0.9	Е

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



# **Appendix M**

**Monthly Summary of Waste Flow Table** 

Name of Department: DSD Contract No.: DC/2014/01

# Monthly Summary Waste Flow Table for <u>03/17</u> (MM/YY)

_					THE E			(1:11:1) 1	•		
	A	Actual Quantities	of Inert C&D	Materials Gen	erated Monthl	У	Actual Quantities of C&D Wastes Generated Monthly				onthly
Month	Total Quantity Generated	Hard Rock and Large Broken Concrete	Reused in the Contract	Reused in other Projects	Disposed as Public Fill	Imported Fill	Metals	Paper/ cardboard packaging	Plastics (see Note 3)	Chemical Waste	Others, e.g. general refuse
	(in '000m <sup>3</sup> )	(in '000m <sup>3</sup> )	(in '000m <sup>3</sup> )	(in '000m <sup>3</sup> )	(in '000m <sup>3</sup> )	(in '000m <sup>3</sup> )	(in '000 kg)	(in '000kg)	(in '000kg)	(in '000kg)	(in '000m <sup>3</sup> )
Jan 2017	0.040	0.040	0.040	(111 000111 )	0.000	(111 000111 )	(III 000 Kg)	, U	(III OOOKg)	-	0
				-		-	-	=	-	-	U
Feb 2017	0.580	0.580	0.080	-	0.500	-	-	-	-	-	0
Mar 2017	0.910	0.910	0.460	=	0.450	-	-	-	-	-	0
Apr 2017											
May 2017											
Jun 2017											
Jul 2017											
Aug 2017											
Sept 2017											
Oct 2017											
Nov 2017											
Dec 2017				·		_					
Total	1.530	1.530	0.580	-	0.950	-	-	-	-	-	0

## Sang Hing – Kuly Joint Venture Environmental Monthly Report for Contract No. DC/2014/01 Castle Peak Road Trunk Sewer and Tuen Mun Village Sewage

	Forecast of Total Quantities of C&D Materials to be Generated from the Contract*									
Total Quantity	Hard Rock and Large Broken	Reused in the	Reused in other	Disposed as Public Fill	Imported Fill	Metals	Paper/ cardboard	Plastics (see Note 3)	Chemical Waste	Others, e.g.
Generated	Concrete	Contract	Projects	Public Fill	_		packaging	(see Note 3)		general refuse
$(in '000m^3)$	(in '000m <sup>3</sup> )	(in '000m <sup>3</sup> )	$(in '000m^3)$	(in '000m <sup>3</sup> )	(in '000m <sup>3</sup> )	(in '000 kg)	(in '000kg)	(in '000kg)	(in '000kg)	(in '000m <sup>3</sup> )
27	10	8	1	1	0	2	1	1	1	2

#### Notes:

- (1) The performance targets are given in ETWB Technical Circular PS Clause 6(14).
- (2) The waste flow table shall also include C&D materials that are specified in the Contract to be imported for use at the Site.
- (3) Plastics refer to plastic bottles/containers, plastic sheets/foam from packaging material
- \*The Contractor shall also submit the latest forecast of the total amount of C&D materials expected to be generated from the Works, together with a breakdown of the nature where the total amount of C&D materials expected to be generated from the Works is equal to or exceeding 50,000 m3. (ETWB Technical Circular PS Clause 5(4)(b) refers). [Delete Note (4) and the table above on the forecast, where inapplicable].

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, : (852)-24508238 : (852)-24508032 Fax Hong Kong. Email : mcl@fugro.com



# Appendix N

**Proactive Environmental Protection Proforma** 

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong.

: (852)-24508238 : (852)-24508032 Tel Fax Email : mcl@fugro.com



Reporting Period	Construction Works	Anticipated Impacts	Recommended Mitigation Measures	
	Hoarding Erection		<ul> <li>Sufficient watering of the works site with active dust emitting activities.</li> <li>Properly cover the stockpiles.</li> </ul>	
20/02/2046	Pre-Drilling	Dust, Noise	Scheduling of noisy construction activities if necessary to avoid persistent noisy operation.      Descriptions of machines.	
29/02/2016 - 31/03/2016	Earth Excavation	and water quality impact.	<ul> <li>Regular maintenance of machines.</li> <li>Use of acoustic barriers if necessary.</li> <li>Provision of appropriate desilting/sedimentation devices provided on site for treatment before disabases.</li> </ul>	
	Plant Mobilization		<ul> <li>before discharge.</li> <li>Regular check and maintenance of desilting/sedimentation devices.</li> <li>Provide sufficient mitigation measures as recommended in approved EIA Manual requirement.</li> </ul>	
01/04/2016 - 30/04/2016		Noise and	<ul> <li>Shield the piling rig to avoid spreading of slurry during boring.</li> <li>Regular maintenance of machines.</li> <li>Use of acoustic barriers if necessary.</li> <li>Provision of appropriate desilting/sedimentation devices provided on site for treatment</li> </ul>	
01/05/2016 - 31/05/2016	Soldier pile work	water quality impact		<ul> <li>before discharge.</li> <li>Regular check and maintenance of desilting/sedimentation devices.</li> <li>Provide sufficient mitigation measures as recommended in approved EIA Manual requirement.</li> </ul>
01/06/2016 - 30/06/2016	Construction of lagging wall	Dust, Noise impact and waste management.	<ul> <li>Water sprays shall be used during the delivery and handling of dusty materials.</li> <li>Carry out good site practice to limit noise emission at source.</li> <li>Avoid simultaneous noisy activities.</li> <li>Surplus material should be sorted on site into C&amp;D waste and that suitable for public fill.</li> <li>Provide sufficient mitigation measures as recommended in approved EIA Manual requirement.</li> </ul>	

The copyright of this document is owned by MateriaLab Consultants Ltd. It may not be reproduced except with prior written approval from the Company.

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Fong, Hong Kong. Tel : (852)-24508238 Fax : (852)-24508032 Email : mcl@fugro.com



Reporting Period	Construction Works	Anticipated Impacts	Recommended Mitigation Measures	
01/07/2016 - 31/07/2016			<ul> <li>Sufficient watering of the works site with active dust emitting activities.</li> <li>Scheduling of noisy construction activities if necessary to avoid persistent noisy operation.</li> <li>Regular maintenance of machines.</li> <li>Use of acoustic barriers if necessary.</li> </ul>	
01/08/2016	Construction of Mini-pile	Dust, Noise and water	• Provision of appropriate desilting/sedimentation devices provided on site for treatment before discharge.	
31/08/2016		quality impact.	<ul> <li>Regular check and maintenance of desilting/sedimentation devices.</li> <li>Provide sufficient mitigation measures as recommended in approved EIA Manual</li> </ul>	
01/09/2016			requirement.	
30/09/2016				
01/10/2016 - 31/10/2016	Proof drill and Loading Test		<ul> <li>Sufficient watering of the works site with active dust emitting activities.</li> <li>Scheduling of noisy construction activities if necessary to avoid persistent noisy operation.</li> <li>Regular maintenance of machines.</li> </ul>	
01/11/2016		Dust, Noise and water quality impact.	<ul><li>Use of acoustic barriers if necessary.</li><li>Provision of appropriate desilting/sedimentation devices provided on site for treatment</li></ul>	
30/11/2016	Construction of ELC		quality	before discharge.  • Regular check and maintenance of desilting/sedimentation devices.
01/12/2016	Construction of ELS		<ul> <li>Provide sufficient mitigation measures as recommended in approved EIA Manual requirement.</li> </ul>	
31/12/2016				

Room 723 & 725, 7/F, Block B,

Profit Industrial Building, Tel : (852)-24508238
1-15 Kwai Fung Crescent, Kwai Fong, Fax : (852)-24508032
Hong Kong. Email : mcl@fugro.com



Reporting Period	Construction Works	Anticipated Impacts	Recommended Mitigation Measures
01/01/2017			Sufficient watering of the works site with active dust emitting activities.     Scheduling of noisy construction activities if necessary to avoid persistent noisy
31/01/2017			<ul><li>operation.</li><li>Regular maintenance of machines.</li></ul>
01/02/2017			Use of acoustic barriers if necessary.
-	Excavation of ELS		• Provision of appropriate desilting/sedimentation devices provided on site for treatment before discharge.
28/02/2017			Regular check and maintenance of desilting/sedimentation devices.
01/03/2017			<ul> <li>Provide sufficient mitigation measures as recommended in approved EIA Manual requirement.</li> </ul>
31/03/2017			
			<ul> <li>Sufficient watering of the works site with active dust emitting activities.</li> <li>Scheduling of noisy construction activities if necessary to avoid persistent noisy operation.</li> </ul>
01/04/2017		Dust, Noise	Regular maintenance of machines.
-	Construction of Wet Well	and water	Use of acoustic barriers if necessary.
30/04/2017	Chamber	quality impact.	• Provision of appropriate desilting/sedimentation devices provided on site for treatment before discharge.
			Regular check and maintenance of desilting/sedimentation devices.
			Provide sufficient mitigation measures as recommended in approved EIA Manual requirement.