



**LEGEND :**

- 500M STUDY AREA
  - - - PROPOSED WORKS LIMIT
  - PROPOSED WEST RAIL
  - PROPOSED NOISE BARRIERS  
LEGEND REFER TO FIG 10.6.3.5
  - CM1** LIMITATION OF THE CONTRACTOR'S WORKS AREA NEAR THE MANGROVES AT THE COASTAL PROTECTION AREA
  - CM2** MINIMISATION OF CUT INTO EXISTING SLOPES
  - CM3** EXCAVATED MATERIAL TO BE USED FOR THE FILLING OF THE PROPOSED WORKS AS TO MINIMISE HAULAGE \*
  - CM4** REGULAR CHECKS OF WORKS SITE BOUNDARIES \*
  - CM5** MEASURES TO ENSURE MINIMISATION OF SOIL EROSION \*
  - CM6** REFINING POSITION OF COLUMNS \*
  - CM7** CAREFUL POSITIONING OF CONSTRUCTION PLANT TO MINIMISE THE POTENTIAL LANDSCAPE AND VISUAL IMPACTS \*
  - CM8** CONTROL OF WASTE DISPOSAL, OIL SPILLAGE ETC. ON SITE (ENTIRE SITE) \*
  - CM9** CONTROL OF NIGHT-TIME LIGHTING (ENTIRE SITE)
  - CM10** LOCATION OF WORK SITES SHOULD BE CAREFULLY SELECTED TO MINIMISE THE POTENTIAL LANDSCAPE AND VISUAL IMPACTS
  - CM11** REPLANTING OF DISTURBED VEGETATION SHOULD BE UNDERTAKEN AND THIS SHOULD USE PREDOMINANTLY NATIVE PLANT SPECIES
  - CM12** SCREEN HOARDING, USING DECORATIVE GRAPHIC AND CHROMATIC DEVISE SHOULD BE ERECTED AROUND THE WORKS WHEREVER POSSIBLE TO SCREEN WORKS WITHIN THE ROAD CORRIDOR.
  - CM13** PLANTING SHOULD BE UNDERTAKEN AT THE EARLIEST POSSIBLE STAGE DURING CONSTRUCTION, AND OPPORTUNITIES SHOULD BE SOUGHT FOR UNDERTAKING ANY ADVANCE PLANTING
  - CM15** TRANSPLANTING MATURE TREES WITH GOOD AMENITY VALUE
- \* DENOTES GENERAL GOOD WORKING PRACTICES TO BE EMPLOYED
- MEASURES TO BE APPLIED GENERALLY CM6, CM9, CM10, CM11 & CM14




Figure 10.6.2  
Construction Phase Mitigation Measure (2 of 3)