



NOTE:
 1. THE DAILY AVERAGE RSP ADD CRITERION IS 180 µg/m³.

LEGEND:

- SITE BOUNDARY
- - - 500m STUDY AREA
- A1 AIR SENSITIVE RECEIVER

TRAFFIC NOISE MITIGATION MEASURES:

- LANDSCAPED DECK
- VERTICAL BARRIER (CONNECTED TO THE DECK)

REV.	DESCRIPTION	DATE

CEDD 土木工程拓展署
 Civil Engineering and Development Department

KAI TAK DEVELOPMENT

KAI TAK DEVELOPMENT - INFRASTRUCTURE AT FORMER RUNWAY AND REMAINING AREAS OF NORTH APRON AND IMPROVEMENT OF ADJACENT WATERWAYS - DESIGN AND CONSTRUCTION

CONTOURS OF CUMULATIVE MAXIMUM DAILY AVERAGE RSP CONCENTRATION IN µG/m³ (AT 1.5m ABOVE GROUND)

AECOM

DRG.NO. 圖紙編號 **60102100/FIGURE 4.6a**

DESIGNED BY 設計	CONTRACT NO. 合約編號	P. OR APPROVED 核准人
DATE OF ISSUE 日期	STATUS 階段	
SCALE 比例尺 A1 1 : 4000 A3 1 : 8000		
DIMENSIONS ARE IN 尺寸單位	© COPYRIGHT RESERVED 版權所有	

Plot File by : 2013-1-30 FENGYL