

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2015				
Third Runway Work Areas				
Works Area	Sources	Parameter		Remarks
Submarine pipeline	Heavy construction Source ID:	Percentage active area, p	15.0 %	Assume % works area for heavy construction
Submarine cable	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day
	Q2:	No. of working days per month, d	30 days	
	Q3: S1, S2, S3	No. of working hours per day, h	24 hour	
	Q4: S1, S2, S3	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
	Wind Erosion Source ID: (as above)	Emission Rate	4.67014E-07 g/m ² /s (unmitigated) 3.87622E-08 g/m ² /s (mitigated)	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Percentage active area, p	15 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	1.2129E-08 g/m ² /s	
(Concurrent project)	Heavy construction Source ID:	Percentage active area, p	16.9 %	Assume % works area for heavy construction
NCD works	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2:	No. of working days per month, d	30 days	
	Q3: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, TRD2, TCPN-1, TCPN-2, TCPN-3, EGC4, EGC5, EGC6, EGC7	No. of working hours per day, h	24 hour	
	Q4: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SSCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
	Wind Erosion Source ID: (as above)	Emission Rate	5.25715E-07 g/m ² /s (unmitigated) 4.36344E-08 g/m ² /s (mitigated)	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Percentage active area, p	16.9 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	1.36536E-08 g/m ² /s	
(Concurrent project)	Heavy construction Source ID:	Percentage active area, p	34.3 %	Assume % works area for heavy construction
ITT works (area sources)	Q1: SSCP1, AES6, AES13, AES14, AES15, EM1, EM2, EGC3-1, EGC3-2, ITT1	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2: SSCP1, AES6, AES13, AES14, AES15, EM1, EM2, EGC3-1, EGC3-2, ITT1	No. of working days per month, d	30 days	
	Q3: SSCP1, AES6, AES13, AES14, AES15, EM1, EM2, EGC3-1, EGC3-2, ITT1	No. of working hours per day, h	24 hour	
	Q4: EM1, EM2, ITT1	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
	Wind Erosion Source ID: (as above)	Emission Rate	1.0673E-06 g/m ² /s (unmitigated) 8.85857E-08 g/m ² /s (mitigated)	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Percentage active area, p	34.3 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	2.77192E-08 g/m ² /s	
(Concurrent project)	Heavy construction Source ID:	Percentage active area, p	34.28 %	Assume % works area for heavy construction
ITT works (line sources) Roadworks - at grade	Q1: SCRE1, SCRE2, SCRE3, SCRE4, SCRE5, SCRE6, SCRE7, SCRE8, SCRE9, SCRE10, AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2: SCRE1, SCRE2, SCRE3, SCRE4, SCRE5, SCRE6, SCRE7, SCRE8, SCRE9, SCRE10, AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	No. of working days per month, d	30 days	
	Q3: SCRE1, SCRE2, SCRE3, SCRE4, SCRE5, SCRE6, SCRE7, SCRE8, SCRE9, SCRE10, AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	No. of working hours per day, h	24 hour	
	Q4:	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
	Wind Erosion Source ID: (as above)	Emission Rate	1.28076E-05 g/m ² /s (unmitigated) 1.06303E-06 g/m ² /s (mitigated)	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
		Percentage active area, p	34.28 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	2.77192E-08 g/m ² /s	
(Concurrent project)	Heavy construction Source ID:	Percentage active area, p	10.0 %	Extracted from HKBCF EIA, assume 10% works area for heavy construction
Boundary Crossing Facilities (BCF)	Q1: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	Mitigation efficiency	87.5 %	Extracted from HKBCF EIA Extracted from HKBCF EIA Extracted from HKBCF EIA AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Q2: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	No. of working days per month, d	26 days	
	Q3: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	No. of working hours per day, h	12 hour	
	Q4: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
	Wind Erosion Source ID: (as above)	Emission Rate	7.18483E-07 g/m ² /s (unmitigated) 8.98104E-08 g/m ² /s (mitigated)	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Percentage active area, p	10 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	8.086E-09 g/m ² /s	
(Concurrent project)	Heavy construction Source ID:	Percentage active area, p	10.0 %	Extracted from HKLR EIA, assume 10% works area for heavy construction
Hong Kong Link Road (HKLR)	Q1: LR-2, LR-3, LR-4, LR-5, LR-6, LR-7, LR-8, LR-9, LR-10, LR-11, LR-12, LR-13, LR-14	Mitigation efficiency	87.5 %	Extracted from HKLR EIA Extracted from HKLR EIA Extracted from HKLR EIA AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Q2:	No. of working days per month, d	26 days	
	Q3:	No. of working hours per day, h	12 hour	
	Q4:	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
	Wind Erosion Source ID: (as above)	Emission Rate	7.18483E-07 g/m ² /s (unmitigated) 8.98104E-08 g/m ² /s (mitigated)	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Percentage active area, p	10 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	8.086E-09 g/m ² /s	

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2016

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities:	Percentage active area, p	0.1 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2:	No. of working days per month, d	30 days	
	Q3:	No. of working hours per day, h	24 hour	
	Q4: 1_03-1, 1_03-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	2.8559E-09 g/m²/s (unmitigated) 2.3704E-10 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.1 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	7.41717E-11 g/m²/s	
Submarine pipeline Submarine cable	Heavy construction Source ID: Q1: S1, S2, S3 Q2: S1, S2, S3 Q3: S1, S2, S3	Percentage active area, p	22.5 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Q4:	Emission Rate	7.00521E-07 g/m²/s (unmitigated) 5.81432E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	22.5 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	1.81935E-08 g/m²/s	
(Concurrent project) NCD works	Heavy construction Source ID: Q1: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TCPN-1, TCPN-2, TCPN-3, SOCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q2: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SOCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q3: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SOCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q4: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SOCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7	Percentage active area, p	16.0 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	4.9862E-07 g/m²/s (unmitigated) 4.13854E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	16.0 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	1.29498E-08 g/m²/s	
(Concurrent project) ITT works (area sources)	Heavy construction Source ID: Q1: AES6, EM1, EM2, ITT1 Q2: AES6, EM1, EM2, ITT1 Q3: AES6, EM1, EM2, ITT1 Q4: AES6, EM1, EM2, ITT1	Percentage active area, p	35.9 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	1.11861E-06 g/m²/s (unmitigated) 9.28444E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	35.9 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	2.90518E-08 g/m²/s	

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2016				
(Concurrent project) ITT works (line sources) Roadworks - at grade	Heavy construction Source ID:	Percentage active area, p	35.93 %	Assume % works area for heavy construction
	Q1: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q2: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q3: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q4: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.34233E-05 g/m²/s (unmitigated) 1.11413E-06 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p	35.93 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 2.90518E-08 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
T2 Expansion - Advanced Works (Temporary Car Parks NCD and Temporary Road Diversion)	Heavy construction Source ID:	Percentage active area, p	1.0 %	Assume % works area for heavy construction
	Q1: TRD1, TRD3, TRD4, TRD5, TRD6 Q2: TRD1, TRD5, TRD6 Q3: TRD1, TRD5, TRD6 Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 3.22126E-08 g/m²/s (unmitigated) 2.67364E-09 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.0 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 8.36605E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) Boundary Crossing Facilities (BCF)	Heavy construction Source ID:	Percentage active area, p	10.0 %	Extracted from HKBCF EIA, assume 10% works area for heavy construction
	Q1: BCF-C4 Q2: BCF-C4 Q3: BCF-C4 Q4: BCF-C4	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	87.5 % 26 days 12 hour 0.0807 Mg/hectare/month of activity 7.18483E-07 g/m²/s (unmitigated) 8.98104E-08 g/m²/s (mitigated)	Extracted from HKBCF EIA Extracted from HKBCF EIA Extracted from HKBCF EIA AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	10 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 8.086E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Other airport facilities related works	Heavy construction Source ID:	Percentage active area, p	5.2 %	Assume % works area for heavy construction
	Q1: ABT1-1 Q2: ABT1-1 Q3: ABT1-1 Q4: ABT1-1	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.6071E-07 g/m²/s (unmitigated) 1.3339E-08 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	5.2 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 4.17387E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Roadworks corresponding to Other airport facilities related works	Heavy construction Source ID:	Percentage active area, p	5.2 %	Assume % works area for heavy construction
	Q1: ABT1-2, ABT1-3 Q2: ABT1-2, ABT1-3 Q3: ABT1-2, ABT1-3 Q4: ABT1-2, ABT1-3	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.92852E-06 g/m²/s (unmitigated) 1.60068E-07 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	5.2 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 4.17387E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2017

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 1_01, 1_03-1, 1_03-2, 1_04, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 1_09-1, 1_09-2, 2_03B, 2_04-1, 2_04-2, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07B, 2_08, 2_09-1, 2_09-2 Q2: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 1_09-1, 1_09-2, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-1, 2_09-2, 3_01A-1, 3_01A-2, 3_01A-3 Q3: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 3_01A-1, 3_01A-2, 3_01A-3 Q4: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08	Percentage active area, p	1.4 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	4.45002E-08 g/m²/s (unmitigated) 3.69352E-09 g/m²/s (mitigated)	=2.69*0.03*1000000/(10000*30*h*60*60)*p/100
	For night-time activities: Q1: Q2: 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3 Q3: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2 Q4: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_02A-1, 3_02A-2, 3_02A-3	Percentage active area, p	1.4 %	
		Mitigation efficiency	91.7 %	
		No. of working days per month, d	30 days	
		No. of working hours per day, h	12 (night) hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	8.90004E-08 g/m²/s (unmitigated) 7.38703E-09 g/m²/s (mitigated)	=2.69*0.03*1000000/(10000*30*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.4 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	1.15573E-09 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: Q2: Q3: Q4: 1_08B-1, 1_08B-2, 3_01A-1, 3_01A-2, 3_01A-3	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	1.6172E-08 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 4_04, 4_05-1 Q2: 4_04, 4_05-1 Q3: 4_04, 4_05-1 Q4: 4_04, 4_05-1	Percentage active area, p	0.0 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	8.58968E-10 g/m²/s (unmitigated) 7.12944E-11 g/m²/s (mitigated)	=2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.0 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	2.23086E-11 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) NCD works	Heavy construction Source ID: Q1: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q2: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q3: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q4: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7	Percentage active area, p	3.1 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	9.65381E-08 g/m²/s (unmitigated) 8.01266E-09 g/m²/s (mitigated)	=2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	3.1 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	2.50723E-09 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2017				
(Concurrent project) ITT works (area sources)	Heavy construction Source ID:	Percentage active area, p	7.2 %	Assume % works area for heavy construction
	Q1: AES6 Q2: Q3: Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.2403E-07 g/m²/s (unmitigated) 1.85945E-08 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	7.2 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 5.81837E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) ITT works (line sources) Roadworks - at grade	Heavy construction Source ID:	Percentage active area, p	7.20 %	Assume % works area for heavy construction
	Q1: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q2: Q3: Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.68836E-06 g/m²/s (unmitigated) 2.23134E-07 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p	7.20 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 5.81837E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - at grade	Heavy construction Source ID:	Percentage active area, p	30.48 %	Assume % works area for heavy construction
	Q1: Q2: CA1, CA2 Q3: CA1, CA2 Q4: CA1, CA2	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.13869E-05 g/m²/s (unmitigated) 9.45115E-07 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p	30.48 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 2.46445E-08 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - viaduct	Heavy construction Source ID:	Percentage active area, p	30.5 %	Assume % works area for heavy construction
	Q1: Q2: CA3, CA4, CA5, CA6, CA7, CA8 Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.18614E-06 g/m²/s (unmitigated) 9.84495E-08 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p	30.5 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 2.46445E-08 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*1000000/(10000*365*24*60*60)*p/100

Roadworks Road 6 viaduct (Concept F, Option 3)	Heavy construction Source ID:	Percentage active area, p	20.7 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Q1: Q2: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Mitigation efficiency	91.7 %	
	No. of working days per month, d	30 days		
	No. of working hours per day, h	24 hour		
	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity		
	Emission Rate	8.04473E-07 g/m²/s (unmitigated) 6.67713E-08 g/m²/s (mitigated)		
	Wind Erosion Source ID: (as above)	Percentage active area, p	20.7 %	
	Emission Factor (0.03)	0.0255 Mg/hectare/year		
	Emission Rate	1.67146E-08 g/m²/s		
	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100			
New APM Interchange Station (AIS)	Heavy construction Source ID:	Percentage active area, p	0.7 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Q1: Q2: Q3: AIS1, AIS2 Q4:	Mitigation efficiency	91.7 %	
	No. of working days per month, d No. of working hours per day, h	30 days 24 hour		
	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity		
	Emission Rate	2.24013E-08 g/m²/s (unmitigated) 1.8593E-09 g/m²/s (mitigated)		
	Wind Erosion Source ID: (as above) Q1:	Percentage active area, p	0.72 %	
	Emission Factor (0.03)	0.0255 Mg/hectare/year		
	Emission Rate	5.81792E-10 g/m²/s		
	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100			
	BHS and APM tunnel	Heavy construction Source ID:	Percentage active area, p	
Q1: Q2: Q3: BAT1, BAT2, NAB3, NAB4 Q4: BAT1, BAT2, NAB3, NAB4		Mitigation efficiency	91.7 %	
No. of working days per month, d No. of working hours per day, h		30 days 24 hour		
Emission Factor (0.03)		0.0807 Mg/hectare/month of activity		
Emission Rate		5.42931E-09 g/m²/s (unmitigated) 4.50633E-10 g/m²/s (mitigated)		
Wind Erosion Source ID: (as above) Q1:		Percentage active area, p	0.17 %	
Emission Factor (0.03)		0.0255 Mg/hectare/year		
Emission Rate		1.41007E-10 g/m²/s		
AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100				
T2 Expansion Area		Heavy construction Source ID:	Percentage active area, p	0.0 %
	Q1: Q2: Q3: T2E-1, T2E-2, T2E-3, BHS1, BHS2, NAB1, NAB2, SAB, NAD1 Q4: T2E-1, T2E-2, T2E-3, AIS1, AIS2, BHS1, BHS2, NAB1, NAB2, SAB, NAD1, EVA1, EVA2, EVA3, EVA4, EVA5, EVA6, EVA7, EVA8, EVA9	Mitigation efficiency	91.7 %	
	No. of working days per month, d No. of working hours per day, h	30 days 24 hour		
	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity		
	Emission Rate	1.44149E-09 g/m²/s (unmitigated) 1.19644E-10 g/m²/s (mitigated)		
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.0 %	
	Emission Factor (0.03)	0.0255 Mg/hectare/year		
	Emission Rate	3.74376E-11 g/m²/s		
	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100			
	T2 Expansion - Emergency Vehicular Access (EVA)	Heavy construction Source ID:	Percentage active area, p	2.0 %
Q1: Q2: Q3: EVA1, EVA2, EVA3, EVA4, EVA5, EVA6, EVA7, EVA8, EVA9 Q4:		Mitigation efficiency	91.7 %	
No. of working days per month, d No. of working hours per day, h		30 days 24 hour		
Emission Factor (0.03)		0.0807 Mg/hectare/month of activity		
Emission Rate		6.20924E-08 g/m²/s (unmitigated) 5.15367E-09 g/m²/s (mitigated)		
Wind Erosion Source ID: (as above)		Percentage active area, p	2.0 %	
Emission Factor (0.03)		0.0255 Mg/hectare/year		
Emission Rate		1.61263E-09 g/m²/s		
AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100				

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2017				
Other airport facilities related works	Heavy construction Source ID: Q1: ABT1-1 Q2: ABT1-1 Q3: ABT1-1 Q4: ABT1-1	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	1.4 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 4.36713E-08 g/m²/s (unmitigated) 3.62472E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.03) Emission Rate	1.4 % 0.0255 Mg/hectare/year 1.1342E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60)*p/100
Roadworks corresponding to Other airport facilities related works	Heavy construction Source ID: Q1: ABT1-2, ABT1-3 Q2: ABT1-2, ABT1-3 Q3: ABT1-2, ABT1-3 Q4: ABT1-2, ABT1-3	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	1.4 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 5.24056E-07 g/m²/s (unmitigated) 4.34966E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.03) Emission Rate	1.4 % 0.0255 Mg/hectare/year 1.1342E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2018				
Third Runway Work Areas				
Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_08B-2, 2_02B-1, 2_02B-2, 2_03A, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2 Q2: 1_02-1, 1_02-2, 1_05, 1_06-1, 1_06-2, 2_02B-1, 2_02B-2, 2_03A, 2_05A, 2_08, 3_02B Q3: 1_06-1, 1_06-2, 2_01, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2 Q4: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05B-1, 2_05B-2	Percentage active area, p	6.8 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	2.10499E-07 g/m²/s (unmitigated) 1.74714E-08 g/m²/s (mitigated)	
	For night-time activities: Q1: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_02A-1, 3_02A-2, 3_02A-3 Q2: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_01A-1, 3_01A-2, 3_01A-3, 3_02A-1, 3_02A-2, 3_02A-3 Q3: 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_01A-1, 3_01A-2, 3_01A-3, 3_02A-1, 3_02A-2, 3_02A-3 Q4: 1_09-1, 1_09-2, 2_09-1, 2_09-2, 3_02A-1, 3_02A-2, 3_02A-3	Percentage active area, p	6.8 %	
		Mitigation efficiency	91.7 %	
		No. of working days per month, d	30 days	
		No. of working hours per day, h	12 (night) hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	4.20998E-07 g/m²/s (unmitigated) 3.49428E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	6.8 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	5.46694E-09 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: 1_07-2, 1_08A-2, 2_03B, 2_07B, 2_08, 3_01A-1, 3_01A-2, 3_01A-3 Q2: 1_01, 1_03-1, 1_03-2, 1_04, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B Q3: 1_09-1, 1_09-2, 2_08, 3_02B Q4: 2_04-1, 2_04-2, 2_05A, 2_06-1, 2_06-2, 2_06-3, 2_08, 3_02B	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	1.6172E-08 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 1_07-1, 1_08A-1, 1_08B-1, 4_04, 4_05-1 Q2: 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 4_04, 4_05-1 Q3: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_07A-1, 2_07A-2, 2_07B, 4_04, 4_05-1 Q4: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_04, 4_05-1	Percentage active area, p	2.4 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	7.43415E-08 g/m²/s (unmitigated) 6.17034E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	2.4 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.93075E-09 g/m²/s	
(Concurrent project) NCD works	Heavy construction Source ID: Q1: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2 Q2: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2 Q3: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2 Q4: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2	Percentage active area, p	26.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	8.18814E-07 g/m²/s (unmitigated) 6.79615E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	26.3 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	2.12657E-08 g/m²/s	

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2018				
Midfield development (MD)	Heavy construction Source ID:	Percentage active area, p	0.7 %	Assume % works area for heavy construction
	Q1: MD Q2: MD Q3: MD Q4: MD	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.1273E-08 g/m²/s (unmitigated) 1.76566E-09 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.7 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 5.52489E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - at grade	Heavy construction Source ID:	Percentage active area, p	43.24 %	Assume % works area for heavy construction
	Q1: CA1, CA2 Q2: CA1, CA2 Q3: CA1, CA2 Q4: CA1, CA2	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.61535E-05 g/m²/s (unmitigated) 1.34074E-06 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p	43.24 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 3.49607E-08 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - viaduct	Heavy construction Source ID:	Percentage active area, p	43.2 %	Assume % works area for heavy construction
	Q1: CA3, CA4, CA5, CA6, CA7, CA8 Q2: CA3, CA4, CA5, CA6, CA7, CA8 Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.68265E-06 g/m²/s (unmitigated) 1.3966E-07 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p	43.2 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 3.49607E-08 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*1000000/(10000*365*24*60*60)*p/100
Roadworks Road 6 - viaduct (Concept F, Option 3)	Heavy construction Source ID:	Percentage active area, p	29.3 %	Assume % works area for heavy construction
	Q1: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q2: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.14122E-06 g/m²/s (unmitigated) 9.47215E-08 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p	29.3 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 2.37113E-08 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
New APM Interchange Station (AIS)	Heavy construction Source ID:	Percentage active area, p	8.1 %	Assume % works area for heavy construction
	Q1: Q2: AIS1, AIS2, EVA6, EVA7, EVA8 Q3: AIS1, AIS2, EVA6, EVA7, EVA8 Q4: AIS1, AIS2, EVA6, EVA7, EVA8	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.51202E-07 g/m²/s (unmitigated) 2.08497E-08 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1:	Percentage active area, p	8.07 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 6.52405E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2018				
Baggage Hall - Baggage Handling System (BHS)	Heavy construction Source ID: Q1: Q2: BHS1, BHS2, EVA9 Q3: BHS1, BHS2, EVA9 Q4: BHS1, BHS2, EVA9	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	10.7 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 3.33502E-07 g/m²/s (unmitigated) 2.76807E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1:	Percentage active area, p Emission Factor (0.03) Emission Rate	10.71 % 0.0255 Mg/hectare/year 8.66151E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
New APM Depot (NAD)	Heavy construction Source ID: Q1: NAD1, NAD2 Q2: NAD1, NAD2 Q3: NAD1, NAD2 Q4: NAD1, NAD2	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.4 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.29094E-08 g/m²/s (unmitigated) 1.07148E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: NAD1, NAD2	Percentage active area, p Emission Factor (0.03) Emission Rate	0.41 % 0.0255 Mg/hectare/year 3.35276E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
BHS and APM tunnel	Heavy construction Source ID: Q1: BAT1, BAT2, NAB3, NAB4 Q2: BAT1, BAT2, NAB3, NAB4 Q3: BAT1, BAT2, NAB3, NAB4 Q4: BAT1, BAT2, NAB3, NAB4	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.5 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.52021E-08 g/m²/s (unmitigated) 1.26177E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BAT1, BAT2, NAB3, NAB4	Percentage active area, p Emission Factor (0.03) Emission Rate	0.49 % 0.0255 Mg/hectare/year 3.94819E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
T2 Expansion Area	Heavy construction Source ID: Q1: T2E-1, T2E-2, T2E-3, AIS1, AIS2, BHS2 Q2: T2E-3 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 5.46382E-09 g/m²/s (unmitigated) 4.53497E-10 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.03) Emission Rate	0.2 % 0.0255 Mg/hectare/year 1.41903E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
T2 Expansion - Car Park North (North Annex Building)	Heavy construction Source ID: Q1: NAB1, NAB2, BHS1 Q2: NAB1, NAB2 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 4.86999E-09 g/m²/s (unmitigated) 4.04209E-10 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.03) Emission Rate	0.2 % 0.0255 Mg/hectare/year 1.2648E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
T2 Expansion - Lounge Limo (South Annex Building)	Heavy construction Source ID: Q1: SAB Q2: SAB Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 5.69905E-09 g/m²/s (unmitigated) 4.73021E-10 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.03) Emission Rate	0.2 % 0.0255 Mg/hectare/year 1.48012E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2019

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 2_01, 2_02A Q2: 2_01, 2_02A, 2_05A Q3: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_05A Q4: 2_02B-1, 2_02B-2, 2_03A	Percentage active area, p	6.6 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	2.06269E-07 g/m²/s (unmitigated) 1.71203E-08 g/m²/s (mitigated)	
	For night-time activities: Q1: 1_09-1, 1_09-2, 2_06-1, 2_06-2, 2_06-3, 3_02A-1, 3_02A-2, 3_02A-3 Q2: 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 3_02A-1, 3_02A-2, 3_02A-3 Q3: 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 3_02A-1, 3_02A-2, 3_02A-3 Q4: 2_09-1	Percentage active area, p	6.6 %	
		Mitigation efficiency	91.7 %	
		No. of working days per month, d	30 days	
		No. of working hours per day, h	12 (night) hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	4.12537E-07 g/m²/s (unmitigated) 3.42406E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	6.6 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	5.35708E-09 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: 2_02B-1, 2_03A, 2_03B, 2_04-1, 2_04-2, 2_05A, 2_05B-1, 2_05B-2, 2_06, 2_09-1, 2_09-2, 3_02B Q2: 2_02B-1, 2_03A, 2_03B, 2_05B-1, 2_05B-2, 3_02B Q3: 1_09-2, 3_02B Q4: 3_02A-1, 3_02A-2, 3_02A-3, 3_02B	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.6172E-08 g/m²/s	
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_07-1, 1_08A-1, 1_08B-1, 2_02B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 4_04 Q2: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_09-1, 2_02B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2, 4_04 Q3: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_09-1, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2, 4_04 Q4: 1_09-1, 1_09-2, 2_01, 2_02A, 2_03B, 2_04-1, 2_04-2, 2_05A, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2, 4_04	Percentage active area, p	1.8 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	5.75391E-08 g/m²/s (unmitigated) 4.77575E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.8 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.49437E-09 g/m²/s	
Midfield development (MD)	Heavy construction Source ID: Q1: MD Q2: MD Q3: MD Q4: MD	Percentage active area, p	1.5 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	4.73069E-08 g/m²/s (unmitigated) 3.92648E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.5 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	1.22863E-09 g/m²/s	

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2019				
South Cargo Roadworks - at grade	Heavy construction Source ID:	Percentage active area, p	11.16 %	Assume % works area for heavy construction
	Q1: CA1, CA2 Q2: CA1, CA2 Q3: CA1, CA2 Q4: CA1, CA2	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 4.16979E-06 g/m²/s (unmitigated) 3.46092E-07 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p	11.16 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 9.0246E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - viaduct	Heavy construction Source ID:	Percentage active area, p	11.2 %	Assume % works area for heavy construction
	Q1: CA3, CA4, CA5, CA6, CA7, CA8 Q2: CA3, CA4, CA5, CA6, CA7, CA8 Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 4.34353E-07 g/m²/s (unmitigated) 3.60513E-08 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p	11.2 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 9.0246E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*1000000/(10000*365*24*60*60)*p/100
Roadworks Road 6 viaduct (Concept F, Option 3)	Heavy construction Source ID:	Percentage active area, p	7.6 %	Assume % works area for heavy construction
	Q1: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q2: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.9459E-07 g/m²/s (unmitigated) 2.4451E-08 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p	7.6 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 6.12074E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
New APM Interchange Station (AIS)	Heavy construction Source ID:	Percentage active area, p	2.6 %	Assume % works area for heavy construction
	Q1: AIS1, AIS2, EVA6, EVA7, EVA8 Q2: Q3: Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 8.20748E-08 g/m²/s (unmitigated) 6.81221E-09 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: AIS1, AIS2, EVA6, EVA7, EVA8	Percentage active area, p	2.64 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 2.1316E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2019				
Baggage Hall - Baggage Handling System (BHS)	Heavy construction Source ID: Q1: BHS1, BHS2, EVA9 Q2: Q3: Q4: BHS1, BHS2, EVA9	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	7.4 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.2904E-07 g/m²/s (unmitigated) 1.90103E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BHS1, BHS2, EVA9	Percentage active area, p Emission Factor (0.03) Emission Rate	7.36 % 0.0255 Mg/hectare/year 5.94849E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
New APM Depot (NAD)	Heavy construction Source ID: Q1: NAD1, NAD2 Q2: NAD1, NAD2 Q3: NAD1, NAD2 Q4: NAD2	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.4 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.29094E-08 g/m²/s (unmitigated) 1.07148E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: NAD1, NAD2	Percentage active area, p Emission Factor (0.03) Emission Rate	0.41 % 0.0255 Mg/hectare/year 3.35276E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
BHS and APM tunnel	Heavy construction Source ID: Q1: BAT1, BAT2, NAB3, NAB4 Q2: BAT1, BAT2, NAB3, NAB4 Q3: BAT1, BAT2, NAB3, NAB4 Q4: BAT1	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.5 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 1.52021E-08 g/m²/s (unmitigated) 1.26177E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BAT1, BAT2, NAB3, NAB4	Percentage active area, p Emission Factor (0.03) Emission Rate	0.49 % 0.0255 Mg/hectare/year 3.94819E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
T2 Expansion Area	Heavy construction Source ID: Q1: Q2: Q3: Q4: AIS1, AIS2, NAB1, NAB2, NAB3, NAB4, BAT2, NAD1, EVA6, EVA7, EVA8	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	0.8 % 91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.4034E-08 g/m²/s (unmitigated) 1.99482E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.03) Emission Rate	0.8 % 0.0255 Mg/hectare/year 6.24196E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2020

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities:	Percentage active area, p	0.1 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2:	No. of working days per month, d	30 days	
	Q3:	No. of working hours per day, h	24 hour	
	Q4:	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	1.95947E-09 g/m²/s (unmitigated) 1.62636E-10 g/m²/s (mitigated)	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
	For night-time activities:	Percentage active area, p	0.1 %	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
	Q1:	Mitigation efficiency	91.7 %	
	Q2: 3_02A-1, 3_02A-2, 3_02A-3	No. of working days per month, d	30 days	
	Q3: 3_02A-1, 3_02A-2, 3_02A-3	No. of working hours per day, h	12 (night) hour	
	Q4:	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	3.91894E-09 g/m²/s (unmitigated) 3.25272E-10 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.1 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	5.08901E-11 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID:	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
	Q1: 2_09-1, 3_02A-1, 3_02A-2, 3_02A-3, 3_02B	Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
	Q2: 2_09-1, 3_02B Q3: 2_09-1, 3_02B Q4: 3_02A-1, 3_02B	Emission Rate	1.6172E-08 g/m²/s	
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 1_09-1, 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2 Q2: 1_09-1, 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2 Q3: 1_09-1, 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2 Q4: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_09-1, 3_02A-2, 3_02A-3	Percentage active area, p	1.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	4.10099E-08 g/m²/s (unmitigated) 3.40382E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.3 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	1.06508E-09 g/m²/s	
Midfield development (MD)	Heavy construction Source ID: Q1: MD Q2: MD Q3: MD Q4: MD	Percentage active area, p	0.7 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	2.05772E-08 g/m²/s (unmitigated) 1.70791E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.7 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	5.34418E-10 g/m²/s	
Western Support Area Emergency Access Road (flyover)	Heavy construction Source ID: Q1: WSA1, WSA2, WSA3, WSA4 Q2: WSA1, WSA2, WSA3, WSA4 Q3: WSA1, WSA2, WSA3, WSA4 Q4: WSA1, WSA2, WSA3, WSA4	Percentage active area, p	55.2 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	2.14727E-06 g/m²/s (unmitigated) 1.78223E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	55.2 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	4.46141E-08 g/m²/s	

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2020				
Western Support Area Emergency Access Road (at grade)	Heavy construction Source ID:	Percentage active area, p	55.2 %	Assume % works area for heavy construction
	Q1: WSA5 Q2: WSA5 Q3: WSA5 Q4: WSA5	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 2.06138E-05 g/m²/s (unmitigated) 1.71095E-06 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p	55.2 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 4.46141E-08 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
New APM Interchange Station (AIS)	Heavy construction Source ID:	Percentage active area, p	1.9 %	Assume % works area for heavy construction
	Q1: AIS1, AIS2, EVA6, EVA7, EVA8 Q2: AIS1, AIS2, EVA6, EVA7, EVA8 Q3: Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 5.93756E-08 g/m²/s (unmitigated) 4.92818E-09 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: AIS1, AIS2, EVA6, EVA7, EVA8	Percentage active area, p	1.91 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 1.54207E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Baggage Hall - Baggage Handling System (BHS)	Heavy construction Source ID:	Percentage active area, p	3.0 %	Assume % works area for heavy construction
	Q1: BHS1, BHS2, EVA9 Q2: BHS1, BHS2, EVA9 Q3: Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 9.39246E-08 g/m²/s (unmitigated) 7.79574E-09 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BHS1, BHS2, EVA9	Percentage active area, p	3.02 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 2.43935E-09 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
New APM Depot (NAD)	Heavy construction Source ID:	Percentage active area, p	0.3 %	Assume % works area for heavy construction
	Q1: NAD2 Q2: NAD1, NAD2 Q3: NAD1, NAD2 Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 9.68208E-09 g/m²/s (unmitigated) 8.03613E-10 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: NAD2	Percentage active area, p	0.31 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 2.51457E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
BHS and APM tunnel	Heavy construction Source ID:	Percentage active area, p	0.2 %	Assume % works area for heavy construction
	Q1: BAT1 Q2: BAT1, BAT2, NAB3, NAB4 Q3: Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 6.51517E-09 g/m²/s (unmitigated) 5.40759E-10 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BAT1	Percentage active area, p	0.21 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 1.69208E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
T2 Expansion Area	Heavy construction Source ID:	Percentage active area, p	0.2 %	Assume % works area for heavy construction
	Q1: NAB1, NAB2, NAB3, NAB4, BAT2, NAD1 Q2: NAB1, NAB2 Q3: Q4:	Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.03) Emission Rate	91.7 % 30 days 24 hour 0.0807 Mg/hectare/month of activity 5.12952E-09 g/m²/s (unmitigated) 4.2575E-10 g/m²/s (mitigated)	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.2 %	
		Emission Factor (0.03) Emission Rate	0.0255 Mg/hectare/year 1.33221E-10 g/m²/s	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2021

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities:	Percentage active area, p	0.9 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2:	No. of working days per month, d	30 days	
	Q3:	No. of working hours per day, h	24 hour	
	Q4: 3_01B-1, 3_01B-2	Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	2.67288E-08 g/m²/s (unmitigated) 2.21849E-09 g/m²/s (mitigated)	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*30*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.9 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	6.94183E-10 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID:	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
	Q1: 3_02A-1, 3_02B	Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
	Q2: 3_02A-1, 3_02B Q3: 3_02A-1, 3_02B Q4: 3_02A-1, 3_02B	Emission Rate	1.6172E-08 g/m²/s	
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID:	Percentage active area, p	0.6 %	Assume % works area for heavy construction
	Q1: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_09-1, 3_02A-2, 3_02A-3 Q2: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_01-1, 4_01-2, 4_01-3, 4_05-1 Q3: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 3_01B-1, 3_01B-2, 4_01-1, 4_01-2, 4_01-3, 4_05-1 Q4: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_01-1, 4_01-2, 4_01-3, 4_03-1, 4_03-2, 4_05-1	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	1.84274E-08 g/m²/s (unmitigated) 1.52947E-09 g/m²/s (mitigated)	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.6 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	4.78584E-10 g/m²/s	
Airside tunnels (AT)	Heavy construction Source ID:	Percentage active area, p	0.4 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2: AT1, AT3 Q3: AT1, AT3 Q4: AT1, AT2, AT3	No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	1.28853E-08 g/m²/s (unmitigated) 1.06948E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.4 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	3.34649E-10 g/m²/s	
Midfield development (MD)	Heavy construction Source ID:	Percentage active area, p	0.6 %	Assume % works area for heavy construction
	Q1: MD Q2: MD Q3: MD Q4: MD	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =2.69*0.03*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	1.74857E-08 g/m²/s (unmitigated) 1.45132E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.6 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	4.54129E-10 g/m²/s	

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2021

South Cargo Roadworks - at grade	Heavy construction Source ID: Q1: Q2: Q3: CA1, CA2 Q4: CA1, CA2	Percentage active area, p	3.63 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
		Mitigation efficiency	91.7 %	
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	1.35651E-06 g/m²/s (unmitigated) 1.1259E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	3.63 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	2.93586E-09 g/m²/s	
South Cargo Roadworks - viaduct	Heavy construction Source ID: Q1: Q2: Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Percentage active area, p	3.6 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
		Mitigation efficiency	91.7 %	
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	1.41303E-07 g/m²/s (unmitigated) 1.17281E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	3.6 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	2.93586E-09 g/m²/s	
Roadworks Road 6 viaduct (Concept F, Option 3)	Heavy construction Source ID: Q1: Q2: Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Percentage active area, p	2.5 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
		Mitigation efficiency	91.7 %	
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	
		Emission Rate	9.58355E-08 g/m²/s (unmitigated) 7.95435E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	2.5 %	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	0.0255 Mg/hectare/year	
		Emission Rate	1.99118E-09 g/m²/s	

Appendix 5.2.15 - Details of Dust Emission Sources for Annual FSP Assessment at Year 2022

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 3_02B Q2: Q3: Q4: 3_02B	Percentage active area, p	0.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	8.80231E-09 g/m²/s (unmitigated) 7.30591E-10 g/m²/s (mitigated)	=2.69*0.03*1000000/(10000*30*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.3 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	2.28608E-10 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: 3_02A-1 Q2: 3_02A-1 Q3: 3_02B Q4:	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	1.6172E-08 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_01-1, 4_01-2, 4_01-3, 4_03-1, 4_03-2, 4_05-1 Q2: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-3, 3_02B, 4_03-1, 4_03-2, 4_05-1 Q3: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_02A-1, 4_05-1 Q4: 2_01, 2_02A, 2_02B-1, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 4_05-1	Percentage active area, p	1.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	4.18554E-08 g/m²/s (unmitigated) 3.474E-09 g/m²/s (mitigated)	=2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.3 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	1.08704E-09 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100
Airside tunnels (AT)	Heavy construction Source ID: Q1: AT1, AT2, AT3 Q2: AT2, AT3 Q3: AT3 Q4: AT3	Percentage active area, p	0.6 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.03)	0.0807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	1.92465E-08 g/m²/s (unmitigated) 1.59746E-09 g/m²/s (mitigated)	=2.69*0.03*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.6 %	
		Emission Factor (0.03)	0.0255 Mg/hectare/year	AP42, Table 11.9-4 Thompson G. Pace, USEPA. Examination of the Multiplier Used to Estimate PM2.5 Fugitive Dust Emissions from PM10, April 2005
		Emission Rate	4.99859E-10 g/m²/s	=0.85*0.03*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 - Details of Dust Emission Sources for FSP Assessment (Annual)

Barging Points, Crushing Plant, Concrete and Asphalt Batching Plants, C&D Stockpile and other Stockpiles (FSP)

Description	Sources	Parameter	Emission Rate	Remarks
Barging Point	Unloading of spoils to barge Source ID: TBP1-6	Particle size multiplier, k Moisture content, M Mean wind speed, U Emission Factor, E No. of operation hour Maximum handling capacity for each barging point Emission height Mitigation efficiency	0.053 5 % 4.9 m/s 6.66E-05 kg/Mg 12 hr 47000 Mg/day 2.61E-01 kg/hr (Asphalt) 0.5 m 90 %	For FSP, AP-42, section 13.2.4, 11/06 ed. Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). HKOAMO 2012 annual average wind speed E=k x (0.0016) x ((U/2.2)^1.3/(M/2)^1.4) (AP-42, section 13.2.4, 11/06 ed.) 26 days per month From engineer Assume 12 working hours (7:00 - 19:00) per day Installation of flexible curtain and shelter with water spray at discharge point
		Emission Rate	7.24E-03 g/s (mitigated)	
Concrete Batching Plant	Paved haul road outside concrete batching plant - For Laden Vehicle Source ID: WAB-HR1 to WAB-HR13 WAB-P4-HR1 to WAB-P4-HR10 WC-HR1 to WC-HR13 WC-P4-HR1 to WC-P4-HR10 EAB-HR1 to EAB-HR4 EAC-HR1 to EAC-HR4 EC-HR1 to EC-HR14 EC-P2-HR1 to EC-P2-HR7	Particle size multiplier, k Road surface silt loading, sL Average truck weight, W Emission height FSP emission factor, E No. of truck trips per day No. of operation hour % of dust suppression Emission Rate	0.15 g/VKT 12 g/m2 28.3 tons 0.5 m 44 g/VKT 96 trips/hr 140 trips/hr 12 hr 97.5 % 2.90E-05 g/m/s (mitigated) 4.23E-05 g/m/s (mitigated)	AP-42, Section 13.2.1, Table 13.2.1-1, 01/11 ed. AP-42, Section 13.2.1, Table 13.2.1-3, 01/11 ed. Full loading of Asphalt Tipper, engineering estimate Assumed that vehicle will lift dust from the road surface and disperse from 0.5m height E=k x (sL)^0.91x (W)^1.02 (AP-42, section 13.2.1, 01/11 ed.) Asphalt Tipper From engineer, Asphalt Tipper Lorries in Asphalt Plant From Engineer, Asphalt Tipper Lorries in Concrete Batching Plant Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). Asphalt Tipper Lorries in Asphalt Plant Asphalt Tipper Lorries in Concrete Batching Plant
Concrete Batching Plant	Paved haul road outside concrete batching plant - For Unladen Vehicle Source ID: WAB-HR1 to WAB-HR13 WAB-P4-HR1 to WAB-P4-HR10 WC-HR1 to WC-HR13 WC-P4-HR1 to WC-P4-HR10 EAB-HR1 to EAB-HR4 EAC-HR1 to EAC-HR4 EC-HR1 to EC-HR14 EC-P2-HR1 to EC-P2-HR7	Particle size multiplier, k Road surface silt loading, sL Average truck weight, W Emission height FSP emission factor, E No. of truck trips per day No. of operation hour % of dust suppression Emission Rate	0.15 g/VKT 12 g/m2 8.24 tons 0.5 m 12 g/VKT 30 trips/hr 140 trips/hr 12 hr 97.5 % 2.6E-06 g/m/s (mitigated) 1.20E-05 g/m/s (mitigated)	AP-42, Section 13.2.1, Table 13.2.1-1, 01/11 ed. AP-42, Section 13.2.1, Table 13.2.1-3, 01/11 ed. Empty loading of Asphalt Tipper, engineering estimate Assumed that vehicle will lift dust from the road surface and disperse from 0.5m height E=k x (sL)^0.91x (W)^1.02 (AP-42, section 13.2.1, 01/11 ed.) Asphalt Tipper From engineer, Asphalt Tipper Lorries in Asphalt Plant From Engineer, Asphalt Tipper Lorries in Concrete Batching Plant Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). Asphalt Tipper Lorries in Asphalt Plant Asphalt Tipper Lorries in Concrete Batching Plant
Concrete Batching Plant (Unloading of raw materials)	Unloading aggregate Source ID: (EP9) WAB-EP9, WAB-P4-EP9, WC-EP9, WC-P4-EP9 EAB-EP9, EC-EP9, EC-2-EP9, EC-3-EP9, EC-P2-EP9	Consumption Rate (Western + Eastern) Consumption Rate (Western only) Particle size multiplier, k Moisture content, M Mean wind speed, U Emission Factor, E Mitigation efficiency No. of operation hour Emission height Emission Rate (Western + Eastern) - Period 2 to 4 Emission Rate (Western only) - Period 1	300 Mg/h (Asphalt) 2000 Mg/h (Concrete) 150 Mg/h (Asphalt) 500 Mg/h (Concrete) 0.053 2 % 4.9 m/s 2.40E-04 kg/Mg 0.07 kg/hr (Asphalt - Westen + Eastern) 0.48 kg/hr (Concrete - Western +Eastern) 0.04 kg/hr (Asphalt - Western only) 0.12 kg/hr (Concrete - Western only) 99 % 12 hr 4 m 1.00E-04 g/s (mitigated) (Asphalt) 3.34E-04 g/s (mitigated) (Concrete) 1.00E-04 g/s (mitigated) (Asphalt) 3.34E-04 g/s (mitigated) (Concrete)	From engineer: Asphalt: 300 ton/hr = 150 ton/hr x 2 plants From engineer: Concrete: 2000 ton/hr = 500 ton/hr x4 plants From engineer: Asphalt: 150 ton/hr From engineer: Concrete: 500 ton/hr For FSP, AP-42, section 13.2.4, 11/06 ed. Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). HKOAMO 2012 annual average wind speed E=k x (0.0016) x ((U/2.2)^1.3/(M/2)^1.4) (AP-42, section 13.2.4, 11/06 ed.) Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). For each plant (150 ton/hr) Period 2 to 4: 150 ton/hr x 2 plants For each plant (500ton/hr) Period 2: 500ton/hr x 2 plants Period 3&4: 500ton/hr x 4 plants For 150 ton/hr only For 500 ton/hr only
Concrete Batching Plant (Cement / PFA Silos)	Small Cementitious Material Silos Source ID: (EP5-EP8) WAB-EP5 to EP8, WAB-P4-EP5 to EP8, WC-EP5 to EP8, WC-P4-EP5 to EP8 EAB-EP5 to EP8, EC-EP5 to EP8, EC-2-EP5 to EP8, EC-3-EP5 to EP8, EC-P2-EP5 to EP8 PFA weight Hopper Source ID: (EP3-EP4) WAB-EP3 to EP4, WAB-P4-EP3 to EP4, WC-EP3 to EP4, WC-P4-EP3 to EP4 EAB-EP3 to EP4, EC-EP3 to EP4, EC-2-EP3 to EP4, EC-3-EP3 to EP4, EC-P2-EP3 to EP4	Density FSP emission factor (0.14) Dust exhaust flow rate for each mixer (Total 4 sources) No. of operation hour No. of small cement silos Emission height Emission Rate (Total 4 sources) Emission Rate (Each source) . Emission Factor (without mitigation) Density Emission factor Production rate (Total 2 sources) Mitigation efficiency Emission height Emission Rate (Total 2 sources)	2.24 Mg/m3 7 mg/m3 60 tons/hr (Asphalt) 1200 tons/hr (Concrete) 26.8 m3/hr (Asphalt) 535.7 m3/hr (Concrete) 12 hr 4 21 or 22 m 5.21E-05 g/s (mitigated) (Asphalt) 1.04E-03 g/s (mitigated) (Concrete) 1.30E-05 g/s (mitigated) (Asphalt) 2.60E-04 g/s (mitigated) (Concrete) 2.60E-03 kg/Mg 2.24 Mg/m3 5.82E-03 kg/m3 25 m3/hr (Asphalt) 429 m3/hr (Concrete) 99 % 13 m 4.04E-04 g/s (mitigated) (Asphalt) 6.94E-03 g/s (mitigated) (Concrete)	For Concrete & Asphalt density Refer to this web "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD Assume volume displacement by loading material For concrete & Asphalt density: 2.24 tons/m3 Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). EP5: 21m, EP6-EP8: 22m Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). Weight hopper loading (uncontrolled), AP-42, section 11.12-4, Table 11.12-1, 6/06 ed. For Concrete & Asphalt density Refer to this web "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" From engineer Total enclosure and fabric filter
Concrete Batching Plant (Mixing Tower)	Mixer Source ID: (EP1-EP2) WAB-EP1 to EP2, WAB-P4-EP1 to EP2, WC-EP1 to EP2, WC-P4-EP1 to EP2 EAB-EP1 to EP2, EC-EP1 to EP2, EC-2-EP1 to EP2, EC-3-EP1 to EP2, EC-P2-EP1 to EP2	Density FSP emission factor (0.14) Dust exhaust flow rate for each mixer (Total 2 sources) No. of operation hour No. of small cement silos Emission height Emission Rate (Total 2 sources)	2.24 Mg/m3 7 mg/m3 60 tons/hr (Asphalt) 1200 tons/hr (Concrete) 26.8 m3/hr (Asphalt) 535.7 m3/hr (Concrete) 12 hr 2 13 m 5.21E-05 g/s (mitigated) (Asphalt) 1.04E-03 g/s (mitigated) (Concrete)	For Concrete & Asphalt density Refer to this web "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD Assume volume displacement by loading material For concrete & Asphalt density: 2.24 tons/m3

Barging Points, Crushing Plant, Concrete and Asphalt Batching Plants, C&D Stockpile and other Stockpiles (FSP)

Description	Sources	Parameter	Emission Rate		Remarks
Stockpile within Asphalt batching plant in western location	Material handling and storage piles Source ID: WABA1, WABA1-P4 WABA2, WABA2-P4	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m ³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	335	m3/month (Asphalt)	
			5,250	m3/month (Aggregate)	
		Maximum hourly output, op	1.1	m3/hr (Asphalt)	
			16.8	m3/hr (Aggregate)	
			2.7	Mg/hr (Asphalt)	
			42.1	Mg/hr (Aggregate)	
		Area of the Asphalt stockpile, A	234	m ² (Asphalt)	
		Area of the Aggregate stockpile, A	2,200	m ² (Aggregate)	
		Emission Rate (Asphalt stockpile)	2.12177E-07	g/m²/s (unmitigated)	
			4.24354E-08	g/m²/s (mitigated)	
		Emission Rate (Aggregate stockpile)	3.53766E-07	g/m²/s (unmitigated)	
			7.07531E-08	g/m²/s (mitigated)	
	Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	20	% (mitigated)	
			0.0255	Mg/hectare/year	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	
			1.6172E-08	g/m²/s (mitigated)	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m ³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Percentage open stockpile area, p	20	%	
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	422	m3/month (Milled Material)	
			15,182	m3/month (Crushed Aggregate)	
			16,275	m3/month (Sub-base stockpile)	
		Maximum hourly output, op	1.4	m3/hr (Milled Material)	
			48.7	m3/hr (Crushed Aggregate)	
			52.2	m3/hr (Sub-base stockpile)	
			3.4	Mg/hr (Milled Material)	
			121.6	Mg/hr (Crushed Aggregate)	
			130.4	Mg/hr (Sub-base stockpile)	
	Area of the Milled Material stockpile, A		279	m ² (Milled Material)	
		Area of the Crushed Aggregate stockpile, A	5,822	m ² (Crushed Aggregate)	
		Area of the Sub-base stockpile, A	6,209	m ² (Sub-base stockpile)	
		Emission Rate (Milled Material stockpile)	2.24376E-07	g/m²/s (unmitigated)	
			4.48752E-08	g/m²/s (mitigated)	
		Emission Rate (Crushed Aggregate stockpile)	3.86492E-07	g/m²/s (unmitigated)	
			7.72983E-08	g/m²/s (mitigated)	
		Emission Rate (Sub-base stockpile)	3.88446E-07	g/m²/s (unmitigated)	
			7.76891E-08	g/m²/s (mitigated)	
			100	% (unmitigated)	
		Emission Factor (0.03)	20	% (mitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
			0.0255	Mg/hectare/year	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	
Stockpile within Asphalt batching plant in eastern location	Material handling and storage piles Source ID: EABA1, EABA2	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m ³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	67	m3/month (Asphalt)	
			1,050	m3/month (Aggregate)	
		Maximum hourly output, op	0.2	m3/hr (Asphalt)	
			3.4	m3/hr (Aggregate)	
			0.5	Mg/hr (Asphalt)	
			8.4	Mg/hr (Aggregate)	
		Area of the Asphalt stockpile, A	154	m ² (Asphalt)	
		Area of the Aggregate stockpile, A	562	m ² (Aggregate)	
		Emission Rate (Asphalt stockpile)	6.46124E-08	g/m²/s (unmitigated)	
			1.29225E-08	g/m²/s (mitigated)	
	Emission Rate (Aggregate stockpile)		2.77069E-07	g/m²/s (unmitigated)	
			5.54139E-08	g/m²/s (mitigated)	
		Percentage open stockpile area, p	100	% (unmitigated)	
			20	% (mitigated)	
		Emission Factor (0.03)	0.0255	Mg/hectare/year	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	
			1.6172E-08	g/m²/s (mitigated)	
			100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	20	% (mitigated)	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	
Stockpile within Airfield batching plant in eastern location	Material handling and storage piles Source ID: EACC1, EACA1	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m ³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	2,540	m3/month (Cement)	
			13,824	m3/month (Aggregate)	
		Maximum hourly output, op	8.1	m3/hr (Cement)	
			44.3	m3/hr (Aggregate)	
			20.3	Mg/hr (Cement)	
			110.8	Mg/hr (Aggregate)	
		Area of the Cement stockpile, A	1,163	m ² (Cement)	
		Area of the Aggregate stockpile, A	5,329	m ² (Aggregate)	
		Emission Rate (Cement stockpile)	3.23687E-07	g/m²/s (unmitigated)	
			6.47373E-08	g/m²/s (mitigated)	
	Emission Rate (Aggregate stockpile)		3.84457E-07	g/m²/s (unmitigated)	
			7.68914E-08	g/m²/s (mitigated)	
		Percentage open stockpile area, p	100	% (unmitigated)	
			20	% (mitigated)	
		Emission Factor (0.03)	0.0255	Mg/hectare/year	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	
			1.6172E-08	g/m²/s (mitigated)	
			100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	20	% (mitigated)	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	
Stockpile within Concrete Batching Plant in eastern location	Material handling and storage piles Source ID: ECC1_2, ECC1_3, ECC1-P2 ECA1_2, ECA1_3, ECA1-P2	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m ³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	43,270	m3/month (Cement)	
			173,079	m3/month (Aggregate)	
		Maximum hourly output, op	138.7	m3/hr (Cement)	
			554.7	m3/hr (Aggregate)	
			346.7	Mg/hr (Cement)	
			1386.8	Mg/hr (Aggregate)	
		Area of the Cement stockpile, A	3,944	m2 (Cement)	
		Area of the Aggregate stockpile, A	14,520	m2(Aggregate)	
		Emission Rate (Cement stockpile)	1.62605E-06	g/m²/s (unmitigated)	
			3.25209E-07	g/m²/s (mitigated)	
	Emission Rate (Aggregate stockpile)		1.7666E-06	g/m²/s (unmitigated)	
			3.5332E-07	g/m²/s (mitigated)	
		Percentage open stockpile area, p	100	% (unmitigated)	
			20	% (mitigated)	
		Emission Factor (0.03)	0.0255	Mg/hectare/year	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	
			1.6172E-08	g/m²/s (mitigated)	
			100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.03)	20	% (mitigated)	
		Emission Rate	8.086E-08	g/m²/s (unmitigated)	

Appendix 5.2.15 - Details of Dust Emission Sources for FSP Assessment (Annual)

Barging Points, Crushing Plant, Concrete and Asphalt Batching Plants, C&D Stockpile and other Stockpiles (FSP)

Description	Sources	Parameter	Emission Rate		Remarks
Crushed Aggregate Stockpile in eastern location	Material handling and storage piles Source ID: ECA2, ECA2-P2	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m ³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	4,364	m3/month	
		Maximum hourly output, op	14.0	m3/hr	
		Area of the stockpile, A	35.0	Mg/hr	
		Emission Rate	1,866	m2	
			3.46531E-07	g/m²/s (unmitigated)	
			6.93062E-08	g/m²/s (mitigated)	
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)		80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
	Emission Factor (0.03)	20	% (mitigated)		
	Emission Rate	0.0255	Mg/hectare/year		
		8.086E-08	g/m²/s (unmitigated)		
		1.6172E-08	g/m²/s (mitigated)		
C&D Stockpile near seawall	Material handling and storage piles Source ID: CD1	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	1,167	m3/month	
		Maximum hourly output, op	3.7	m3/hr	
		Area of the stockpile, A	7.5	Mg/hr	
		Emission Rate	3,900	m2	
			3.54683E-08	g/m²/s (unmitigated)	
			7.09366E-09	g/m²/s (mitigated)	
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)		80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
	Emission Factor (0.03)	20	% (mitigated)		
	Emission Rate	0.0255	Mg/hectare/year		
		8.086E-08	g/m²/s (unmitigated)		
		1.6172E-08	g/m²/s (mitigated)		
C&D Stockpile at midfield	Material handling and storage piles Source ID: CD2, CD3	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.053		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	6.65864E-05	kg/Mg	
		Monthly output	33,222	m3/month	
		Maximum hourly output, op	106.5	m3/hr	
		Area of the stockpile, A	213.0	Mg/hr	
		Emission Rate	8,100	m2	
			4.86297E-07	g/m²/s (unmitigated)	
			9.72595E-08	g/m²/s (mitigated)	
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)		80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.85*0.03*1000000/(10000*365*24*60*60)*p/100
	Emission Factor (0.03)	20	% (mitigated)		
	Emission Rate	0.0255	Mg/hectare/year		
		8.086E-08	g/m²/s (unmitigated)		
		1.6172E-08	g/m²/s (mitigated)		
Crushing Plant	Screening Source ID: CP1, CP2	FSP emission factor (0.03)	1.5	mg/m3	Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Mineral Works (Stone Crushing Plants), EPD Assume the same as approved EIA South East New Territories (SENT) Landfill Extension (EIA-143/2007) Annex A2 From engineer
		Density of rock	1760	Kg/m3	
		Maximum handling capcity	700	Mg/hr	
		No. of operation hour	12	hr	
		Emission height	15	m	
		Emission Rate	1.66E-04	g/s (mitigated)	
Crushing Plant	Tertiary Crushing Source ID: CP1, CP2	FSP emission factor (0.03)	1.5	mg/m3	Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Mineral Works (Stone Crushing Plants), EPD Assume the same as approved EIA South East New Territories (SENT) Landfill Extension (EIA-143/2007) Annex A2 From engineer
		Density of rock	1760	Kg/m3	
		Maximum handling capcity	700	Mg/hr	
		No. of operation hour	12	hr	
		Emission height	15	m	
		Emission Rate	1.66E-04	g/s (mitigated)	
Crushing Plant	Paved haul road outside crushing plant - For Laden Vehicle Source ID: WAB-HR1 to WAB-HR13 WC-HR1 to WC-HR13	Particle size multiplier, k	0.15	g/VKT	AP-42, Section 13.2.1, Table 13.2.1-1, 01/11 ed. AP-42, Section 13.2.1, Table 13.2.1-3, 01/11 ed. Full loading of truck, assume the same as Asphalt Tipper, engineering estimate Assumed that vehicle will lift dust from the road surface and disperse from 0.5m height E=k x (sL)^0.91x (W)^1.02 (AP-42, section 13.2.1, 01/11 ed.) Truck From engineer: 700Mg/hr * (1/(6m3/veh)) * (1/1760 kg/m3) * 1000 Assume density = 1760kg/m3, truck loading = 6m3/veh Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). Truck for crushing plant
		Road surface silt loading, sL	12	g/m2	
		Average truck weight, W	28.3	tons	
		Emission height	0.5	m	
		FSP emission factor, E	44	g/VKT	
		No. of truck trips per day	66	trips/hr	
		No. of operation hour	12	hr	
		% of dust suppression	97.5	%	
		Emission Rate	2.00E-05	g/m/s (mitigated)	
Crushing Plant	Paved haul road outside crushing plant - For Unladen Vehicle Source ID: WAB-HR1 to WAB-HR13 WC-HR1 to WC-HR13	Particle size multiplier, k	0.15	g/VKT	AP-42, Section 13.2.1, Table 13.2.1-1, 01/11 ed. AP-42, Section 13.2.1, Table 13.2.1-3, 01/11 ed. Empty loading of truck, assume the same as Asphalt Tipper, engineering estimate Assumed that vehicle will lift dust from the road surface and disperse from 0.5m height E=k x (sL)^0.91x (W)^1.02 (AP-42, section 13.2.1, 01/11 ed.) Truck From engineer: 700Mg/hr * (1/(6m3/veh)) * (1/1760 kg/m3) * 1000 Assume density = 1760kg/m3, truck loading = 6m3/veh Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). Truck for crushing plant
		Road surface silt loading, sL	12	g/m2	
		Average truck weight, W	8.24	tons	
		Emission height	0.5	m	
		FSP emission factor, E	12	g/VKT	
		No. of truck trips per day	66	trips/hr	
		No. of operation hour	12	hr	
		% of dust suppression	97.5	%	
		Emission Rate	5.7E-06	g/m/s (mitigated)	

(Annual) Floating Concrete Batching Plant

Description	Sources	Parameter	Emission Rate		Remarks
Floating Concrete Batching Plant (Unloading of raw materials)	Unloading aggregate Source ID: F-EP1	Consumption Rate	39.6	Mg/h (Concrete)	From engineer: Concrete: 39.6 ton/hr = 1900 ton / (2 days * 24 h) From engineer From engineer For FSP, AP-42, section 13.2.4, 11/06 ed. Assume as the same as land-based CBP HKOAMO 2012 annual average wind speed E=k x (0.0016) x ((U/2.2)^1.3/(M/2)^1.4) (AP-42, section 13.2.4, 11/06 ed.) Fully covered and handling with water spraying system (From engineer) Assume worst case From engineer
		Aggregate tank capacity	1900	tons	
		Refill frequency	2	days	
		Particle size multiplier, k	0.053		
		Moisture content, M	2	%	
		Mean wind speed, U	4.9	m/s	
		Emission Factor, E	2.40E-04	kg/Mg	
			0.01	kg/hr (Concrete)	
		Mitigation efficiency	99	%	
		No. of operation hours	24	hr	
		Emission height	10	m	
		Emission Rate	2.64E-05	g/s (mitigated) (Concrete)	
Floating Concrete Batching Plant (Cement / PFA / CSF Silos)	Cement Silos Source ID: F-EP2	Density	2.24	Mg/m3	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer From engineer From engineer: 7.33 ton/hr = 4 silos * (110 ton / (2.5 days * 24 h)) For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		FSP emission factor (0.14)	7	mg/m3	
		Cement silo capacity (Each silo)	110	tons	
		Refill frequency	2.5	days	
		Dust exhaust flow rate (Total 4 silos)	7.33	tons/hr (Concrete)	
			3.3	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of small cement silos	4		
		Emission height	10	m	
		Emission Rate (Total 4 silos)	6.37E-06	g/s (mitigated) (Concrete)	
	PFA Silos Source ID: F-EP3	Density	2.24	Mg/m3	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer From engineer From engineer: 3.75 ton/hr = 2 silos * (90 ton / (2 days * 24 h)) For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		FSP emission factor (0.14)	7	mg/m3	
		PFA silo capacity (Each silo)	90	tons	
		Refill frequency	2	days	
		Dust exhaust flow rate (Total 2 silos)	3.75	tons/hr (Concrete)	
			1.7	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of PFA silos	2		
		Emission height	10	m	
		Emission Rate (Total 2 silos)	3.26E-06	g/s (mitigated) (Concrete)	
	CSF Silos Source ID: F-EP4	Density	2.24	Mg/m3	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer From engineer From engineer: 0.5 ton/hr = 2 silos * (30 ton / (5 days * 24 h)) For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		FSP emission factor (0.14)	7	mg/m3	
		CSF silo capacity (Each silo)	30	tons	
		Refill frequency	5	days	
		Dust exhaust flow rate (Total 2 silos)	0.50	tons/hr (Concrete)	
			0.2	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of CSF silos	2		
		Emission height	10	m	
		Emission Rate (Total 2 silos)	4.34E-07	g/s (mitigated) (Concrete)	
Floating Concrete Batching Plant (Mixing Tower)	Mixer Source ID: F-EP5	Density	2.24	Mg/m3	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer: 280 ton/hr * 2 mixers For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		FSP emission factor (0.14)	7	mg/m3	
		Dust exhaust flow rate (Total 2 mixers)	560	tons/hr (Concrete)	
			250.0	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of mixers	2		
		Emission height	17	m	
		Emission Rate (Total 2 mixers)	4.86E-04	g/s (mitigated) (Concrete)	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2015				
Third Runway Work Areas				
Works Area	Sources	Parameter		Remarks
Submarine pipeline Submarine cable	Heavy construction Source ID:	Percentage active area, p	15.0 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day
	Q2:	No. of working days per month, d	30 days	
	Q3: S1, S2, S3	No. of working hours per day, h	24 hour	
	Q4: S1, S2, S3	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	4.67014E-06 g/m²/s (unmitigated) 3.87622E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	15 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) NCD works	Heavy construction Source ID:	Percentage active area, p	16.9 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day
	Q2:	No. of working days per month, d	30 days	Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q3: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, TRD2, TCPN-1, TCPN-2, TCPN-3, EGC4, EGC5, EGC6, EGC7	No. of working hours per day, h	24 hour	
	Q4: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	5.25715E-06 g/m²/s (unmitigated) 4.36344E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	16.9 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) ITT works (area sources)	Heavy construction Source ID:	Percentage active area, p	34.3 %	Assume % works area for heavy construction
	Q1: SCCP1, AES6, AES13, AES14, AES15, EM1, EM2, EGC3-1, EGC3-2, ITT1	Mitigation efficiency	91.7 %	Water suppression 12 times a day
	Q2: SCCP1, AES6, AES13, AES14, AES15, EM1, EM2, EGC3-1, EGC3-2, ITT1	No. of working days per month, d	30 days	Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q3: SCCP1, AES6, AES13, AES14, AES15, EM1, EM2, EGC3-1, EGC3-2, ITT1	No. of working hours per day, h	24 hour	
	Q4: EM1, EM2, ITT1	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	1.0673E-05 g/m²/s (unmitigated) 8.85857E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	34.3 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) ITT works (line sources) Roadworks - at grade	Heavy construction Source ID:	Percentage active area, p	34.28 %	Assume % works area for heavy construction
	Q1: SCRE1, SCRE2, SCRE3, SCRE4, SCRE5, SCRE6, SCRE7, SCRE8, SCRE9, SCRE10, AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	Mitigation efficiency	91.7 %	Water suppression 12 times a day
	Q2: SCRE1, SCRE2, SCRE3, SCRE4, SCRE5, SCRE6, SCRE7, SCRE8, SCRE9, SCRE10, AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	No. of working days per month, d	30 days	Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q3: SCRE1, SCRE2, SCRE3, SCRE4, SCRE5, SCRE6, SCRE7, SCRE8, SCRE9, SCRE10, AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	No. of working hours per day, h	24 hour	
	Q4:	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
		Emission Rate	0.000128076 g/m²/s (unmitigated) 1.06303E-05 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	34.28 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) Boundary Crossing Facilities (BCF)	Heavy construction Source ID:	Percentage active area, p	10.0 %	Extracted from HKBCF EIA, assume 10% works area for heavy construction
	Q1: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	Mitigation efficiency	87.5 %	Extracted from HKBCF EIA
	Q2: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	No. of working days per month, d	26 days	Extracted from HKBCF EIA
	Q3: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	No. of working hours per day, h	12 hour	Extracted from HKBCF EIA
	Q4: BCF-A, BCF-B, BCF-C1, BCF-C2, BCF-C3, BCF-C4	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	7.18483E-06 g/m²/s (unmitigated) 8.98104E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	10 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) Hong Kong Link Road (HKLR)	Heavy construction Source ID:	Percentage active area, p	10.0 %	Extracted from HKLR EIA, assume 10% works area for heavy construction
	Q1: LR-2, LR-3, LR-4, LR-5, LR-6, LR-7, LR-8, LR-9, LR-10, LR-11, LR-12, LR-13, LR-14	Mitigation efficiency	87.5 %	Extracted from HKLR EIA
	Q2:	No. of working days per month, d	26 days	Extracted from HKLR EIA
	Q3:	No. of working hours per day, h	12 hour	Extracted from HKLR EIA
	Q4:	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	7.18483E-06 g/m²/s (unmitigated) 8.98104E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	10 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2016

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: Q2: Q3: Q4: 1_03-1, 1_03-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3	Percentage active area, p	0.1 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69**0.3*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	2.8559E-08 g/m²/s (unmitigated) 2.3704E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.1 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	7.41717E-10 g/m²/s	
Submarine pipeline Submarine cable	Heavy construction Source ID: Q1: S1, S2, S3 Q2: S1, S2, S3 Q3: S1, S2, S3 Q4:	Percentage active area, p	22.5 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	7.00521E-06 g/m²/s (unmitigated) 5.81432E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	22.5 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	1.81935E-07 g/m²/s	
(Concurrent project) NCD works	Heavy construction Source ID: Q1: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q2: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q3: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q4: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7	Percentage active area, p	16.0 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	4.9862E-06 g/m²/s (unmitigated) 4.13854E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	16.0 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	1.29498E-07 g/m²/s	
(Concurrent project) ITT works (area sources)	Heavy construction Source ID: Q1: AES6, EM1, EM2, ITT1 Q2: AES6, EM1, EM2, ITT1 Q3: AES6, EM1, EM2, ITT1 Q4: AES6, EM1, EM2, ITT1	Percentage active area, p	35.9 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	1.11861E-05 g/m²/s (unmitigated) 9.28444E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	35.9 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	2.90518E-07 g/m²/s	
(Concurrent project) ITT works (line sources) Roadworks - at grade	Heavy construction Source ID: Q1: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q2: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q3: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q4: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12	Percentage active area, p	35.93 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
		Emission Rate	0.000134233 g/m²/s (unmitigated) 1.11413E-05 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	35.93 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	2.90518E-07 g/m²/s	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2016				
T2 Expansion - Advanced Works (Temporary Car Park NCD and Temporary Road Diversion)	Heavy construction Source ID: Q1: TRD1, TRD3, TRD4, TRD5, TRD6 Q2: TRD1, TRD5, TRD6 Q3: TRD1, TRD5, TRD6 Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	1.0 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 3.22126E-07 g/m²/s (unmitigated) 2.67364E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	1.0 % 0.255 Mg/hectare/year 8.36605E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project) Boundary Crossing Facilities (BCF)	Heavy construction Source ID: Q1: BCF-C4 Q2: BCF-C4 Q3: BCF-C4 Q4: BCF-C4	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	10.0 % 87.5 % 26 days 12 hour 0.807 Mg/hectare/month of activity 7.18483E-06 g/m²/s (unmitigated) 8.98104E-07 g/m²/s (mitigated)	Extracted from HKBCF EIA, assume 10% works area for heavy construction Extracted from HKBCF EIA Extracted from HKBCF EIA Extracted from HKBCF EIA AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	10 % 0.255 Mg/hectare/year 8.086E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Other airport facilities related works	Heavy construction Source ID: Q1: ABT1-1 Q2: ABT1-1 Q3: ABT1-1 Q4: ABT1-1	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	5.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.6071E-06 g/m²/s (unmitigated) 1.3339E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	5.2 % 0.255 Mg/hectare/year 4.17387E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Roadworks corresponding to Other airport facilities related works	Heavy construction Source ID: Q1: ABT1-2, ABT1-3 Q2: ABT1-2, ABT1-3 Q3: ABT1-2, ABT1-3 Q4: ABT1-2, ABT1-3	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	5.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.92852E-05 g/m²/s (unmitigated) 1.60068E-06 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	5.2 % 0.255 Mg/hectare/year 4.17387E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2017

Third Runway Work Areas				
Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 1_01, 1_03-1, 1_03-2, 1_04, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 1_09-1, 1_09-2, 2_03B, 2_04-1, 2_04-2, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07B, 2_08, 2_09-1, 2_09-2 Q2: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 1_09-1, 1_09-2, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-1, 2_09-2, 3_01A-1, 3_01A-2, 3_01A-3 Q3: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 3_01A-1, 3_01A-2, 3_01A-3 Q4: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	1.4 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 4.45002E-07 g/m²/s (unmitigated) 3.69352E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*30*h*60*60)*p/100
	For night-time activities: Q1: Q2: 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3 Q3: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2 Q4: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_02A-1, 3_02A-2, 3_02A-3	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	1.4 % 91.7 % 30 days 12 (night) hour 0.807 Mg/hectare/month of activity 8.90004E-07 g/m²/s (unmitigated) 7.38703E-08 g/m²/s (mitigated)	 AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*30*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	1.4 % 0.255 Mg/hectare/year 1.15573E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
	Wind Erosion Source ID:	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
	Q1:	Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
	Q2: Q3: Q4: 1_08B-1, 1_08B-2, 3_01A-1, 3_01A-2, 3_01A-3	Emission Rate	1.6172E-07 g/m²/s	
	Heavy construction Source ID: Q1: 4_04, 4_05-1 Q2: 4_04, 4_05-1 Q3: 4_04, 4_05-1 Q4: 4_04, 4_05-1	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.0 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 8.58968E-09 g/m²/s (unmitigated) 7.12944E-10 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.0 % 0.255 Mg/hectare/year 2.23086E-10 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project)	Heavy construction Source ID: Q1: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q2: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q3: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7 Q4: NCD1-1, NCD1-2, NCD1-3, NCD1-4, NCD1-5, NCD2-1, NCD2-2, NCD2-3, TRD2, TRD3, TRD4, TCPN-1, TCPN-2, TCPN-3, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2, EGC4, EGC5, EGC6, EGC7	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	3.1 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 9.65381E-07 g/m²/s (unmitigated) 8.01266E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	3.1 % 0.255 Mg/hectare/year 2.50723E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project)	Heavy construction Source ID: Q1: AES6 Q2: Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	7.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.2403E-06 g/m²/s (unmitigated) 1.85945E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	7.2 % 0.255 Mg/hectare/year 5.81837E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
(Concurrent project)	Heavy construction Source ID: Q1: AES1, AES2, AES3, AES4, AES5, AES7, AES8, AES9, AES10, AES11, AES12 Q2: Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	7.20 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.68836E-05 g/m²/s (unmitigated) 2.23134E-06 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	7.20 % 0.255 Mg/hectare/year 5.81837E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2017

South Cargo Roadworks - at grade	Heavy construction Source ID: Q1: Q2: CA1, CA2 Q3: CA1, CA2 Q4: CA1, CA2	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	30.48 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 0.000113869 g/m²/s (unmitigated) 9.45115E-06 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	30.48 % 0.255 Mg/hectare/year 2.46445E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - viaduct	Heavy construction Source ID: Q1: Q2: CA3, CA4, CA5, CA6, CA7, CA8 Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	30.5 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.18614E-05 g/m²/s (unmitigated) 9.84495E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	30.5 % 0.255 Mg/hectare/year 2.46445E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Roadworks Road 6 - viaduct (Concept F, Option 3)	Heavy construction Source ID: Q1: Q2: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	20.7 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 8.04473E-06 g/m²/s (unmitigated) 6.67713E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	20.7 % 0.255 Mg/hectare/year 1.67146E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
New APM Interchange Station (AIS)	Heavy construction Source ID: Q1: Q2: Q3: AIS1, AIS2 Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.7 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.24013E-07 g/m²/s (unmitigated) 1.8593E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.72 % 0.255 Mg/hectare/year 5.81792E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
BHS and APM tunnel	Heavy construction Source ID: Q1: Q2: Q3: BAT1, BAT2, NAB3, NAB4 Q4: BAT1, BAT2, NAB3, NAB4	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 5.42931E-08 g/m²/s (unmitigated) 4.50633E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.17 % 0.255 Mg/hectare/year 1.41007E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2017

T2 Expansion Area	Heavy construction Source ID: Q1: Q2: Q3: T2E-1, T2E-2, T2E-3, BHS1, BHS2, NAB1, NAB2, SAB, NAD1 Q4: T2E-1, T2E-2, T2E-3, AIS1, AIS2, BHS1, BHS2, NAB1, NAB2, SAB, NAD1, EVA1, EVA2, EVA3, EVA4, EVA5, EVA6, EVA7, EVA8, EVA9	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.0 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.44149E-08 g/m²/s (unmitigated) 1.19644E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.0 % 0.255 Mg/hectare/year 3.74376E-10 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
T2 Expansion - Emergency Vehicular Access (EVA)	Heavy construction Source ID: Q1: Q2: Q3: EVA1, EVA2, EVA3, EVA4, EVA5, EVA6, EVA7, EVA8, EVA9 Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	2.0 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 6.20924E-07 g/m²/s (unmitigated) 5.15367E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	2.0 % 0.255 Mg/hectare/year 1.61263E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Other airport facilities related works	Heavy construction Source ID: Q1: ABT1-1 Q2: ABT1-1 Q3: ABT1-1 Q4: ABT1-1	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	1.4 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 4.36713E-07 g/m²/s (unmitigated) 3.62472E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	1.4 % 0.255 Mg/hectare/year 1.1342E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Roadworks corresponding to Other airport facilities related works	Heavy construction Source ID: Q1: ABT1-2, ABT1-3 Q2: ABT1-2, ABT1-3 Q3: ABT1-2, ABT1-3 Q4: ABT1-2, ABT1-3	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	1.4 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 5.24056E-06 g/m²/s (unmitigated) 4.34966E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	1.4 % 0.255 Mg/hectare/year 1.1342E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2018

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_08B-2, 2_02B-1, 2_02B-2, 2_03A, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2 Q2: 1_02-1, 1_02-2, 1_05, 1_06-1, 1_06-2, 2_02B-1, 2_02B-2, 2_03A, 2_05A, 2_08, 3_02B Q3: 1_06-1, 1_06-2, 2_01, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2 Q4: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05B-1, 2_05B-2	Percentage active area, p	6.8 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69**0.3*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	2.10499E-06 g/m²/s (unmitigated) 1.74714E-07 g/m²/s (mitigated)	
	For night-time activities: Q1: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_02A-1, 3_02A-2, 3_02A-3 Q2: 1_09-1, 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_01A-1, 3_01A-2, 3_01A-3, 3_02A-1, 3_02A-2, 3_02A-3 Q3: 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 2_09-2, 3_01A-1, 3_01A-2, 3_01A-3, 3_02A-1, 3_02A-2, 3_02A-3 Q4: 1_09-1, 1_09-2, 2_09-1, 2_09-2, 3_02A-1, 3_02A-2, 3_02A-3	Percentage active area, p	6.8 %	
		Mitigation efficiency	91.7 %	
		No. of working days per month, d	30 days	
		No. of working hours per day, h	12 (night) hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69**0.3*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	4.20998E-06 g/m²/s (unmitigated) 3.49428E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	6.8 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	5.46694E-08 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: 1_07-2, 1_08A-2, 2_03B, 2_07B, 2_08, 3_01A-1, 3_01A-2, 3_01A-3 Q2: 1_01, 1_03-1, 1_03-2, 1_04, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B Q3: 1_09-1, 1_09-2, 2_08, 3_02B Q4: 2_04-1, 2_04-2, 2_05A, 2_06-1, 2_06-2, 2_06-3, 2_08, 3_02B	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.6172E-07 g/m²/s	
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 1_07-1, 1_08A-1, 1_08B-1, 4_04, 4_05-1 Q2: 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 4_04, 4_05-1 Q3: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_07A-1, 2_07A-2, 2_07B, 4_04, 4_05-1 Q4: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_07-1, 1_07-2, 1_08A-1, 1_08A-2, 1_08B-1, 1_08B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_04, 4_05-1	Percentage active area, p	2.4 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	7.43415E-07 g/m²/s (unmitigated) 6.17034E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	2.4 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.93075E-08 g/m²/s	
(Concurrent project) NCD works	Heavy construction Source ID: Q1: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2 Q2: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2 Q3: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2 Q4: NCD2-1, NCD2-2, NCD2-3, TRD3, TRD4, SCCP1, EGC1, EGC2, EGC3-1, EGC3-2	Percentage active area, p	26.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	8.18814E-06 g/m²/s (unmitigated) 6.79615E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	26.3 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	2.12657E-07 g/m²/s	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2018

Midfield development (MD)	Heavy construction Source ID: Q1: MD Q2: MD Q3: MD Q4: MD	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.7 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.1273E-07 g/m²/s (unmitigated) 1.76566E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.7 % 0.255 Mg/hectare/year 5.52489E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - at grade	Heavy construction Source ID: Q1: CA1, CA2 Q2: CA1, CA2 Q3: CA1, CA2 Q4: CA1, CA2	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	43.24 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 0.000161535 g/m²/s (unmitigated) 1.34074E-05 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	43.24 % 0.255 Mg/hectare/year 3.49607E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
South Cargo Roadworks - viaduct	Heavy construction Source ID: Q1: CA3, CA4, CA5, CA6, CA7, CA8 Q2: CA3, CA4, CA5, CA6, CA7, CA8 Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	43.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.68265E-05 g/m²/s (unmitigated) 1.3966E-06 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	43.2 % 0.255 Mg/hectare/year 3.49607E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Roadworks Road 6 - viaduct (Concept F, Option 3)	Heavy construction Source ID: Q1: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q2: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	29.3 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.14122E-05 g/m²/s (unmitigated) 9.47215E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	29.3 % 0.255 Mg/hectare/year 2.37113E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
New APM Interchange Station (AIS)	Heavy construction Source ID: Q1: Q2: AIS1, AIS2, EVA6, EVA7, EVA8 Q3: AIS1, AIS2, EVA6, EVA7, EVA8 Q4: AIS1, AIS2, EVA6, EVA7, EVA8	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	8.1 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.51202E-06 g/m²/s (unmitigated) 2.08497E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	8.07 % 0.255 Mg/hectare/year 6.52405E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2018

Baggage Hall - Baggage Handling System (BHS)	Heavy construction Source ID: Q1: Q2: BHS1, BHS2, EVA9 Q3: BHS1, BHS2, EVA9 Q4: BHS1, BHS2, EVA9	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	10.7 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 3.33502E-06 g/m²/s (unmitigated) 2.76807E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	10.71 % 0.255 Mg/hectare/year 8.66151E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
New APM Depot (NAD)	Heavy construction Source ID: Q1: NAD1, NAD2 Q2: NAD1, NAD2 Q3: NAD1, NAD2 Q4: NAD1, NAD2	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.4 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.29094E-07 g/m²/s (unmitigated) 1.07148E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: NAD1, NAD2	Percentage active area, p Emission Factor (0.3) Emission Rate	0.41 % 0.255 Mg/hectare/year 3.35276E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
BHS and APM tunnel	Heavy construction Source ID: Q1: BAT1, BAT2, NAB3, NAB4 Q2: BAT1, BAT2, NAB3, NAB4 Q3: BAT1, BAT2, NAB3, NAB4 Q4: BAT1, BAT2, NAB3, NAB4	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.5 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.52021E-07 g/m²/s (unmitigated) 1.26177E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BAT1, BAT2, NAB3, NAB4	Percentage active area, p Emission Factor (0.3) Emission Rate	0.49 % 0.255 Mg/hectare/year 3.94819E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
T2 Expansion Area	Heavy construction Source ID: Q1: T2E-1, T2E-2, T2E-3, AIS1, AIS2, BHS2 Q2: T2E-3 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 5.46382E-08 g/m²/s (unmitigated) 4.53497E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.2 % 0.255 Mg/hectare/year 1.41903E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
T2 Expansion - Car Park North (North Annex Building)	Heavy construction Source ID: Q1: NAB1, NAB2, BHS1 Q2: NAB1, NAB2 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 4.86999E-08 g/m²/s (unmitigated) 4.04209E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.2 % 0.255 Mg/hectare/year 1.2648E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
T2 Expansion - Lounge Limo (South Annex Building)	Heavy construction Source ID: Q1: SAB Q2: SAB Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 5.69905E-08 g/m²/s (unmitigated) 4.73021E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.2 % 0.255 Mg/hectare/year 1.48012E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2019

Third Runway Work Areas

Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 2_01, 2_02A Q2: 2_01, 2_02A, 2_05A Q3: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_05A Q4: 2_02B-1, 2_02B-2, 2_03A	Percentage active area, p	6.6 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69**0.3*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	2.06269E-06 g/m²/s (unmitigated) 1.71203E-07 g/m²/s (mitigated)	
	For night-time activities: Q1: 1_09-1, 1_09-2, 2_06-1, 2_06-2, 2_06-3, 3_02A-1, 3_02A-2, 3_02A-3 Q2: 1_09-2, 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 3_02A-1, 3_02A-2, 3_02A-3 Q3: 2_04-1, 2_04-2, 2_06-1, 2_06-2, 2_06-3, 2_09-1, 3_02A-1, 3_02A-2, 3_02A-3 Q4: 2_09-1	Percentage active area, p	6.6 %	
		Mitigation efficiency	91.7 %	
		No. of working days per month, d	30 days	
		No. of working hours per day, h	12 (night) hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69**0.3*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	4.12537E-06 g/m²/s (unmitigated) 3.42406E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	6.6 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	5.35708E-08 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: 2_02B-1, 2_03A, 2_03B, 2_04-1, 2_04-2, 2_05A, 2_05B-1, 2_05B-2, 2_08, 2_09-1, 2_09-2, 3_02B Q2: 2_02B-1, 2_03A, 2_03B, 2_05B-1, 2_05B-2, 3_02B Q3: 1_09-2, 3_02B Q4: 3_02A-1, 3_02A-2, 3_02A-3, 3_02B	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.6172E-07 g/m²/s	
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_07-1, 1_08A-1, 1_08B-1, 2_02B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 4_04 Q2: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_09-1, 2_02B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2, 4_04 Q3: 1_01, 1_02-1, 1_02-2, 1_03-1, 1_03-2, 1_04, 1_05, 1_06-1, 1_06-2, 1_09-1, 2_03B, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2, 4_04 Q4: 1_09-1, 1_09-2, 2_01, 2_02A, 2_03B, 2_04-1, 2_04-2, 2_05A, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2, 4_04	Percentage active area, p	1.8 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	5.75391E-07 g/m²/s (unmitigated) 4.77575E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.8 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.49437E-08 g/m²/s	
Midfield development (MD)	Heavy construction Source ID: Q1: MD Q2: MD Q3: MD Q4: MD	Percentage active area, p	1.5 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	4.73069E-07 g/m²/s (unmitigated) 3.92648E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.5 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.22863E-08 g/m²/s	
South Cargo Roadworks - at grade	Heavy construction Source ID: Q1: CA1, CA2 Q2: CA1, CA2 Q3: CA1, CA2 Q4: CA1, CA2	Percentage active area, p	11.16 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
		Emission Rate	4.16979E-05 g/m²/s (unmitigated) 3.46092E-06 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	11.16 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	9.0246E-08 g/m²/s	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2019

South Cargo Roadworks - viaduct	Heavy construction Source ID: Q1: CA3, CA4, CA5, CA6, CA7, CA8 Q2: CA3, CA4, CA5, CA6, CA7, CA8 Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate 4.34353E-06 g/m²/s (unmitigated) 3.60513E-07 g/m²/s (mitigated)	11.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 4.34353E-06 g/m²/s (unmitigated) 3.60513E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	11.2 % 0.255 Mg/hectare/year 9.0246E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Roadworks Road 6 - viaduct (Concept F, Option 3)	Heavy construction Source ID: Q1: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q2: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate 2.9459E-06 g/m²/s (unmitigated) 2.4451E-07 g/m²/s (mitigated)	7.6 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.9459E-06 g/m²/s (unmitigated) 2.4451E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	7.6 % 0.255 Mg/hectare/year 6.12074E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
New APM Interchange Station (AIS)	Heavy construction Source ID: Q1: AIS1, AIS2, EVA6, EVA7, EVA8 Q2: Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate 8.20748E-07 g/m²/s (unmitigated) 6.81221E-08 g/m²/s (mitigated)	2.6 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 8.20748E-07 g/m²/s (unmitigated) 6.81221E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: AIS1, AIS2, EVA6, EVA7, EVA8	Percentage active area, p Emission Factor (0.3) Emission Rate	2.64 % 0.255 Mg/hectare/year 2.1316E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Baggage Hall - Baggage Handling System (BHS)	Heavy construction Source ID: Q1: BHS1, BHS2, EVA9 Q2: Q3: Q4: BHS1, BHS2, EVA9	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate 2.2904E-06 g/m²/s (unmitigated) 1.90103E-07 g/m²/s (mitigated)	7.4 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.2904E-06 g/m²/s (unmitigated) 1.90103E-07 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BHS1, BHS2, EVA9	Percentage active area, p Emission Factor (0.3) Emission Rate	7.36 % 0.255 Mg/hectare/year 5.94849E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
New APM Depot (NAD)	Heavy construction Source ID: Q1: NAD1, NAD2 Q2: NAD1, NAD2 Q3: NAD1, NAD2 Q4: NAD2	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate 1.29094E-07 g/m²/s (unmitigated) 1.07148E-08 g/m²/s (mitigated)	0.4 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 1.29094E-07 g/m²/s (unmitigated) 1.07148E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: NAD1, NAD2	Percentage active area, p Emission Factor (0.3) Emission Rate	0.41 % 0.255 Mg/hectare/year 3.35276E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2019

BHS and APM tunnel	Heavy construction Source ID: Q1: BAT1, BAT2, NAB3, NAB4 Q2: BAT1, BAT2, NAB3, NAB4 Q3: BAT1, BAT2, NAB3, NAB4 Q4: BAT1	Percentage active area, p	0.5 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Mitigation efficiency	91.7 %	
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.3) Emission Rate	0.807 Mg/hectare/month of activity 1.52021E-07 g/m²/s (unmitigated) 1.26177E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above) Q1: BAT1, BAT2, NAB3, NAB4	Percentage active area, p	0.49 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	3.94819E-09 g/m²/s	
T2 Expansion Area	Heavy construction Source ID: Q1: Q2: Q3: Q4: AIS1, AIS2, NAB1, NAB2, NAB3, NAB4, BAT2, NAD1, EVA6, EVA7, EVA8	Percentage active area, p	0.8 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Mitigation efficiency	91.7 %	
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.3) Emission Rate	0.807 Mg/hectare/month of activity 2.4034E-07 g/m²/s (unmitigated) 1.99482E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.8 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	6.24196E-09 g/m²/s	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2020

Third Runway Work Areas				
Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: Q2: Q3: Q4:	Percentage active area, p	0.1 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	1.95947E-08 g/m²/s (unmitigated) 1.62636E-09 g/m²/s (mitigated)	
	For night-time activities: Q1: Q2: 3_02A-1, 3_02A-2, 3_02A-3 Q3: 3_02A-1, 3_02A-2, 3_02A-3 Q4:	Percentage active area, p	0.1 %	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*30*h*60*60)*p/100
		Mitigation efficiency	91.7 %	
		No. of working days per month, d	30 days	
		No. of working hours per day, h	12 (night) hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	3.91894E-08 g/m²/s (unmitigated) 3.25272E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.1 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	5.08901E-10 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: 2_09-1, 3_02A-1, 3_02A-2, 3_02A-3, 3_02B Q2: 2_09-1, 3_02B Q3: 2_09-1, 3_02B Q4: 3_02A-1, 3_02B	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999
		Emission Rate	1.6172E-07 g/m²/s	=0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 1_09-1, 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2 Q2: 1_09-1, 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_06-1, 2_06-2, 2_06-3, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2 Q3: 1_09-1, 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_08, 2_09-2 Q4: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_09-1, 3_02A-2, 3_02A-3	Percentage active area, p	1.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	4.10099E-07 g/m²/s (unmitigated) 3.40382E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.3 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	1.06508E-08 g/m²/s	
Midfield development (MD)	Heavy construction Source ID: Q1: MD Q2: MD Q3: MD Q4: MD	Percentage active area, p	0.7 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	2.05772E-07 g/m²/s (unmitigated) 1.70791E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.7 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	5.34418E-09 g/m²/s	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2020

Western Support Area Emergency Access Road (flyover)	Heavy construction Source ID: Q1: WSA1, WSA2, WSA3, WSA4 Q2: WSA1, WSA2, WSA3, WSA4 Q3: WSA1, WSA2, WSA3, WSA4 Q4: WSA1, WSA2, WSA3, WSA4	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	55.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 2.14727E-05 g/m²/s (unmitigated) 1.78223E-06 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	55.2 % 0.255 Mg/hectare/year 4.46141E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Western Support Area Emergency Access Road (at grade)	Heavy construction Source ID: Q1: WSA5 Q2: WSA5 Q3: WSA5 Q4: WSA5	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	55.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 0.000206138 g/m²/s (unmitigated) 1.71095E-05 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	55.2 % 0.255 Mg/hectare/year 4.46141E-07 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
New APM Interchange Station (AIS)	Heavy construction Source ID: Q1: AIS1, AIS2, EVA6, EVA7, EVA8 Q2: AIS1, AIS2, EVA6, EVA7, EVA8 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	1.9 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 5.93756E-07 g/m²/s (unmitigated) 4.92818E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: AIS1, AIS2, EVA6, EVA7, EVA8	Percentage active area, p Emission Factor (0.3) Emission Rate	1.91 % 0.255 Mg/hectare/year 1.54207E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Baggage Hall - Baggage Handling System (BHS)	Heavy construction Source ID: Q1: BHS1, BHS2, EVA9 Q2: BHS1, BHS2, EVA9 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	3.0 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 9.39246E-07 g/m²/s (unmitigated) 7.79574E-08 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BHS1, BHS2, EVA9	Percentage active area, p Emission Factor (0.3) Emission Rate	3.02 % 0.255 Mg/hectare/year 2.43935E-08 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2020

New APM Depot (NAD)	Heavy construction Source ID: Q1: NAD2 Q2: NAD1, NAD2 Q3: NAD1, NAD2 Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.3 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 9.68208E-08 g/m²/s (unmitigated) 8.03613E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: NAD2	Percentage active area, p Emission Factor (0.3) Emission Rate	0.31 % 0.255 Mg/hectare/year 2.51457E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
BHS and APM tunnel	Heavy construction Source ID: Q1: BAT1 Q2: BAT1, BAT2, NAB3, NAB4 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 6.51517E-08 g/m²/s (unmitigated) 5.40759E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above) Q1: BAT1	Percentage active area, p Emission Factor (0.3) Emission Rate	0.21 % 0.255 Mg/hectare/year 1.69208E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
T2 Expansion Area	Heavy construction Source ID: Q1: NAB1, NAB2, NAB3, NAB4, BAT2, NAD1 Q2: NAB1, NAB2 Q3: Q4:	Percentage active area, p Mitigation efficiency No. of working days per month, d No. of working hours per day, h Emission Factor (0.3) Emission Rate	0.2 % 91.7 % 30 days 24 hour 0.807 Mg/hectare/month of activity 5.12952E-08 g/m²/s (unmitigated) 4.2575E-09 g/m²/s (mitigated)	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p Emission Factor (0.3) Emission Rate	0.2 % 0.255 Mg/hectare/year 1.33221E-09 g/m²/s	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2021

Third Runway Work Areas				
Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities:	Percentage active area, p	0.9 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2:	No. of working days per month, d	30 days	
	Q3:	No. of working hours per day, h	24 hour	
	Q4: 3_01B-1, 3_01B-2	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	2.67288E-07 g/m²/s (unmitigated) 2.21849E-08 g/m²/s (mitigated)	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*30*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.9 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	6.94183E-09 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID:	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
	Q1: 3_02A-1, 3_02B	Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999
	Q2: 3_02A-1, 3_02B Q3: 3_02A-1, 3_02B Q4: 3_02A-1, 3_02B	Emission Rate	1.6172E-07 g/m²/s	=0.85*0.3*1000000/(10000*365*24*60*60)*p/100
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID:	Percentage active area, p	0.6 %	Assume % works area for heavy construction
	Q1: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 2_09-1, 3_02A-2, 3_02A-3	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_01-1, 4_01-2, 4_01-3, 4_05-1	No. of working days per month, d	30 days	
	Q3: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 3_01B-1, 3_01B-2, 4_01-1, 4_01-2, 4_01-3, 4_05-1	No. of working hours per day, h	24 hour	
	Q4: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_01-1, 4_01-2, 4_01-3, 4_03-1, 4_03-2, 4_05-1	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	1.84274E-07 g/m²/s (unmitigated) 1.52947E-08 g/m²/s (mitigated)	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.6 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	4.78584E-09 g/m²/s	
Airside tunnels (AT)	Heavy construction Source ID:	Percentage active area, p	0.4 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2: AT1, AT3 Q3: AT1, AT3 Q4: AT1, AT2, AT3	No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	1.28853E-07 g/m²/s (unmitigated) 1.06948E-08 g/m²/s (mitigated)	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.4 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	3.34649E-09 g/m²/s	
Midfield development (MD)	Heavy construction Source ID:	Percentage active area, p	0.6 %	Assume % works area for heavy construction
	Q1: MD Q2: MD Q3: MD Q4: MD	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	1.74857E-07 g/m²/s (unmitigated) 1.45132E-08 g/m²/s (mitigated)	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.6 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	4.54129E-09 g/m²/s	
South Cargo Roadworks - at grade	Heavy construction Source ID:	Percentage active area, p	3.63 %	Assume % works area for heavy construction
	Q1:	Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
	Q2:	No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
	Q3: CA1, CA2 Q4: CA1, CA2	Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	1.35651E-05 g/m²/s (unmitigated) 1.1259E-06 g/m²/s (mitigated)	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume road width equals 12m, therefore multiply emission rate by 12m. =2.69*0.3*1000000/(10000*d*h*60*60)*p/100 * 12
	Wind Erosion Source ID: (as above)	Percentage active area, p	3.63 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	2.93586E-08 g/m²/s	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2021

South Cargo Roadworks - viaduct	Heavy construction Source ID: Q1: Q2: Q3: CA3, CA4, CA5, CA6, CA7, CA8 Q4: CA3, CA4, CA5, CA6, CA7, CA8	Percentage active area, p	3.6 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
		Mitigation efficiency	91.7 %	
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	1.41303E-06 g/m²/s (unmitigated)	
			1.17281E-07 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	3.6 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	2.93586E-08 g/m²/s	
Roadworks Road 6 - viaduct (Concept F, Option 3)	Heavy construction Source ID: Q1: Q2: Q3: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37 Q4: RF1, RF2, RF3, RF4, RF5, RF6, RF7, RF8, RF9, RF10, RF11, RF12, RF13, RF14, RF15, RF16, RF17, RF18, RF19, RF20, RF21, RF22, RF23, RF24, RF25, RF26, RF27, RF28, RF29, RF30, RF31, RF32, RF33, RF34, RF35, RF36, RF37	Percentage active area, p	2.5 %	Assume % works area for heavy construction Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 Assume 30m spacing between road piers (base:5mx 5m), therefore total active area equals 5m divided by 30m. Since the road is approximated to a line, assume width of 7.5m (i.e. 5m pile width + 50% extra for works) '=2.69*0.3*1000000/(10000*30*h*60*60)*p/100 * (5/30) * 7.5
		Mitigation efficiency	91.7 %	
		No. of working days per month, d No. of working hours per day, h	30 days 24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	
		Emission Rate	9.58355E-07 g/m²/s (unmitigated)	
			7.95435E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	2.5 %	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Factor (0.3)	0.255 Mg/hectare/year	
		Emission Rate	1.99118E-08 g/m²/s	

Appendix 5.2.15 Details of Dust Emission Sources for Annual RSP Assessment at Year 2022

Third Runway Work Areas				
Works Area	Sources	Parameter		Remarks
Third Runway Land Formation	Heavy construction Source ID: For 24hrs activities: Q1: 3_02B Q2: Q3: Q4: 3_02B	Percentage active area, p	0.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*30*h*60*60)*p/100
		Emission Rate	8.80231E-08 g/m²/s (unmitigated) 7.30591E-09 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.3 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	2.28608E-09 g/m²/s	
Third Runway Wind Erosion (only)	Wind Erosion Source ID: Q1: 3_02A-1 Q2: 3_02A-1 Q3: 3_02B Q4:	Percentage active area, p	20.0 %	Based on maximum fines content of 20% in reclamation fill material (Type C), Table 3.1, Working Paper No. 3 Fill Management (Deliverable D6.3) (rev. 01), Atkins, October 2012
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.6172E-07 g/m²/s	
Third Runway Other Construction Works/Facilities on newly formed land	Heavy construction Source ID: Q1: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-1, 3_01A-2, 3_01A-3, 4_01-1, 4_01-2, 4_01-3, 4_03-1, 4_03-2, 4_05-1 Q2: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_01A-3, 3_02B, 4_03-1, 4_03-2, 4_05-1 Q3: 2_01, 2_02A, 2_02B-1, 2_02B-2, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 2_07A-1, 2_07A-2, 2_07B, 3_02A-1, 4_05-1 Q4: 2_01, 2_02A, 2_02B-1, 2_03A, 2_03B, 2_05A, 2_05B-1, 2_05B-2, 4_05-1	Percentage active area, p	1.3 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	4.18554E-07 g/m²/s (unmitigated) 3.474E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	1.3 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	1.08704E-08 g/m²/s	
Airside tunnels (AT)	Heavy construction Source ID: Q1: AT1, AT2, AT3 Q2: AT2, AT3 Q3: AT3 Q4: AT3	Percentage active area, p	0.6 %	Assume % works area for heavy construction
		Mitigation efficiency	91.7 %	Water suppression 12 times a day Equation (3-2) in the USEPA's Control of Open Fugitive Dust Sources Final Report
		No. of working days per month, d	30 days	
		No. of working hours per day, h	24 hour	
		Emission Factor (0.3)	0.807 Mg/hectare/month of activity	AP42, Section 13.2.3.3 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =2.69*0.3*1000000/(10000*d*h*60*60)*p/100
		Emission Rate	1.92465E-07 g/m²/s (unmitigated) 1.59746E-08 g/m²/s (mitigated)	
	Wind Erosion Source ID: (as above)	Percentage active area, p	0.6 %	
		Emission Factor (0.3)	0.255 Mg/hectare/year	AP42, Table 11.9-4 USEPA document Estimating Particulate Matter Emissions from Construction Operations, 1999 =0.85*0.3*1000000/(10000*365*24*60*60)*p/100
		Emission Rate	4.99859E-09 g/m²/s	

Appendix 5.2.15 - Details of Dust Emission Sources for RSP Assessment (Annual)

Barging Points, Crushing Plant, Concrete and Asphalt Batching Plants, C&D Stockpile and other Stockpiles

Description	Sources	Parameter	Emission Rate		Remarks
Barging Point	Unloading of spoils to barge Source ID: TBP1-6	Particle size multiplier, k	0.35		For RSP, AP-42, section 13.2.4, 11/06 ed. Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). HKOAMO 2012 annual average wind speed E=k x (0.0016) x ((U/2.2)^1.3/(M/2)^1.4) (AP-42, section 13.2.4, 11/06 ed.) 26 days per month From engineer Assume 12 working hours (7:00 - 19:00) per day Installation of flexible curtain and shelter with water spray at discharge point
		Moisture content, M	5	%	
		Mean wind speed, U	4.9	m/s	
		Emission Factor, E	4.40E-04	kg/Mg	
		No. of operation hour	12	hr	
		Maximum handling capcity for each barging point	47000	Mg/day	
		Emission height	1.72E+00	kg/hr (Asphalt)	
Concrete Batching Plant	Paved haul road outside concrete batching plant - For Laden Vehicle Source ID: WAB-HR1 to WAB-HR13 WAB-P4-HR1 to WAB-P4-HR10 WC-HR1 to WC-HR13 WC-P4-HR1 to WC-P4-HR10 EAB-HR1 to EAB-HR4 EAC-HR1 to EAC-HR4 EC-HR1 to EC-HR14 EC-P2-HR1 to EC-P2-HR7	Emission height	0.5	m	AP-42, Section 13.2.1, Table 13.2.1-1, 01/11 ed. AP-42, Section 13.2.1, Table 13.2.1-3, 01/11 ed. Full loading of Asphalt Tipper, engineering estimate Assumed that vehicle will lift dust from the road surface and disperse from 0.5m height E=k x (sL)^0.91x (W)^1.02 (AP-42, section 13.2.1, 01/11 ed.) Asphalt Tipper From engineer, Asphalt Tipper Lorries in Asphalt Plant From Enginner, Asphalt Tipper Lorries in Concrete Batching Plant Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). Asphalt Tipper Lorries in Asphalt Plant Asphalt Tipper Lorries in Concrete Batching Plant
		RSP emission factor, E	180	g/VKT	
		No. of truck trips per day	96	trips/hr	
		No. of operation hour	140	trips/hr	
		% of dust suppression	12	hr	
			97.5	%	
		Emission Rate	1.20E-04	g/m/s (mitigated)	
Concrete Batching Plant	Paved haul road outside concrete batching plant - For Unladen Vehicle Source ID: WAB-HR1 to WAB-HR13 WAB-P4-HR1 to WAB-P4-HR10 WC-HR1 to WC-HR13 WC-P4-HR1 to WC-P4-HR10 EAB-HR1 to EAB-HR4 EAC-HR1 to EAC-HR4 EC-HR1 to EC-HR14 EC-P2-HR1 to EC-P2-HR7	Particle size multiplier, k	0.62	g/VKT	AP-42, Section 13.2.1, Table 13.2.1-1, 01/11 ed. AP-42, Section 13.2.1, Table 13.2.1-3, 01/11 ed. Empty loading of Asphalt Tipper, engineering estimate Assumed that vehicle will lift dust from the road surface and disperse from 0.5m height E=k x (sL)^0.91x (W)^1.02 (AP-42, section 13.2.1, 01/11 ed.) Asphalt Tipper From engineer, Asphalt Tipper Lorries in Asphalt Plant From Enginner, Asphalt Tipper Lorries in Concrete Batching Plant Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). Asphalt Tipper Lorries in Asphalt Plant Asphalt Tipper Lorries in Concrete Batching Plant
		Road surface silt loading, sL	12	g/m2	
		Average truck weight, W	28.3	tons	
		Emission height	0.5	m	
		RSP emission factor, E	51	g/VKT	
		No. of truck trips per day	30	trips/hr	
		No. of operation hour	140	trips/hr	
Concrete Batching Plant (Unloading of raw materials)	Unloading aggregate Source ID: (EP9) WAB-EP9, WAB-P4-EP9, WC-EP9, WC-P4-EP9 EAB-EP9, EC-EP9, EC-2-EP9, EC-3-EP9, EC-P2-EP9	Consumption Rate (Western + Eastern)	1.1E-05	g/m/s (mitigated)	From engineer: Asphalt: 300 ton/hr = 150 ton/hr x 2 plants From engineer: Concrete: 2000 ton/hr = 500 ton/hr x4 plants From engineer: Asphalt: 150 ton/hr From engineer: Concrete: 500 ton/hr For RSP, AP-42, section 13.2.4, 11/06 ed. Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). HKOAMO 2012 annual average wind speed E=k x (0.0016) x ((U/2.2)^1.3/(M/2)^1.4) (AP-42, section 13.2.4, 11/06 ed.) Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). For each plant (150 ton/hr) Period 2 to 4: 150 ton/hr x 2 plants For each plant (500ton/hr) Period 2: 500ton/hr x 2 plants Period 3&4: 500ton/hr x 4 plants For 150 ton/hr only For 500 ton/hr only
		Consumption Rate (Western only)	4.97E-05	g/m/s (mitigated)	
		Particle size multiplier, k	300	Mg/h (Asphalt)	
		Moisture content, M	2000	Mg/h (Concrete)	
		Mean wind speed, U	150	Mg/h (Asphalt)	
		Emission Factor, E	500	Mg/h (Concrete)	
		Emission Rate (Western + Eastern) - Period 2 to 4	0.35		
Concrete Batching Plant (Cement / PFA Silos)	Small Cementitious Material Silos Source ID: (EP5-EP8) WAB-EP5 to EP8, WAB-P4-EP5 to EP8, WC-EP5 to EP8, WC-P4-EP5 to EP8 EAB-EP5 to EP8, EC-EP5 to EP8, EC-2-EP5 to EP8, EC-3-EP5 to EP8, EC-P2-EP5 to EP8	Mean wind speed, U	0.48	kg/hr (Asphalt - Westen + Eastern)	Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). For concrete & Asphalt density: 2.24 tons/m3 Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). EP5: 21m, EP6-EP8: 22m Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C).
		Emission Factor, E	3.17	kg/hr (Concrete - Western +Eastern)	
			0.24	kg/hr (Asphalt - Westen only)	
			0.79	kg/hr (Concrete - Western only)	
		Mitigation efficiency	99	%	
		No. of operation hour	12	hr	
		Emission height	4	m	
Concrete Batching Plant (Mixing Tower)	Mixer Source ID: (EP1-EP2) WAB-EP1 to EP2, WAB-P4-EP1 to EP2, WC-EP1 to EP2, WC-P4-EP1 to EP2 EAB-EP1 to EP2, EC-EP1 to EP2, EC-2-EP1 to EP2, EC-3-EP1 to EP2, EC-P2-EP1 to EP2	Emission Rate (Western + Eastern) - Period 2 to 4	6.61E-04	g/s (mitigated) (Asphalt)	For Concrete & Asphalt density Refer to this web "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD Assume volume displacement by loading material For concrete & Asphalt density: 2.24 tons/m3 Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C). EP5: 21m, EP6-EP8: 22m Assume as the same as Express Rail Link and Extracted from SP License of XRL (Appendix C).
		Emission Rate (Western only) - Period 1	2.20E-03	g/s (mitigated) (Concrete)	
			6.61E-04	g/s (mitigated) (Asphalt)	
			2.20E-03	g/s (mitigated) (Concrete)	
			6.61E-04	g/s (mitigated) (Asphalt)	
			2.20E-03	g/s (mitigated) (Concrete)	
			6.61E-04	g/s (mitigated) (Asphalt)	

Barging Points, Crushing Plant, Concrete and Asphalt Batching Plants, C&D Stockpile and other Stockpiles

Description	Sources	Parameter	Emission Rate		Remarks
Stockpile within Asphalt batching plant in western location	Material handling and storage piles Source ID: WABA1, WABA1-P4 WABA2, WABA2-P4	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed $E=k*0.0016*[(U/2.2)^{1.3}/(M/2)^{1.4}]$ From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	335	m3/month (Asphalt)	
			5,250	m3/month (Aggregate)	
		Maximum hourly output, op	1.1	m3/hr (Asphalt)	
			16.8	m3/hr (Aggregate)	
			2.7	Mg/hr (Asphalt)	
			42.1	Mg/hr (Aggregate)	
			234	m²(Asphalt)	
			2,200	m²(Aggregate)	
		Area of the Asphalt stockpile, A	1.40117E-06	g/m²/s (unmitigated)	
		Area of the Aggregate stockpile, A	2.80234E-07	g/m²/s (mitigated)	
Emission Rate (Asphalt stockpile)	2.33619E-06	g/m²/s (unmitigated)			
Emission Rate (Aggregate stockpile)	4.67237E-07	g/m²/s (mitigated)			
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.3*0.85*1000000/(10000*365*24*60*60)*p/100	
		20	% (mitigated)		
		0.255	Mg/hectare/year		
		8.086E-07	g/m²/s (unmitigated)		
		1.6172E-07	g/m²/s (mitigated)		
Milled Material, Crushed Aggregate and Sub-base Stockpile in western location	Material handling and storage piles Source ID: WAR1, WAR1-P4 WCAS1, WCAS1-P4 WSS1, WSS1-P4	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed $E=k*0.0016*[(U/2.2)^{1.3}/(M/2)^{1.4}]$ From engineer From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	422	m3/month (Milled Material)	
			15,182	m3/month (Crushed Aggregate)	
			16,275	m3/month (Sub-base stockpile)	
		Maximum hourly output, op	1.4	m3/hr (Milled Material)	
			48.7	m3/hr (Crushed Aggregate)	
			52.2	m3/hr (Sub-base stockpile)	
			3.4	Mg/hr (Milled Material)	
			121.6	Mg/hr (Crushed Aggregate)	
			130.4	Mg/hr (Sub-base stockpile)	
			279	m² (Milled Material)	
Area of the Milled Material stockpile, A	5,822	m²(Crushed Aggregate)			
Area of the Crushed Aggregate stockpile, A	6,209	m²(Sub-base stockpile)			
Area of the Sub-base stockpile, A	1.48173E-06	g/m²/s (unmitigated)			
Emission Rate (Milled Material stockpile)	2.96346E-07	g/m²/s (mitigated)			
Emission Rate (Crushed Aggregate stockpile)	2.5523E-06	g/m²/s (unmitigated)			
	5.10461E-07	g/m²/s (mitigated)			
Emission Rate (Sub-base stockpile)	2.56521E-06	g/m²/s (unmitigated)			
	5.13041E-07	g/m²/s (mitigated)			
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.3*0.85*1000000/(10000*365*24*60*60)*p/100	
		20	% (mitigated)		
		0.255	Mg/hectare/year		
		8.086E-07	g/m²/s (unmitigated)		
		1.6172E-07	g/m²/s (mitigated)		
Stockpile within Asphalt batching plant in eastern location	Material handling and storage piles Source ID: EABA1, EABA2	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed $E=k*0.0016*[(U/2.2)^{1.3}/(M/2)^{1.4}]$ From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	67	m3/month (Asphalt)	
			1,050	m3/month (Aggregate)	
		Maximum hourly output, op	0.2	m3/hr (Asphalt)	
			3.4	m3/hr (Aggregate)	
			0.5	Mg/hr (Asphalt)	
			8.4	Mg/hr (Aggregate)	
			154	m²(Asphalt)	
			562	m²(Aggregate)	
		Area of the Asphalt stockpile, A	4.26685E-07	g/m²/s (unmitigated)	
		Area of the Aggregate stockpile, A	8.53371E-08	g/m²/s (mitigated)	
Emission Rate (Asphalt stockpile)	1.8297E-06	g/m²/s (unmitigated)			
Emission Rate (Aggregate stockpile)	3.65941E-07	g/m²/s (mitigated)			
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.3*0.85*1000000/(10000*365*24*60*60)*p/100	
		20	% (mitigated)		
		0.255	Mg/hectare/year		
		8.086E-07	g/m²/s (unmitigated)		
		1.6172E-07	g/m²/s (mitigated)		
Stockpile within Airfield batching plant in eastern location	Material handling and storage piles Source ID: EACC1, EACA1	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed $E=k*0.0016*[(U/2.2)^{1.3}/(M/2)^{1.4}]$ From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	2,540	m3/month (Cement)	
			13,824	m3/month (Aggregate)	
		Maximum hourly output, op	8.1	m3/hr (Cement)	
			44.3	m3/hr (Aggregate)	
			20.3	Mg/hr (Cement)	
			110.8	Mg/hr (Aggregate)	
			1,163	m² (Cement)	
			5,329	m²(Aggregate)	
		Area of the Cement stockpile, A	2.13755E-06	g/m²/s (unmitigated)	
		Area of the Aggregate stockpile, A	4.27511E-07	g/m²/s (mitigated)	
Emission Rate (Cement stockpile)	2.53887E-06	g/m²/s (unmitigated)			
Emission Rate (Aggregate stockpile)	5.07773E-07	g/m²/s (mitigated)			
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.3*0.85*1000000/(10000*365*24*60*60)*p/100	
		20	% (mitigated)		
		0.255	Mg/hectare/year		
		8.086E-07	g/m²/s (unmitigated)		
		1.6172E-07	g/m²/s (mitigated)		
Stockpile within Concrete Batching Plant in eastern location	Material handling and storage piles Source ID: ECC1_2, ECC1_3, ECC1-P2 ECA1_2, ECA1_3, ECA1-P2	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed $E=k*0.0016*[(U/2.2)^{1.3}/(M/2)^{1.4}]$ From engineer From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate'=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	43,270	m3/month (Cement)	
			173,079	m3/month (Aggregate)	
		Maximum hourly output, op	138.7	m3/hr (Cement)	
			554.7	m3/hr (Aggregate)	
			346.7	Mg/hr (Cement)	
			1386.8	Mg/hr (Aggregate)	
			3,944	m2 (Cement)	
			14,520	m2(Aggregate)	
		Area of the Cement stockpile, A	1.0738E-05	g/m²/s (unmitigated)	
		Area of the Aggregate stockpile, A	2.14761E-06	g/m²/s (mitigated)	
Emission Rate (Cement stockpile)	1.16662E-05	g/m²/s (unmitigated)			
Emission Rate (Aggregate stockpile)	2.33324E-06	g/m²/s (mitigated)			
Wind erosion Source ID: As above	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets AP42, Section 11.9.4 =0.3*0.85*1000000/(10000*365*24*60*60)*p/100	
		20	% (mitigated)		
		0.255	Mg/hectare/year		
		8.086E-07	g/m²/s (unmitigated)		
		1.6172E-07	g/m²/s (mitigated)		

Barging Points, Crushing Plant, Concrete and Asphalt Batching Plants, C&D Stockpile and other Stockpiles

Description	Sources	Parameter	Emission Rate		Remarks
Crushed Aggregate Stockpile in eastern location	Material handling and storage piles Source ID: ECA2, ECA2-P2	Percentage open stockpile area, p	20	%	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Assume capacity of dump truck is 6m ³ and 15 tons Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	4,364	m3/month	
		Maximum hourly output, op	14.0	m3/hr	
	Wind erosion Source ID: As above	Area of the stockpile, A	35.0	Mg/hr	
		Emission Rate	1,866	m2	
		Emission Rate	2.28841E-06	g/m²/s (unmitigated)	
C&D Stockpile near seawall	Material handling and storage piles Source ID: CD1	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	1,167	m3/month	
		Maximum hourly output, op	3.7	m3/hr	
	Wind erosion Source ID: As above	Area of the stockpile, A	7.5	Mg/hr	
		Emission Rate	3,900	m2	
		Emission Rate	2.34225E-07	g/m²/s (unmitigated)	
C&D Stockpile at midfield	Material handling and storage piles Source ID: CD2, CD3	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	33,222	m3/month	
		Maximum hourly output, op	106.5	m3/hr	
	Wind erosion Source ID: As above	Area of the stockpile, A	213.0	Mg/hr	
		Emission Rate	8,100	m2	
		Emission Rate	3.2114E-06	g/m²/s (unmitigated)	
Crushing Plant	Screening Source ID: CP1, CP2	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	33,222	m3/month	
		Maximum hourly output, op	106.5	m3/hr	
	Wind erosion Source ID: As above	Area of the stockpile, A	213.0	Mg/hr	
		Emission Rate	8,100	m2	
		Emission Rate	3.2114E-06	g/m²/s (unmitigated)	
Crushing Plant	Tertiary Crushing Source ID: CP1, CP2	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	33,222	m3/month	
		Maximum hourly output, op	106.5	m3/hr	
	Wind erosion Source ID: As above	Area of the stockpile, A	213.0	Mg/hr	
		Emission Rate	8,100	m2	
		Emission Rate	3.2114E-06	g/m²/s (unmitigated)	
Crushing Plant	Paved haul road outside crushing plant - For Laden Vehicle Source ID: WAB-HR1 to WAB-HR13 WC-HR1 to WC-HR13	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	33,222	m3/month	
		Maximum hourly output, op	106.5	m3/hr	
	Wind erosion Source ID: As above	Area of the stockpile, A	213.0	Mg/hr	
		Emission Rate	8,100	m2	
		Emission Rate	3.2114E-06	g/m²/s (unmitigated)	
Crushing Plant	Paved haul road outside crushing plant - For Unladen Vehicle Source ID: WAB-HR1 to WAB-HR13 WC-HR1 to WC-HR13	Percentage open stockpile area, p	100	% (unmitigated)	80% stockpiling area is covered by impervious sheets and all dusty material should be sprayed with water immediately prior to any loading or transfer operation so as to keep the dusty material wet. k (particle size < 30µm) Assume worst case scenario HKOAMO 2012 annual average wind speed E=k*0.0016*[(U/2.2)^1.3/(M/2)^1.4] From engineer 26 days per month, 12 working hours per day Density of C&D material: 2Mg/m3 (from engineer) Unmitigated Emission Rate=E*1000*op/(A*60*60) Mitigated Emission Rate=E*1000*op/(A*60*60)*p/100
		Particle size multiplier, k	0.35		
		Moisture content, M	5	%	
		Average wind speed, U	4.9	m/s	
		Emission Factor, E	0.000439721	kg/Mg	
		Monthly output	33,222	m3/month	
		Maximum hourly output, op	106.5	m3/hr	
	Wind erosion Source ID: As above	Area of the stockpile, A	213.0	Mg/hr	
		Emission Rate	8,100	m2	
		Emission Rate	3.2114E-06	g/m²/s (unmitigated)	

(Annual) Floating Concrete Batching Plant

Description	Sources	Parameter	Emission Rate		Remarks
Floating Concrete Batching Plant (Unloading of raw materials)	Unloading aggregate Source ID: F-EP1	Consumption Rate	39.6	Mg/h (Concrete)	From engineer: Concrete: 39.6 ton/hr = 1900 ton / (2 days * 24 h) From engineer From engineer For RSP, AP-42, section 13.2.4, 11/06 ed. Assume as the same as land-based CBP HKOAMO 2012 annual average wind speed $E=k \times (0.0016) \times ((U/2.2)^{1.3}/(M/2)^{1.4})$ (AP-42, section 13.2.4, 11/06 ed.) Fully covered and handling with water spraying system (From engineer) Assume worst case From engineer
		Aggregate tank capacity	1900	tons	
		Refill frequency	2	days	
		Particle size multiplier, k	0.35		
		Moisture content, M	2	%	
		Mean wind speed, U	4.9	m/s	
		Emission Factor, E	1.59E-03	kg/Mg	
			0.06	kg/hr (Concrete)	
		Mitigation efficiency	99	%	
		No. of operation hours	24	hr	
Floating Concrete Batching Plant (Cement / PFA / CSF Silos)	Cement Silos Source ID: F-EP2	Emission height	10	m	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer From engineer From engineer: 7.33 ton/hr = 4 silos * (110 ton / (2.5 days * 24 h)) For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		Emission Rate	1.74E-04	g/s (mitigated) (Concrete)	
		Density	2.24	Mg/m3	
		RSP emission factor (0.37)	18.5	mg/m3	
		Cement silo capacity (Each silo)	110	tons	
		Refill frequency	2.5	days	
		Dust exhaust flow rate (Total 4 silos)	7.33	tons/hr (Concrete)	
			3.3	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of small cement silos	4		
	PFA Silos Source ID: F-EP3	Emission height	10	m	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer From engineer From engineer: 3.75 ton/hr = 2 silos * (90 ton / (2 days * 24 h)) For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		Emission Rate (Total 4 silos)	1.68E-05	g/s (mitigated) (Concrete)	
		Density	2.24	Mg/m3	
		RSP emission factor (0.37)	18.5	mg/m3	
		PFA silo capacity (Each silo)	90	tons	
		Refill frequency	2	days	
		Dust exhaust flow rate (Total 2 silos)	3.75	tons/hr (Concrete)	
			1.7	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of PFA silos	2		
	CSF Silos Source ID: F-EP4	Emission height	10	m	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer From engineer From engineer: 0.5 ton/hr = 2 silos * (30 ton / (5 days * 24 h)) For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		Emission Rate (Total 2 silos)	1.15E-06	g/s (mitigated) (Concrete)	
		Density	2.24	Mg/m3	
		RSP emission factor (0.37)	18.5	mg/m3	
		CSF silo capacity (Each silo)	30	tons	
		Refill frequency	5	days	
		Dust exhaust flow rate (Total 2 silos)	0.50	tons/hr (Concrete)	
			0.2	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of CSF silos	2		
Floating Concrete Batching Plant (Mixing Tower)	Mixer Source ID: F-EP5	Emission height	17	m	For Concrete density, refer to this website "http://www.aqua-calc.com/page/density-table/substance/concrete-coma-and-blank-asphalt" Concretration limit, Annex I, A Guidance Note on the Best Praticable Means for Cement Works (Concrete Batching Plant), EPD From engineer: 280 ton/hr * 2 mixers For concrete density: 2.24 tons/m3 Assume worst case From engineer From engineer
		Emission Rate (Total 2 mixers)	1.28E-03	g/s (mitigated) (Concrete)	
		Density	2.24	Mg/m3	
		RSP emission factor (0.37)	18.5	mg/m3	
		Dust exhaust flow rate (Total 2 mixers)	560	tons/hr (Concrete)	
			250.0	m3/hr (Concrete)	
		No. of operation hours	24	hr	
		No. of mixers	2		
		Emission height	17	m	
		Emission Rate (Total 2 mixers)	1.28E-03	g/s (mitigated) (Concrete)	