Calculation of Watering Efficiency (for Construction Site)

With reference to Cowherd et al., "Control of Open Fugitive Dust Sources, EPA-450/3-88-008, U.S. Environmental Protection Agency, Research Triangle Park, NC, percentage of dust mitigation efficiency is calculated from Equation (3-2) :

$$C = 100 - \frac{0.8 \, pdt}{i}$$

where

- p = Potential average hourly daytime evaporation rate, mm/hour = 0.23676 [1]
- d = Average hourly daytime traffic rate per hour = 35 per hour [2]
- I = Application intensity = 0.8 L/sq.m [3]

Note: [1]

p = 0.0049 x 48.3189 inch, where 48.3189inch is equivalent to the total evaoporation of 1227.3mm obtained from Hong Kong Observatory (http://www.weather.gov.hk/cis/normal/1981_2010/normals_e.htm)

- [2] Estimated by Engineer
- [3] The assumptions provided are for the purpose of assessment predictions only. Actual figures would be defined in the detailed design stage.

By applying the Equation (3-2) with the above assumptions,

Dust suppression efficiency = $100 - 0.8 \times (0.23676 \times 35 \times t) / 0.8 [t = time between application, hr]$

Therefore,

For watering once per hour (i.e. t =1 hour), the estimated dust suppression efficiency is 91.7%.