

REMARKS:
 AAO CRITERION FOR DAILY AVERAGE FSP CONCENTRATION IS 75 µg/m³ WITH 9 EXCEEDANCE CASES ALLOWED.

LEGEND:

- EXISTING REPRESENTATIVE ASR (FOR BOTH CONSTRUCTION AND OPERATIONAL PHASE ASSESSMENT)
- PLANNED REPRESENTATIVE ASR (FOR BOTH CONSTRUCTION AND OPERATIONAL PHASE ASSESSMENT)
- PLANNED REPRESENTATIVE ASR (FOR OPERATIONAL PHASE ASSESSMENT ONLY)
- LTR/SMR R/W
- 500M ASSESSMENT AREA
- PATH Grid Cell (1,1)

This drawing has been prepared for the use of AECOM's client. It may not be used, modified, reproduced or relied upon by third parties, except as agreed by AECOM or as required by law. AECOM accepts no responsibility, and denies any liability whatsoever, to any party that uses or relies on this drawing without AECOM's express written consent. Do not scale this document. All measurements must be obtained from the stated dimensions.

AECOM

Project
 DEVELOPMENT OF ANDERSON ROAD QUARRY SITE - INVESTIGATION, DESIGN AND CONSTRUCTION

CLIENT
 土木工程拓展署
 CEDD
 Civil Engineering and Development Department

CONSULTANT
 AECOM Asia Company Ltd.
 www.aecom.com


ISSUE/REVISION

NO.	DATE	DESCRIPTION	CHK.

SCALE

A3 1 : 7000

KEY PLA



PROJECT NO. 60328348
CONTRACT NO. CE 10/2014 (CE)
SHEET TITLE CONTOURS OF CUMULATIVE HIGHEST 10TH DAILY AVERAGE FSP CONCENTRATION IN µg/m³ AT 1.5m ABOVE GROUND (LTR R/W) (UNMITIGATED)
SHEET NUMBER 60328348/EIA_RIW/FIGURE 4.15