Appendix 5.1A

Prevailing Background Noise Levels

A.1 Details of prevailing background noise measurement at selected representative locations are provided in **Table 1**. The measurement results of the prevailing noise levels are listed in **Table 2**.

 Table 1
 Details of Background Noise Measurement

	Sung Wong Toi Road, Ma Tau Kok [a]	Junction of Sung Wong Toi Road and To Kwa Wan Road [b]	Bridges Street, Sheung Wan [c]
Height (mAG)	5.5	5.5	5.5
Distance from nearest vertical reflective surface (m)	>20	3	2

[[]a]: Measurement location 1 on Figure 5-2.

Table 2 Measurement Results for Prevailing Noise Levels

	Leq (30 mins), dB(A)			
Time	Sung Wong Toi Road, Ma Tau Kok (9-4-2015)	Junction of Sung Wong Toi Road and To Kwa Wan Road (29-9-2015)	Bridges Street, Sheung Wan (6-3-2015)	
2030-2100	68.1	66.7	66.0	
2100-2130	68.7	65.1	64.9	
2130-2200	67.6	66.3	63.1	
2200-2230	66.7	65.4	67.5	
2230-2300	67.0	65.4	65.2	
2300-2330	65.3	63.4	63.1	
2330-0000	64.7	63.9	60.3	
0000-0030	63.8	63.3	60.5	
0030-0100	-	-	59.3	

A.2 For conservative approach, the lowest measured noise levels (rounded to nearest integer) in the respective time period (day/evening time or night time) are taken as the prevailing background noise when assessing the noise impact from open air entertainment activities.

IA14016\App 5.1A 5.1A-1 CCLMLALJV

[[]b]: Measurement location 2 on Figure 5-2.

[[]c]: Measurement location on Figure 5-3.